

SCOPE OF ACCREDITATION TO ISO/IEC 17025:2017 & KS Q ISO/IEC 17025:2017

Institute of Calibration Technology Co.,Ltd

72, Dongtancheomdansaneop 2-ro, Hwaseong-si, Gyeonggi-do, Republic of Korea

Phone : 82-31-379-5114, Fax : 82-31-379-5115 e-mail : sictadmin@sict.co.kr

CALIBRATION

Valid To : Oct. 29. 2025

Accreditation No : KC01-018

In recognition of the successful completion of the KOLAS evaluation process, accreditation is granted to this laboratory to perform the following calibrations

Field Code	Item of Calibration	On-Site	Field Code	Item of Calibration	On-Site	Field Code	Item of Calibration	On-Site
102. Linear dimension			10235	Ultrasonic/coating thickness specimens	N	104. Form		
10201	Balls	N				10401	Form testers	Y
10203	Electrical/Mechanical comparators	Y	10236	Coating thickness testers	Y	10404	Optical flats	N
			10237	Torque arms	N	10405	Optical parallels	N
10204	Gauge block comparators	Y	10238	Width measuring specimens	N	10406	Parallel blocks	Y
10206	Dial/cylinder gauge testers	N	103. Angle			10407	Precision surface plates	Y
10207	Doctor blades	N	10302	Angle gauge blocks	N	10408	Profile gauges	N
10208	Distance meters; electrooptic /laser/ultrasonic	N	10303	Autocollimators	N	10409	Roundness measurement instruments	Y
			10304	Bevel protractors	Y			
10209	End bars	N	10306	Clinometers	N	10410	Form standard specimens	N
10210	Extensometers, linear displacement transducers	Y	10307	Collimators	Y	10411	Roundness standard/roundness magnification standard specimens	N
10211	Filler gauges	Y	10308	Fine angle generators, level comparators	N			
10212	Film applicators	N	10310	Indexing tables	N	10412	Straight edges	Y
10213	Gap gauges	N	10311	Plate/square/electric levels	N	10413	Straight rules	N
10214	Gauge blocks, by comparison	N	10312	Auto levels	N	10415	Test bars	N
10216	Height gauges/measuring machines	Y	10314	Penta-prisms	N	10416	Spherometers	N
			10315	Polygons	N	105. Complex geometry		
10219	Linear scales	N	10316	Rotary tables	Y	10501	Base gauges for electric bulb	N
10220	Standard measuring machines	Y	10317	Sine bars, plates, tables, centers	N			
10221	Micro scales/Standard scales	N				10318	Squareness testers, right angle testers	Y
10223	Electronic micrometers	Y	10319	Cylindrical squares	N	10504	Non-contact coordinate measuring machines	Y
10224	Height micrometers, riser blocks	N	10320	Precision squares	N			
10225	Laser scan micrometers	Y	10321	Theodolites, transits	N	10505	Gauge block accessories	N
10227	Standard tape rules, peripheral gauges	N	10322	Angular displacement transducers	Y	10508	Hardness indenters	N
10228	Cylindrical plug/pin gauges, Thread measuring wire gauges	Y				10323	Alignment telescopes, line of sight collimators	N
10229	Radius gauges	N	10324	Calibration system for survey instruments	Y	10512	Micro measuring microscopes	Y
10230	Cylindrical ring gauges	N				10513	Orifice plates	N
10231	Step blocks	N	10325	Jig transits	N	10514	Taper plug gauges	N
10232	Step gauges	N	10326	Laser levels	N	10517	Stylus type roughness testers	Y
10233	Taper thickness gauges	N	10327	Optical wedges	N			
10234	Ultrasonic thickness gauges	Y						

Field Code	Item of Calibration	On-Site	Field Code	Item of Calibration	On-Site	Field Code	Item of Calibration	On-Site
10518	Socket gauges for electric bulb	N	202. Force			20706	Hydrometers; density, specific gravity, alcohol, API, baume, sugar, milk, soil, salinity, LPG, etc.	N
			20202	Force measuring devices	N			
10519	Roughness standard /comparison specimens	N	20203	Tension/compression testing machines	Y			
10525	Thread plug gauges	N	20204	push-pull gauge	Y	20707	Chloride meters	N
10526	Taper thread plug gauges	N	203. Torque			20799	Others; Solid density	N
10527	Thread ring gauges	N	20302	Torque measuring devices	Y	208. Viscosity		
10528	Taper thread ring gauges	N	20303	Torque wrenches/drivers	Y	20801	Kinematic viscometers; capillary, etc.	N
10529	V-blocks, box blocks	N	204. Pressure					
10530	Position gauges	N	20401	Altimeters	Y	20802	Dynamic viscometers; rotaional, etc.	Y
10531	SEM/TEM/SPM/AFM microscopes	Y	20402	Manometers	Y			
106. Various dimensional			20403	Pneumatic pressure ballances	N	209. Fluid flow		
10601	Inside/outside/gear tooth calipers, caliper gauges	Y	20404	Hydraulic pressure ballances	N	20901	Anemometers; hot-wire	N
			20405	Air data test systems	Y	20902	Anemometers; pitot tube, etc.	N
10603	Cylinder/bore gauges	Y	20406	Absolute pressure gauges	Y			
10604	Depth gauges, depth micrometers	Y	20407	Blood pressure gauges	Y	20908	Gas flowmeters; differential pressure	N
			20408	Compound pressure gauges	Y			
10605	Dial/digital gauges	Y	20409	Differential pressure gauges	Y	20909	Liquid flowmeters; differential pressure	N
10606	Geodesic baselines	Y	20411	Gauge pressure gauges	Y			
10608	Grind gauges	N	20412	Pressure transducers/transmitters	Y	20910	Liquid flowmeters; electromagnetic	N
10609	Micro indicators, test indicators	Y	20413	Dial type vacuum gauges	Y	20911	Gas flowmeters; thermal mass, etc.	N
10610	Micrometer heads	Y	20414	Water depth meters	Y			
10611	3-points, micrometers	Y	205. Vacuum			20912	Liquid flowmeters; Coriolis, etc.	N
10612	Inside micrometers	Y	20501	Capacitance diaphragm gauges	N			
10613	Outside micrometers	Y	20502	Spinning rotor gauges	N	20914	Gas flowmeters; positive displacement	N
10615	Particle counters	N	20503	Ionization gauges	N			
10617	Standard sieves	N	20504	Thermal conductivity gauge; pirani, thermocouple, convectron, etc.	N	20915	Liquid flowmeters; positive displacement	N
10619	Water level meters	N				20916	Gas flowmeters; turbine	N
10620	Welding gauges	N				20917	Liquid flowmeters; turbine	N
10621	Optical micrometers	N	20505	Standard leaks, Helium leak detectors	Y	20918	Gas flowmeters; ultrasonic	N
201. Mass			206. Volume			20919	Liquid flowmeters; ultrasonic	N
20102	Auto-hopper scale balances	Y	20601	Volumetric glasswares	N			
20103	Auto-packer scale balances	Y	20602	Pycnometers	N	20920	Gas flowmeters; variable area	N
20104	Axle weigher balances	N	20603	Rain gauges	Y			
20106	Dial platform scale balances	Y	20604	Standard volume vessels	Y	20921	Liquid flowmeters; variable area	N
20107	Dial swing scale balances	Y	20605	Concrete air content meters	N			
20109	Electric balances	Y	20606	Piston type volume meters	N	20922	Gas flowmeters; vortex	N
20111	Manual swing scale balances	Y	207. Density			20923	Liquid flowmeters; vortex	N
20112	Platform scale balances	Y	20702	Liquid density meters	N	20925	Anemometers; vane, etc	N
20113	Spring scale balances	Y	20704	Salinity meters	N	20999	Others; Anemometers; ultrasonic waves	N
20116	Weights	Y	20705	Sucrose meters	N			

Field Code	Item of Calibration	On-Site	Field Code	Item of Calibration	On-Site	Field Code	Item of Calibration	On-Site
210. Hardness			402. Resistance, Capacitance and Inductance			404. Other DC & LF measurements		
21001	Brinell hardness testers	Y				40401	LF amplifiers	Y
21002	Rockwell hardness testers	Y	40201	Capacitance bridges	Y	40402	DC/LF attenuators	Y
21003	Shore hardness testers	Y		/indicators		40403	Multimeter calibrators	N
21004	Vickers hardness testers	Y	40202	Decade capacitors	Y	40404	Oscilloscope calibrators	N
21005	Durometer hardness testers	N	40204	Standard capacitors	Y	40405	CD/DVD meters/analyzers	Y
21006	Leeb hardness testers	Y	40205	Earth testers	Y	40406	Video signal generators	Y
211. Impact			40206	Inductance bridges	Y	40407	Audio distortion analyzers	Y
21102	Charpy impact testers	Y		/indicators			/meters	
21103	Izod impact testers	Y	40208	Inductors	Y	40408	LF filters	Y
301. Time/frequency			40210	Insulation testers	Y	40409	LF/audio signal analyzers	Y
30102	Frequency standards	N	40211	Q-meters	Y	40410	Line frequency meters	Y
30103	General frequency sources	Y	40213	Resistance bridges &	Y	40411	Function generators	Y
30104	Frequency meters/counters	Y		similar instruments		40412	Genescopes	Y
30105	Time interval sources	Y	40214	Resistance meters	Y	40413	AC/DC high voltage	Y
30106	Time interval meters	Y	40215	Resistors	Y		voltmeters	
	/stop watches/timers		40217	Impedance bridges/LCR meters	Y	40415	Jitter meters	Y
302. Velocity & revolution			403. AC voltage, current & power			40416	Leakage current testers	Y
30201	Standard RPM generators	Y	40301	AC ammeters	Y	40417	Electronic AC/DC loads	Y
30202	Contact type tachometers	Y	40302	Clamp ammeters/voltmeters	Y	40418	Modulation meters	Y
30203	Photo tachometers	Y	40303	AC voltage/current	Y	40419	Analogue/digital multimeters	Y
	/stroboscopes			calibrators		40420	Noise meters	Y
30204	Speed meters	Y	40304	Wattmeter calibrators	N	40421	Oscilloscopes	Y
30205	Wow-flutter generators	N	40305	AC current shunts	Y	40422	LF phase meters	Y
30206	Wow-flutter meters	Y	40306	Phase angle generators,	N	40424	Voltage/current recorders	Y
401. DC Voltage & current				synchro resolve generators		40425	Relay test sets	Y
40101	DC ammeters	Y	40307	Voltage/current phase angle	N	40426	LF signal generators	Y
40102	Transconductance amplifiers	Y		meters/synchro resolve		40427	LF spectrum analyzers	Y
40103	DC voltage/current	Y		meters		40428	Spot generators	Y
	calibrators		40308	Potential transformer test	Y	40429	Sweep generators	Y
40104	Electrical temperature	Y		sets		40430	Signal transducers	Y
	calibrators		40309	Potential transformer	N	40432	Transistor curve tracers	Y
40105	DC current shunts	Y	40310	Power factor meters	Y	40434	AC/DC high voltage	Y
40106	Galvanometers	Y	40311	AC power meters	Y		generators	
	/null detectors		40312	AC power supplies	Y	40435	AC/DC high voltage probes	Y
40107	Potentiometers	Y	40313	Puncture/safety testers	Y	40436	Logic analyzers	Y
40108	DC power supplies	Y	40314	Power recorders	Y	40437	Telephone testers	Y
40110	DC voltage dividers	N	40315	Current transformer test	Y	40438	Video signal analyzers	Y
40111	DC voltage standards	N		sets		405. Low frequency electric &		
40112	DC voltmeters	Y	40316	Current/turn current coil	N	magnetic field		
40113	Static/ionic voltmeters	N		transformers		40503	Flux meters	Y
			40318	AC voltmeters	Y	40504	Flux sources	N
			40319	Watt hour meters	N	40508	Magnetometers	Y
			40321	Ratio transformers	N	40510	Reference/standard magnets	N

Field Code	Item of Calibration	On-Site	Field Code	Item of Calibration	On-Site	Field Code	Item of Calibration	On-Site
406. Radio frequency measurement			40652	Field strength meters	Y	50302	Relative humidity hygrometers; polimer thin film, hair, etc.	Y
40601	RF amplifiers	Y	40653	AM/FM test sources	Y			
40602	Coaxial attenuators	Y	40654	Dip simulators	Y			
40605	Burst pulse generators	Y	407. Field strength & antenna			50303	Psychrometers; Assmann ventilated, PRT type, etc.	N
40606	Attenuator calibrators	N	40702	Probes	N			
40607	RF power meter calibrators	Y	40703	Dipole antennas	N			
40608	EMC transducers; current probes, absorbing clamps, etc.	Y	40704	Loop antennas	N	50304	Temperature humidity recorders; hygrothermograph, etc	Y
			40705	Monopole antennas	N			
			40707	Horn antennas	N			
40610	Coaxial directional couplers /splitters	Y	501. Contact thermometry			50305	Transducers; dew-point /relative humidity	N
40613	Electrostatic discharge generators	Y	50101	Temperature generators: ovens, furnaces, isothermal liquid baths, ice-point baths, dry-block calibrators	Y	50306	Humidity generators; two-pressure, two-temperature, flow mixing humidity generator, constant temperature and humidity chamber, etc.	Y
40614	EMC receivers	Y						
40615	RF filters	Y	50102	Temperature indicators /recorders/controllers, temperature calibrators	Y			
40616	RF impedance meters	N						
40617	RF impulse generators	Y						
40618	Line impedance stabilization networks; LISN, CDN, ISN, etc.	Y	50103	Glass thermometers; liquid-in-glass, Beckmann	N	504. Moisture		
40619	Coaxial standard mismatches	Y	50104	Resistance thermometers; SPRT, IPRT, thermistors, etc.	Y	50401	Cereal moisture meters	Y
40621	Mobile communication test sets	Y				50402	Wood moisture meters	N
40622	Modulation meters	Y				50403	Paper moisture meters	N
40623	Network analyzers	Y	50105	Thermal expansion thermometers; bimetal, gas or liquid type	Y	601. Sound in air		
40624	Noise figure meters	Y				60102	Sound calibrators	N
40625	Noise generators	N				60104	Microphones	N
40626	Noise impulse simulators	Y				60106	Sound level meters	Y
40627	RF phase noise meters	N	50106	Thermocouples: noble metal, base metal, pure metal, special type, etc.	Y	603. Vibration		
40628	Coaxial noise sources	N				60301	Vibration calibrators	N
40635	RF power meters	Y				60302	Vibration transducers	N
40636	Diode power sensors	Y	50107	Temperature transducers	Y	60303	Vibration measuring instruments	N
40637	Thermocouple power sensors	Y	50108	Primary fixed-point cells and apparatus	N	701. Photometry		
40638	Pulse generators	Y	502. Non contact thermometry			70101	Iluminance meters	N
40639	Radar test sets	Y	50203	Optical pyrometers	N	70102	Luminance meters	N
40640	RF signal generators	Y	50204	Standard radiation thermometers	N	70103	Total luminous flux meters	Y
40641	RF spectrum analyzers	Y	50205	Thermal image apparatus	N	70104	Luminous intensity meters	Y
40642	RF speed guns	Y	50206	Blackbody furnaces	Y	702. Property of detectos & sources		
40643	Surge generators	Y	50207	Others; ear thermometers, etc.	N	70202	Color temperature meters	Y
40644	SWR meters	N				70203	Color temperature standard lamps	N
40645	RF terminations	Y	503. Humidity			70204	Colorimeters; source color	Y
40646	Coaxial thermistor mounts	Y	50301	Dew-point hygrometers; chilled mirror, alumina thin film, etc.	N	70207	Laser power meters	N
40650	RF voltmeters	Y				70208	Standard LED light sources	N
40651	Vector voltmeters	Y						

Field Code	Item of Calibration	On-Site	Field Code	Item of Calibration	On-Site	Field Code	Item of Calibration	On-Site
70209	Total luminous flux standard lamps	N	703. Property of materials			70415	Optical multimeters	Y
			70301	Colorimeters; material color	Y	70416	Optical network analyzers	Y
70210	Optical detectors	N	70304	Color standard tiles	N	70417	Optical spectrum analyzers	Y
70211	Pyranometers and pyrhemometers	N	70306	Gloss meters	Y	70418	Optical time domain reflectometers; OTDR	Y
			70307	Gloss standard plates	Y			
70213	Display color analyzers; luminance, chromaticity, white balance, etc.	Y	70308	Haze meters	Y	70423	Return loss meters	Y
			70312	Lens meters	Y	70429	Frequency stabilized lasers and LDs	Y
			70315	Optical densitometers	Y			
70214	Luminous intensity standard lamps	N	70319	Reflectance meters	Y	70430	ASE light sources	Y
			70321	Refractometers	Y	70433	Optical power stabilized lasers and LDs	Y
70215	Spectral irradiance standard lamps	N	70323	Transmittance meters	Y			
70216	Total spectral radiant flux standard lamps	N	70325	Spectrophotometers including FT-IR spectrophotometers	Y	90101	Breath alcohol analyzers	N
						90102	Environmental air quality monitoring instruments	Y
70217	Luminance standard sources	N	70326	Wavelength reference materials; absorption cell, bandpass filter, etc.	N	90103	Gas analyzers	Y
70218	Spectral radiance standard sources	N				90104	Exhaust gas test instruments	Y
70219	UV irradiance meters	N	704. Fiber optics			90199	Others; pH meter, Electrical conductivity meter	Y
70220	Spectral irradiance meters	Y	70402	Broadband light sources	Y			
70221	Total spectral radiant flux meters	Y	70410	Optical attenuators	Y			
			70412	Fiber-optic power meters	Y			
70222	Spectral radiance meters	Y	70413	Optical loss testers	Y			

Note

1. This laboratory provides calibration services in permanent standard laboratory and at on-site.
2. Laboratory conducts on-site calibration should meet requirements of KOLAS-SR-007.
3. On-site calibration is allowed to items with marking 'Y', not allowed to items with marking 'N'.
4. Measurement uncertainty normally is quoted as an expanded uncertainty at a coverage probability of 95%, which usually requires the use of a coverage factor of $k = 2$. It expresses the lowest uncertainty of measurement that can be provided by accredited calibration laboratories in normal conditions.
5. Due to the calibration environment such as reference standards or customers' facilities, it is note that uncertainty of measurement on a calibration certificate may be expressed larger than measurement uncertainty on scope of accreditation in general.

102. Linear dimension

Measured Quantity Instrument or Gauge	Field Code	Range	Measurement uncertainty (The Confidence Level is about 95 %)	Standard/Method of Measurement etc.
Balls	10201	(0.3 ~ 100) mm	$\sqrt{0.38^2 + (0.0046 \times l_0)^2}$ μm	Mesuring Machine, Standard/ SICT-CP-10201
Electrical/Mechanical comparators	10203	(0 ~ 5) mm	0.14 μm	Gauge Block/ SICT-CP-10203
Gauge block comparators (Differences of central length) Comparison Direct	10204	(0 ~ 10) μm (0 ~ 10) mm	$\sqrt{24^2 + (0.33 \times l_0)^2}$ nm 0.043 μm	Gauge Block/ SICT-CP-10204
Dial/cylinder gauge testers	10206	(0 ~ 100) mm	$\sqrt{0.12^2 + (0.0030 \times l_0)^2}$ μm	Laser Measurement Machine/ SICT-CP-10206
Doctor blades	10207	(0 ~ 10) mm	1.6 μm	Electronic Micrometer/ SICT-CP-10207
Distance meters; electrooptic/laser/ultrasonic	10208	(0 ~ 40) m	$\sqrt{0.28^2 + (0.005 \times l_0)^2}$ mm	Laser interferometer/ SICT-CP-10208
End bars	10209	(25 ~ 1 500) mm	$\sqrt{0.6^2 + (0.0016 \times l_0)^2}$ μm	Linear measuring system/ SICT-CP-10209
Extensometers, linear displacement transducers	10210	(0 ~ 500) mm (500 ~ 1 000) mm	$\sqrt{1.9^2 + (0.0042 \times l_0)^2}$ μm $\sqrt{7.8^2 + (0.058 \times l_0)^2}$ μm	Gauge Block, Laser Measurement Machine/ SICT-CP-10210
Filler gauges	10211	(0 ~ 10) mm	1.2 μm	Mesuring Machine, Standard/ SICT-CP-10211
Film applicators	10212	(0 ~ 10) mm	1.6 μm	Electronic Micrometer/ SICT-CP-10212
Gap gauges	10213	(1 ~ 500) mm	$\sqrt{0.72^2 + (0.0048 \times l_0)^2}$ μm	Gauge Block, contact coordinate measuring machines/ SICT-CP-10213
Gauge blocks, by comparison	10214	(0.1 ~ 100) mm (100 ~ 250) mm (250 ~ 500) mm	$\sqrt{70^2 + (1.3 \times l_0)^2}$ nm $\sqrt{80^2 + (0.71 \times l_0)^2}$ nm $\sqrt{152^2 + (0.71 \times l_0)^2}$ nm	Gauge Block Comparator/ SICT-CP-10214
Height gauges/measuring machines	10216	(0 ~ 1 500) mm	$\sqrt{0.68^2 + (0.0035 \times l_0)^2}$ μm	Gauge Block, Step gauge/ SICT-CP-10216
Linear scales	10219	(0 ~ 40) m	$\sqrt{0.03^2 + (0.0027 \times l_0)^2}$ mm	Laser interferometer/ SICT-CP-10219
Standard measuring machines	10220	(0 ~ 500) mm	$\sqrt{0.38^2 + (0.002 \times l_0)^2}$ μm	Gauge Block/ SICT-CP-10220
Micro scales/Standard scales	10221	(0.01 ~ 1 500) mm	$\sqrt{0.17^2 + (0.0003 \times l_0)^2}$ μm	Linear measuring system/ SICT-CP-10221
Electronic micrometers	10223	(0 ~ 5) mm	0.14 μm	Gage Block/ SICT-CP-10223
Height micrometers, riser blocks Block Head	10224	(0 ~ 600) mm (0 ~ 25) mm	$\sqrt{1.1^2 + (0.0019 \times l_0)^2}$ μm 1.2 μm	Gauge Block Electronic Micrometer/ SICT-CP-10224
Laser scan micrometers	10225	(0.5 ~ 85) mm	$\sqrt{0.46^2 + (0.003 \times l_0)^2}$ μm	Cylindrical plug/pin gauge/ SICT-CP-10225
Standard tape rules, peripheral gauges	10227	(0 ~ 40) m (40 ~ 80) m (80 ~ 100) m	$\sqrt{0.22^2 + (0.0046 \times l_0)^2}$ mm $\sqrt{0.25^2 + (0.0046 \times l_0)^2}$ mm $\sqrt{0.34^2 + (0.0046 \times l_0)^2}$ mm	Laser Measurement Machine/ SICT-CP-10227

Note 1. l_0 unit : mm (10208,10227 unit : m)

102. Linear dimension

Measured Quantity Instrument or Gauge	Field Code	Range	Measurement uncertainty (The Confidence Level is about 95 %)	Standard/Method of Measurement etc.
Cylindrical plug/pin gauges, Thread measuring wire gauges Cylindrical plug/pin gauges Thread measuring wire gauges	10228	(0.01 ~ 200) mm (\varnothing 0.1 ~ \varnothing 10) mm	$\sqrt{0.42^2 + (0.003 \times l_0)^2}$ μm 0.41 μm	Mesuring Machine, Standard/ SICT-CP-10228
Radius gauges	10229	(0.1 ~ 100) mm	2.8 μm	non-contact coordinate measuring machines, Standard/
Cylindrical ring gauges	10230	(1.0 ~ 100) mm (100 ~ 300) mm	$\sqrt{0.55^2 + (0.003 \ 0 \times l)^2}$ μm $\sqrt{1.0^2 + (0.003 \ 0 \times l)^2}$ μm	Mesuring Machine, Standard/ SICT-CP-10230
Step blocks	10231	(0 ~ 300) μm	0.23 μm	Gauge Block/ SICT-CP-10231
Step gauges	10232	(0 ~ 1 510) mm	$\sqrt{0.28^2 + (0.000 \ 95 \times l_0)^2}$ μm	Linear measuring system/ SICT-CP-10232
Taper thickness gauges	10233	(0 ~ 60) mm	4.3 μm	Profile Projector/ SICT-CP-10233
Ultrasonic thickness gauges	10234	(2.5 ~ 100) mm	3 μm	Ultrasonic Tester Blocks/ SICT-CP-10234
Ultrasonic/coating thickness specimens coating thickness specimens Plateness Ultrasonic thickness specimens	10235	(0.01 ~ 25) mm (0.5 ~ 500) mm	1.9 μm 0.8 μm $\sqrt{0.64^2 + (0.006 \times l_0)^2}$ μm	Gauge Block, Mesuring Machine, Standard/ SICT-CP-10235
Coating thickness testers	10236	(0 ~ 25) mm	1.2 μm	Thickness specimens/ SICT-CP-10236
Torque arms Torque arms Wires	10237	(1 ~ 1 500) mm (0 ~ 5) mm	$\sqrt{0.60^2 + (0.006 \ 1 \times l_0)^2}$ μm 1.2 μm	Gauge Block, contact coordinate measuring machines/ SICT-CP-10237
Width measuring specimens	10238	(0 ~ 200) mm (200 ~ 1 000) mm	$\sqrt{1.3^2 + (0.003 \ 4 \times l)^2}$ μm $\sqrt{1.2^2 + (0.005 \ 4 \times l)^2}$ μm	Mesuring Machine, contact coordinate measuring machines/ SICT-CP-10237

Note 1. l_0 unit : mm (10208,10227 unit : m)

103. Angle

Measured Quantity Instrument or Gauge	Field Code	Range	Measurement uncertainty (The Confidence Level is about 95 %)	Standard/Method of Measurement etc.
Angle gauge blocks Angle	10302	(0 ~ 360)°	0.6"	Indexing tables/ SICT-CP-10302
Autocollimators Angle	10303	(-1 000 ~ 1 000)"	0.5"	Fine angle generators/ SICT-CP-10303
Bevel protractors Angle Accuracy Accessory Angle	10304	(0 ~ 360)° (0 ~ 90)°	0.9' 0.7'	Angle Gauge Block, Coordinate Measur Machine/ SICT-CP-10304
Clinometers Angle	10306	(0 ~ 360)°	3.3"	Rotary tables/ SICT-CP-10306
Collimators Angle scale on the reticle	10307	(-30 ~ 30)'	5"	Total station/ SICT-CP-10307
Fine angle generators, level comparators Angle	10308	±1 000"	0.4"	Autocollimators/ SICT-CP-10308
Indexing tables Angle	10310	(0 ~ 360)°	0.5"	Polygons/ SICT-CP-10310
Plate/Square/Electric levels Angle Inclino meter Squareness	10311	(0 ~ 516)" (516 ~ 1 000)" (0 ~ 90)° (0 ~ 400) mm	0.4" 1.2" 0.05' 1.8 μm	Fine angle generators, Rotary tables/ SICT-CP-10311
Auto levels Straightness of Line of Sight Horizontal Angle Automatic level compensation range	10312	(0.6 ~ ∞) m (0 ~ 360)° (-30 ~ 30)°	0.03 mm 1.3' 5"	Calibration system for survey instrument, Indexing table, Rotary table/ SICT-CP-10312
Penta-prisms Angle	10314	90°	0.6"	Autocollimators/ SICT-CP-10314
Polygons Angle	10315	(0 ~ 360)°	0.4"	Indexing tables/ SICT-CP-10315
Rotary tables Angle	10316	(0 ~ 360)°	0.5"	Polygons/ SICT-CP-10316
Sine bars, plates, tables, centers (Sinebars) distance, between two roller center parallelism, between two roller parallelism, between flat-two roller (Plates) Center length Flatness Parallelism	10317	(100 ~ 300) mm (100 ~ 300) mm (100 ~ 300) mm (100 ~ 300) mm (100 ~ 300) mm (100 ~ 300) mm	$\sqrt{0.36^2 + (0.002 \times L_0)^2}$ μm 0.5 μm 0.6 μm $\sqrt{0.12^2 + (0.028 \times L_0)^2}$ μm 1.0 μm 1.2 μm	Mesuring Machine, Standard/ SICT-CP-10317
Squareness testers, right angle testers	10318	(0 ~ 600) mm	2.0 μm	Cylindrical Square, Precision Square/ SICT-CP-10318
Cylindrical squares	10319	(0 ~ 300) mm (300 ~ 600) mm	1.6 μm 1.9 μm	Cylindrical Square/ SICT-CP-10319
Precision squares Squareness Parallelism	10320	(0 ~ 600) mm (0 ~ 600) mm	2.9 μm 2.0 μm	contact coordinate measuring machines/ SICT-CP-10320
Theodolites, transits Straightness of Line of Sight Horizontal Angle Vertical Angle	10321	(0.6 ~ ∞) m (0 ~ 360)° (-45 ~ 45)°	0.09 mm 1.3" 1.3"	Calibration system for survey instrument, Indexing table/ SICT-CP-10321

103. Angle

Measured Quantity Instrument or Gauge	Field Code	Range	Measurement uncertainty (The Confidence Level is about 95 %)	Standard/Method of Measurement etc.
Angular displacement transducers Angle	10322	(0 ~ 360)°	2.9"	Rotary tables/ SICT-CP-10322
Alignment telescopes, line of sight collimators Straightness of Line of Sight Optical micrometer	10323	0 ~ ∞ (0 ~ 1.2) mm	0.022 mm 2 μm	Calibration system for survey instrument, Alignment telescope/ SICT-CP-10323
Calibration system for survey instruments Straightness of Line of Sight Horizontal Angle Vertical Angle	10324	(0.6 ~ ∞) m (0 ~ 360)° (-45 ~ 45)°	0.022 mm 2.1" 2.0"	Total station, Alignment telescope/ SICT-CP-10324
Jig transits Straightness of Line of Sight Horizontal Angle Vertical Angle	10325	(0.6 ~ ∞) m (0 ~ 360)° (-30 ~ 30)°	0.09 mm 1.3" 4.2"	Calibration system for survey instrument, Indexing table/ SICT-CP-10325
Laser levels Difference from absolute horizontal Difference to vertical about absolute horizontal Automatic level compensation range	10326	(0 ~ 4)' (0 ~ 4)' (-10 ~ 10)°	5" 8" 5"	Autocollimator, Rotary table/ SICT-CP-10326
Optical wedges Angular value on the wedge scale	10327	(-30 ~ 30)"	0.7"	Autocollimator, Rotary table/ SICT-CP-10327

104. Form

Measured Quantity Instrument or Gauge	Field Code	Range	Measurement uncertainty (The Confidence Level is about 95 %)	Standard/Method of Measurement etc.
Form testers Height length Width Angle	10401	(0 ~ 50) mm (0 ~ 50) mm 15° ~ 120°	1.0 μm 1.4 μm 2 ~	Form Standard Specimens Gage Block, Angle Gage Block/ SICT-CP-10401
Optical flats Flatness	10404	∅(0 ~ 60) mm ∅(60 ~ 100) mm	0.05 μm 0.08 μm	Optical Flat/ SICT-CP-10404
Optical parallels Flatness Parallelism	10405	∅(0 ~ 30) mm ∅(0 ~ 30) mm	0.05 μm 0.07 μm	Optical Flat,Gauge block comparator/ SICT-CP-10405
Parallel blocks Parallelism Flatness Length Difference	10406	(0 ~ 1 000) mm (0 ~ 1 000) mm (0 ~ 1 000) mm	1.5 μm 1.5 μm 2.2 μm	Electronic Micrometer/ SICT-CP-10406
Precision surface plates Flatness	10407	(2 000 × 2 000) mm (5 000 × 5 000) mm	2.0 μm 4.8 μm	Electronic Level/ SICT-CP-10407
Profile gauges	10408	(0 ~ 5) mm	0.7 μm	Gage Block/ SICT-CP-10408
Roundness measurement instruments Detector accuracy Rotational accuracy of spindle Rotational accuracy of axis	10409	(0 ~ 20) μm 360° 360°	0.51 μm 0.03 μm 0.04 μm	Roundness Standard Ball/ SICT-CP-10409
Form standard specimens Height Width Radius Angle	10410	(0 ~ 50) mm (0 ~ 100) mm (2.5 ~ 10) mm (10 ~ 50) mm (0 ~ 90)°	0.9 μm $\sqrt{0.59^2 + (0.0079 \times l_0)^2}$ μm 1.0 μm 1.4 μm 0.007°	Standard measuring machine, Non-contact coordinate measuring machine/ SICT-CP-10410
Roundness standard/roundness magnification standard specimens Standard specimens Standard ball	10411	(0 ~ 300) μm 360°	0.52 μm 0.08 μm	Roundness Tester/ SICT-CP-10411
Straight edges Straightness Parallelism	10412	(0 ~ 2 000) mm (0 ~ 2 000) mm	1.8 μm 1.8 μm	Electronic levels/ SICT-CP-10412
Straight rules Length	10413	(0 ~ 2 000) mm	0.10 mm	LASER INTERFEROMETER/ SICT-CP-10413
Test bars Roundness Cylindricity Run-out	10415	(0 ~ 400) mm (0 ~ 400) mm (0 ~ 400) mm	0.6 μm 0.6 μm 1.1 μm	Roundness Tester,Electronic Micrometer/ SICT-CP-10415
Spherometers	10416	(0 ~ 30) mm	0.3 μm	Gauge Block/ SICT-CP-10416

Note 1. l_0 unit : mm

105. Complex geometry

Measured Quantity Instrument or Gauge	Field Code	Range	Measurement uncertainty (The Confidence Level is about 95 %)	Standard/Method of Measurement etc.
Base gauges for electric bulb Inside diameter of pass/stop and screw Pitch	10501	(1 ~ 50) mm (0.3 ~ 10) mm	$\sqrt{0.47^2 + (0.0028 \times l_0)^2}$ μm 1.6 μm	Mesuring Machine, Standard/ SICT-CP-10501
Bench centers Difference of both center Flatness of both bed Center height difference	10502	(0 ~ 200) mm (200 ~ 500) mm (0 ~ 500) mm (0 ~ 200) mm (200 ~ 500) mm	1.8 μm 3.4 μm 1.5 μm 1.8 μm 3.4 μm	Test Bar/ SICT-CP-10502
Contact coordinate measuring machines	10503	(0 ~ 1 500) mm (0 ~ 600) mm (0 ~ 600) mm	$\sqrt{0.56^2 + (0.0044 \times l_0)^2}$ μm 3.2 μm 1.2 μm	Step Gauge/ SICT-CP-10503
Non-contact coordinate measuring machines	10504	(0 ~ 1 000) mm	$\sqrt{0.43^2 + (0.0034 \times l_0)^2}$ μm	Standard Scale/ SICT-CP-10504
Gauge block accessories Round the ministry of Justice A he ministry of Justice,Base block Center point Plane figure Parallelism(triangle edge) Parallelism(equilibrium tide)	10505	(0 ~ 50) mm (0 ~ 50) mm (0 ~ 20) mm (0 ~ 50) mm (0 ~ 300) mm (0 ~ 150) mm	$\sqrt{0.32^2 + (0.0044 \times l_0)^2}$ μm $\sqrt{0.26^2 + (0.0044 \times l_0)^2}$ μm 1.1 μm 0.04 μm 0.4 μm 0.4 μm	Gauge Block/ SICT-CP-10505
Hardness indenters Diameter Radius Angle	10508	(1 ~ 13) mm (0.2 ~ 6) mm (0 ~ 173) °	0.5 μm 1.0 μm 0.012 °	Standard measuring machine, Non-contact coordinate measuring machine/ SICT-CP-10410
Measuring microscopes, Profile projectors Length Magnification Angle	10511	(0 ~ 500) mm (5 ~ 100) ㎞ (0 ~ 360) °	$\sqrt{0.43^2 + (0.0034 \times l_0)^2}$ μm 0.04 % 0.9'	Standard Scale/ SICT-CP-10511
Micro measuring microscopes	10512	(0 ~ 1) mm (1 ~ 50) mm	0.7 μm 3.0 μm	Standard Scale/ SICT-CP-10512
Orifice plates Inside diameter Thickness	10513	(12.7 ~ 100) mm (100 ~ 300) mm (0 ~ 15) mm	$\sqrt{0.55^2 + (0.0030 \times l_0)^2}$ μm $\sqrt{1.0^2 + (0.0030 \times l_0)^2}$ μm 0.6 μm	Standard measuring machine/ SICT-CP-10513
Taper plug gauges Small end diameter Big end diameter Plane angle Gage height	10514	(2 ~ 200) mm (2 ~ 200) mm (0 ~ 90) ° (2 ~ 200) mm	$\sqrt{1.3^2 + (0.0041 \times l_0)^2}$ μm $\sqrt{1.4^2 + (0.0041 \times l_0)^2}$ μm 5.9" $\sqrt{1.2^2 + (0.0044 \times l_0)^2}$ μm	Measuring Machine, Standard/ SICT-CP-10514
Taper ring gauges Small end diameter Big end diameter Plane angle	10515	(5 ~ 200) mm (5 ~ 200) mm (0 ~ 90) °	2.5 μm 2.5 μm 0.006°	contact coordinate measuring machines/ SICT-CP-10515

Note 1. l_0 unit : mm

105. Complex geometry

Measured Quantity Instrument or Gauge	Field Code	Range	Measurement uncertainty (The Confidence Level is about 95 %)	Standard/Method of Measurement etc.
Stylus type roughness testers Roughness parameter(Ra) Roughness parameter(Rz) Mean width(RSm) H,D	10517	(0 ~ 2) μm (2 ~ 10) μm (0 ~ 7) μm (7 ~ 30) μm (0 ~ 300) μm (0 ~ 6) μm (6 ~ 20) μm	9 nm 24 nm 77 nm 0.27 μm 1.3 μm 63 nm 97 nm	Roughness Specimen/ SICT-CP-10517
Socket gauges for electric bulb Outside diameter of pass/stop and screw Pitch	10518	(1 ~ 50) mm (0.3 ~ 10) mm	$\sqrt{0.44^2 + (0.0028 \times l_0)^2}$ μm 1.6 μm	Mesuring Machine, Standard/ SICT-CP-10518
Roughness standard/comparison specimens Depth(H) Mean width(RSm) Roughness parameter(Ra) Roughness parameter(Rz)	10519	(0 ~ 6) μm (6 ~ 20) μm (0 ~ 300) μm (0 ~ 2) μm (2 ~ 10) μm (0 ~ 7) μm (7 ~ 30) μm	$\sqrt{(9.6 \times R)^2 + 12^2}$ nm $\sqrt{(8.94 \times R)^2 + 15^2}$ nm $\sqrt{(0.01 \times R)^2 + 0.51^2}$ μm $\sqrt{(10 \times R)^2 + 2.6^2}$ nm $\sqrt{(9.2 \times R)^2 + 7.4^2}$ nm $\sqrt{(29.2 \times R)^2 + 7.4^2}$ nm $\sqrt{(0.025 \times R)^2 + 0.096^2}$ μm	Roughness Tester/ SICT-CP-10519
Thread plug gauges Outside diameter Effective diameter Pitch Half angle	10525	(1 ~ 205) mm (1 ~ 210) mm (0.3 ~ 10) mm (0.5 ~ 45) °	1.7 μm 1.1 μm 1.2 μm 2'	Mesuring Machine, Standard/ SICT-CP-10525
Taper thread plug gauges Half angle Pitch Gage length Notch length Small outside diameter Big outside diameter Small effective diameter Big effective diameter	10526	(0 ~ 45) ° (0.3 ~ 6) mm (2 ~ 50) mm (2 ~ 50) mm (2 ~ 200) mm (2 ~ 200) mm (2 ~ 200) mm (2 ~ 200) mm	2' 1.3 μm 2.6 μm 3.6 μm 2.3 μm 4.8 μm 2.9 μm 5.1 μm	Mesuring Machine, Standard/ SICT-CP-10526
Thread ring gauges Minor diameter Effective diameter Pitch	10527	(3 ~ 200) mm (3 ~ 200) mm (0.3 ~ 10) mm	1.5 μm 2.3 μm 1.6 μm	Mesuring Machine, Standard/ SICT-CP-10527
Taper thread ring gauges Alternation Thickness Notch length	10528	±3 mm (0 ~ 100) mm (0 ~ 100) mm	2.7 μm 2.3 μm 3.2 μm	Mesuring Machine, Standard/ SICT-CP-10528
V-blocks, box blocks Plane figure Parallelism Difference of both part	10529	(5 ~ 300) mm (5 ~ 300) mm (5 ~ 300) mm	1.7 μm 2.0 μm 2.8 μm	contact coordinate measuring machines/ SICT-CP-10529
Position gauges Distance Diameter Angle	10530	(0 ~ 1 000) mm (2 ~ 12) mm (12 ~ 200) mm (0 ~ 360) °	$\sqrt{4.9^2 + (0.0054 \times l)^2}$ μm $\sqrt{2.4^2 + (0.0028 \times l)^2}$ μm $\sqrt{3.3^2 + (0.0028 \times l)^2}$ μm 5.2°	Contact coordinate measuring machine/ SICT-CP-10530
SEM/TEM/SPM/AFM microscopes Magnification	10531	(5 ~ 100) × (100 ~ 500 000) ×	0.003 5 0.003 0	Magnification reference specimen/ SICT-CP-10531

Note 1. l_0 unit : mm, R unit : μm

106. Various dimensional

Measured Quantity Instrument or Gauge	Field Code	Range	Measurement uncertainty (The Confidence Level is about 95 %)	Standard/Method of Measurement etc.
Inside/outside/gear tooth calipers, caliper gauges Inside/Outside calipers Caliper gauges	10601	(0 ~ 2 000) mm (0 ~ 300) mm	$\sqrt{8.2^2 + (0.007 \times l_0)^2}$ μm $\sqrt{3.7^2 + (0.0032 \times l_0)^2}$ μm	Gauge Block/ SICT-CP-10601
Cylinder/bore gauges Cylinder gauges Hole gauges	10603	(0 ~ 1 000) mm (0.1 ~ 25) mm	1.0 μm 3.3 μm	Dial Gauge Tester/ SICT-CP-10603
Depth gauges, depth micrometers Depth micrometers Depth gauges	10604	(0 ~ 300) mm (0 ~ 1 000) mm	$\sqrt{0.86^2 + (0.0034 \times l_0)^2}$ μm $\sqrt{5.9^2 + (0.0048 \times l_0)^2}$ μm	Gauge Block/ SICT-CP-10604
Dial/digital gauges	10605	(0 ~ 100) mm (0 ~ 25) mm	$\sqrt{0.21^2 + (0.0082 \times l_0)^2}$ μm $\sqrt{0.59^2 + (0.004 \times l_0)^2}$ μm	Dial Gauge Tester/
Geodesic baselines	10606	(5 ~ 280) m	$\sqrt{1.7^2 + 0.0033^2 \times l^2}$ mm	Total station/ SICT-CP-10606
Grind gauges Depth Straightness	10608	(0 ~ 1) mm (0 ~ 150) mm	1.8 μm 2.5 μm	Electronic micrometer/ SICT-CP-10608
Micro indicators, test indicators	10609	(0 ~ 5) mm	0.22 μm	Dial Gauge Tester/ SICT-CP-10609
Micrometer heads	10610	(0 ~ 50) mm	0.8 μm	Gauge Block/ SICT-CP-10610
3-points, Micrometers	10611	(2 ~ 200) mm (200 ~ 300) mm	$\sqrt{1.3^2 + (0.0034 \times l_0)^2}$ μm 3 μm	Ring Gauge/ SICT-CP-10611
Inside micrometers Length Accuracy of scale Extension rod	10612	(5 ~ 300) mm (25 ~ 500) mm (13 ~ 500) mm	$\sqrt{1.1^2 + (0.0042 \times l_0)^2}$ μm $\sqrt{1.1^2 + (0.0042 \times l_0)^2}$ μm $\sqrt{1.2^2 + (0.0048 \times l_0)^2}$ μm	Gauge Block/ SICT-CP-10612
Outside micrometers Outside micrometers V-anvil micrometers	10613	(0 ~ 25) mm (25 ~ 1 000) mm (1 ~ 85) mm	$\sqrt{0.2^2 + (0.003 \times l_0)^2}$ μm $\sqrt{0.83^2 + (0.003 \times l_0)^2}$ μm 0.8 μm	Gauge Block, cylindrical plug gauges/ SICT-CP-10613
Particle counters (Air) Flow Threshold voltage Counting efficiency (Liquid) Flow Threshold voltage	10615	(0.1 ~ 1) μm (0 ~ 100) L/min (0 ~ 10) V (0 ~ 110) % (0.05 ~ 25) μm (0 ~ 100) mL/min (0 ~ 10) V	0.09 L/min 0.42 mV 4.1 % 1.4 mL/min 0.42 mV	Particle calibration system/ SICT-CP-10615

Note 1. l_0 unit : mm (10606 unit : m)

106. Various dimensional

Measured Quantity Instrument or Gauge	Field Code	Range	Measurement uncertainty (The Confidence Level is about 95 %)	Standard/Method of Measurement etc.
Standard sieves Sieve opening Wire rod diameter	10617	(0.004 ~ 10) mm (0.004 ~ 130) mm	1.5 μm 2.4 μm	Non-contact coordinate measuring machines/ SICT-CP-10617
Water level meters	10619	(0.05 ~ 6.5) m	1.6 mm	Laser distance meter/ SICT-CP-10619
Welding gauges Height or depth Rule Angle	10620	(0 ~ 100) mm (0 ~ 100) mm (0 ~ 90)°	8.2 μm 6.0 μm 0.7'	Non-contact coordinate measuring machine,Gauge Block/ SICT-CP-10620
Optical micrometers Optical axis shift	10621	(0 ~ 1.2) mm (1.2 ~ 5) mm (5 ~ 10) mm	2 μm 3 μm 0.03 mm	Standard Scale/ SICT-CP-10621

201. Mass

Measured Quantity Instrument or Gauge	Field Code	Range	Measurement uncertainty (The Confidence Level is about 95 %)	Standard/Method of Measurement etc.
Auto-hopper scale balances	20102	(0 ~ 10) kg (10 ~ 50) kg (50 ~ 200) kg (200 ~ 500) kg (500 ~ 1 000) kg	1.2 g 14 g 21 g 49 g 0.10 kg	Hopper Scale Weight/ SICT-CP-20102
Auto-packer scale balances	20103	(0 ~ 10) kg (10 ~ 50) kg (50 ~ 200) kg	0.8 g 7.7 g 16 g	Weight/ SICT-CP-20103
Axle weigher balances Portable	20104	(100 ~ 500) kg (500 ~ 1 000) kg (1 000 ~ 2 000) kg (2 000 ~ 5 000) kg (5 000 ~ 10 000) kg (10 000 ~ 30 000) kg	0.2 kg 0.4 kg 1 kg 5 kg 10 kg 24 kg	Force Calibration Machine/ SICT-CP-20104
Dial platform scale balances	20106	(0 ~ 30) kg (30 ~ 60) kg (60 ~ 100) kg	42 g 0.08 kg 0.21 kg	Weight/ SICT-CP-20106
Dial swing scale balances	20107	(0 ~ 1) kg (1 ~ 10) kg (10 ~ 20) kg (20 ~ 50) kg (50 ~ 100) kg (100 ~ 200) kg (200 ~ 500) kg (500 ~ 1 000) kg (1 000 ~ 2 000) kg (2 000 ~ 5 000) kg	0.96 g 9.6 g 20 g 48 g 96 g 0.23 kg 0.48 kg 0.96 kg 1.9 kg 4.6 kg	Weight/ SICT-CP-20107
Electric balances	20109	(0 ~ 2) g (2 ~ 6) g (6 ~ 20) g (20 ~ 50) g (50 ~ 100) g (100 ~ 200) g (200 ~ 500) g (500 ~ 1 000) g (1 ~ 2) kg (2 ~ 5) kg (5 ~ 10) kg (10 ~ 25) kg (25 ~ 40) kg (40 ~ 60) kg (60 ~ 150) kg (150 ~ 600) kg (600 ~ 1 000) kg (1 000 ~ 2 000) kg (2 000 ~ 5 000) kg	7.0 μg 9.3 μg 14 μg 19 μg 29 μg 0.05 mg 0.10 mg 0.20 mg 0.5 mg 1.0 mg 3 mg 6 mg 16 mg 24 mg 0.30 g 1.2 g 2.0 g 38 g 0.10 kg	Weight/ SICT-CP-20109

201. Mass

Measured Quantity Instrument or Gauge	Field Code	Range	Measurement uncertainty (The Confidence Level is about 95 %)	Standard/Method of Measurement etc.
Manual swing scale balances	20111	(0 ~ 50) kg (50 ~ 200) kg (200 ~ 500) kg (500 ~ 1 000) kg	38 g 0.19 kg 0.38 kg 0.94 kg	Weight/ SICT-CP-20111
Platform scale balances	20112	(0 ~ 200) kg (200 ~ 500) kg (500 ~ 1 000) kg	46 g 0.09 kg 0.46 kg	Weight/ SICT-CP-20112
Spring scale balances	20113	(0 ~ 10) kg (10 ~ 50) kg (50 ~ 100) kg	21 g 0.08 kg 0.21 kg	Weight/ SICT-CP-20113
Weights	20116	(1 mg ~ 20 kg) 1 mg 2 mg 5 mg 10 mg 20 mg 50 mg 100 mg 200 mg 500 mg 1 g 2 g 5 g 10 g 20 g 50 g 100 g 200 g 500 g 1 kg 2 kg 5 kg 10 kg 20 kg (20 ~ 100) kg 50 kg 100 kg (100 ~ 200) kg 200 kg (200 ~ 1 000) kg 500 kg 1 000 kg	(Class E2) 1.0 µg 1.0 µg 1.0 µg 1.0 µg 1.2 µg 1.4 µg 1.7 µg 2.3 µg 2.9 µg 3.5 µg 4.6 µg 5.8 µg 7.0 µg 9.3 µg 12 µg 18 µg 36 µg 95 µg 0.12 mg 0.36 mg 0.94 mg 1.8 mg 3.7 mg (Class F2) 0.12 g 0.21 g (Class M1) 1.0 g (Class F2) 1.3 g 2.1 g	Weights, Mass Comparator/ SICT-CP-20116

202. Force

Measured Quantity Instrument or Gauge	Field Code	Range	Measurement uncertainty (The Confidence Level is about 95 %)	Standard/Method of Measurement etc.
Force measuring devices Force	20202	(0.4 ~ 20) N (20 ~ 50) N (50 ~ 100) N (100 ~ 200) N (200 ~ 500) N (0.5 ~ 1) kN (1 ~ 2) kN (2 ~ 5) kN (5 ~ 10) kN (10 ~ 20) kN (20 ~ 50) kN (50 ~ 100) kN (100 ~ 200) kN (200 ~ 500) kN (500 ~ 1 000) kN	6.0×10^{-4} 8.4×10^{-5} 8.5×10^{-5} 7.3×10^{-5} 6.9×10^{-5} 9.2×10^{-5} 9.0×10^{-5} 8.4×10^{-5} 8.7×10^{-5} 3.6×10^{-4} 4.1×10^{-4} 4.8×10^{-4} 4.5×10^{-4} 4.3×10^{-4} 4.5×10^{-4}	Force Calibration Machine/ SICT-CP-20202
Tension/compression testing machines tensile compression	20203	0.1 N ~ 2 kN (2 ~ 5) kN (5 ~ 10) kN (10 ~ 20) kN (20 ~ 50) kN (50 ~ 100) kN (100 ~ 300) kN (0.1 ~ 50) N (50 ~ 100) N (100 ~ 200) N (200 ~ 500) N (0.5 ~ 1) kN (1 ~ 2) kN (2 ~ 5) kN (5 ~ 10) kN (10 ~ 20) kN (20 ~ 50) kN (50 ~ 100) kN (100 ~ 300) kN (300 ~ 500) kN (500 ~ 1 000) kN (1 000 ~ 3 000) kN	1.2×10^{-3} 1.3×10^{-3} 1.4×10^{-3} 1.5×10^{-3} 1.4×10^{-3} 1.5×10^{-3} 1.4×10^{-3} 1.2×10^{-3} 1.5×10^{-3} 1.3×10^{-3} 1.4×10^{-3} 1.3×10^{-3} 1.4×10^{-3} 1.3×10^{-3} 1.4×10^{-3} 1.3×10^{-3} 1.4×10^{-3} 1.5×10^{-3} 1.4×10^{-3} 1.5×10^{-3} 1.4×10^{-3} 1.5×10^{-3} 1.4×10^{-3} 1.6×10^{-3}	Weights, Force Measuring Device/ SICT-CP-20203
push-pull gauge Force	20204	(0.02 ~ 0.2) N 0.2 N ~ 2 kN (2 ~ 5) kN	1.4×10^{-2} 1.3×10^{-3} 8.4×10^{-4}	Weights, Force Calibration Machine/ SICT-CP-20204

203. Torque

Measured Quantity Instrument or Gauge	Field Code	Range	Measurement uncertainty (The Confidence Level is about 95 %)	Standard/Method of Measurement etc.
Torque measuring devices Torque	20302	(0.001 ~ 1) N·m (1 ~ 10) N·m (10 ~ 20) N·m (20 ~ 50) N·m (50 ~ 100) N·m (100 ~ 200) N·m (200 ~ 500) N·m (500 ~ 1 000) N·m (1 000 ~ 2 000) N·m	3.3×10^{-3} 4.1×10^{-4} 7.5×10^{-4} 2.3×10^{-4} 3.4×10^{-4} 2.1×10^{-4} 2.2×10^{-4} 1.5×10^{-4} 1.6×10^{-4}	Torque Calibration Machine/ SICT-CP-20302
Torque wrenches/drivers Torque	20303	(0.02 ~ 0.1) N·m (0.1 ~ 0.5) N·m (0.5 ~ 1) N·m (1 ~ 2) N·m (2 ~ 5) N·m (5 ~ 10) N·m (10 ~ 20) N·m (20 ~ 50) N·m (50 ~ 100) N·m (100 ~ 200) N·m (200 ~ 500) N·m (500 ~ 1 000) N·m (1 000 ~ 2 000) N·m	1.4×10^{-2} 9.5×10^{-3} 7.8×10^{-3} 6.2×10^{-3} 4.6×10^{-3} 4.5×10^{-3} 4.7×10^{-3} 4.5×10^{-3} 4.9×10^{-3} 3.8×10^{-3} 3.7×10^{-3} 3.8×10^{-3} 2.8×10^{-3}	Torque Measuring Device/ SICT-CP-20303

204. Pressure

Measured Quantity Instrument or Gauge	Field Code	Range	Measurement uncertainty (The Confidence Level is about 95 %)	Standard/Method of Measurement etc.
Altimeters	20401	(-4 000 ~ 20 000) m (20 000 ~ 47 000) m	12 m 15 m	Digital Manometer, Air Dead Weight Tester/ SICT-CP-20401
Manometers	20402	(0 ~ 200) kPa	2.9×10^{-3}	Digital Manometer, Air Dead Weight Tester/ SICT-CP-20402
Pneumatic pressure ballances	20403	(5 ~ 7 000) kPa	4.2×10^{-5}	Dead Weight Tester/ SICT-CP-20403
Hydraulic pressure ballances	20404	(0.2 ~ 20) MPa (20 ~ 200) MPa	6.4×10^{-5} 7.0×10^{-5}	Dead Weight Tester/ SICT-CP-20404
Air data test systems Static pressure Dynamic pressure	20405	(-2 500 ~ 20 000) m (20 000 ~ 30 500) m (0 ~ 342) km/hr (342 ~ 2 122) km/hr	0.8 m 7 m 0.1 km/hr 0.3 km/hr	Digital Manometer, Air Dead Weight Tester/ SICT-CP-20405
Absolute pressure gauges Dial, digital	20406	(5 ~ 350) kPa abs (350 ~ 7 000) kPa abs (7 ~ 200) MPa abs	4.0×10^{-5} 4.3×10^{-5} 7.4×10^{-5}	Digital Manometer, Air Dead Weight Tester/ SICT-CP-20406
Blood pressure gauges	20407	(0 ~ 40) kPa	0.01 kPa	Digital Manometer/ SICT-CP-20407
Compound pressure gauges	20408	(-95 ~ 7 000) kPa	4.4×10^{-5}	Air Dead Weight Tester/ SICT-CP-20408
Differential pressure gauges	20409	(0 ~ 500) Pa (500 ~ 5 000) Pa (5 ~ 350) kPa (350 ~ 7 000) kPa	0.10 Pa 1.0 Pa 4.2×10^{-5} 4.6×10^{-5}	Digital Manometer, Air Dead Weight Tester/ SICT-CP-20409
Gauge pressure gauges	20411	(0 ~ 500) Pa (500 ~ 5 000) Pa (5 ~ 350) kPa (350 ~ 7 000) kPa (7 ~ 200) MPa (200 ~ 500) MPa	0.10 Pa 1.0 Pa 4.2×10^{-5} 4.6×10^{-5} 8.6×10^{-5} 2.6×10^{-4}	Digital Manometer, Air Dead Weight Tester, Oil Dead Weight Tester/ SICT-CP-20411
Pressure transducers/transmitters Absolute pressure Gauge pressure	20412	(5 ~ 5 000) kPa abs (5 ~ 200) MPa abs (0 ~ 500) Pa (500 ~ 5 000) Pa (5 ~ 5 000) kPa (5 ~ 500) MPa	2.2×10^{-4} 2.4×10^{-4} 0.10 Pa 1.0 Pa 2.2×10^{-4} 2.4×10^{-4}	Digital Manometer, Air Dead Weight Tester, Oil Dead Weight Tester/ SICT-CP-20412
Dial type vacuum gauges	20413	(-95 ~ 0) kPa	0.059 kPa	Air Dead Weight Tester, SICT-CP-20413
Water depth meters	20414	(0 ~ 198.12) m (198.12 ~ 350.52) m	0.062 m 0.46 m	Digital Manometer/ SICT-CP-20414

205. Vacuum

Measured Quantity Instrument or Gauge	Field Code	Range	Measurement uncertainty (The Confidence Level is about 95 %)	Standard/Method of Measurement etc.
Capacitance diaphragm gauges Vacuum	20501	(0.133 ~ 13.3) Pa abs (13.3 ~ 133.3) Pa abs (133.3 ~ 1 333) Pa abs (1.333 ~ 13.332) kPa abs (13.332 ~ 133.322) kPa abs	0.051 Pa abs 0.49 Pa abs 1.5 Pa abs 12 Pa abs 17 Pa abs	Baratron gauge, SRG / SICT-CP-20501
Spinning rotor gauges Vacuum	20502	0.15 mPa abs ~ 0.01 Pa abs	3.4×10^{-2}	Baratron gauge, SRG / SICT-CP-20502
Ionization gauges Vacuum	20503	0.093 mPa abs ~ 0.15 mPa abs 0.15 mPa abs ~ 0.01 Pa abs	6.0×10^{-2} 3.5×10^{-2}	Baratron gauge, SRG, Ion / SICT-CP-20503
Thermal conductivity gauges; pirani, thermocouple, convection, etc. Vacuum	20504	(0.133 ~ 13.3) Pa abs (13.3 ~ 133.3) Pa abs (133.3 ~ 1 333) Pa abs (1.333 ~ 13.332) kPa abs (13.332 ~ 133.322) kPa abs	0.051 Pa abs 0.49 Pa abs 1.5 Pa abs 13 Pa abs 17 Pa abs	Baratron gauge, SRG / SICT-CP-20504
Standard leaks, Helium leak detectors Leak	20505	22.0 $\mu\text{Pa m}^3/\text{s}$ 1.60 $\mu\text{Pa m}^3/\text{s}$ 0.51 $\mu\text{Pa m}^3/\text{s}$ 15.0 nPa m^3/s 6.4 nPa m^3/s 0.24 nPa m^3/s	4.8 $\mu\text{Pa m}^3/\text{s}$ 0.38 $\mu\text{Pa m}^3/\text{s}$ 0.098 $\mu\text{Pa m}^3/\text{s}$ 3.2 nPa m^3/s 1.3 nPa m^3/s 0.049 nPa m^3/s	Standard leaks, Helium leak detectors / SICT-CP-20505

206. Volume

Measured Quantity Instrument or Gauge	Field Code	Range	Measurement uncertainty (The Confidence Level is about 95 %)	Standard/Method of Measurement etc.
Volumetric glasswares	20601	(0 ~ 0.1) ml (0.1 ~ 0.5) ml (0.5 ~ 1) ml (1 ~ 2) ml (2 ~ 5) ml (2 ~ 10) ml (10 ~ 25) ml (25 ~ 50) ml (50 ~ 100) ml (100 ~ 200) ml (200 ~ 250) ml (250 ~ 500) ml (500 ~ 1 000) ml (1 000 ~ 2 000) ml (2 000 ~ 5 000) ml (5 000 ~ 10 000) ml	0.31 μ l 0.40 μ l 0.43 μ l 1.1 μ l 1.7 μ l 2.5 μ l 4.3 μ l 5.1 μ l 7.9 μ l 13 μ l 43 μ l 69 μ l 92 μ l 0.17 ml 0.49 ml 0.87 ml	Weight, balances / SICT-CP-20601
Pycnometers	20602	(0 ~ 50) ml (50 ~ 100) ml (100 ~ 250) ml (250 ~ 500) ml	2.4 μ l 4.4 μ l 10 μ l 21 μ l	Weight, balances / SICT-CP-20602
Rain gauges	20603	tipping bucket type : Rainfall intensity : (5 ~ 300) mm/h (0.1 ~ 1) mm standard type : (0.1 ~ 10) mm (10 ~ 50.8) mm (50.8 ~ 178) mm	 1.2 $\times 10^{-3}$ 0.021 mm 0.054 mm 0.30 mm	Weight, balances / SICT-CP-20603
Standard volume vessels	20604	(0 ~ 20) L (20 ~ 200) L (200 ~ 10 000) L	 9.0 $\times 10^{-5}$ 1.3 $\times 10^{-4}$ 1.1 $\times 10^{-3}$	Balances, Master Meter, Standard volume vessel/ SICT-CP-20604
Concrete air content meters	20605	(0 ~ 10) %	0.032 %	Weight, balances / SICT-CP-20605
Piston type volume meters	20606	(0 ~ 1) μ l (1 ~ 2) μ l (2 ~ 5) μ l (5 ~ 10) μ l (0.01 ~ 0.02) ml (0.02 ~ 0.05) ml (0.05 ~ 0.1) ml (0.1 ~ 0.2) ml (0.2 ~ 0.5) ml (0.5 ~ 1) ml (1 ~ 2) ml (2 ~ 5) ml (5 ~ 10) ml (10 ~ 20) ml (20 ~ 50) ml (50 ~ 100) ml	0.004 μ l 0.005 μ l 0.006 μ l 0.008 μ l 0.018 μ l 0.035 μ l 0.047 μ l 0.14 μ l 0.35 μ l 0.65 μ l 1.6 μ l 1.9 μ l 2.4 μ l 5.0 μ l 14 μ l 64 μ l	Weight, balances / SICT-CP-20606

207. Density

Measured Quantity Instrument or Gauge	Field Code	Range	Measurement uncertainty (The Confidence Level is about 95 %)	Standard/Method of Measurement etc.
Liquid density meters	20702	(0.7 ~ 1.4) g/cm ³	0.000 078 g/cm ³	Density standard materials/ SICT-CP-20702
Salinity meters	20704	(0 ~ 10) % (10 ~ 26) %	0.004 % 0.007 %	NaCl/ SICT-CP-20704
Sucrose meters	20705	(0 ~ 20) % (20 ~ 60) % (60 ~ 80) %	0.014 % 0.016 % 0.025 %	Sucrose/ SICT-CP-20705
Hydrometers; density, specific gravity, alcohol, API, baume, sugar, milk, soil, salinity, LPG, etc.	20706			
density		(0.600 ~ 0.700) g/cm ³ (0.700 ~ 0.800) g/cm ³ (0.800 ~ 0.900) g/cm ³ (0.900 ~ 1.000) g/cm ³ (1.000 ~ 1.100) g/cm ³ (1.100 ~ 1.200) g/cm ³ (1.200 ~ 1.300) g/cm ³ (1.300 ~ 1.400) g/cm ³ (1.400 ~ 1.500) g/cm ³ (1.500 ~ 1.600) g/cm ³ (1.600 ~ 1.700) g/cm ³ (1.700 ~ 1.800) g/cm ³ (1.800 ~ 1.900) g/cm ³ (1.900 ~ 2.000) g/cm ³ (2.000 ~ 2.200) g/cm ³ (2.200 ~ 3.000) g/cm ³ (3.000 ~ 3.600) g/cm ³ (3.600 ~ 4.000) g/cm ³	0.000 035 g/cm ³ 0.000 038 g/cm ³ 0.000 042 g/cm ³ 0.000 046 g/cm ³ 0.000 050 g/cm ³ 0.000 055 g/cm ³ 0.000 059 g/cm ³ 0.000 066 g/cm ³ 0.000 071 g/cm ³ 0.000 075 g/cm ³ 0.000 079 g/cm ³ 0.000 084 g/cm ³ 0.000 088 g/cm ³ 0.000 093 g/cm ³ 0.000 25 g/cm ³ 0.000 28 g/cm ³ 0.000 30 g/cm ³ 0.000 32 g/cm ³	Solid density standard material, Hydrostatic weighing Apparatus/ SICT-CP-20706-1
specific gravity		0.590 ~ 0.700 0.700 ~ 0.800 0.800 ~ 0.900 0.900 ~ 1.000 1.000 ~ 1.100 1.100 ~ 1.200 1.200 ~ 1.300 1.300 ~ 1.400 1.400 ~ 1.500 1.500 ~ 1.600 1.600 ~ 1.800 1.800 ~ 2.000 2.000 ~ 2.020 2.020 ~ 2.500 2.500 ~ 3.000	0.000 068 0.000 069 0.000 072 0.000 075 0.000 078 0.000 082 0.000 086 0.000 091 0.000 096 0.000 10 0.000 11 0.000 12 0.000 26 0.000 60 0.000 61	Solid density standard material, Hydrostatic weighing Apparatus/ SICT-CP-20706-2

* 20704, 20705, 20706, 20707 unit % is weight percent.

207. Density

Measured Quantity Instrument or Gauge	Field Code	Range	Measurement uncertainty (The Confidence Level is about 95 %)	Standard/Method of Measurement etc.	
Hydrometers; density, specific gravity, alcohol, API, baume, sugar, milk, soil, salinity, LPG, etc.	20706	alcohol (Volumn)	(0 ~ 10) %	0.039 %	Solid density standard material, Hydrostatic weighing Apparatus/ SICT-CP-20706-3
			(10 ~ 30) %	0.043 %	
			(30 ~ 40) %	0.038 %	
			(40 ~ 50) %	0.030 %	
			(50 ~ 60) %	0.025 %	
			(60 ~ 70) %	0.023 %	
			(70 ~ 80) %	0.020 %	
			(80 ~ 90) %	0.019 %	
			(90 ~ 100) %	0.017 %	
		API	-1 ~ 51	0.013	Solid density standard material, Hydrostatic weighing Apparatus/ SICT-CP-20706-4
			51 ~ 101	0.014	
		Baumé-light	10 ~ 30	0.015	Solid density standard material, Hydrostatic weighing Apparatus/ SICT-CP-20706-5
			30 ~ 40	0.016	
			40 ~ 60	0.018	
			60 ~ 70	0.019	
			70 ~ 100	0.12	
		Baumé - heavy	0 ~ 40	0.014	Solid density standard material, Hydrostatic weighing Apparatus/ SICT-CP-20706-5
			40 ~ 75	0.013	
		sugar	(0 ~ 10) %	0.018 %	Solid density standard material, Hydrostatic weighing Apparatus/ SICT-CP-20706-6
			(10 ~ 90) %	0.017 %	
		milk	(15 ~ 20)	0.081	Solid density standard material, Hydrostatic weighing Apparatus/ SICT-CP-20706-7
			(20 ~ 40)	0.082	
		Bouyoucos	(-5.0 ~ 60.0) g/L	0.14 g/L	Solid density standard material, Hydrostatic weighing Apparatus/ SICT-CP-20706-8
		salinity	(0 ~ 26.4) %	0.025 %	Solid density standard material, Hydrostatic weighing Apparatus/ SICT-CP-20706-9
		LPG	(0.50 ~ 0.55) g/cm ³	0.000 065 g/cm ³	Solid density standard material, Hydrostatic weighing Apparatus/ SICT-CP-20706-10
			(0.55 ~ 0.60) g/cm ³	0.000 066 g/cm ³	
			(0.60 ~ 0.65) g/cm ³	0.000 068 g/cm ³	

* 20704, 20705, 20706, 20707 unit % is weight percent.

207. Density

Measured Quantity Instrument or Gauge	Field Code	Range	Measurement uncertainty (The Confidence Level is about 95 %)	Standard/Method of Measurement etc.
Hydrometers; density, specific gravity, alcohol, API, baume, sugar, milk, soil, salinity, LPG, etc. Twaddell	20706	0 ~ 12 12 ~ 74 74 ~ 102 102 ~ 170 170 ~ 200	0.016 0.059 0.060 0.061 0.062	Solid density standard material, Hydrostatic weighing Apparatus/ SICT-CP-20706-11
Chloride meters	20707	(0 ~ 0.1) % (0.1 ~ 2.0) %	0.000 2 % 0.001 0 %	Chlorine standard liquid/ SICT-CP-20707
Others; Solid density Stainless steel Glass	20799	(1 ~ 2) g (2 ~ 5) g (5 ~ 10) g (10 ~ 20) g (20 ~ 50) g (50 ~ 100) g (100 ~ 500) g (1 ~ 2) g (2 ~ 5) g (5 ~ 10) g (10 ~ 20) g (20 ~ 500) g	0.004 6 g/cm ³ 0.002 4 g/cm ³ 0.001 0 g/cm ³ 0.000 59 g/cm ³ 0.000 43 g/cm ³ 0.000 37 g/cm ³ 0.000 36 g/cm ³ 0.000 46 g/cm ³ 0.000 25 g/cm ³ 0.000 14 g/cm ³ 0.000 12 g/cm ³ 0.000 11 g/cm ³	Solid density standard material, Hydrostatic weighing Apparatus/ SICT-CP-20706-11

* 20704, 20705, 20706, 20707 unit % is weight percent.

208. Viscosity

Measured Quantity Instrument or Gauge	Field Code	Range	Measurement uncertainty (The Confidence Level is about 95 %)	Standard/Method of Measurement etc.
Kinematic viscometers; capillary, etc.	20801	(2.5 ~ 100 000) mPa·s	1.3×10^{-2}	Viscosity CRM/ SICT-CP-20801
Dynamic viscometers; rotational, etc. Viscosity	20802	(2.5 ~ 200 000) mPa·s	1.7×10^{-2}	Viscosity CRM/ SICT-CP-20802

209. Fluid flow

Measured Quantity Instrument or Gauge	Field Code	Range	Measurement uncertainty (The Confidence Level is about 95 %)	Standard/Method of Measurement etc.
Anemometers; hot-wire	20901	(0.1 ~ 1.0) m/s (1.0 ~ 2.0) m/s (2.0 ~ 70) m/s	8.7×10^{-2} 8.4×10^{-3} 4.8×10^{-3}	Wind Tunnel, Pitot tube, LDV/ SICT-CP-20901
Anemometers; pitot tube, etc.	20902	(0.1 ~ 1.0) m/s (1.0 ~ 2.0) m/s (2.0 ~ 70) m/s	8.7×10^{-2} 8.4×10^{-3} 4.8×10^{-3}	Wind Tunnel, Pitot tube, LDV/ SICT-CP-20902
Gas flowmeters; differential pressure	20908	$(1.2 \times 10^{-5} \sim 0.12) \text{ m}^3/\text{h}$ (0.12 ~ 300) m ³ /h (300 ~ 4 000) m ³ /h	1.9×10^{-3} 2.0×10^{-3} 3.6×10^{-3}	Sonic Nozzle/SICT-CP-20928 Master Meter/SICT-CP-20929
Liquid flowmeters; differential pressure	20909	(0.01 ~ 50) m ³ /h (0.000 12 ~ 0.01) m ³ /h (0.01 ~ 50) m ³ /h	1.2×10^{-3} 2.6×10^{-3} 7.0×10^{-4}	Master Meter/SICT-CP-20926 Weight measuring method/ SICT-CP-20927
Liquid flowmeters; electromagnetic	20910	(0.01 ~ 50) m ³ /h (0.000 12 ~ 0.01) m ³ /h (0.01 ~ 50) m ³ /h	1.2×10^{-3} 2.6×10^{-3} 7.0×10^{-4}	Master Meter/SICT-CP-20926 Weight measuring method/ SICT-CP-20927
Gas flowmeters; thermal mass, etc.	20911	$(1.2 \times 10^{-5} \sim 0.12) \text{ m}^3/\text{h}$ (0.12 ~ 300) m ³ /h (300 ~ 4 000) m ³ /h	1.9×10^{-3} 2.0×10^{-3} 3.6×10^{-3}	Sonic Nozzle/SICT-CP-20928 Master Meter/SICT-CP-20929
Liquid flowmeters; Coriolis, etc.	20912	(0.01 ~ 50) m ³ /h (0.000 12 ~ 0.01) m ³ /h (0.01 ~ 50) m ³ /h	1.2×10^{-3} 2.6×10^{-3} 7.0×10^{-4}	Master Meter/SICT-CP-20926 Weight measuring method/ SICT-CP-20927
Gas flowmeters; positive displacement	20914	$(1.2 \times 10^{-5} \sim 0.12) \text{ m}^3/\text{h}$ (0.12 ~ 300) m ³ /h (300 ~ 4 000) m ³ /h	1.9×10^{-3} 2.0×10^{-3} 3.6×10^{-3}	Sonic Nozzle/SICT-CP-20928 Master Meter/SICT-CP-20929
Liquid flowmeters; positive displacement	20915	(0.01 ~ 50) m ³ /h (0.000 12 ~ 0.01) m ³ /h (0.01 ~ 50) m ³ /h	1.2×10^{-3} 2.6×10^{-3} 7.0×10^{-4}	Master Meter/SICT-CP-20926 Weight measuring method/ SICT-CP-20927
Gas flowmeters; turbine	20916	$(1.2 \times 10^{-5} \sim 0.12) \text{ m}^3/\text{h}$ (0.12 ~ 300) m ³ /h (300 ~ 4 000) m ³ /h	1.9×10^{-3} 2.0×10^{-3} 3.6×10^{-3}	Sonic Nozzle/SICT-CP-20928 Master Meter/SICT-CP-20929
Liquid flowmeters; turbine	20917	(0.01 ~ 50) m ³ /h (0.000 12 ~ 0.01) m ³ /h (0.01 ~ 50) m ³ /h	1.2×10^{-3} 2.6×10^{-3} 7.0×10^{-4}	Master Meter/SICT-CP-20926 Weight measuring method/ SICT-CP-20927
Gas flowmeters; ultrasonic	20918	$(1.2 \times 10^{-5} \sim 0.12) \text{ m}^3/\text{h}$ (0.12 ~ 300) m ³ /h (300 ~ 4 000) m ³ /h	1.9×10^{-3} 2.0×10^{-3} 3.6×10^{-3}	Sonic Nozzle/SICT-CP-20928 Master Meter/SICT-CP-20929

209. Fluid flow

Measured Quantity Instrument or Gauge	Field Code	Range	Measurement uncertainty (The Confidence Level is about 95 %)	Standard/Method of Measurement etc.
Liquid flowmeters; ultrasonic	20919	(0.01 ~ 50) m ³ /h	1.2×10^{-3}	Master Meter/SICT-CP-20926
		(0.000 12 ~ 0.01) m ³ /h	2.6×10^{-3}	Weight measuring method/ SICT-CP-20927
		(0.01 ~ 50) m ³ /h	7.0×10^{-4}	
Gas flowmeters; variable area	20920	(1.2×10^{-5} ~ 0.12) m ³ /h	1.9×10^{-3}	Sonic Nozzle/SICT-CP-20928
		(0.12 ~ 300) m ³ /h	2.0×10^{-3}	Master Meter/SICT-CP-20929
		(300 ~ 4 000) m ³ /h	3.6×10^{-3}	
Liquid flowmeters; variable area	20921	(0.01 ~ 50) m ³ /h	1.2×10^{-3}	Master Meter/SICT-CP-20926
		(0.000 12 ~ 0.01) m ³ /h	2.6×10^{-3}	Weight measuring method/ SICT-CP-20927
		(0.01 ~ 50) m ³ /h	7.0×10^{-4}	
Gas flowmeters; vortex	20922	(1.2×10^{-5} ~ 0.12) m ³ /h	1.9×10^{-3}	Sonic Nozzle/SICT-CP-20928
		(0.12 ~ 300) m ³ /h	2.0×10^{-3}	Master Meter/SICT-CP-20929
		(300 ~ 4 000) m ³ /h	3.6×10^{-3}	
Liquid flowmeters; vortex	20923	(0.01 ~ 50) m ³ /h	1.2×10^{-3}	Master Meter/SICT-CP-20926
		(0.000 12 ~ 0.01) m ³ /h	2.6×10^{-3}	Weight measuring method/ SICT-CP-20927
		(0.01 ~ 50) m ³ /h	7.0×10^{-4}	
Anemometers; vane, etc	20925	(0.1 ~ 1.0) m/s	8.7×10^{-2}	Wind Tunnel, Pitot tube, LDV/ SICT-CP-20925
		(1.0 ~ 2.0) m/s	8.4×10^{-3}	
		(2.0 ~ 70) m/s	4.8×10^{-3}	
Others; Anemometers; Ultrasonic current meter	20999	(0.1 ~ 1.0) m/s	8.7×10^{-2}	Wind Tunnel, Pitot tube, LDV/ SICT-CP-20999
		(1.0 ~ 2.0) m/s	8.4×10^{-3}	
		(2.0 ~ 70) m/s	4.8×10^{-3}	

210. Hardness

Measured Quantity Instrument or Gauge	Field Code	Range	Measurement uncertainty (The Confidence Level is about 95 %)	Standard/Method of Measurement etc.
Brinell hardness testers	21001	(100 ~ 250) HBW 10/3 000 (250 ~ 450) HBW 10/3 000 (450 ~ 650) HBW 10/3 000	3.1 HBW 10/3 000 4.9 HBW 10/3 000 8.2 HBW 10/3 000	Brinell Hardness CRM/ SICT-CP-21001
Rockwell hardness testers	21002	(20 ~ 70) HRC (20 ~ 100) HRBW (42 ~ 86) HR30N (29 ~ 82) HR30TW	0.45 HRC 0.80 HRBW 0.70 HR30N 1.1 HR30TW	Rockwell Hardness CRM/ SICT-CP-21002
Shore hardness testers	21003	(20 ~ 100) HS	0.9 HS	Shore Hardness CRM/ SICT-CP-21003
Vickers hardness testers	21004	(50 ~ 300) HV 0.2 (300 ~ 600) HV 0.2 (600 ~ 850) HV 0.2 (50 ~ 300) HV 0.3 (300 ~ 600) HV 0.3 (600 ~ 850) HV 0.5 (50 ~ 300) HV 0.5 (300 ~ 600) HV 0.5 (600 ~ 850) HV 1 (50 ~ 300) HV 10 (300 ~ 600) HV 10 (600 ~ 850) HV 10 (300 ~ 600) HV 30 (600 ~ 850) HV 30	6.0 HV 0.2 18 HV 0.2 27 HV 0.2 5.0 HV 0.3 14 HV 0.3 26 HV 0.5 6.0 HV 0.5 15 HV 0.5 20 HV 1 3.0 HV 10 8.0 HV 10 11 HV 10 8.0 HV 30 11 HV 30	Vickers Hardness CRM/ SICT-CP-21004
Durometer hardness testers	21005	(0 ~ 100) HDA (0 ~ 100) HDAM (0 ~ 100) HDAO (0 ~ 100) HDB (0 ~ 100) HDC (0 ~ 100) HDC2 (0 ~ 100) HDCS (0 ~ 100) HDD (0 ~ 100) HDD0 (0 ~ 100) HDE (0 ~ 100) HDE2 (0 ~ 100) HDF (0 ~ 100) HDF0 (0 ~ 100) HDM (0 ~ 100) HDO (0 ~ 100) HD00 (0 ~ 100) HD000 (0 ~ 100) HD000-S	0.4 HDA 0.8 HDAM 0.4 HDAO 0.4 HDB 0.3 HDC 0.6 HDC2 0.3 HDCS 0.3 HDD 0.3 HDD0 0.4 HDE 0.6 HDE2 0.6 HDF 0.6 HDF0 0.8 HDM 0.3 HDO 0.4 HD00 0.4 HD000 0.3 HD000-S	Durometer Calibration device/ SICT-CP-21005
Leeb hardness testers	21006	(400 ~ 1 000) HLD	4.6 HLD	Leeb Hardness CRM/ SICT-CP-21006

211. Impact

측정량/장비	분류번호	교정범위	측정불확도 (신뢰수준 약 95 %)	사용표준/측정방법 등
Charpy impact testers	21102	(0.5 ~ 900) J	-	Laser Distance Meter, Electronic Force Measuring Device/ SICT-CP-21102
Izod impact testers	21103	(0.5 ~ 900) J	-	Laser Distance Meter, Electronic Force Measuring Device/ SICT-CP-21103

301. Time/frequency

Measured Quantity Instrument or Gauge	Field Code	Range	Measurement uncertainty (The Confidence Level is about 95 %)	Standard/Method of Measurement etc.
Frequency standards Time Base Frequency	30102	(0.1 ~ 10) MHz	1.0×10^{-12}	GPS Receiver, Universal Counter/ SICT-CP-30102
General frequency sources Time Base Frequency	30103	10 kHz ~ 100 MHz	1.0×10^{-12}	GPS Receiver, Universal Counter/ SICT-CP-30103
Frequency meters/counters Time Base Frequency Input Frequency	30104	(1 ~ 10) MHz 0.01 Hz ~ 1 Hz 1 Hz ~ 60 GHz	1.0×10^{-12} 64 pHz 6.4×10^{-11}	GPS Receiver, Universal Counter/ SICT-CP-30104
Time interval sources Period Time interval	30105	1 ns ~ 10 s (1 ~ 100) ns 100 ns ~ 1 ms 1 ms ~ 10 s	6.1×10^{-9} 0.15 ns 1.3 ns 2.1 ns	GPS Receiver, Universal Counter/ SICT-CP-30105
Time interval meters/stop watches/timers Trigger Voltage Period Reference Frequency Relative Time Difference Time rate Timer Count	30106	(-5 ~ 5) V (5 ~ 100) ns (1 ~ 10) MHz day month (-9.95 ~ 9.95) s / day (-300 ~ 300) s / month (1 ~ 100) s (100 ~ 1 000) s (1 000 ~ 10 000) s ≥ 1	1.2×10^{-4} 6.2×10^{-5} ns 6.2×10^{-11} 1.1×10^{-7} 3.6×10^{-7} 6.1 ms 6.2 ms 5.8×10^{-6} 8.2×10^{-6} 5.8×10^{-5} 0.58	Stop Watch Calibrator/ SICT-CP-30106

302. Velocity & revolution

Measured Quantity Instrument or Gauge	Field Code	Range	Measurement uncertainty (The Confidence Level is about 95 %)	Standard/Method of Measurement etc.
Standard RPM generators Revolution Velocity Measurement Revolution Velocity Measurement (Centrifuge)	30201	(1 ~ 10 000) min ⁻¹ (30 ~ 5 000) min ⁻¹ (5 000 ~ 8 500) min ⁻¹ (8 500 ~ 50 000) min ⁻¹ (50 000 ~ 80 000) min ⁻¹ (80 000 ~ 99 000) min ⁻¹	0.004 0 min ⁻¹ 0.059 min ⁻¹ 0.099 min ⁻¹ 0.59 min ⁻¹ 0.93 min ⁻¹ 1.1 min ⁻¹	GPS Receiver, Synthesizer Function Generator/ SICT-CP-30201
Contact type tachometers Revolution Velocity Measurement	30202	(1 ~ 10) min ⁻¹ (10 ~ 1 000) min ⁻¹ (1 000 ~ 5 000) min ⁻¹	0.10 min ⁻¹ 0.016 min ⁻¹ 0.063 min ⁻¹	GPS Receiver, Tachometer Cal System/ SICT-CP-30202
Photo tachometers/stroboscopes Revolution Velocity Measurement (Photo-tachometer) Revolution Velocity Measurement (Stroboscope)	30203	(1 ~ 999.99) min ⁻¹ (1 000.0 ~ 99 999.9) min ⁻¹ (100 000 ~ 600 000) min ⁻¹ (30 ~ 9 000) min ⁻¹ (9 000 ~ 90 000) min ⁻¹ (90 000 ~ 500 000) min ⁻¹	0.006 1 min ⁻¹ 0.061 min ⁻¹ 0.61 min ⁻¹ 0.005 8 min ⁻¹ 0.058 min ⁻¹ 0.58 min ⁻¹	GPS Receiver, Photo Signal Detector/ SICT-CP-30203
Speed meters Speed Test	30204	(0 ~ 400) km/h	6.1×10^{-3} km/h	GPS Receiver, Synthesizer Function Generator/ SICT-CP-30204
Wow-flutter generators Carrier Frequency Function Frequency Wow/Flutter Deviation Output Level CCIR Pulse	30205	10 Hz ~ 99.99 kHz 1 Hz ~ 10 kHz (10 ~ 30) kHz (1 Hz ~ 100 Hz) (0 ~ 3) % (1 ~ 10) mV (10 ~ 100) mV (0.1 ~ 6) V 10 ms 30 ms 60 ms 100 ms	6.2×10^{-6} 6.2×10^{-6} 2.1×10^{-6} 0.025 % 5.8×10^{-4} 1.7×10^{-4} 1.3×10^{-4} 1.0×10^{-2} ms 3.0×10^{-2} ms 6.0×10^{-2} ms 1.0×10^{-1} ms	GPS Receiver, Universal Counter/ SICT-CP-30205
Wow-flutter meters Wow/Flutter Deviation Carrier Frequency CCIR Pulse Output Voltage	30206	(0.1 ~ 0.3) % (0.3 ~ 3) % 3 kHz 3.15 kHz (10 ~ 100) ms (1 ~ 100) mV (0.1 ~ 1) V (1 ~ 10) V	0.019 % 0.020 % 6.2×10^{-5} kHz 6.2×10^{-5} kHz 0.59 % 6.8 μV 9.8 μV 76 μV	GPS Receiver, Wow Flutter Calibrator/ SICT-CP-30206

401. DC voltage & current

Measured Quantity Instrument or Gauge	Field Code	Range	Measurement uncertainty (The Confidence Level is about 95 %)	Standard/Method of Measurement etc.
DC ammeters DC Current	40101	(±) 0 pA (0 ~ 1) pA (1 ~ 10) pA (10 ~ 100) pA (0.1 ~ 100) nA (0.1 ~ 1) μA (1 ~ 10) μA (10 ~ 100) μA (0.1 ~ 1) mA (1 ~ 10) mA (10 ~ 100) mA (100 ~ 200) mA (0.2 ~ 1) A (1 ~ 10) A (10 ~ 100) A	13 fA 2.4×10^{-2} 9.4×10^{-3} 2.3×10^{-3} 8.5×10^{-4} 9.3×10^{-4} 4.5×10^{-5} 3.0×10^{-5} 2.5×10^{-5} 2.7×10^{-5} 2.0×10^{-5} 1.7×10^{-5} 3.0×10^{-5} 1.4×10^{-4} 1.5×10^{-4}	Calibrator/ SICT-CP-40101
Transconductance amplifiers DC Current AC Current	40102	(±) 10 μA ~ 10 A (10 ~ 50) A (50 ~ 100) A (10 μA) 10 Hz ~ 10 kHz (10 ~ 100) μA 10 Hz ~ 1 kHz (1 ~ 10) kHz (100 μA ~ 1 mA) 10 Hz 10 Hz ~ 1 kHz (1 ~ 10) kHz (1 ~ 100) mA 10 Hz 10 Hz ~ 1 kHz (1 ~ 10) kHz (100 mA ~ 1 A) 10 Hz 10 Hz ~ 1 kHz (1 ~ 10) kHz (1 ~ 2) A 10 Hz 10 Hz ~ 1 kHz (1 ~ 10) kHz (2 ~ 5) A 10 Hz 10 Hz ~ 1 kHz (1 ~ 10) kHz	1.3×10^{-5} 4.3×10^{-5} 4.4×10^{-5} 2.6×10^{-3} 3.6×10^{-4} 6.4×10^{-4} 9.8×10^{-5} 7.5×10^{-5} 9.4×10^{-5} 7.8×10^{-5} 4.6×10^{-5} 4.2×10^{-5} 8.1×10^{-5} 4.9×10^{-5} 4.4×10^{-5} 7.9×10^{-5} 4.7×10^{-5} 4.5×10^{-5} 8.2×10^{-5} 5.2×10^{-5} 5.0×10^{-5}	AC-DC Active Current Shunt/ SICT-CP-40102

401. DC voltage & current

Measured Quantity Instrument or Gauge	Field Code	Range	Measurement uncertainty (The Confidence Level is about 95 %)	Standard/Method of Measurement etc.
Transconductance amplifiers AC Current	40102	(5 ~ 10) A 10 Hz 10 Hz ~ 1 kHz (1 ~ 10) kHz (10 ~ 20) A 10 Hz 10 Hz ~ 1 kHz (1 ~ 10) kHz (20 ~ 50) A 10 Hz 10 Hz ~ 1 kHz (1 ~ 10) kHz (50 ~ 100) A 10 Hz 10 Hz ~ 1 kHz (1 ~ 10) kHz (100 ~ 120) A 60 Hz	8.6×10^{-5} 5.9×10^{-5} 7.8×10^{-5} 9.3×10^{-5} 6.8×10^{-5} 7.8×10^{-5} 1.0×10^{-4} 8.3×10^{-5} 1.1×10^{-4} 1.2×10^{-4} 9.7×10^{-5} 1.3×10^{-5} 4.6×10^{-4}	AC-DC Active Current Shunt/ SICT-CP-40102
DC voltage/current calibrators DC Voltage DC Current	40103	(±) 0 mV (0 ~ 1) mV (1 ~ 2) mV (2 ~ 5) mV (5 ~ 10) mV (10 ~ 20) mV (20 ~ 50) mV (50 ~ 100) mV (0.1 ~ 1) V (1 ~ 10) V (10 ~ 100) V (100 ~ 1 000) V (±) 0 pA (0 ~ 1) pA (1 ~ 10) pA (10 ~ 100) pA (0.1 ~ 100) nA 100 nA ~ 10 A (10 ~ 100) A	0.29 μ V 4.8×10^{-4} 2.4×10^{-4} 9.6×10^{-5} 4.9×10^{-5} 2.5×10^{-5} 1.1×10^{-5} 6.9×10^{-6} 3.7×10^{-6} 3.3×10^{-6} 5.4×10^{-6} 5.7×10^{-6} 9.6 fA 2.1×10^{-2} 6.8×10^{-3} 2.2×10^{-3} 8.5×10^{-4} 1.4×10^{-5} 4.5×10^{-5}	Reference Multimeter/ SICT-CP-40103
Electrical temperature calibrators TEMPERATURE(SOURCE) T/C	40104	(-9.835 ~ 0.000) mV 0.000 mV (0.000 ~ 13.421) mV (13.421 ~ 37.006) mV (37.006 ~ 61.017) mV (61.017 ~ 76.373) mV	0.42 μ V 0.24 μ V 0.42 μ V 0.48 μ V 0.53 μ V 0.57 μ V	디지털 멀티미터/ SICT-CP-40104

401. DC voltage & current

Measured Quantity Instrument or Gauge	Field Code	Range	Measurement uncertainty (The Confidence Level is about 95 %)	Standard/Method of Measurement etc.
Electrical temperature calibrators RTD	40104	0.999 Ω (0.999 ~ 2.499) Ω (2.499 ~ 4.322) Ω (4.322 ~ 100.000) Ω (100.000 ~ 177.155) Ω (177.155 ~ 313.708) Ω (313.708 ~ 627.422) Ω (627.422 ~ 3 233.3) Ω	0.063 mΩ 3.0×10^{-5} 1.9×10^{-5} 9.9×10^{-6} 8.8×10^{-6} 1.1×10^{-5} 9.2×10^{-6} 1.1×10^{-5}	디지털 멀티미터/ SICT-CP-40104
DC Voltage(SOURCE)		(±) 0 mV (1 ~ 2) mV (2 ~ 3) mV (3 ~ 4) mV (4 ~ 5) mV (5 ~ 10) mV (10 ~ 50) mV (50 ~ 100) mV (0.1 ~ 0.2) V (0.2 ~ 0.3) V (0.3 ~ 0.6) V (0.6 ~ 1) V (1 ~ 6) V (6 ~ 10) V (10 ~ 70) V (70 ~ 100) V	0.24 μV 4.0×10^{-4} 2.0×10^{-4} 1.3×10^{-4} 1.0×10^{-4} 8.2×10^{-5} 4.2×10^{-5} 6.3×10^{-6} 6.2×10^{-5} 3.1×10^{-5} 3.1×10^{-5} 9.5×10^{-6} 3.1×10^{-5} 9.3×10^{-6} 6.2×10^{-5} 9.2×10^{-6}	
DC Current(SOURCE)		(±) 0 mA (0 ~ 1) mA (1 ~ 2) mA (2 ~ 5) mA (5 ~ 7) mA (7 ~ 10) mA (10 ~ 20) mA (20 ~ 30) mA (30 ~ 40) mA (40 ~ 100) mA	0.064 μA 9.2×10^{-5} 6.2×10^{-5} 3.5×10^{-5} 2.3×10^{-5} 1.9×10^{-5} 3.3×10^{-5} 8.2×10^{-5} 7.0×10^{-5} 6.3×10^{-5}	
Resistance(SOURCE)		0 Ω (0 ~ 0.6) Ω (0.6 ~ 1) Ω (1 ~ 10) Ω (10 ~ 20) Ω (20 ~ 30) Ω (30 ~ 50) Ω (50 ~ 70) Ω (70 ~ 100) Ω (0.1 ~ 0.2) kΩ (0.2 ~ 0.3) kΩ (0.3 ~ 0.5) kΩ (0.5 ~ 0.8) kΩ (0.8 ~ 1) kΩ	0.061 mΩ 6.1×10^{-4} 8.9×10^{-5} 6.7×10^{-5} 3.3×10^{-5} 2.3×10^{-5} 1.8×10^{-5} 1.4×10^{-5} 1.2×10^{-5} 3.2×10^{-5} 2.3×10^{-5} 1.8×10^{-5} 1.4×10^{-5} 1.1×10^{-5}	

401. DC voltage & current

Measured Quantity Instrument or Gauge	Field Code	Range	Measurement uncertainty (The Confidence Level is about 95 %)	Standard/Method of Measurement etc.
Electrical temperature calibrators	40104	(1 ~ 2) kΩ	3.2×10^{-5}	디지털 멀티미터/ SICT-CP-40104
Resistance(SOURCE)		(2 ~ 3) kΩ	2.3×10^{-5}	
		(3 ~ 5) kΩ	1.8×10^{-5}	
		(5 ~ 8) kΩ	1.4×10^{-5}	
		(8 ~ 10) kΩ	1.1×10^{-5}	
		(10 ~ 20) kΩ	3.2×10^{-5}	
		(20 ~ 30) kΩ	2.4×10^{-5}	
		(30 ~ 40) kΩ	1.9×10^{-5}	
		(40 ~ 50) kΩ	1.6×10^{-5}	
		(50 ~ 100) kΩ	1.1×10^{-5}	
TEMPERATURE(MEASURE)	T/C	(-9.835 ~ 0.000) mV	0.59 μV	
		0.000 mV	0.50 μV	
		(0.000 ~ 13.422) mV	0.62 μV	
		(13.422 ~ 28.947) mV	0.75 μV	
		(28.947 ~ 45.094) mV	0.88 μV	
		(45.094 ~ 53.113) mV	0.95 μV	
		(53.113 ~ 76.374) mV	1.1 μV	
	RTD	0.998 Ω	0.24 mΩ	
		(0.998 ~ 2.496) Ω	1.0×10^{-4}	
		(2.496 ~ 4.315) Ω	7.1×10^{-5}	
		(4.315 ~ 16.994) Ω	3.9×10^{-5}	
		(16.994 ~ 249.580) Ω	3.5×10^{-5}	
		(249.580 ~ 317.988) Ω	4.3×10^{-5}	
		(317.988 ~ 390.474) Ω	4.0×10^{-5}	
		(390.474 ~ 3 233.2) Ω	3.5×10^{-5}	
DC Voltage(MEASURE)	(±)	0 mV	0.50 μV	
		(1 ~ 5) mV	5.2×10^{-4}	
		(5 ~ 10) mV	9.3×10^{-5}	
		(10 ~ 100) mV	5.9×10^{-5}	
		(0.1 ~ 0.5) V	6.3×10^{-5}	
		(0.5 ~ 0.8) V	1.3×10^{-5}	
		(0.8 ~ 1) V	1.6×10^{-5}	
		(1 ~ 10) V	6.6×10^{-6}	
		(10 ~ 20) V	9.1×10^{-6}	
		(20 ~ 40) V	7.9×10^{-6}	
		(40 ~ 70) V	6.9×10^{-6}	
		(70 ~ 100) V	6.4×10^{-6}	
		(100 ~ 200) V	7.8×10^{-6}	
		(200 ~ 300) V	2.2×10^{-5}	

401. DC voltage & current

Measured Quantity Instrument or Gauge	Field Code	Range	Measurement uncertainty (The Confidence Level is about 95 %)	Standard/Method of Measurement etc.
Electrical temperature calibrators DC Current(MEASURE)	40104	(±) 0 mA (0 ~ 0.1) mA (0.1 ~ 0.2) mA (0.2 ~ 0.3) mA (0.3 ~ 0.7) mA (0.7 ~ 1) mA (1 ~ 2) mA (2 ~ 5) mA (5 ~ 10) mA (10 ~ 20) mA (20 ~ 30) mA (30 ~ 40) mA (40 ~ 50) mA (50 ~ 100) mA (100 ~ 130) mA	0.062 μA 6.4×10^{-4} 3.2×10^{-4} 2.2×10^{-4} 1.7×10^{-4} 9.3×10^{-5} 9.9×10^{-5} 7.6×10^{-5} 5.8×10^{-5} 9.9×10^{-5} 8.2×10^{-5} 7.4×10^{-5} 7.0×10^{-5} 6.7×10^{-5} 8.7×10^{-5}	디지털 멀티미터/ SICT-CP-40104
Resistance(MEASURE)		0 Ω (0 ~ 1) Ω (1 ~ 10) Ω (10 ~ 100) Ω (0.1 ~ 1) kΩ (1 ~ 10) kΩ (10 ~ 20) kΩ (20 ~ 30) kΩ (30 ~ 40) kΩ (40 ~ 50) kΩ (50 ~ 100) kΩ	0.098 mΩ 6.4×10^{-5} 1.1×10^{-5} 9.6×10^{-6} 6.5×10^{-5} 6.1×10^{-5} 4.7×10^{-5} 4.0×10^{-5} 4.2×10^{-5} 3.9×10^{-5} 3.4×10^{-5}	
DC current shunts Resistance	40105	1 μΩ (0.001 ~ 0.01) mΩ (0.01 ~ 0.2) mΩ (0.2 ~ 1) mΩ (1 ~ 10) mΩ (10 ~ 100) mΩ (0.1 ~ 1) Ω (1 ~ 10) Ω (10 ~ 100) Ω (0.1 ~ 1) kΩ (1 ~ 10) kΩ (10 ~ 100) kΩ (0.1 ~ 1) MΩ (1 ~ 10) MΩ (10 ~ 100) MΩ	0.32 nΩ 2.8×10^{-4} 1.8×10^{-4} 1.5×10^{-4} 1.1×10^{-6} 2.8×10^{-6} 8.1×10^{-7} 1.3×10^{-6} 6.7×10^{-7} 6.2×10^{-7} 7.9×10^{-7} 2.0×10^{-6} 1.4×10^{-6} 5.3×10^{-6} 9.8×10^{-6}	Trans Conductance Amplifier/ SICT-CP-40105
Galvanometers/null detectors DC Voltage	40106	(±) (100 ~ 300) μV (0.3 ~ 1) mV 1 mV ~ 1 000 V	1.4×10^{-2} 1.2×10^{-2} 6.8×10^{-3}	Calibrator/ SICT-CP-40106
Potentiometers DC Voltage	40107	(100 ~ 300) μV (0.3 ~ 1) mV (1 ~ 3) mV 3 mV ~ 1 000 V	5.7×10^{-3} 2.2×10^{-3} 6.0×10^{-4} 3.0×10^{-4}	Calibrator/ SICT-CP-40107

401. DC voltage & current

Measured Quantity Instrument or Gauge	Field Code	Range	Measurement uncertainty (The Confidence Level is about 95 %)	Standard/Method of Measurement etc.
DC power supplies DC Voltage DC Current Load regulation Ripple	40108	(±) 0 mV (0 ~ 10) mV (10 ~ 100) mV (0.1 ~ 1) V (1 ~ 10) V (10 ~ 100) V (100 ~ 600) V (600 ~ 1 000) V (1 ~ 10) mA (10 ~ 100) mA (0.1 ~ 1) A (1 ~ 10) A (10 ~ 300) A (300 ~ 500) A (500 ~ 1 000) A (1 000 ~ 3 000) A (0 ~ 2) mV (2 ~ 20) mV (20 ~ 200) mV (0.1 ~ 0.4) mV (0.4 ~ 0.6) mV (0.6 ~ 1) mV (1 ~ 10) mV (10 ~ 50) mV	5.8 μV 5.8×10^{-4} 5.8×10^{-5} 7.5×10^{-6} 3.3×10^{-6} 7.7×10^{-6} 1.3×10^{-5} 6.6×10^{-5} 5.8×10^{-3} 5.9×10^{-4} 2.4×10^{-4} 3.1×10^{-4} 2.4×10^{-4} 2.6×10^{-4} 4.7×10^{-5} 5.1×10^{-4} 0.16 mV 7.8×10^{-2} 8.2×10^{-3} 3.8×10^{-1} 1.1×10^{-1} 7.3×10^{-2} 4.4×10^{-2} 7.1×10^{-2}	DC Electronics Load/ SICT-CP-40108
DC voltage dividers DC Voltage Ratio	40110	(±) (0.01 ~ 1 000) V (1 ~ 50) kV (50 ~ 100) kV	4.5×10^{-6} 8.8×10^{-5} 8.4×10^{-5}	Calibrator/ SICT-CP-40110
DC voltage standards DC Voltage	40111	1 V 1.018 V 10 V	1.6 μV 0.8 μV 3.1 μV	Null Detector/ SICT-CP-40111
DC voltmeters DC Voltage	40112	(±) 0 mV (0 ~ 1) mV (1 ~ 2) mV (2 ~ 5) mV (5 ~ 10) mV (10 ~ 20) mV (20 ~ 50) mV (50 ~ 80) mV (80 ~ 100) mV (0.1 ~ 1 000) V	0.51 μV 5.0×10^{-4} 2.5×10^{-4} 1.0×10^{-4} 6.2×10^{-5} 5.0×10^{-5} 2.5×10^{-5} 1.0×10^{-5} 6.2×10^{-6} 8.0×10^{-6}	Calibrator/ SICT-CP-40112
Static/ionic voltmeters DC Voltage	40113	(±) 0 V 0 V ~ 50 kV	68 mV 1.3×10^{-2}	DC Power Supply/ SICT-CP-40113

402. Resistance, Capacitance and Inductance

Measured Quantity Instrument or Gauge	Field Code	Range	Measurement uncertainty (The Confidence Level is about 95 %)	Standard/Method of Measurement etc.	
Capacitance bridges/indicators	40201	50 Hz ~ 100 MHz	6.8×10^{-8}	Standard Capacitance Set/ SICT-CP-40201	
Frequency					
Capacitance		(1 pF)			
		50 Hz ~ 1 kHz	3.6×10^{-4}		
		1 kHz ~ 1 MHz	3.7×10^{-4}		
		2 MHz	4.2×10^{-4}		
		3 MHz	5.4×10^{-4}		
		4 MHz	7.2×10^{-4}		
		5 MHz	9.5×10^{-4}		
		10 MHz	2.5×10^{-3}		
		13 MHz	3.7×10^{-3}		
		(10 pF)			
		50 Hz ~ 5 MHz	3.6×10^{-4}		
		10 MHz	3.7×10^{-4}		
		13 MHz	3.9×10^{-4}		
		(100 pF)			
		(50 ~ 120) Hz	3.5×10^{-4}		
		120 Hz ~ 4 MHz	3.6×10^{-4}		
		5 MHz	3.8×10^{-4}		
		10 MHz	4.9×10^{-4}		
		13 MHz	6.1×10^{-4}		
		(1 000 pF)			
		50 Hz ~ 1 MHz	3.6×10^{-4}		
		2 MHz	3.8×10^{-4}		
	3 MHz	4.5×10^{-4}			
	4 MHz	5.7×10^{-4}			
	5 MHz	7.2×10^{-4}			
	10 MHz	2.0×10^{-3}			
	13 MHz	3.0×10^{-3}			
	(10 nF)				
	(50 ~ 100) Hz	3.0×10^{-4}			
	100 Hz ~ 100 kHz	8.2×10^{-5}			
	(100 nF)				
	(50 ~ 100) Hz	3.0×10^{-4}			
	100 Hz ~ 100 kHz	8.2×10^{-5}			
	(1 μF)				
	(50 ~ 100) Hz	7.0×10^{-4}			
	100 Hz ~ 10 kHz	8.2×10^{-5}			
	(10 ~ 100) kHz	1.1×10^{-4}			

402. Resistance, Capacitance and Inductance

Measured Quantity Instrument or Gauge	Field Code	Range	Measurement uncertainty (The Confidence Level is about 95 %)	Standard/Method of Measurement etc.
Capacitance bridges/indicators Capacitance (Schering bridges) Capacitance tan δ	40201	(10 μF) 120 Hz ~ 1 kHz	1.3×10^{-3}	Standard Capacitance Set/ SICT-CP-40201 SICT-CP-40201-1
		(100 μF) 120 Hz	1.4×10^{-3}	
		(1 mF) 120 Hz	1.5×10^{-3}	
		(3 mF) 120 Hz	1.5×10^{-3}	
		(10 mF) 120 Hz	1.5×10^{-3}	
		(30 mF) 120 Hz	2.9×10^{-3}	
		(50 ~ 60) Hz 100 pF	7.7×10^{-5}	
		1 000 pF	3.9×10^{-5}	
		0.000 0 ~ 0.001 0	1.7×10^{-4}	
		0.001 0 ~ 0.003 0	1.8×10^{-4}	
		0.003 0 ~ 0.005 0	1.9×10^{-4}	
		0.005 0 ~ 0.008 0	2.1×10^{-4}	
		0.008 0 ~ 0.010 0	2.2×10^{-4}	
		0.010 0 ~ 0.030 0	3.3×10^{-4}	
		0.030 0 ~ 0.050 0	4.4×10^{-4}	
		0.050 0 ~ 0.080 0	6.2×10^{-4}	
0.080 0 ~ 0.100 0	7.4×10^{-4}			
Decade capacitors Capacitance	40202	(50 Hz ~ 20 kHz) 1 pF	5.7×10^{-5}	Standard Capacitance Set/ SICT-CP-40202
		(1 ~ 10) pF	4.6×10^{-5}	
		(10 ~ 100) pF	3.8×10^{-5}	
		(100 ~ 1 000) pF	4.6×10^{-5}	
		1 000 pF ~ 100 nF	2.9×10^{-4}	
		100 nF ~ 1 μF	5.1×10^{-4}	
		(1 kHz) 1 pF	2.5×10^{-5}	
		(1 ~ 1 000) pF	2.4×10^{-5}	
		1 000 pF ~ 100 nF	5.5×10^{-5}	
		100 nF ~ 1 μF	9.3×10^{-5}	

402. Resistance, Capacitance and Inductance

Measured Quantity Instrument or Gauge	Field Code	Range	Measurement uncertainty (The Confidence Level is about 95 %)	Standard/Method of Measurement etc.
Standard capacitors Capacitance	40204	(50 Hz ~ 20 kHz) 1 pF (1 ~ 10) pF (10 ~ 100) pF (100 ~ 1 000) pF 1 000 pF ~ 100 nF 100 nF ~ 1 μF (1 kHz) 1 pF (1 ~ 10) pF (10 ~ 100) pF (100 ~ 1 000) pF 1 000 pF ~ 100 nF 100 nF ~ 1 μF (1 pF) 1 kHz 1 kHz ~ 1 MHz (1 ~ 2) MHz (2 ~ 3) MHz (3 ~ 4) MHz (4 ~ 5) MHz (5 ~ 10) MHz (10 ~ 13) MHz (1 ~ 10) pF 1 kHz ~ 3 MHz (3 ~ 5) MHz (5 ~ 10) MHz (10 ~ 13) MHz (10 ~ 100) pF 1 kHz ~ 1 MHz (1 ~ 3) MHz (3 ~ 4) MHz (4 ~ 5) MHz (5 ~ 10) MHz (10 ~ 13) MHz (100 pF ~ 1 nF) 1 kHz 1 kHz ~ 1 MHz (1 ~ 2) MHz (2 ~ 3) MHz (3 ~ 4) MHz (4 ~ 5) MHz (5 ~ 10) MHz (10 ~ 13) MHz	5.2×10^{-5} 4.0×10^{-5} 3.0×10^{-5} 4.0×10^{-5} 2.9×10^{-4} 5.1×10^{-4} 9.1×10^{-6} 7.1×10^{-6} 6.1×10^{-6} 7.1×10^{-6} 5.0×10^{-5} 9.0×10^{-5} 2.4×10^{-4} 2.5×10^{-4} 3.3×10^{-4} 4.7×10^{-4} 6.7×10^{-4} 9.1×10^{-4} 2.5×10^{-3} 3.7×10^{-3} 2.3×10^{-4} 2.4×10^{-4} 2.6×10^{-4} 2.8×10^{-4} 2.3×10^{-4} 2.4×10^{-4} 2.5×10^{-4} 2.7×10^{-4} 4.0×10^{-4} 5.4×10^{-4} 2.3×10^{-4} 2.4×10^{-4} 2.8×10^{-4} 3.6×10^{-4} 5.0×10^{-4} 6.6×10^{-4} 1.9×10^{-3} 2.8×10^{-3}	Standard Capacitance Set/ Capacitance Bridge SICT-CP-40204

402. Resistance, Capacitance and Inductance

Measured Quantity Instrument or Gauge	Field Code	Range	Measurement uncertainty (The Confidence Level is about 95 %)	Standard/Method of Measurement etc.
Standard capacitors Capacitance	40204	(1 ~ 100) nF 120 Hz ~ 100 kHz (100 nF ~ 1 μF) 120 Hz 120 Hz ~ 10 kHz (10 ~ 100) kHz (1 ~ 10) μF 120 Hz ~ 1 kHz (30 μF) 120 Hz (100 μF) 120 Hz (300 μF) 120 Hz (1 mF) 120 Hz (3 mF) 120 Hz (10 mF) 120 Hz (30 mF) 120 Hz	2.3×10^{-4} 2.4×10^{-4} 2.3×10^{-4} 2.4×10^{-4} 1.2×10^{-3} 1.3×10^{-3} 1.3×10^{-3} 1.5×10^{-3} 1.4×10^{-3} 1.5×10^{-3} 1.4×10^{-3} 2.9×10^{-3}	Standard Capacitance Set/ Capacitance Bridge SICT-CP-40204
Earth testers Test Voltage Resistance AC Current out Timer	40205	1 V (1 ~ 10) V (10 ~ 50) V (50 ~ 100) V (100 ~ 500) V (500 ~ 1 000) V 1 mΩ (1 ~ 10) mΩ 10 mΩ ~ 100 kΩ 1 A (1 ~ 3) A (3 ~ 20) A (20 ~ 30) A (30 ~ 60) A (60 ~ 100) A (100 ~ 150) A (150 ~ 200) A 1 s (1 ~ 100) s (100 ~ 1 000) s (1 000 ~ 10 000) s	6.4×10^{-3} 6.4×10^{-4} 1.3×10^{-3} 6.4×10^{-4} 1.6×10^{-4} 6.4×10^{-4} 8.6×10^{-4} 7.2×10^{-4} 6.8×10^{-4} 1.2×10^{-3} 1.5×10^{-3} 9.7×10^{-4} 1.0×10^{-3} 8.4×10^{-4} 1.0×10^{-3} 4.6×10^{-3} 3.7×10^{-3} 5.8×10^{-6} 5.8×10^{-6} 8.2×10^{-6} 5.8×10^{-5}	Decade Resistor/ SICT-CP-40205

402. Resistance, Capacitance and Inductance

Measured Quantity Instrument or Gauge	Field Code	Range	Measurement uncertainty (The Confidence Level is about 95 %)	Standard/Method of Measurement etc.
Inductance bridges/indicators Frequency Inductance	40206	50 Hz ~ 100 MHz (1 kHz) 100 μH 1 mH 10 mH 100 mH 1 H 10 H	7.0×10^{-8} 1.9×10^{-4} 1.3×10^{-4} 1.3×10^{-4} 1.3×10^{-4} 1.3×10^{-4} 1.3×10^{-4}	Standard Inductor/ SICT-CP-40206
Inductors Standard Inductance Decade Inductance	40208	(1 kHz) 100 μH 1 mH 10 mH 100 mH 1 H 10 H (1 kHz) 100 μH ~ 10 H	 28 nH 0.24 μH 2.4 μH 24 μH 0.24 mH 2.5 mH 3.5×10^{-3}	Standard Inductor/ SICT-CP-40208
Insulation testers AC Voltage Insulation Voltage Insulation Resistance	40210	1 V (1 ~ 10) V (10 ~ 100) V (100 ~ 1 000) V 1 V (1 ~ 10) V (10 ~ 25) V (25 ~ 50) V (50 ~ 100) V (100 ~ 250) V (250 ~ 500) V (500 ~ 1 000) V (1 000 ~ 5 000) V (5 000 ~ 10 000) V 1 kΩ (1 ~ 10) kΩ (10 ~ 100) kΩ (0.1 ~ 1) MΩ (1 ~ 10) MΩ (10 ~ 100) MΩ (0.1 ~ 1) GΩ (1 ~ 10) GΩ (10 ~ 100) GΩ (0.1 ~ 1) TΩ 10 TΩ	8.8×10^{-5} 9.0×10^{-5} 1.0×10^{-4} 1.1×10^{-4} 6.4×10^{-4} 6.4×10^{-5} 2.5×10^{-4} 1.3×10^{-4} 6.4×10^{-5} 2.5×10^{-4} 1.3×10^{-4} 6.4×10^{-5} 6.5×10^{-3} 6.1×10^{-3} 7.1×10^{-5} 3.7×10^{-5} 2.5×10^{-5} 3.1×10^{-5} 9.5×10^{-5} 2.4×10^{-5} 3.1×10^{-5} 6.1×10^{-5} 1.3×10^{-4} 2.6×10^{-4} 6.3×10^{-4}	High Resistance Decade/ SICT-CP-40210
Q-meters Frequency Test Quality Factor	40211	60 Hz ~ 100 MHz 0 ~ 1 000	7.0×10^{-8} 9.7×10^{-4}	Universal Counter/ SICT-CP-40211

402. Resistance, Capacitance and Inductance

Measured Quantity Instrument or Gauge	Field Code	Range	Measurement uncertainty (The Confidence Level is about 95 %)	Standard/Method of Measurement etc.
Resistance bridges & similar instruments Resistance(Rheostat Arm)	40213	1 mΩ (1 ~ 10) mΩ (10 ~ 100) mΩ (0.1 ~ 1) Ω (1 ~ 10) Ω (10 ~ 100) Ω (0.1 ~ 1) kΩ (1 ~ 10) kΩ (10 ~ 100) kΩ (0.1 ~ 1) MΩ (1 ~ 10) MΩ (10 ~ 100) MΩ	1.4×10^{-6} 7.5×10^{-7} 4.0×10^{-6} 4.7×10^{-7} 5.1×10^{-7} 4.4×10^{-7} 2.4×10^{-7} 5.1×10^{-7} 1.1×10^{-6} 1.3×10^{-6} 5.3×10^{-6} 1.1×10^{-5}	Standard Resistance Set/ SICT-CP-40213
Resistance(Ratio Arm)		1 mΩ (1 ~ 10) mΩ (10 ~ 100) mΩ (0.1 ~ 1) Ω (1 ~ 10) Ω (10 ~ 100) Ω (0.1 ~ 1) kΩ (1 ~ 10) kΩ (10 ~ 100) kΩ (0.1 ~ 1) MΩ (1 ~ 10) MΩ (10 ~ 100) MΩ	1.4×10^{-6} 7.5×10^{-7} 4.0×10^{-6} 4.7×10^{-7} 5.1×10^{-7} 4.4×10^{-7} 2.4×10^{-7} 5.1×10^{-7} 1.1×10^{-6} 1.3×10^{-6} 5.3×10^{-6} 1.1×10^{-5}	
Resistance Ratio		0.1 ~ 1.3	33×10^{-9}	
Resistance meters DC Resistance	40214	1 μΩ 5 μΩ 10 μΩ 25 μΩ 100 μΩ 1 mΩ (1 ~ 10) mΩ (10 ~ 100) mΩ (0.1 ~ 1) Ω (1 ~ 10) Ω (10 ~ 100) Ω (0.1 ~ 1) kΩ (1 ~ 10) kΩ (10 ~ 100) kΩ (0.1 ~ 1) MΩ (1 ~ 10) MΩ (10 ~ 100) MΩ (0.1 ~ 1) GΩ (1 ~ 10) GΩ (10 ~ 100) GΩ (0.1 ~ 1) TΩ 10 TΩ	8.7×10^{-4} 5.8×10^{-4} 4.8×10^{-4} 5.2×10^{-4} 3.0×10^{-4} 1.2×10^{-6} 7.5×10^{-7} 4.0×10^{-6} 4.7×10^{-7} 5.1×10^{-7} 4.4×10^{-7} 2.4×10^{-7} 5.1×10^{-7} 1.1×10^{-6} 1.3×10^{-6} 5.3×10^{-6} 1.1×10^{-5} 2.5×10^{-4} 7.1×10^{-4} 9.4×10^{-4} 1.5×10^{-3} 7.1×10^{-4}	Standard Resistance Set/ SICT-CP-40214

402. Resistance, Capacitance and Inductance

Measured Quantity Instrument or Gauge	Field Code	Range	Measurement uncertainty (The Confidence Level is about 95 %)	Standard/Method of Measurement etc.
Resistance meters	40214			Standard Resistance Set/ SICT-CP-40214
Frequency		1 kHz	6.8×10^{-8}	
AC Voltage		10 mV (10 ~ 100) mV (0.1 ~ 10) V	2.4×10^{-4} 8.0×10^{-5} 8.2×10^{-5}	
AC Resistance		(1 kHz) 1 mΩ (1 ~ 10) mΩ (10 ~ 100) mΩ (0.1 ~ 1) Ω 1 Ω ~ 10 kΩ (10 ~ 100) kΩ (0.1 ~ 1) MΩ (1 ~ 10) MΩ	5.1×10^{-3} 5.2×10^{-4} 3.3×10^{-4} 1.5×10^{-4} 1.3×10^{-4} 1.6×10^{-4} 3.1×10^{-4} 3.0×10^{-3}	
Resistors	40215			Standard Resistance Set/ SICT-CP-40215
DC Resistance		1 mΩ (1 ~ 10) mΩ (10 ~ 100) mΩ (0.1 ~ 1) Ω (1 ~ 10) Ω (10 ~ 100) Ω (0.1 ~ 1) kΩ (1 ~ 10) kΩ (10 ~ 100) kΩ (0.1 ~ 1) MΩ (1 ~ 10) MΩ (10 ~ 100) MΩ (0.1 ~ 1) GΩ (1 ~ 10) GΩ (10 ~ 100) GΩ (0.1 ~ 1) TΩ (1 ~ 10) TΩ (10 ~ 100) TΩ	1.6×10^{-6} 1.1×10^{-6} 2.8×10^{-6} 8.1×10^{-7} 1.3×10^{-6} 6.7×10^{-7} 6.2×10^{-7} 7.9×10^{-7} 2.0×10^{-6} 1.4×10^{-6} 5.2×10^{-6} 9.7×10^{-6} 2.3×10^{-4} 6.9×10^{-4} 9.3×10^{-4} 1.4×10^{-3} 4.1×10^{-3} 7.6×10^{-3}	
AC Resistance		(50 Hz ~ 1 kHz) 1 mΩ (1 ~ 10) mΩ (10 ~ 100) mΩ (0.1 ~ 1) Ω (1 ~ 100) Ω (10 Ω) 1 kHz 1 MHz 2 MHz 3 MHz 4 MHz 5 MHz 10 MHz 13 MHz	1.0×10^{-3} 5.9×10^{-4} 3.9×10^{-4} 2.4×10^{-4} 2.5×10^{-4} 2.4×10^{-4} 4.0×10^{-4} 5.6×10^{-4} 6.5×10^{-4} 7.5×10^{-4} 1.0×10^{-3} 4.0×10^{-3} 6.0×10^{-3}	

402. Resistance, Capacitance and Inductance

Measured Quantity Instrument or Gauge	Field Code	Range	Measurement uncertainty (The Confidence Level is about 95 %)	Standard/Method of Measurement etc.
Resistors AC Resistance	40215	(10 ~ 100) Ω 1 kHz 1 MHz 2 MHz 3 MHz 4 MHz 5 MHz 10 MHz 13 MHz	2.4×10^{-4} 4.0×10^{-4} 4.8×10^{-4} 5.6×10^{-4} 5.6×10^{-4} 5.6×10^{-4} 2.0×10^{-3} 3.0×10^{-3}	Standard Resistance Set/ SICT-CP-40215
		(100 Ω ~ 1 kΩ) 1 kHz 100 kHz 1 MHz 2 MHz 3 MHz 4 MHz 5 MHz 10 MHz 13 MHz	2.4×10^{-4} 4.0×10^{-4} 4.0×10^{-4} 4.0×10^{-4} 4.0×10^{-4} 4.8×10^{-4} 5.6×10^{-4} 2.0×10^{-3} 3.0×10^{-3}	
		(1 ~ 10) kΩ 1 kHz 100 kHz 1 MHz	2.4×10^{-4} 3.3×10^{-4} 4.0×10^{-4}	
		(10 ~ 100) kΩ 1 kHz 100 kHz 1 MHz	2.4×10^{-4} 4.0×10^{-4} 4.0×10^{-4}	
		(100 kΩ ~ 1 MΩ) 1 kHz	3.8×10^{-4}	
		(1 ~ 10) MΩ 1 kHz	3.0×10^{-3}	
Decade Resistance		0 Ω	64 μΩ	
		(0 ~ 10) mΩ	6.5 μΩ	
		(10 ~ 100) mΩ	64 μΩ	
		(0.1 ~ 1) Ω	66 μΩ	
		(1 ~ 7) Ω	3.9×10^{-5}	
		(7 ~ 10) Ω	1.3×10^{-5}	
		(10 ~ 70) Ω	2.0×10^{-5}	
		(70 ~ 100) Ω	9.8×10^{-6}	
		(100 ~ 700) Ω	1.9×10^{-5}	
		(0.7 ~ 1) kΩ	9.6×10^{-6}	

402. Resistance, Capacitance and Inductance

Measured Quantity Instrument or Gauge	Field Code	Range	Measurement uncertainty (The Confidence Level is about 95 %)	Standard/Method of Measurement etc.
Resistors Decade Resistance	40215	(1 ~ 7) kΩ (7 ~ 10) kΩ (10 ~ 70) kΩ (70 ~ 100) kΩ (100 ~ 600) kΩ (0.6 ~ 1) MΩ (1 ~ 7) MΩ (7 ~ 10) MΩ (10 ~ 100) MΩ (0.1 ~ 1) GΩ (1 ~ 10) GΩ (10 ~ 100) GΩ (0.1 ~ 1) TΩ (1 ~ 10) TΩ	3.5×10^{-5} 1.2×10^{-5} 2.0×10^{-5} 9.8×10^{-6} 2.9×10^{-5} 1.2×10^{-5} 8.0×10^{-5} 2.7×10^{-5} 2.0×10^{-4} 2.5×10^{-4} 7.0×10^{-4} 1.0×10^{-3} 1.5×10^{-3} 4.3×10^{-3}	Standard Resistance Set/ SICT-CP-40215
Impedance bridges/LCR meters Frequency AC Voltage Capacitance	40217	50 Hz ~ 100 MHz 1 mV (1 ~ 10) mV (10 ~ 100) mV (0.1 ~ 10) V (10 ~ 100) V (1 pF) 50 Hz ~ 1 kHz 1 kHz ~ 1 MHz 2 MHz 3 MHz 4 MHz 5 MHz 10 MHz 13 MHz (10 pF) 50 Hz ~ 5 MHz 10 MHz 13 MHz (100 pF) 50 Hz ~ 3 MHz 4 MHz 5 MHz 10 MHz 13 MHz	7.0×10^{-8} 2.1×10^{-3} 4.4×10^{-4} 8.8×10^{-5} 8.2×10^{-5} 8.9×10^{-5} 3.5×10^{-4} 3.6×10^{-4} 4.2×10^{-4} 5.4×10^{-4} 7.2×10^{-4} 9.4×10^{-4} 2.5×10^{-3} 3.6×10^{-3} 3.5×10^{-4} 3.7×10^{-4} 3.8×10^{-4} 3.5×10^{-4} 3.6×10^{-4} 3.7×10^{-4} 4.8×10^{-4} 6.0×10^{-4}	Standard Capacitor Set, Standard Resistor Set, Standard Inductor/ SICT-CP-40217

402. Resistance, Capacitance and Inductance

Measured Quantity Instrument or Gauge	Field Code	Range	Measurement uncertainty (The Confidence Level is about 95 %)	Standard/Method of Measurement etc.
Impedance bridges/LCR meters Capacitance	40217	(1 000 pF)		Standard Capacitor Set, Standard Resistor Set, Standard Inductor/ SICT-CP-40217
		50 Hz ~ 1 MHz	3.5×10^{-4}	
		2 MHz	3.8×10^{-4}	
		3 MHz	4.5×10^{-4}	
		4 MHz	5.6×10^{-4}	
		5 MHz	7.2×10^{-4}	
		10 MHz	2.0×10^{-3}	
		13 MHz	2.9×10^{-3}	
		(10 nF)		
		(50 ~ 100) Hz	3.0×10^{-4}	
		100 Hz ~ 100 kHz	8.1×10^{-5}	
		(100 nF)		
		(50 ~ 100) Hz	3.0×10^{-4}	
		100 Hz ~ 100 kHz	8.1×10^{-5}	
		(1 μF)		
		(50 ~ 100) Hz	5.1×10^{-4}	
		100 Hz ~ 10 kHz	8.1×10^{-5}	
		(10 ~ 100) kHz	1.0×10^{-4}	
		(10 μF)		
		120 Hz ~ 1 kHz	1.2×10^{-3}	
		(100 μF)		
		120 Hz	1.3×10^{-3}	
		(1 mF)		
		120 Hz	1.4×10^{-3}	
		(3 mF)		
		120 Hz	1.4×10^{-3}	
		(10 mF)		
120 Hz	1.4×10^{-3}			
(30 mF)				
120 Hz	2.9×10^{-3}			
(1 pF)				
1 kHz ~ 1 MHz	0.000 12			
1 MHz ~ 5 MHz	0.000 23			
5 MHz ~ 13 MHz	0.000 84			
(10 pF)				
1 kHz ~ 13 MHz	0.000 15			
(100 pF)				
1 kHz ~ 5 MHz	0.000 13			
5 MHz ~ 13 MHz	0.000 27			

402. Resistance, Capacitance and Inductance

Measured Quantity Instrument or Gauge	Field Code	Range	Measurement uncertainty (The Confidence Level is about 95 %)	Standard/Method of Measurement etc.
Impedance bridges/LCR meters Dissipation Factor	40217	(1 pF)		Standard Capacitor Set, Standard Resistor Set, Standard Inductor/ SICT-CP-40217
		1 kHz ~ 1 MHz	0.000 12	
		(1 ~ 5) MHz	0.000 23	
		(5 ~ 13) MHz	0.000 84	
		(10 pF)		
		1 kHz ~ 13 MHz	0.000 15	
		(100 pF)		
		1 kHz ~ 5 MHz	0.000 13	
		(5 ~ 13) MHz	0.000 27	
		(1 000 pF)		
		1 kHz ~ 1 MHz	0.000 12	
		(1 ~ 5) MHz	0.000 24	
		(5 ~ 13) MHz	0.000 86	
		(10 nF)		
		120 Hz ~ 100 kHz	0.000 46	
		(100 nF)		
		120 Hz ~ 100 kHz	0.000 58	
		(1 μF)		
		120 Hz ~ 100 kHz	0.000 81	
Resistance	40217	(1 mΩ)		
		50 Hz	6.0×10^{-3}	
		50 Hz ~ 1 kHz	5.0×10^{-3}	
		(10 mΩ)		
		50 Hz	1.0×10^{-3}	
		50 Hz ~ 1 kHz	5.2×10^{-4}	
		(100 mΩ)		
		50 Hz	7.1×10^{-4}	
		50 Hz ~ 1 kHz	3.3×10^{-4}	
		(1 Ω)		
		50 Hz	6.8×10^{-4}	
		50 Hz ~ 1 kHz	1.3×10^{-4}	
		(10 Ω)		
		50 Hz	9.1×10^{-4}	
		50 Hz ~ 1 kHz	1.3×10^{-4}	
		1 kHz ~ 1 MHz	3.3×10^{-4}	
		(1 ~ 2) MHz	5.2×10^{-4}	
		(2 ~ 3) MHz	6.1×10^{-4}	
		(3 ~ 4) MHz	7.1×10^{-4}	
		(4 ~ 5) MHz	1.0×10^{-3}	
(5 ~ 10) MHz	4.0×10^{-3}			
(10 ~ 13) MHz	6.0×10^{-3}			

402. Resistance, Capacitance and Inductance

Measured Quantity Instrument or Gauge	Field Code	Range	Measurement uncertainty (The Confidence Level is about 95 %)	Standard/Method of Measurement etc.
Impedance bridges/LCR meters	40217	Resistance	(100 Ω)	Standard Capacitor Set, Standard Resistor Set, Standard Inductor/ SICT-CP-40217
		50 Hz	6.2×10^{-4}	
		50 Hz ~ 1 kHz	1.3×10^{-4}	
		1 kHz ~ 1 MHz	3.3×10^{-4}	
		(1 ~ 2) MHz	4.2×10^{-4}	
		(2 ~ 5) MHz	5.2×10^{-4}	
		(5 ~ 10) MHz	2.0×10^{-3}	
		(10 ~ 13) MHz	3.0×10^{-3}	
		(1 kΩ)		
		1 kHz	1.3×10^{-4}	
		1 kHz ~ 3 MHz	3.3×10^{-4}	
		(3 ~ 4) MHz	4.2×10^{-4}	
		(4 ~ 5) MHz	5.2×10^{-4}	
		(5 ~ 10) MHz	2.0×10^{-3}	
		(10 ~ 13) MHz	3.0×10^{-3}	
		(10 kΩ)		
		1 kHz	1.3×10^{-4}	
		(1 ~ 100) kHz	2.4×10^{-4}	
		100 kHz ~ 1 MHz	3.3×10^{-4}	
		(100 kΩ)		
		1 kHz	1.4×10^{-4}	
		100 kHz ~ 1 MHz	3.3×10^{-4}	
		(1 MΩ)		
		1 kHz	3.0×10^{-4}	
		(10 MΩ)		
		1 kHz	2.9×10^{-3}	
		Inductance		
		(1 kHz)		
		100 μH	1.9×10^{-4}	
		1 mH	1.3×10^{-4}	
		10 mH	1.3×10^{-4}	
		100 mH	1.3×10^{-4}	
		1 H	1.3×10^{-4}	
		10 H	1.3×10^{-4}	
		DC Bias		
		(±)		
		0 μV	0.68 μV	
		0 μV ~ 100 mV	1.1×10^{-5}	
		(0.1 ~ 1) V	7.5×10^{-6}	
		(1 ~ 10) V	7.2×10^{-6}	
		(10 ~ 100) V	8.2×10^{-6}	
		DC Current		
		0 μA	5.8 μA	
		0 μA ~ 200 mA	4.1×10^{-5}	
		(0.2 ~ 2) A	3.6×10^{-5}	
		(2 ~ 20) A	1.9×10^{-4}	
		(20 ~ 100) A	1.4×10^{-4}	

403. AC voltage, current & power

Measured Quantity Instrument or Gauge	Field Code	Range	Measurement uncertainty (The Confidence Level is about 95 %)	Standard/Method of Measurement etc.
AC ammeters AC Current	40301	(100 μ A) 40 Hz ~ 1 kHz (1 ~ 5) kHz (5 ~ 10) kHz (100 μ A ~ 1 mA) 40 Hz ~ 1 kHz (1 ~ 5) kHz (5 ~ 10) kHz (1 ~ 10) mA 40 Hz ~ 1 kHz (1 ~ 5) kHz (5 ~ 10) kHz (10 ~ 100) mA 40 Hz ~ 1 kHz (1 ~ 5) kHz (5 ~ 10) kHz (100 mA ~ 1 A) 40 Hz ~ 1 kHz (1 ~ 5) kHz (5 ~ 10) kHz (1 ~ 10) A (40 ~ 100) Hz 100 Hz ~ 5 kHz (10 ~ 20) A (40 ~ 100) Hz 100 Hz ~ 5 kHz (20 ~ 100) A (40 ~ 100) Hz 100 Hz ~ 5 kHz (100 ~ 200) A 60 Hz	2.2×10^{-4} 4.9×10^{-4} 2.1×10^{-3} 1.8×10^{-4} 3.8×10^{-4} 2.1×10^{-3} 1.8×10^{-4} 3.4×10^{-4} 1.9×10^{-3} 1.7×10^{-4} 3.2×10^{-4} 1.5×10^{-3} 3.5×10^{-4} 6.7×10^{-4} 8.3×10^{-3} 2.1×10^{-4} 5.8×10^{-4} 2.0×10^{-4} 5.3×10^{-4} 1.9×10^{-4} 5.9×10^{-4} 8.5×10^{-4}	Power Calibrator, Calibrator/ SICT-CP-40301
Clamp ammeters/voltmeters AC Current	40302	(100 μ A) 40 Hz ~ 1 kHz (1 ~ 5) kHz (5 ~ 10) kHz (100 ~ 300) μ A 40 Hz ~ 1 kHz (1 ~ 5) kHz (5 ~ 10) kHz (300 ~ 900) μ A 40 Hz ~ 1 kHz (1 ~ 5) kHz (5 ~ 10) kHz	6.5×10^{-4} 7.8×10^{-4} 2.1×10^{-3} 3.8×10^{-4} 7.9×10^{-4} 4.0×10^{-3} 3.1×10^{-4} 6.4×10^{-4} 3.3×10^{-3}	Power Calibrator, Calibrator/ SICT-CP-40302

403. AC voltage, current & power

Measured Quantity Instrument or Gauge	Field Code	Range	Measurement uncertainty (The Confidence Level is about 95 %)	Standard/Method of Measurement etc.
Clamp ammeters/voltmeters AC Current	40302	(900 μ A ~ 1 mA)		Power Calibrator, Calibrator/ SICT-CP-40302
		40 Hz ~ 1 kHz	6.3×10^{-4}	
		(1 ~ 5) kHz	7.2×10^{-4}	
		(5 ~ 10) kHz	2.1×10^{-3}	
		(1 ~ 3) mA		
		40 Hz ~ 1 kHz	3.8×10^{-4}	
		(1 ~ 5) kHz	7.2×10^{-4}	
		(5 ~ 10) kHz	3.8×10^{-3}	
		(3 ~ 9) mA		
		40 Hz ~ 1 kHz	3.1×10^{-4}	
		(1 ~ 5) kHz	5.8×10^{-4}	
		(5 ~ 10) kHz	3.1×10^{-3}	
		(9 ~ 10) mA		
		40 Hz ~ 1 kHz	6.3×10^{-4}	
		(1 ~ 5) kHz	7.0×10^{-4}	
		(5 ~ 10) kHz	2.0×10^{-3}	
		(10 ~ 30) mA		
		40 Hz ~ 1 kHz	3.6×10^{-4}	
		(1 ~ 5) kHz	6.8×10^{-4}	
		(5 ~ 10) kHz	2.6×10^{-3}	
		(30 ~ 90) mA		
		40 Hz ~ 1 kHz	2.9×10^{-4}	
		(1 ~ 5) kHz	5.4×10^{-4}	
		(5 ~ 10) kHz	2.2×10^{-3}	
(90 ~ 100) mA				
40 Hz ~ 1 kHz	6.3×10^{-4}			
(1 ~ 5) kHz	6.9×10^{-4}			
(5 ~ 10) kHz	1.6×10^{-3}			
(100 ~ 300) mA				
40 Hz	3.3×10^{-4}			
40 Hz ~ 1 kHz	5.7×10^{-4}			
(1 ~ 5) kHz	1.2×10^{-3}			
(5 ~ 10) kHz	9.3×10^{-3}			
(300 ~ 900) mA				
40 Hz	5.1×10^{-4}			
40 Hz ~ 1 kHz	4.8×10^{-4}			
(1 ~ 5) kHz	1.0×10^{-3}			
(5 ~ 10) kHz	8.9×10^{-3}			
(900 mA ~ 1 A)				
40 Hz ~ 1 kHz	7.0×10^{-4}			
(1 ~ 5) kHz	9.0×10^{-4}			
(5 ~ 10) kHz	5.1×10^{-3}			

403. AC voltage, current & power

Measured Quantity Instrument or Gauge	Field Code	Range	Measurement uncertainty (The Confidence Level is about 95 %)	Standard/Method of Measurement etc.
Clamp ammeters/voltmeters AC Current	40302	(1 ~ 2) A		Power Calibrator, Calibrator/ SICT-CP-40302
		40 Hz ~ 1 kHz	4.3×10^{-4}	
		(1 ~ 5) kHz	6.6×10^{-4}	
		(5 ~ 10) kHz	4.6×10^{-3}	
		(2 ~ 3) A		
		(40 ~ 100) Hz	5.7×10^{-4}	
		100 Hz ~ 5 kHz	9.7×10^{-4}	
		(5 ~ 10) kHz	4.5×10^{-3}	
		(3 ~ 9) A		
		(40 ~ 100) Hz	4.4×10^{-4}	
		100 Hz ~ 5 kHz	8.2×10^{-4}	
		(5 ~ 10) kHz	4.4×10^{-3}	
		(9 ~ 10) A		
		(40 ~ 100) Hz	6.4×10^{-4}	
		100 Hz ~ 5 kHz	8.5×10^{-4}	
		(5 ~ 10) kHz	4.3×10^{-3}	
		(10 ~ 30) A		
		(40 ~ 100) Hz	3.6×10^{-4}	
		100 Hz ~ 5 kHz	7.0×10^{-4}	
		(5 ~ 10) kHz	6.2×10^{-2}	
		(30 ~ 90) A		
		(40 ~ 100) Hz	2.5×10^{-4}	
		100 Hz ~ 5 kHz	6.4×10^{-4}	
		(5 ~ 10) kHz	5.5×10^{-2}	
(90 ~ 100) A				
(40 ~ 100) Hz	1.8×10^{-4}			
100 Hz ~ 5 kHz	5.4×10^{-4}			
(5 ~ 10) kHz	4.3×10^{-2}			
(100 ~ 1 000) A				
40 Hz	1.3×10^{-3}			
40 Hz ~ 1 kHz	2.5×10^{-3}			
(1 000 ~ 2 500) A				
(40 ~ 60) Hz	1.3×10^{-3}			
(2 500 ~ 3 000) A				
60 Hz	1.3×10^{-3}			
(3 000 ~ 10 000) A				
60 Hz	3.6×10^{-4}			

403. AC voltage, current & power

Measured Quantity Instrument or Gauge	Field Code	Range	Measurement uncertainty (The Confidence Level is about 95 %)	Standard/Method of Measurement etc.	
Clamp ammeters/voltmeters	40302	DC Current	0 μ A	9.2 nA	Power Calibrator, Calibrator/ SICT-CP-40302
			(0 ~ 0.1) μ A	9.2×10^{-2}	
		(0.1 ~ 0.2) μ A	4.6×10^{-2}		
		(0.2 ~ 0.3) μ A	3.1×10^{-2}		
		(0.3 ~ 0.9) μ A	2.3×10^{-2}		
		(0.9 ~ 1) μ A	9.3×10^{-3}		
		(1 ~ 2) μ A	4.7×10^{-3}		
		(2 ~ 3) μ A	3.1×10^{-3}		
		(3 ~ 9) μ A	2.3×10^{-3}		
		(9 ~ 10) μ A	9.6×10^{-4}		
		(10 ~ 20) μ A	5.1×10^{-4}		
		(20 ~ 30) μ A	3.5×10^{-4}		
		(30 ~ 50) μ A	2.7×10^{-4}		
		(50 ~ 90) μ A	1.9×10^{-4}		
		(90 ~ 100) μ A	6.2×10^{-4}		
		(100 ~ 200) μ A	3.2×10^{-4}		
		(200 ~ 700) μ A	2.2×10^{-4}		
		(700 ~ 900) μ A	9.3×10^{-5}		
		(0.9 ~ 1) mA	6.1×10^{-4}		
		(1 ~ 2) mA	3.1×10^{-4}		
		(2 ~ 7) mA	2.2×10^{-4}		
		(7 ~ 9) mA	9.1×10^{-5}		
		(9 ~ 10) mA	6.1×10^{-4}		
		(10 ~ 20) mA	3.1×10^{-4}		
		(20 ~ 70) mA	2.2×10^{-4}		
		(70 ~ 90) mA	9.9×10^{-5}		
		(90 ~ 100) mA	6.1×10^{-4}		
		(100 ~ 200) mA	3.1×10^{-4}		
		(200 ~ 700) mA	2.5×10^{-4}		
		(700 ~ 900) mA	1.3×10^{-4}		
		(0.9 ~ 1) A	6.4×10^{-4}		
		(1 ~ 2) A	3.4×10^{-4}		
		(2 ~ 3) A	4.5×10^{-4}		
		(3 ~ 7) A	3.6×10^{-4}		
		(7 ~ 9) A	2.2×10^{-4}		
		(9 ~ 10) A	6.4×10^{-4}		
		(10 ~ 30) A	3.4×10^{-4}		
		(30 ~ 70) A	2.6×10^{-4}		
		(70 ~ 100) A	1.7×10^{-4}		
		(100 ~ 2 500) A	1.3×10^{-3}		
		AC Voltage	(1 mV)		
			40 Hz ~ 10 kHz	4.8×10^{-3}	
			(10 ~ 50) kHz	5.0×10^{-3}	
			(50 ~ 100) kHz	6.5×10^{-3}	
			(1 ~ 2) mV		
			40 Hz ~ 10 kHz	2.4×10^{-3}	
			(10 ~ 50) kHz	2.6×10^{-3}	
			(50 ~ 100) kHz	3.5×10^{-3}	

403. AC voltage, current & power

Measured Quantity Instrument or Gauge	Field Code	Range	Measurement uncertainty (The Confidence Level is about 95 %)	Standard/Method of Measurement etc.
Clamp ammeters/voltmeters AC Voltage	40302	(2 ~ 5) mV		Power Calibrator, Calibrator/ SICT-CP-40302
		40 Hz ~ 10 kHz	1.7×10^{-3}	
		(10 ~ 50) kHz	1.9×10^{-3}	
		(50 ~ 100) kHz	2.7×10^{-3}	
		(5 ~ 7) mV		
		40 Hz ~ 10 kHz	8.9×10^{-4}	
		(10 ~ 50) kHz	1.0×10^{-3}	
		(50 ~ 100) kHz	1.6×10^{-3}	
		(7 ~ 9) mV		
		40 Hz ~ 10 kHz	6.9×10^{-4}	
		(10 ~ 50) kHz	8.4×10^{-4}	
		(50 ~ 100) kHz	1.4×10^{-3}	
		(9 ~ 10) mV		
		40 Hz ~ 10 kHz	8.3×10^{-4}	
		(10 ~ 50) kHz	9.4×10^{-4}	
		(50 ~ 100) kHz	1.3×10^{-3}	
		(10 ~ 30) mV		
		40 Hz ~ 10 kHz	4.5×10^{-4}	
		(10 ~ 50) kHz	5.6×10^{-4}	
		(50 ~ 100) kHz	1.1×10^{-3}	
		(30 ~ 50) mV		
		40 Hz ~ 10 kHz	3.2×10^{-4}	
		(10 ~ 50) kHz	4.0×10^{-4}	
		(50 ~ 100) kHz	9.0×10^{-4}	
(50 ~ 70) mV				
40 Hz ~ 10 kHz	2.3×10^{-4}			
(10 ~ 50) kHz	3.1×10^{-4}			
(50 ~ 100) kHz	7.1×10^{-4}			
(70 ~ 90) mV				
40 Hz ~ 10 kHz	1.9×10^{-4}			
(10 ~ 50) kHz	2.6×10^{-4}			
(50 ~ 100) kHz	6.2×10^{-4}			
(90 ~ 100) mV				
40 Hz ~ 10 kHz	1.6×10^{-4}			
(10 ~ 50) kHz	2.4×10^{-4}			
(50 ~ 100) kHz	5.7×10^{-4}			
(100 ~ 200) mV				
40 Hz ~ 10 kHz	1.1×10^{-4}			
(10 ~ 50) kHz	1.8×10^{-4}			
(50 ~ 100) kHz	4.6×10^{-4}			

403. AC voltage, current & power

Measured Quantity Instrument or Gauge	Field Code	Range	Measurement uncertainty (The Confidence Level is about 95 %)	Standard/Method of Measurement etc.
Clamp ammeters/voltmeters AC Voltage	40302	(200 ~ 500) mV 40 Hz ~ 10 kHz (10 ~ 50) kHz (50 ~ 100) kHz	8.8×10^{-5} 1.4×10^{-4} 2.2×10^{-4}	Power Calibrator, Calibrator/ SICT-CP-40302
		(500 ~ 700) mV 40 Hz ~ 10 kHz (10 ~ 50) kHz (50 ~ 100) kHz	7.1×10^{-5} 1.0×10^{-4} 1.6×10^{-4}	
		(700 ~ 900) mV 40 Hz ~ 10 kHz (10 ~ 50) kHz (50 ~ 100) kHz	6.5×10^{-5} 9.5×10^{-5} 1.4×10^{-4}	
		(900 mV ~ 1 V) 40 Hz ~ 10 kHz (10 ~ 50) kHz (50 ~ 100) kHz	8.6×10^{-5} 1.1×10^{-4} 1.5×10^{-4}	
		(1 ~ 2) V 40 Hz ~ 10 kHz (10 ~ 50) kHz (50 ~ 100) kHz	6.4×10^{-5} 9.0×10^{-5} 1.2×10^{-4}	
		(2 ~ 5) V 40 Hz 40 Hz ~ 10 kHz (10 ~ 50) kHz (50 ~ 100) kHz	1.3×10^{-4} 9.7×10^{-5} 1.5×10^{-4} 2.2×10^{-4}	
		(5 ~ 7) V 40 Hz 40 Hz ~ 10 kHz (10 ~ 50) kHz (50 ~ 100) kHz	8.2×10^{-5} 6.8×10^{-5} 1.1×10^{-4} 1.5×10^{-4}	
		(7 ~ 9) V 40 Hz 40 Hz ~ 10 kHz (10 ~ 50) kHz (50 ~ 100) kHz	7.0×10^{-5} 6.2×10^{-5} 9.9×10^{-5} 1.3×10^{-4}	
		(9 ~ 10) V 40 Hz 40 Hz ~ 10 kHz (10 ~ 50) kHz (50 ~ 100) kHz	8.9×10^{-5} 8.4×10^{-5} 1.1×10^{-4} 1.4×10^{-4}	
		(10 ~ 20) V 40 Hz ~ 10 kHz (10 ~ 50) kHz (50 ~ 100) kHz	6.2×10^{-5} 9.0×10^{-5} 1.1×10^{-4}	

403. AC voltage, current & power

Measured Quantity Instrument or Gauge	Field Code	Range	Measurement uncertainty (The Confidence Level is about 95 %)	Standard/Method of Measurement etc.
Clamp ammeters/voltmeters AC Voltage	40302	(20 ~ 50) V		Power Calibrator, Calibrator/ SICT-CP-40302
		40 Hz ~ 10 kHz	1.6×10^{-4}	
		(10 ~ 50) kHz	1.7×10^{-4}	
		(50 ~ 100) kHz	3.4×10^{-4}	
		(50 ~ 70) V		
		40 Hz	9.8×10^{-5}	
		40 Hz ~ 10 kHz	8.3×10^{-5}	
		(10 ~ 50) kHz	1.2×10^{-4}	
		(50 ~ 100) kHz	2.4×10^{-4}	
		(70 ~ 90) V		
		40 Hz	8.5×10^{-5}	
		40 Hz ~ 10 kHz	7.5×10^{-5}	
		(10 ~ 50) kHz	1.1×10^{-4}	
		(50 ~ 100) kHz	2.2×10^{-4}	
		(90 ~ 100) V		
		40 Hz ~ 10 kHz	9.9×10^{-5}	
		(10 ~ 50) kHz	1.2×10^{-4}	
		(50 ~ 100) kHz	2.2×10^{-4}	
		(100 ~ 200) V		
		40 Hz ~ 10 kHz	7.3×10^{-5}	
		(10 ~ 50) kHz	1.0×10^{-4}	
		(50 ~ 100) kHz	1.9×10^{-4}	
		(200 ~ 500) V		
		40 Hz ~ 1 kHz	1.3×10^{-4}	
		(1 ~ 10) kHz	2.2×10^{-4}	
		(10 ~ 20) kHz	6.6×10^{-4}	
		(500 ~ 1 000) V		
		40 Hz ~ 1 kHz	1.5×10^{-4}	
		(1 ~ 10) kHz	2.2×10^{-4}	
		(10 ~ 20) kHz	9.9×10^{-4}	
		DC Voltage		
		0 mV	61 μ V	
		(0 ~ 10) mV	6.1×10^{-3}	
		(10 ~ 20) mV	3.1×10^{-3}	
		(20 ~ 30) mV	2.0×10^{-3}	
		(30 ~ 60) mV	1.5×10^{-3}	
		(60 ~ 70) mV	8.7×10^{-4}	
		(70 ~ 80) mV	7.6×10^{-4}	
		(80 ~ 100) mV	6.8×10^{-4}	
		(100 ~ 200) mV	3.3×10^{-5}	
		(200 ~ 300) mV	2.2×10^{-5}	
		(300 ~ 800) mV	1.7×10^{-5}	
		(800 ~ 900) mV	9.6×10^{-6}	
		(0.9 ~ 1) V	6.1×10^{-5}	
		(1 ~ 2) V	3.1×10^{-5}	
		(2 ~ 3) V	2.1×10^{-5}	

403. AC voltage, current & power

Measured Quantity Instrument or Gauge	Field Code	Range	Measurement uncertainty (The Confidence Level is about 95 %)	Standard/Method of Measurement etc.
Clamp ammeters/voltmeters DC Voltage	40302	(3 ~ 6) V (6 ~ 7) V (7 ~ 9) V (9 ~ 10) V (10 ~ 20) V (20 ~ 30) V (30 ~ 80) V (80 ~ 90) V (90 ~ 100) V (100 ~ 200) V (200 ~ 300) V (300 ~ 500) V (500 ~ 900) V (900 ~ 1 000) V	1.6×10^{-5} 9.8×10^{-6} 8.8×10^{-6} 6.1×10^{-5} 3.1×10^{-5} 2.2×10^{-5} 1.7×10^{-5} 9.3×10^{-6} 6.1×10^{-5} 3.2×10^{-5} 2.3×10^{-5} 1.8×10^{-5} 1.3×10^{-5} 6.2×10^{-5}	Power Calibrator, Calibrator/ SICT-CP-40302
Resistance		0 Ω (0 ~ 9) Ω (9 ~ 100) Ω (100 ~ 900) Ω (0.9 ~ 9) kΩ (9 ~ 90) kΩ (0.090 ~ 1) MΩ (1 ~ 10) MΩ (10 ~ 100) MΩ	0.61 mΩ 0.66 mΩ 6.2 mΩ 9.2 mΩ 92 mΩ 1.1 Ω 63 Ω 0.77 kΩ 13 kΩ	
AC voltage/current calibrators AC Voltage	40303	(1 mV) 10 Hz ~ 10 kHz (10 ~ 100) kHz 100 kHz ~ 1 MHz (1 ~ 2) mV 10 Hz ~ 10 kHz (10 ~ 100) kHz 100 kHz ~ 1 MHz (2 ~ 5) mV 10 Hz 10 Hz ~ 10 kHz (10 ~ 100) kHz 100 kHz ~ 1 MHz (5 ~ 10) mV 10 Hz 10 Hz ~ 10 kHz (10 ~ 100) kHz 100 kHz ~ 1 MHz (10 ~ 20) mV 10 Hz 10 Hz ~ 10 kHz (10 ~ 100) kHz 100 kHz ~ 1 MHz	1.7×10^{-3} 3.0×10^{-3} 1.2×10^{-2} 1.1×10^{-3} 1.7×10^{-3} 7.7×10^{-3} 6.4×10^{-4} 5.8×10^{-4} 1.0×10^{-3} 5.4×10^{-3} 4.2×10^{-4} 3.5×10^{-4} 5.8×10^{-4} 3.9×10^{-3} 1.8×10^{-4} 1.4×10^{-4} 2.2×10^{-4} 2.2×10^{-3}	Alternating Voltage Measurement Standard, Reference Multimeter, Current Shunt/ SICT-CP-40303

403. AC voltage, current & power

Measured Quantity Instrument or Gauge	Field Code	Range	Measurement uncertainty (The Confidence Level is about 95 %)	Standard/Method of Measurement etc.
AC voltage/current calibrators AC Voltage	40303	(20 ~ 50) mV		Alternating Voltage Measurement Standard, Reference Multimeter, Current Shunt/ SICT-CP-40303
		10 Hz	1.4×10^{-4}	
		10 Hz ~ 10 kHz	9.2×10^{-5}	
		(10 ~ 100) kHz	1.6×10^{-4}	
		100 kHz ~ 1 MHz	1.4×10^{-3}	
		(50 ~ 100) mV		
		10 Hz	1.1×10^{-4}	
		10 Hz ~ 10 kHz	6.6×10^{-5}	
		(10 ~ 100) kHz	1.2×10^{-4}	
		100 kHz ~ 1 MHz	1.3×10^{-3}	
		(100 ~ 200) mV		
		10 Hz	8.2×10^{-5}	
		10 Hz ~ 10 kHz	3.9×10^{-5}	
		(10 ~ 100) kHz	7.6×10^{-5}	
		100 kHz ~ 1 MHz	1.1×10^{-3}	
		(200 ~ 500) mV		
		10 Hz	7.8×10^{-5}	
		10 Hz ~ 10 kHz	3.6×10^{-5}	
		(10 ~ 100) kHz	7.1×10^{-5}	
		100 kHz ~ 1 MHz	1.1×10^{-3}	
		(500 mV ~ 1 V)		
		10 Hz	7.6×10^{-5}	
		10 Hz ~ 10 kHz	3.3×10^{-5}	
		(10 ~ 100) kHz	6.6×10^{-5}	
		100 kHz ~ 1 MHz	1.1×10^{-3}	
		(1 ~ 2) V		
		10 Hz	7.1×10^{-5}	
		10 Hz ~ 10 kHz	2.7×10^{-5}	
		(10 ~ 100) kHz	5.8×10^{-5}	
		100 kHz ~ 1 MHz	1.0×10^{-3}	
		(2 ~ 5) V		
		10 Hz	7.2×10^{-5}	
		10 Hz ~ 10 kHz	2.6×10^{-5}	
		10 kHz ~ 100 kHz	7.5×10^{-5}	
		100 kHz ~ 1 MHz	1.4×10^{-3}	
		(5 ~ 20) V		
		10 Hz	7.2×10^{-5}	
		10 Hz ~ 10 kHz	2.8×10^{-5}	
		(10 ~ 100) kHz	7.5×10^{-5}	
		100 kHz ~ 1 MHz	1.4×10^{-3}	
(20 ~ 50) V				
10 Hz	7.2×10^{-5}			
10 Hz ~ 10 kHz	3.0×10^{-5}			
(10 ~ 100) kHz	8.0×10^{-5}			

403. AC voltage, current & power

Measured Quantity Instrument or Gauge	Field Code	Range	Measurement uncertainty (The Confidence Level is about 95 %)	Standard/Method of Measurement etc.
AC voltage/current calibrators	40303	(50 ~ 200) V		Alternating Voltage Measurement Standard, Reference Multimeter, Current Shunt/ SICT-CP-40303
		10 Hz	7.4×10^{-5}	
AC Voltage	10 Hz ~ 10 kHz	3.3×10^{-5}		
	(10 ~ 100) kHz	8.5×10^{-5}		
	(200 ~ 1 000) V			
	10 Hz	7.7×10^{-5}		
	10 Hz ~ 10 kHz	3.3×10^{-5}		
	(10 ~ 100) kHz	5.8×10^{-4}		
AC Current	(10 μ A)			
	10 Hz ~ 10 kHz	2.6×10^{-3}		
	(10 ~ 100) μ A			
	10 Hz ~ 1 kHz	3.6×10^{-4}		
	(1 ~ 10) kHz	6.4×10^{-4}		
	(100 μ A ~ 1 mA)			
	10 Hz	9.8×10^{-5}		
	10 Hz ~ 1 kHz	7.5×10^{-5}		
	(1 ~ 10) kHz	9.4×10^{-5}		
	(1 ~ 100) mA			
	10 Hz	7.8×10^{-5}		
	10 Hz ~ 1 kHz	4.6×10^{-5}		
	(1 ~ 10) kHz	4.2×10^{-5}		
	(100 mA ~ 1 A)			
	10 Hz	8.1×10^{-5}		
	10 Hz ~ 1 kHz	4.9×10^{-5}		
	(1 ~ 10) kHz	4.4×10^{-5}		
	(1 ~ 2) A			
	10 Hz	7.9×10^{-5}		
	10 Hz ~ 1 kHz	4.7×10^{-5}		
	(1 ~ 10) kHz	4.5×10^{-5}		
	(2 ~ 5) A			
	10 Hz	8.2×10^{-5}		
	10 Hz ~ 1 kHz	5.2×10^{-5}		
	(1 ~ 10) kHz	5.0×10^{-5}		
	(5 ~ 10) A			
	10 Hz	8.6×10^{-5}		
	10 Hz ~ 1 kHz	5.9×10^{-5}		
	(1 ~ 10) kHz	7.8×10^{-5}		
	(10 ~ 20) A			
	10 Hz	9.3×10^{-5}		
	10 Hz ~ 1 kHz	6.8×10^{-5}		
	(1 ~ 10) kHz	7.8×10^{-5}		

403. AC voltage, current & power

Measured Quantity Instrument or Gauge	Field Code	Range	Measurement uncertainty (The Confidence Level is about 95 %)	Standard/Method of Measurement etc.
AC voltage/current calibrators AC Current	40303	(20 ~ 50) A 10 Hz 10 Hz ~ 1 kHz (1 ~ 10) kHz (50 ~ 100) A 10 Hz 10 Hz ~ 1 kHz (1 ~ 10) kHz (100 ~ 200) A 60 Hz	 1.0×10^{-4} 8.3×10^{-5} 1.1×10^{-4} 1.2×10^{-4} 9.7×10^{-5} 1.3×10^{-4} 4.5×10^{-4}	Alternating Voltage Measurement Standard, Reference Multimeter, Current Shunt/ SICT-CP-40303
Wattmeter calibrators AC Voltage	40304	(1 mV) 10 Hz ~ 10 kHz (10 ~ 100) kHz 100 kHz ~ 1 MHz (1 ~ 2) mV 10 Hz ~ 10 kHz (10 ~ 100) kHz 100 kHz ~ 1 MHz (2 ~ 5) mV 10 Hz 10 Hz ~ 10 kHz (10 ~ 100) kHz 100 kHz ~ 1 MHz (5 ~ 10) mV 10 Hz 10 Hz ~ 10 kHz (10 ~ 100) kHz 100 kHz ~ 1 MHz (10 ~ 20) mV 10 Hz 10 Hz ~ 10 kHz (10 ~ 100) kHz 100 kHz ~ 1 MHz (20 ~ 50) mV 10 Hz 10 Hz ~ 10 kHz (10 ~ 100) kHz 100 kHz ~ 1 MHz (50 ~ 100) mV 10 Hz 10 Hz ~ 10 kHz (10 ~ 100) kHz 100 kHz ~ 1 MHz	 1.7×10^{-3} 3.0×10^{-3} 1.2×10^{-2} 1.1×10^{-3} 1.7×10^{-3} 7.7×10^{-3} 6.4×10^{-4} 5.8×10^{-4} 1.0×10^{-3} 5.4×10^{-3} 4.2×10^{-4} 3.5×10^{-4} 5.8×10^{-4} 3.9×10^{-3} 1.8×10^{-4} 1.4×10^{-4} 2.2×10^{-4} 2.2×10^{-3} 1.4×10^{-4} 9.2×10^{-5} 1.6×10^{-4} 1.4×10^{-3} 1.1×10^{-4} 6.6×10^{-5} 1.2×10^{-4} 1.3×10^{-3}	Power Standard, Counter/ SICT-CP-40304

403. AC voltage, current & power

Measured Quantity Instrument or Gauge	Field Code	Range	Measurement uncertainty (The Confidence Level is about 95 %)	Standard/Method of Measurement etc.
Wattmeter calibrators AC Voltage	40304	(100 ~ 200) mV		Power Standard, Counter/ SICT-CP-40304
		10 Hz	8.2×10^{-5}	
		10 Hz ~ 10 kHz	3.9×10^{-5}	
		(10 ~ 100) kHz	7.6×10^{-5}	
		100 kHz ~ 1 MHz	1.1×10^{-3}	
		(200 ~ 500) mV		
		10 Hz	7.8×10^{-5}	
		10 Hz ~ 10 kHz	3.6×10^{-5}	
		(10 ~ 100) kHz	7.1×10^{-5}	
		100 kHz ~ 1 MHz	1.1×10^{-3}	
		(500 mV ~ 1 V)		
		10 Hz	7.6×10^{-5}	
		10 Hz ~ 10 kHz	3.3×10^{-5}	
		(10 ~ 100) kHz	6.6×10^{-5}	
		100 kHz ~ 1 MHz	1.1×10^{-3}	
		(1 ~ 2) V		
		10 Hz	7.1×10^{-5}	
		10 Hz ~ 10 kHz	2.7×10^{-5}	
		(10 ~ 100) kHz	5.8×10^{-5}	
		100 kHz ~ 1 MHz	1.0×10^{-3}	
		(2 ~ 5) V		
		10 Hz	7.2×10^{-5}	
		10 Hz ~ 10 kHz	2.6×10^{-5}	
		(10 ~ 100) kHz	7.5×10^{-5}	
		100 kHz ~ 1 MHz	1.4×10^{-3}	
		(5 ~ 20) V		
		10 Hz	7.2×10^{-5}	
		10 Hz ~ 10 kHz	2.8×10^{-5}	
(10 ~ 100) kHz	7.5×10^{-5}			
100 kHz ~ 1 MHz	1.4×10^{-3}			
(20 ~ 50) V				
10 Hz	7.2×10^{-5}			
10 Hz ~ 10 kHz	3.0×10^{-5}			
(10 ~ 100) kHz	8.0×10^{-5}			
(50 ~ 200) V				
10 Hz	7.4×10^{-5}			
10 Hz ~ 10 kHz	3.3×10^{-5}			
(10 ~ 100) kHz	8.5×10^{-5}			
(200 ~ 1 000) V				
10 Hz	7.7×10^{-5}			
10 Hz ~ 10 kHz	3.3×10^{-5}			
(10 ~ 100) kHz	5.8×10^{-4}			

403. AC voltage, current & power

Measured Quantity Instrument or Gauge	Field Code	Range	Measurement uncertainty (The Confidence Level is about 95 %)	Standard/Method of Measurement etc.
Wattmeter calibrators AC Current	40304	(10 μ A) 10 Hz ~ 10 kHz	2.6×10^{-3}	Power Standard, Counter/ SICT-CP-40304
		(10 ~ 100) μ A 10 Hz ~ 1 kHz (1 ~ 10) kHz	3.6×10^{-4} 6.4×10^{-4}	
		(100 μ A ~ 1 mA) 10 Hz 10 Hz ~ 1 kHz (1 ~ 10) kHz	9.8×10^{-5} 7.5×10^{-5} 9.4×10^{-5}	
		(1 ~ 100) mA 10 Hz 10 Hz ~ 1 kHz (1 ~ 10) kHz	7.8×10^{-5} 4.6×10^{-5} 4.2×10^{-5}	
		(100 mA ~ 1 A) 10 Hz 10 Hz ~ 1 kHz (1 ~ 10) kHz	8.1×10^{-5} 4.9×10^{-5} 4.4×10^{-5}	
		(1 ~ 2) A 10 Hz 10 Hz ~ 1 kHz (1 ~ 10) kHz	7.9×10^{-5} 4.7×10^{-5} 4.5×10^{-5}	
		(2 ~ 5) A 10 Hz 10 Hz ~ 1 kHz (1 ~ 10) kHz	8.2×10^{-5} 5.2×10^{-5} 5.0×10^{-5}	
		(5 ~ 10) A 10 Hz 10 Hz ~ 1 kHz (1 ~ 10) kHz	8.6×10^{-5} 5.9×10^{-5} 7.8×10^{-5}	
		(10 ~ 20) A 10 Hz 10 Hz ~ 1 kHz (1 ~ 10) kHz	9.3×10^{-5} 6.8×10^{-5} 7.8×10^{-5}	
		(20 ~ 50) A 10 Hz 10 Hz ~ 1 kHz (1 ~ 10) kHz	1.0×10^{-4} 8.3×10^{-5} 1.1×10^{-4}	
		(50 ~ 100) A 10 Hz 10 Hz ~ 1 kHz (1 ~ 10) kHz	1.2×10^{-4} 9.7×10^{-5} 1.3×10^{-4}	
		(100 ~ 200) A 60 Hz	4.5×10^{-4}	

403. AC voltage, current & power

Measured Quantity Instrument or Gauge	Field Code	Range	Measurement uncertainty (The Confidence Level is about 95 %)	Standard/Method of Measurement etc.
Wattmeter calibrators AC Power	40304	(50 ~ 60) Hz		Power Standard, Counter/ SICT-CP-40304
		0 mW	0.05 mW	
		(0 ~ 0.22) mW	3.2×10^{-1}	
		(0.22 ~ 1.1) mW	6.3×10^{-2}	
		(1.1 ~ 2.2) mW	3.1×10^{-2}	
		(2.2 ~ 11) mW	6.3×10^{-3}	
		(11 ~ 22) mW	3.1×10^{-3}	
		(22 ~ 44) mW	1.6×10^{-3}	
		(44 ~ 66) mW	1.1×10^{-3}	
		(66 ~ 88) mW	8.0×10^{-4}	
		(88 ~ 110) mW	6.4×10^{-4}	
		(110 ~ 480) mW	2.6×10^{-4}	
		(480 ~ 550) mW	2.3×10^{-4}	
		(0.55 ~ 1.1) W	1.4×10^{-4}	
		(1.1 ~ 5.5) W	1.6×10^{-4}	
5.5 W ~ 1.1 kW	1.4×10^{-4}			
(1.1 ~ 2.2) kW	1.5×10^{-4}			
(2.2 ~ 24) kW	1.4×10^{-4}			
Power Factor	(50 ~ 60) Hz	(0 ~ 550) mW		
		-1 ~ 1	2.3×10^{-4}	
		550 mW ~ 24 kW		
		-1 ~ 1	1.5×10^{-4}	
Harmonic Voltage	(50 ~ 60) Hz	(0.5 ~ 3) %	0.042 %	
		(3 ~ 10) %	0.052 %	
		(10 ~ 20) %	0.081 %	
Harmonic Current	(50 ~ 60) Hz	(0.5 ~ 3) %	0.042 %	
		(3 ~ 10) %	0.052 %	
		(10 ~ 20) %	0.055 %	
Flicker	P_{st} (0.25 ~ 5), (50 Hz) Modulation Frequency	8.333 mHz	2.7×10^{-3}	
		16.667 mHz	2.7×10^{-3}	
		58.333 mHz	2.7×10^{-3}	
		325.000 mHz	2.7×10^{-3}	
		916.667 mHz	2.7×10^{-3}	
		13.500 Hz	2.7×10^{-3}	
		33.333 Hz	2.7×10^{-3}	
Frequency	(10 ~ 100) Hz	(100 ~ 400) Hz	7.0×10^{-7}	
		(100 ~ 400) Hz	3.8×10^{-7}	
		400 Hz ~ 1 MHz	7.0×10^{-7}	

403. AC voltage, current & power

Measured Quantity Instrument or Gauge	Field Code	Range	Measurement uncertainty (The Confidence Level is about 95 %)	Standard/Method of Measurement etc.
AC current shunts AC Resistance	40305	(100 ~ 200) A (60 Hz) 1 mΩ	8.4×10^{-4}	Reference Multimeter, Calibrator/ SICT-CP-40305
		(40 ~ 60) Hz (1 ~ 10) mΩ (10 ~ 100) mΩ	2.1×10^{-4} 3.5×10^{-4}	
		(60 Hz ~ 1 kHz) (1 ~ 10) mΩ (10 ~ 100) mΩ	5.7×10^{-4} 3.4×10^{-4}	
		(40 Hz ~ 1 kHz) 100 mΩ ~ 100 Ω 100 Ω ~ 10 kΩ	1.8×10^{-4} 2.3×10^{-4}	
AC Voltage dividers		(50 Hz) (1 ~ 100) kV (60 Hz) (1 ~ 100) kV	2.6×10^{-4} 1.9×10^{-4}	
Phase angle generators, synchro resolve generators Phase	40306	(-180 ~ 180) ° 50 Hz (50 ~ 500) Hz (500 ~ 1 000) Hz	0.0016° 0.0031° 0.010°	전력 교정기/ SICT-CP-40307
Voltage/current phase angle meters/synchro resolve meters Phase	40307	(50 ~ 60) Hz (-180 ~ 180) °	0.0088°	Power Calibrator/ SICT-CP-40307
Potential transformer test sets Ratio	40308	(110 ~ 1 100) V (-19.99 ~ 19.99) % (-680 ~ 680)'	0.020% $0.70'$	Standard Potential transforme, Ratio transformers/ SICT-CP-40308
		(1 100 ~ 100 000) V (-19.99 ~ 19.99) % Phase (-680 ~ 680)'	0.016% $0.50'$	
Potential transformer Ratio	40309	(110 ~ 1 100) V (-19.99 ~ 19.99) % (-680 ~ 680)'	0.020% $0.70'$	Standard Potential transforme/ SICT-CP-40309
		(1 100 ~ 100 000) V (-19.99 ~ 19.99) % Phase (-680 ~ 680)'	0.016% $0.50'$	

403. AC voltage, current & power

Measured Quantity Instrument or Gauge	Field Code	Range	Measurement uncertainty (The Confidence Level is about 95 %)	Standard/Method of Measurement etc.
Power factor meters AC Power Factor	40310	(50 Hz, 60 Hz) -1 ~ 1	1.1×10^{-4}	Power Calibrator/ SICT-CP-40310
AC power meters AC Voltage	40311	(1 mV) 40 Hz ~ 10 kHz (10 ~ 50) kHz (50 ~ 100) kHz (1 ~ 2) mV 40 Hz ~ 10 kHz (10 ~ 50) kHz (50 ~ 100) kHz (2 ~ 5) mV 40 Hz ~ 10 kHz (10 ~ 50) kHz (50 ~ 100) kHz (5 ~ 7) mV 40 Hz ~ 10 kHz (10 ~ 50) kHz (50 ~ 100) kHz (7 ~ 9) mV 40 Hz ~ 10 kHz (10 ~ 50) kHz (50 ~ 100) kHz (9 ~ 10) mV 40 Hz ~ 10 kHz (10 ~ 50) kHz (50 ~ 100) kHz (10 ~ 30) mV 40 Hz ~ 10 kHz (10 ~ 50) kHz (50 ~ 100) kHz (30 ~ 60) mV 40 Hz ~ 10 kHz (10 ~ 50) kHz (50 ~ 100) kHz (60 ~ 200) mV 40 Hz ~ 10 kHz (10 ~ 50) kHz (50 ~ 100) kHz	4.8×10^{-3} 5.0×10^{-3} 6.5×10^{-3} 2.4×10^{-3} 2.6×10^{-3} 3.5×10^{-3} 1.7×10^{-3} 1.9×10^{-3} 2.7×10^{-3} 8.9×10^{-4} 1.0×10^{-3} 1.6×10^{-3} 6.9×10^{-4} 8.4×10^{-4} 1.4×10^{-3} 5.7×10^{-4} 7.1×10^{-4} 1.2×10^{-3} 3.6×10^{-4} 4.7×10^{-4} 1.1×10^{-3} 2.9×10^{-4} 3.7×10^{-4} 8.8×10^{-4} 1.9×10^{-4} 2.7×10^{-4} 6.5×10^{-4}	Power Calibrator, Calibrator/ SICT-CP-40311

403. AC voltage, current & power

Measured Quantity Instrument or Gauge	Field Code	Range	Measurement uncertainty (The Confidence Level is about 95 %)	Standard/Method of Measurement etc.
AC power meters AC Voltage	40311	(200 ~ 300) mV		Power Calibrator, Calibrator/ SICT-CP-40311
		40 Hz ~ 10 kHz	8.6×10^{-5}	
		(10 ~ 50) kHz	1.3×10^{-4}	
		(50 ~ 100) kHz	2.2×10^{-4}	
		(300 ~ 600) mV		
		40 Hz ~ 10 kHz	7.6×10^{-5}	
		(10 ~ 50) kHz	1.2×10^{-4}	
		(50 ~ 100) kHz	1.9×10^{-4}	
		(600 mV ~ 1 V)		
		40 Hz ~ 10 kHz	6.7×10^{-5}	
		(10 ~ 50) kHz	9.8×10^{-5}	
		(50 ~ 100) kHz	1.5×10^{-4}	
		(1 ~ 2) V		
		40 Hz ~ 10 kHz	5.6×10^{-5}	
		(10 ~ 50) kHz	8.5×10^{-5}	
		(50 ~ 100) kHz	1.2×10^{-4}	
		(2 ~ 3) V		
		40 Hz	1.3×10^{-4}	
		40 Hz ~ 10 kHz	9.5×10^{-5}	
		(10 ~ 50) kHz	1.5×10^{-4}	
		(50 ~ 100) kHz	2.2×10^{-4}	
		(3 ~ 5) V		
		40 Hz	1.1×10^{-4}	
		40 Hz ~ 10 kHz	8.0×10^{-5}	
		(10 ~ 50) kHz	1.3×10^{-4}	
		(50 ~ 100) kHz	1.8×10^{-4}	
		(5 ~ 7) V		
		40 Hz	8.1×10^{-5}	
		40 Hz ~ 10 kHz	6.7×10^{-5}	
		(10 ~ 50) kHz	1.1×10^{-4}	
		(50 ~ 100) kHz	1.5×10^{-4}	
		(7 ~ 20) V		
		40 Hz	7.0×10^{-5}	
		40 Hz ~ 10 kHz	6.1×10^{-5}	
		(10 ~ 50) kHz	9.9×10^{-5}	
		(50 ~ 100) kHz	1.3×10^{-4}	
(20 ~ 60) V				
40 Hz	1.6×10^{-4}			
40 Hz ~ 10 kHz	1.2×10^{-4}			
(10 ~ 50) kHz	1.6×10^{-4}			
(50 ~ 100) kHz	3.4×10^{-4}			

403. AC voltage, current & power

Measured Quantity Instrument or Gauge	Field Code	Range	Measurement uncertainty (The Confidence Level is about 95 %)	Standard/Method of Measurement etc.	
AC power meters AC Voltage	40311	(60 ~ 100) V		Power Calibrator, Calibrator/ SICT-CP-40311	
		40 Hz	9.0×10^{-5}		
		40 Hz ~ 10 kHz	7.8×10^{-5}		
		(10 ~ 50) kHz	1.2×10^{-4}		
		(50 ~ 100) kHz	2.3×10^{-4}		
		(100 ~ 200) V			
		40 Hz	6.7×10^{-5}		
		40 Hz ~ 10 kHz	6.5×10^{-5}		
		(10 ~ 50) kHz	9.9×10^{-5}		
		(50 ~ 100) kHz	1.9×10^{-4}		
		(200 ~ 400) V			
		40 Hz	1.4×10^{-4}		
		40 Hz ~ 1 kHz	1.1×10^{-4}		
		(1 ~ 10) kHz	2.2×10^{-4}		
		(10 ~ 20) kHz	6.6×10^{-4}		
		(400 ~ 500) V			
		40 Hz	1.3×10^{-4}		
		40 Hz ~ 1 kHz	1.1×10^{-4}		
		(1 ~ 10) kHz	2.1×10^{-4}		
		(10 ~ 20) kHz	5.4×10^{-4}		
		(500 ~ 600) V			
		40 Hz	1.5×10^{-4}		
		40 Hz ~ 1 kHz	1.3×10^{-4}		
		(1 ~ 10) kHz	2.2×10^{-4}		
		(10 ~ 20) kHz	9.9×10^{-4}		
		(600 ~ 700) V			
		40 Hz	1.4×10^{-4}		
		40 Hz ~ 1 kHz	1.2×10^{-4}		
		(1 ~ 10) kHz	2.2×10^{-4}		
		(10 ~ 20) kHz	8.5×10^{-4}		
		(700 ~ 900) V			
		40 Hz	1.3×10^{-4}		
		40 Hz ~ 1 kHz	1.1×10^{-4}		
		(1 ~ 10) kHz	2.1×10^{-4}		
(10 ~ 20) kHz	7.5×10^{-4}				
(900 ~ 1 000) V					
40 Hz	1.2×10^{-4}				
40 Hz ~ 1 kHz	1.0×10^{-4}				
(1 ~ 10) kHz	2.1×10^{-4}				
(10 ~ 20) kHz	6.1×10^{-4}				

403. AC voltage, current & power

Measured Quantity Instrument or Gauge	Field Code	Range	Measurement uncertainty (The Confidence Level is about 95 %)	Standard/Method of Measurement etc.
AC power meters AC Current	40311	(100 μ A) 40 Hz ~ 1 kHz (1 ~ 5) kHz (5 ~ 10) kHz	2.3×10^{-4} 4.9×10^{-4} 2.1×10^{-3}	Power Calibrator, Calibrator/ SICT-CP-40311
		(100 ~ 300) μ A 40 Hz ~ 1 kHz (1 ~ 5) kHz (5 ~ 10) kHz	2.3×10^{-4} 4.6×10^{-4} 1.8×10^{-3}	
		(300 μ A ~ 2 mA) 40 Hz ~ 1 kHz (1 ~ 5) kHz (5 ~ 10) kHz	1.9×10^{-4} 3.8×10^{-4} 2.1×10^{-3}	
		(2 ~ 4) mA 40 Hz ~ 1 kHz (1 ~ 5) kHz (5 ~ 10) kHz	3.2×10^{-4} 6.9×10^{-4} 3.8×10^{-3}	
		(4 ~ 7) mA 40 Hz ~ 1 kHz (1 ~ 5) kHz (5 ~ 10) kHz	2.3×10^{-4} 4.8×10^{-4} 2.7×10^{-3}	
		(7 ~ 20) mA 40 Hz ~ 1 kHz (1 ~ 5) kHz (5 ~ 10) kHz	1.9×10^{-4} 3.7×10^{-4} 2.1×10^{-3}	
		(20 ~ 30) mA 40 Hz ~ 1 kHz (1 ~ 5) kHz (5 ~ 10) kHz	2.9×10^{-4} 6.5×10^{-4} 2.6×10^{-3}	
		(30 ~ 60) mA 40 Hz ~ 1 kHz (1 ~ 5) kHz (5 ~ 10) kHz	2.4×10^{-4} 5.2×10^{-4} 2.2×10^{-3}	
		(60 ~ 200) mA 40 Hz ~ 1 kHz (1 ~ 5) kHz (5 ~ 10) kHz	1.8×10^{-4} 3.7×10^{-4} 1.7×10^{-3}	
		(200 ~ 300) mA 40 Hz (40 ~ 60) Hz 60 Hz ~ 1 kHz (1 ~ 5) kHz (5 ~ 10) kHz	5.8×10^{-4} 1.2×10^{-4} 5.3×10^{-4} 1.2×10^{-3} 9.3×10^{-3}	

403. AC voltage, current & power

Measured Quantity Instrument or Gauge	Field Code	Range	Measurement uncertainty (The Confidence Level is about 95 %)	Standard/Method of Measurement etc.
AC power meters AC Current	40311	(300 ~ 500) mA		Power Calibrator, Calibrator/ SICT-CP-40311
		40 Hz	4.9×10^{-4}	
		(40 ~ 60) Hz	1.1×10^{-4}	
		60 Hz ~ 1 kHz	4.6×10^{-4}	
		(1 ~ 5) kHz	1.0×10^{-3}	
		(5 ~ 10) kHz	8.9×10^{-3}	
		(500 ~ 800) mA		
		40 Hz	4.0×10^{-4}	
		(40 ~ 60) Hz	1.3×10^{-4}	
		60 Hz ~ 1 kHz	3.9×10^{-4}	
		(1 ~ 5) kHz	8.3×10^{-4}	
		(5 ~ 10) kHz	8.6×10^{-3}	
		(800 mA ~ 2 A)		
		40 Hz	3.5×10^{-4}	
		(40 ~ 60) Hz	9.5×10^{-5}	
		60 Hz ~ 1 kHz	3.5×10^{-4}	
		(1 ~ 5) kHz	7.2×10^{-4}	
		(5 ~ 10) kHz	8.4×10^{-3}	
		(2 ~ 3) A		
		40 Hz	5.3×10^{-4}	
(40 ~ 60) Hz	1.5×10^{-4}			
(60 ~ 100) Hz	5.3×10^{-4}			
100 Hz ~ 5 kHz	9.4×10^{-4}			
(5 ~ 10) kHz	4.5×10^{-3}			
(3 ~ 6) A				
40 Hz	4.1×10^{-4}			
(40 ~ 60) Hz	1.3×10^{-4}			
(60 ~ 100) Hz	4.1×10^{-4}			
100 Hz ~ 5 kHz	8.1×10^{-4}			
(5 ~ 10) kHz	4.4×10^{-3}			
(6 ~ 10) A				
40 Hz	2.6×10^{-4}			
(40 ~ 60) Hz	1.1×10^{-4}			
(60 ~ 100) Hz	2.6×10^{-4}			
100 Hz ~ 5 kHz	6.4×10^{-4}			
(5 ~ 10) kHz	4.3×10^{-3}			
(10 ~ 50) A				
40 Hz	2.4×10^{-4}			
(40 ~ 60) Hz	1.1×10^{-4}			
(60 ~ 100) Hz	2.4×10^{-4}			
100 Hz ~ 5 kHz	6.6×10^{-4}			
(5 ~ 10) kHz	6.2×10^{-2}			
(50 ~ 100) A				
(40 ~ 100) Hz	1.9×10^{-4}			
100 Hz ~ 5 kHz	5.7×10^{-4}			
(5 ~ 10) kHz	4.8×10^{-2}			

403. AC voltage, current & power

Measured Quantity Instrument or Gauge	Field Code	Range	Measurement uncertainty (The Confidence Level is about 95 %)	Standard/Method of Measurement etc.
AC power meters	AC Current	(100 ~ 1 000) A		Power Calibrator, Calibrator/ SICT-CP-40311
		(40 ~ 100) Hz	1.3×10^{-3}	
		100 Hz ~ 1 kHz	2.7×10^{-3}	
AC Wattage		(1 000 ~ 2 500) A		
		(40 ~ 60) Hz	1.2×10^{-3}	
		(2 500 ~ 3 000) A		
		60 Hz	1.3×10^{-3}	
		(50 ~ 60) Hz		
		0 mW	70 μ W	
		(0 ~ 0.22) mW	2.1×10^{-1}	
		(0.22 ~ 1.1) mW	4.1×10^{-2}	
		(1.1 ~ 2.2) mW	2.1×10^{-2}	
		(2.2 ~ 11) mW	4.1×10^{-3}	
		(11 ~ 22) mW	2.1×10^{-3}	
		(22 ~ 44) mW	1.0×10^{-3}	
		(44 ~ 66) mW	7.0×10^{-4}	
		(66 ~ 88) mW	5.3×10^{-4}	
		(88 ~ 110) mW	4.3×10^{-4}	
(110 ~ 480) mW	2.1×10^{-4}			
480 mW ~ 12 kW	1.2×10^{-4}			
(12 ~ 24) kW	6.8×10^{-4}			
(24 ~ 300) kW	1.2×10^{-3}			
(300 ~ 600) kW	1.4×10^{-3}			
DC Voltage		0 mV	0.78 μ V	
		(0 ~ 1) mV	8.0×10^{-4}	
		(1 ~ 2) mV	4.0×10^{-4}	
		(2 ~ 3) mV	2.7×10^{-4}	
		(3 ~ 4) mV	2.0×10^{-4}	
		(4 ~ 8) mV	1.6×10^{-4}	
		(8 ~ 9) mV	9.4×10^{-5}	
		(9 ~ 10) mV	8.5×10^{-5}	
		(10 ~ 20) mV	4.5×10^{-5}	
		(20 ~ 30) mV	3.2×10^{-5}	
		(30 ~ 60) mV	2.6×10^{-5}	
		(60 ~ 200) mV	1.8×10^{-5}	
		(200 ~ 300) mV	9.3×10^{-6}	
		(300 ~ 400) mV	8.3×10^{-6}	
		(400 ~ 700) mV	7.8×10^{-6}	
		(700 ~ 900) mV	6.9×10^{-6}	
		(0.9 ~ 1) V	9.0×10^{-6}	
		(1 ~ 2) V	7.2×10^{-6}	
		(2 ~ 3) V	5.6×10^{-6}	
		(3 ~ 9) V	5.1×10^{-6}	
		(9 ~ 10) V	7.5×10^{-6}	
		(10 ~ 20) V	6.0×10^{-6}	
		(20 ~ 40) V	7.9×10^{-6}	
		(40 ~ 90) V	6.9×10^{-6}	
(90 ~ 200) V	8.8×10^{-6}			
(200 ~ 400) V	9.9×10^{-6}			
(400 ~ 900) V	8.7×10^{-6}			
(900 ~ 1 000) V	1.0×10^{-5}			

403. AC voltage, current & power

Measured Quantity Instrument or Gauge	Field Code	Range	Measurement uncertainty (The Confidence Level is about 95 %)	Standard/Method of Measurement etc.		
AC power meters	40311	0 μ A	9.0 nA	Power Calibrator, Calibrator/ SICT-CP-40311		
DC Current		(0 ~ 0.1) μ A	9.0×10^{-2}			
		(0.1 ~ 0.2) μ A	4.5×10^{-2}			
		(0.2 ~ 0.3) μ A	3.0×10^{-2}			
		(0.3 ~ 0.4) μ A	2.3×10^{-2}			
		(0.4 ~ 0.9) μ A	1.8×10^{-2}			
		(0.9 ~ 1) μ A	9.1×10^{-3}			
		(1 ~ 2) μ A	4.5×10^{-3}			
		(2 ~ 3) μ A	3.0×10^{-3}			
		(3 ~ 4) μ A	2.3×10^{-3}			
		(4 ~ 9) μ A	1.8×10^{-3}			
		(9 ~ 10) μ A	9.4×10^{-4}			
		(10 ~ 20) μ A	5.0×10^{-4}			
		(20 ~ 30) μ A	3.4×10^{-4}			
		(30 ~ 50) μ A	2.7×10^{-4}			
		(50 ~ 90) μ A	1.9×10^{-4}			
		(90 ~ 100) μ A	1.3×10^{-4}			
		(100 ~ 200) μ A	8.6×10^{-5}			
		(200 ~ 300) μ A	6.5×10^{-5}			
		(300 ~ 500) μ A	5.5×10^{-5}			
		(0.5 ~ 2) mA	5.1×10^{-5}			
		(2 ~ 3) mA	7.3×10^{-5}			
		(3 ~ 4) mA	6.3×10^{-5}			
		(4 ~ 7) mA	5.7×10^{-5}			
		(7 ~ 20) mA	4.9×10^{-5}			
		(20 ~ 30) mA	8.2×10^{-5}			
		(30 ~ 50) mA	7.4×10^{-5}			
		(50 ~ 100) mA	6.6×10^{-5}			
		(100 ~ 200) mA	5.7×10^{-5}			
		(200 ~ 600) mA	1.5×10^{-4}			
		(0.6 ~ 2) A	1.1×10^{-4}			
		(2 ~ 3) A	4.0×10^{-4}			
		(3 ~ 4) A	3.2×10^{-4}			
		(4 ~ 7) A	2.8×10^{-4}			
		(7 ~ 10) A	2.1×10^{-4}			
		(10 ~ 20) A	1.5×10^{-4}			
		(20 ~ 30) A	2.5×10^{-4}			
		(30 ~ 80) A	2.1×10^{-4}			
		(80 ~ 100) A	1.5×10^{-4}			
		(100 ~ 2 500) A	1.3×10^{-3}			
DC Wattage			0 mW		61 nW	
			(0 ~ 1) mW		7.7×10^{-5}	
			(1 ~ 10) mW		4.8×10^{-5}	
		(10 ~ 100) mW	6.1×10^{-5}			
		(0.1 ~ 100) W	1.1×10^{-4}			
		(0.1 ~ 10) kW	1.9×10^{-4}			
		(10 ~ 20) kW	1.5×10^{-4}			
		(20 ~ 1 000) kW	1.0×10^{-3}			
		(1 000 ~ 2 500) kW	1.3×10^{-3}			

403. AC voltage, current & power

Measured Quantity Instrument or Gauge	Field Code	Range	Measurement uncertainty (The Confidence Level is about 95 %)	Standard/Method of Measurement etc.
AC power meters	40311			Power Calibrator, Calibrator/ SICT-CP-40311
Harmonic Voltage		(50 ~ 60) Hz (0.5 ~ 3) % (3 ~ 5) % (5 ~ 10) % (10 ~ 20) %	0.030 % 0.033 % 0.042 % 0.065 %	
Harmonic Current		(50 ~ 60) Hz (0.5 ~ 3) % (3 ~ 10) % (5 ~ 20) %	0.030 % 0.032 % 0.038 %	
Flicker		P_{st} (0.25 ~ 5), (50 Hz) Modulation Frequency 8.333 mHz 16.667 mHz 58.333 mHz 325 mHz 916.667 mHz 13.5 Hz 33.333 Hz	3.5×10^{-2} 3.5×10^{-2} 3.5×10^{-2} 3.5×10^{-2} 3.5×10^{-2} 3.5×10^{-2} 3.5×10^{-2}	
Frequency		10 Hz ~ 10 MHz	1.3×10^{-4}	
Power Factor		(50 ~ 60) Hz -1 ~ 1	1.1×10^{-4}	
Current burden		(50 ~ 60) Hz 1.25 VA (1.25 ~ 3.75) VA (3.75 ~ 5) VA (5 ~ 10) VA (10 ~ 100) VA	2.9×10^{-3} 1.5×10^{-3} 8.0×10^{-4} 5.1×10^{-4} 4.0×10^{-4}	
Current burden factor		0.5 ~ 1	2.2×10^{-4}	
Voltage burden		(50 ~ 60) Hz 1.25 VA (1.25 ~ 3.75) VA (3.75 ~ 5) VA (5 ~ 10) VA (10 ~ 100) VA	7.4×10^{-4} 4.6×10^{-4} 3.7×10^{-4} 3.0×10^{-4} 3.1×10^{-4}	
Voltage burden factor		0.5 ~ 1	1.6×10^{-4}	

403. AC voltage, current & power

Measured Quantity Instrument or Gauge	Field Code	Range	Measurement uncertainty (The Confidence Level is about 95 %)	Standard/Method of Measurement etc.	
AC power supplies	40312	AC Voltage	(10 mV) 40 Hz ~ 5 kHz	2.2×10^{-4}	Voltage Standard, Multimeter, Current Shunt/ SICT-CP-40312
		(10 ~ 100) mV 40 Hz ~ 5 kHz	7.9×10^{-5}		
		(100 mV ~ 1 V) 40 Hz ~ 5 kHz	6.7×10^{-5}		
		(1 ~ 10) V 40 Hz ~ 5 kHz	6.8×10^{-5}		
		(10 ~ 100) V 40 Hz ~ 5 kHz	7.0×10^{-5}		
		(100 ~ 600) V 40 Hz ~ 5 kHz	4.1×10^{-5}		
		(600 ~ 1 000) V 40 Hz ~ 5 kHz	7.1×10^{-5}		
		Frequency	10 Hz	9.5×10^{-5}	
		(10 ~ 50) Hz	1.9×10^{-5}		
		(50 ~ 100) Hz	7.7×10^{-6}		
		(0.1 ~ 1) kHz	8.4×10^{-7}		
		(1 ~ 5) kHz	3.8×10^{-7}		
		AC Current	(1 mA) (50 ~ 60) Hz	6.4×10^{-4}	
		(1 ~ 10) mA (50 ~ 60) Hz	3.6×10^{-4}		
		(10 ~ 100) mA (50 ~ 60) Hz	2.4×10^{-4}		
		(100 mA ~ 1 A) (50 ~ 60) Hz	2.1×10^{-4}		
		(1 ~ 10) A (50 ~ 60) Hz	2.3×10^{-4}		
		(10 ~ 20) A (50 ~ 60) Hz	4.0×10^{-4}		
		(20 ~ 30) A (50 ~ 60) Hz	6.4×10^{-4}		
		(30 ~ 50) A (50 ~ 60) Hz	4.2×10^{-4}		

403. AC voltage, current & power

Measured Quantity Instrument or Gauge	Field Code	Range	Measurement uncertainty (The Confidence Level is about 95 %)	Standard/Method of Measurement etc.
AC power supplies	40312	(±)		Voltage Standard, Multimeter, Current Shunt/ SICT-CP-40312
DC Voltage		0 mV	5.8 μV	
		(0 ~ 10) mV	5.8×10^{-4}	
		(10 ~ 100) mV	5.8×10^{-5}	
		(0.1 ~ 100) V	7.7×10^{-6}	
		(100 ~ 600) V	1.3×10^{-5}	
		(600 ~ 1 000) V	6.6×10^{-5}	
DC Current		(1 ~ 10) mA	5.8×10^{-3}	
		(10 ~ 100) mA	5.9×10^{-4}	
		(0.1 ~ 1) A	2.4×10^{-4}	
		(1 ~ 10) A	3.1×10^{-4}	
		(10 ~ 300) A	2.4×10^{-4}	
		(300 ~ 500) A	2.6×10^{-4}	
		(500 ~ 1 000) A	4.7×10^{-5}	
		(1 000 ~ 3 000) A	5.1×10^{-4}	
Load Regulation		(0 ~ 2) mV	0.16 mV	
		(2 ~ 20) mV	7.8×10^{-2}	
		(20 ~ 200) mV	8.2×10^{-3}	
Ripple		(0.1 ~ 0.4) mV	3.8×10^{-1}	
		(0.4 ~ 0.6) mV	1.1×10^{-1}	
		(0.6 ~ 1) mV	7.3×10^{-2}	
	(1 ~ 10) mV	4.4×10^{-2}		
	(10 ~ 50) mV	7.1×10^{-2}		
Harmonic Voltage	(50 ~ 60) Hz			
	0.5 %	0.050 %		
	(0.5 ~ 10) %	0.051 %		
	(10 ~ 20) %	0.082 %		
Harmonic Current	(50 ~ 60) Hz			
	0.5 %	0.050 %		
	(0.5 ~ 20) %	0.051 %		
Puncture/safety testers	40313	(±)		AC/DC Kilovoltmeter, High Voltage Digital Meter, Reference Multimeter/ SICT-CP-40313
DC Voltage		0 kV	0.58 V	
		(0 ~ 0.5) kV	1.2×10^{-3}	
		(0.5 ~ 1) kV	6.1×10^{-4}	
		(1 ~ 2) kV	3.0×10^{-4}	
		(2 ~ 100) kV	2.3×10^{-4}	
		(100 ~ 200) kV	1.2×10^{-2}	
AC Voltage		(50 ~ 60) Hz		
		0.01 kV	0.58 V	
		(0.01 ~ 0.5) kV	1.2×10^{-3}	
		(0.5 ~ 1) kV	6.2×10^{-4}	
		(1 ~ 100) kV	5.7×10^{-4}	
		(100 ~ 200) kV	1.2×10^{-2}	

403. AC voltage, current & power

Measured Quantity Instrument or Gauge	Field Code	Range	Measurement uncertainty (The Confidence Level is about 95 %)	Standard/Method of Measurement etc.
Puncture/safety testers	40313	(50 ~ 60) Hz		AC/DC Kilovoltmeter, High Voltage Digital Meter, Reference Multimeter/ SICT-CP-40313
AC Breaking Current		0.1 mA	5.3×10^{-4}	
		(0.1 ~ 0.5) mA	4.4×10^{-4}	
		(0.5 ~ 1) mA	7.3×10^{-4}	
		(1 ~ 2) mA	7.1×10^{-4}	
		(2 ~ 5) mA	4.4×10^{-4}	
		(5 ~ 10) mA	3.6×10^{-4}	
		(10 ~ 20) mA	7.1×10^{-4}	
		(20 ~ 50) mA	4.4×10^{-4}	
		(50 ~ 100) mA	7.3×10^{-4}	
DC Breaking Current		0.1 mA	3.9×10^{-4}	
		(0.1 ~ 0.5) mA	1.3×10^{-4}	
		(0.5 ~ 1) mA	6.4×10^{-4}	
		(1 ~ 2) mA	3.2×10^{-4}	
		(2 ~ 5) mA	1.3×10^{-4}	
		(5 ~ 10) mA	6.5×10^{-5}	
		(10 ~ 20) mA	3.3×10^{-4}	
		(20 ~ 50) mA	1.4×10^{-4}	
		(50 ~ 100) mA	6.4×10^{-4}	
Resistance		1 mΩ	8.6×10^{-4}	
		(1 ~ 10) mΩ	7.2×10^{-4}	
		10 mΩ ~ 100 kΩ	6.8×10^{-4}	
Insulation Voltage		1 V	6.4×10^{-4}	
		(1 ~ 10) V	6.4×10^{-5}	
		(10 ~ 25) V	2.5×10^{-4}	
		(25 ~ 50) V	1.3×10^{-4}	
		(50 ~ 100) V	6.4×10^{-5}	
		(100 ~ 250) V	2.5×10^{-4}	
		(250 ~ 500) V	1.3×10^{-4}	
		(500 ~ 1 000) V	6.4×10^{-5}	
		(1 000 ~ 5 000) V	6.5×10^{-3}	
		(5 000 ~ 10 000) V	6.1×10^{-3}	
Insulation Resistance		1 kΩ	7.1×10^{-5}	
		(1 ~ 10) kΩ	3.7×10^{-5}	
		(10 ~ 100) kΩ	2.5×10^{-5}	
		(0.1 ~ 1) MΩ	3.1×10^{-5}	
	(1 ~ 10) MΩ	9.5×10^{-5}		
	(10 ~ 100) MΩ	2.4×10^{-5}		
	(0.1 ~ 1) GΩ	3.1×10^{-5}		
	(1 ~ 10) GΩ	6.1×10^{-5}		
	(10 ~ 100) GΩ	1.3×10^{-4}		
	(0.1 ~ 1) TΩ	2.6×10^{-4}		
	10 TΩ	6.3×10^{-4}		

403. AC voltage, current & power

Measured Quantity Instrument or Gauge	Field Code	Range	Measurement uncertainty (The Confidence Level is about 95 %)	Standard/Method of Measurement etc.
Puncture/safety testers	40313			AC/DC Kilovoltmeter, High Voltage Digital Meter, Reference Multimeter/ SICT-CP-40313
Leakage current(DC)		0 μA (0 ~ 1) μA (1 ~ 2) μA (2 ~ 5) μA (5 ~ 10) μA (10 ~ 20) μA (20 ~ 50) μA (50 ~ 100) μA (100 ~ 200) μA (0.2 ~ 100) mA	7.0 nA 7.0×10^{-3} 3.6×10^{-3} 1.4×10^{-3} 7.4×10^{-4} 4.0×10^{-4} 1.8×10^{-4} 1.3×10^{-4} 8.5×10^{-5} 6.1×10^{-4}	
Leakage current(AC)		(20 μA) 10 Hz (10 ~ 20) Hz 20 Hz ~ 1 kHz (1 ~ 5) kHz (5 ~ 10) kHz (20 ~ 50) μA 10 Hz (10 ~ 20) Hz 20 Hz ~ 1 kHz (1 ~ 5) kHz (5 ~ 10) kHz (50 ~ 100) μA 10 Hz (10 ~ 20) Hz 20 Hz ~ 1 kHz (1 ~ 5) kHz (5 ~ 10) kHz (100 ~ 200) μA 10 Hz (10 ~ 20) Hz 20 Hz ~ 1 kHz (1 ~ 5) kHz (5 ~ 10) kHz (200 ~ 500) μA 10 Hz (10 ~ 20) Hz 20 Hz ~ 1 kHz (1 ~ 5) kHz (5 ~ 10) kHz 500 μA ~ 1 mA 10 Hz (10 ~ 20) Hz 20 Hz ~ 1 kHz (1 ~ 5) kHz (5 ~ 10) kHz	1.3×10^{-3} 8.5×10^{-4} 7.0×10^{-4} 1.3×10^{-3} 5.5×10^{-3} 6.8×10^{-4} 4.4×10^{-4} 3.4×10^{-4} 6.8×10^{-4} 2.8×10^{-3} 4.9×10^{-4} 3.2×10^{-4} 2.3×10^{-4} 4.9×10^{-4} 4.0×10^{-4} 3.9×10^{-4} 2.5×10^{-4} 1.7×10^{-4} 4.0×10^{-4} 1.7×10^{-3} 4.4×10^{-4} 3.2×10^{-4} 2.4×10^{-4} 5.4×10^{-4} 2.8×10^{-3} 7.0×10^{-4} 6.6×10^{-4} 6.3×10^{-4} 7.2×10^{-4} 2.1×10^{-3}	

403. AC voltage, current & power

Measured Quantity Instrument or Gauge	Field Code	Range	Measurement uncertainty (The Confidence Level is about 95 %)	Standard/Method of Measurement etc.
Puncture/safety testers Leakage current(AC) Output AC Current Timer	40313	(1 ~ 100) mA 10 Hz (10 ~ 20) Hz 20 Hz ~ 1 kHz (1 ~ 5) kHz (5 ~ 10) kHz (60 Hz) 1 A (1 ~ 3) A (3 ~ 20) A (20 ~ 30) A (30 ~ 60) A (60 ~ 100) A (100 ~ 150) A (150 ~ 200) A 1 s (1 ~ 100) s (100 ~ 1 000) s (1 000 ~ 10 000) s	 7.0×10^{-4} 6.6×10^{-4} 6.3×10^{-4} 7.0×10^{-4} 2.7×10^{-3} 1.2×10^{-3} 1.5×10^{-3} 9.7×10^{-4} 1.0×10^{-3} 8.4×10^{-4} 1.0×10^{-3} 4.6×10^{-3} 3.7×10^{-3} 5.8×10^{-6} 5.8×10^{-6} 8.2×10^{-6} 5.8×10^{-5}	AC/DC Kilovoltmeter, High Voltage Digital Meter, Reference Multimeter/ SICT-CP-40313
Power recorders AC Wattage DC Wattage	40314	(50 ~ 60) Hz 0 mW (0 ~ 0.22) mW (0.22 ~ 1.1) mW (1.1 ~ 2.2) mW (2.2 ~ 11) mW (11 ~ 22) mW (22 ~ 44) mW (44 ~ 66) mW (66 ~ 88) mW (88 ~ 110) mW (110 ~ 480) mW 480 mW ~ 12 kW (12 ~ 24) kW (24 ~ 300) kW (300 ~ 600) kW 0 mW (0 ~ 1) mW (1 ~ 10) mW (10 ~ 100) mW (0.1 ~ 100) W (0.1 ~ 10) kW (10 ~ 20) kW (20 ~ 1 000) kW (1 000 ~ 2 500) kW	 70 μ W 2.1×10^{-1} 4.1×10^{-2} 2.1×10^{-2} 4.1×10^{-3} 2.1×10^{-3} 1.0×10^{-3} 7.0×10^{-4} 5.3×10^{-4} 4.3×10^{-4} 2.1×10^{-4} 1.2×10^{-4} 6.8×10^{-4} 1.2×10^{-3} 1.4×10^{-3} 61 nW 7.7×10^{-5} 4.8×10^{-5} 6.1×10^{-5} 1.1×10^{-4} 1.9×10^{-4} 1.5×10^{-4} 1.0×10^{-3} 1.3×10^{-3}	Power Energy Calibrator/ SICT-CP-40314

403. AC voltage, current & power

Measured Quantity Instrument or Gauge	Field Code	Range	Measurement uncertainty (The Confidence Level is about 95 %)	Standard/Method of Measurement etc.
Current transformer test sets Ratio	40315	(5 ~ 1 500) A (-19.99 ~ 19.99) %	0.020 %	Current transforme, Ratio transformers/ SICT-CP-40315
Phase		(-680 ~ 680)'	0.70'	
Current/turn current coil transformers Ratio	40316	(5 ~ 10 000) A (-19.99 ~ 19.99) %	0.020 %	Current transforme/ SICT-CP-40316
Phase		(-680 ~ 680)'	0.70'	
Current Coil		(AC) 2 ~ 50	0.10 %	
		(DC) 2 ~ 50	0.10 %	
transducers		(±) (10 A) 50 : 1 ~ 5 000 : 1	1.2×10^{-4}	
		(10 ~ 1 000) A 50 : 1 ~ 5 000 : 1	1.9×10^{-4}	
		(1 000 ~ 2 000) A 50 : 1 ~ 5 000 : 1	2.5×10^{-4}	
AC voltmeters AC Voltage	40318	(600 μV) 1 kHz	7.8×10^{-3}	Reference Multimeter, Calibrator/ SICT-CP-40318
		(600 μV ~ 1 mV) 10 Hz 10 Hz ~ 10 kHz (10 ~ 100) kHz	5.0×10^{-3} 4.8×10^{-3} 6.5×10^{-3}	
		(1 ~ 3) mV 10 Hz 10 Hz ~ 10 kHz (10 ~ 100) kHz	2.0×10^{-3} 1.7×10^{-3} 2.8×10^{-3}	
		(3 ~ 10) mV 10 Hz 10 Hz ~ 10 kHz (10 ~ 100) kHz	7.7×10^{-4} 5.7×10^{-4} 1.2×10^{-3}	
		(10 ~ 30) mV 10 Hz 10 Hz ~ 10 kHz (10 ~ 100) kHz	8.0×10^{-4} 3.7×10^{-4} 1.1×10^{-3}	
		(30 ~ 100) mV 10 Hz 10 Hz ~ 10 kHz (10 ~ 100) kHz	4.3×10^{-4} 1.7×10^{-4} 5.7×10^{-4}	
		(100 mV ~ 10 V) 10 Hz 10 Hz ~ 10 kHz (10 ~ 100) kHz	4.9×10^{-4} 1.1×10^{-4} 2.6×10^{-4}	

403. AC voltage, current & power

Measured Quantity Instrument or Gauge	Field Code	Range	Measurement uncertainty (The Confidence Level is about 95 %)	Standard/Method of Measurement etc.
AC voltmeters AC Voltage	40318	(10 ~ 100) V		Reference Multimeter, Calibrator/ SICT-CP-40318
		10 Hz	5.3×10^{-4}	
		10 Hz ~ 10 kHz	1.3×10^{-4}	
		(10 ~ 100) kHz	3.6×10^{-4}	
		(100 ~ 1 000) V		
		50 Hz	3.7×10^{-4}	
		50 Hz ~ 1 kHz	1.1×10^{-4}	
		(1 mV)		
		100 kHz	6.5×10^{-3}	
		100 kHz ~ 1 MHz	2.7×10^{-2}	
		(1 ~ 10) mV		
		100 kHz	1.2×10^{-3}	
		100 kHz ~ 1 MHz	5.6×10^{-3}	
		(10 ~ 100) mV		
		100 kHz	5.7×10^{-4}	
		100 kHz ~ 1 MHz	3.7×10^{-3}	
		(100 mV ~ 1 V)		
		100 kHz	1.5×10^{-4}	
		100 kHz ~ 1 MHz	2.3×10^{-3}	
		(1 ~ 10) V		
		100 kHz	4.7×10^{-5}	
		100 kHz ~ 1 MHz	7.0×10^{-4}	
		(10 ~ 20) V		
		100 kHz	7.6×10^{-5}	
		100 kHz ~ 1 MHz	1.3×10^{-3}	
		(25 mV)		
		1 MHz	1.9×10^{-2}	
		(1 ~ 30) MHz	2.3×10^{-2}	
		(25 ~ 100) mV		
		1 MHz	2.3×10^{-2}	
		(1 ~ 30) MHz	2.8×10^{-2}	
		(100 ~ 300) mV		
		1 MHz	3.7×10^{-2}	
		(1 ~ 30) MHz	4.0×10^{-2}	
		(300 mV ~ 1 V)		
		1 MHz	2.4×10^{-2}	
		(1 ~ 30) MHz	2.7×10^{-2}	
		(1 ~ 2) V		
		1 MHz	1.5×10^{-2}	
		(1 ~ 30) MHz	1.8×10^{-2}	

403. AC voltage, current & power

Measured Quantity Instrument or Gauge	Field Code	Range	Measurement uncertainty (The Confidence Level is about 95 %)	Standard/Method of Measurement etc.	
AC voltmeters AC Output Voltage	40318	(1 mV) 10 Hz ~ 10 kHz (10 ~ 100) kHz	1.9×10^{-3} 3.1×10^{-3}	Reference Multimeter, Calibrator/ SICT-CP-40318	
		(1 ~ 10) mV 10 Hz ~ 10 kHz (10 ~ 100) kHz	2.6×10^{-4} 3.7×10^{-4}		
		(10 ~ 100) mV 10 Hz 10 Hz ~ 10 kHz (10 ~ 100) kHz	9.2×10^{-5} 4.8×10^{-5} 9.1×10^{-5}		
		(100 mV ~ 1 V) 10 Hz 10 Hz ~ 10 kHz (10 ~ 100) kHz	7.2×10^{-5} 1.8×10^{-5} 5.9×10^{-5}		
DC Output Voltage		1 mV (1 ~ 10) mV (10 ~ 100) mV (0.1 ~ 1) V	7.5×10^{-4} 7.6×10^{-5} 9.4×10^{-6} 2.2×10^{-5}		
Watt hour meters Watt Hour	40319	(50 ~ 60) Hz 0 mWh (0 ~ 480) mWh 480 mWh ~ 12 kWh (12 ~ 24) kWh (24 ~ 300) kWh (300 ~ 600) kWh	44 μ Wh 4.0×10^{-4} 3.6×10^{-4} 7.6×10^{-4} 1.3×10^{-3} 1.4×10^{-3}		Power Calibrator/ SICT-CP-40319
		(DC) 0 mWh (0 ~ 1) mWh (1 ~ 100) mWh 100 mWh ~ 100 Wh 100 Wh ~ 10 kWh (10 ~ 20) kWh (20 ~ 1 000) kWh (1 000 ~ 2 500) kWh	61 nWh 3.5×10^{-4} 3.4×10^{-4} 3.5×10^{-4} 3.8×10^{-4} 3.7×10^{-4} 1.1×10^{-3} 1.3×10^{-3}		

403. AC voltage, current & power

Measured Quantity Instrument or Gauge	Field Code	Range	Measurement uncertainty (The Confidence Level is about 95 %)	Standard/Method of Measurement etc.	
Ratio transformers	Ratio	PT (±)		Calibrator/ SICT-CP-40321	
		(0.1 ~ 1.000) %	0.006 %		
		(1.000 ~ 19.00) %	0.01 %		
		CT (±)			
		(0.1 ~ 1.000) %	0.019 %		
		(1.000 ~ 19.00) %	0.02 %		
	Phase	PT (±)			
		(0.040 ~ 1.999) ′	0.060 ′		
		(1.999 ~ 19.99) ′	0.06 ′		
		(19.99 ~ 199.9) ′	0.2 ′		
		(199.9 ~ 600) ′	1 ′		
		CT (±)			
		(0.040 ~ 1.999) ′	0.060 ′		
		(1.999 ~ 19.99) ′	0.06 ′		
(19.99 ~ 199.9) ′	0.2 ′				
(199.9 ~ 600) ′	1 ′				

404. Other DC & LF measurements

Measured Quantity Instrument or Gauge	Field Code	Range	Measurement uncertainty (The Confidence Level is about 95 %)	Standard/Method of Measurement etc.
LF amplifiers Amplifier	40401	(DC) 1 mV (1 ~ 10) mV (10 ~ 100) mV (0.1 ~ 1) V (1 ~ 1 000) V (10 Hz ~ 10 kHz) 1 mV (1 ~ 10) mV (10 ~ 100) mV (0.1 ~ 1) V (1 ~ 1 000) V (10 ~ 100) kHz 1 mV (1 ~ 10) mV (10 ~ 100) mV (0.1 ~ 1) V (1 ~ 1 000) V	0.4 μV 7.4×10^{-5} 6.1×10^{-5} 6.0×10^{-5} 1.0×10^{-4} 1.7 μV 2.6×10^{-4} 1.1×10^{-4} 9.0×10^{-5} 1.0×10^{-4} 3.1 μV 3.7×10^{-4} 1.1×10^{-4} 8.0×10^{-5} 1.0×10^{-4}	Reference Multimeter/ SICT-CP-40401
DC/LF attenuators Attenuation	40402	10 Hz ~ 100 kHz (0 ~ -20) dB (-20 ~ -60) dB (-60 ~ -70) dB (-70 ~ -80) dB	0.001 9 dB 0.001 7 dB 0.005 5 dB 0.008 7 dB	Reference Multimeter/ SICT-CP-40402
Multimeter calibrators DC Voltage DC Current AC Voltage	40403	(±) 0 mV (0 ~ 100) mV (0.1 ~ 1) V (1 ~ 10) V (10 ~ 100) V (100 ~ 1 000) V (±) 1 nA (1 ~ 100) nA 100 nA ~ 10 A (10 ~ 50) A (50 ~ 100) A (1 mV) 10 Hz ~ 10 kHz (10 ~ 100) kHz 100 kHz ~ 1 MHz (1 ~ 2) mV 10 Hz ~ 10 kHz (10 ~ 100) kHz 100 kHz ~ 1 MHz	0.05 μV 3.3×10^{-6} 1.4×10^{-6} 1.0×10^{-6} 1.6×10^{-6} 2.1×10^{-6} 7.0 pA 4.7×10^{-3} 1.2×10^{-5} 4.0×10^{-5} 4.4×10^{-5} 1.7×10^{-3} 3.0×10^{-3} 1.2×10^{-2} 1.1×10^{-3} 1.7×10^{-3} 7.7×10^{-3}	Reference Multimeter/ SICT-CP-40403

404. Other DC & LF measurements

Measured Quantity Instrument or Gauge	Field Code	Range	Measurement uncertainty (The Confidence Level is about 95 %)	Standard/Method of Measurement etc.
Multimeter calibrators AC Voltage	40403	(2 ~ 5) mV		Reference Multimeter/ SICT-CP-40403
		10 Hz	6.4×10^{-4}	
		10 Hz ~ 10 kHz	5.8×10^{-4}	
		(10 ~ 100) kHz	1.0×10^{-3}	
		100 kHz ~ 1 MHz	5.4×10^{-3}	
		(5 ~ 10) mV		
		10 Hz	4.2×10^{-4}	
		10 Hz ~ 10 kHz	3.5×10^{-4}	
		(10 ~ 100) kHz	5.8×10^{-4}	
		100 kHz ~ 1 MHz	3.9×10^{-3}	
		(10 ~ 20) mV		
		10 Hz	1.8×10^{-4}	
		10 Hz ~ 10 kHz	1.4×10^{-4}	
		(10 ~ 100) kHz	2.2×10^{-4}	
		100 kHz ~ 1 MHz	2.2×10^{-3}	
		(20 ~ 50) mV		
		10 Hz	1.4×10^{-4}	
		10 Hz ~ 10 kHz	9.2×10^{-5}	
		(10 ~ 100) kHz	1.6×10^{-4}	
		100 kHz ~ 1 MHz	1.4×10^{-3}	
		(50 ~ 100) mV		
		10 Hz	1.1×10^{-4}	
		10 Hz ~ 10 kHz	6.6×10^{-5}	
		(10 ~ 100) kHz	1.2×10^{-4}	
		100 kHz ~ 1 MHz	1.3×10^{-3}	
		(100 ~ 200) mV		
		10 Hz	8.2×10^{-5}	
		10 Hz ~ 10 kHz	3.9×10^{-5}	
		(10 ~ 100) kHz	7.6×10^{-5}	
		100 kHz ~ 1 MHz	1.1×10^{-3}	
		(200 ~ 500) mV		
		10 Hz	7.8×10^{-5}	
		10 Hz ~ 10 kHz	3.6×10^{-5}	
		(10 ~ 100) kHz	7.1×10^{-5}	
		100 kHz ~ 1 MHz	1.1×10^{-3}	
		(0.5 ~ 1) V		
		10 Hz	7.6×10^{-5}	
		10 Hz ~ 10 kHz	3.3×10^{-5}	
		(10 ~ 100) kHz	6.6×10^{-5}	
		100 kHz ~ 1 MHz	1.1×10^{-3}	
		(1 ~ 2) V		
		10 Hz	7.1×10^{-5}	
		10 Hz ~ 10 kHz	2.7×10^{-5}	
		(10 ~ 100) kHz	5.8×10^{-5}	
		100 kHz ~ 1 MHz	1.0×10^{-3}	

404. Other DC & LF measurements

Measured Quantity Instrument or Gauge	Field Code	Range	Measurement uncertainty (The Confidence Level is about 95 %)	Standard/Method of Measurement etc.
Multimeter calibrators	40403	AC Voltage	(2 ~ 5) V 10 Hz 10 Hz ~ 10 kHz (10 ~ 100) kHz 100 kHz ~ 1 MHz	Reference Multimeter/ SICT-CP-40403
			(5 ~ 20) V 10 Hz 10 Hz ~ 10 kHz (10 ~ 100) kHz 100 kHz ~ 1 MHz	
			(20 ~ 50) V 10 Hz 10 Hz ~ 10 kHz (10 ~ 100) kHz	
			(50 ~ 200) V 10 Hz 10 Hz ~ 10 kHz (10 ~ 100) kHz	
			(200 ~ 1 000) V 10 Hz 10 Hz ~ 10 kHz (10 ~ 100) kHz	
		AC Current	(10 μA) 10 Hz ~ 10 kHz	
			(10 ~ 100) μA 10 Hz ~ 1 kHz (1 ~ 10) kHz	
			(0.1 ~ 1) mA 10 Hz 10 Hz ~ 1 kHz (1 ~ 10) kHz	
			(1 ~ 100) mA 10 Hz 10 Hz ~ 1 kHz (1 ~ 10) kHz	
			(0.1 ~ 1) A 10 Hz 10 Hz ~ 1 kHz (1 ~ 10) kHz	
			(1 ~ 2) A 10 Hz 10 Hz ~ 1 kHz (1 ~ 10) kHz	

404. Other DC & LF measurements

Measured Quantity Instrument or Gauge	Field Code	Range	Measurement uncertainty (The Confidence Level is about 95 %)	Standard/Method of Measurement etc.
Multimeter calibrators	40403	AC Current		Reference Multimeter/ SICT-CP-40403
		Resistance		
		(2 ~ 5) A		
		10 Hz	8.2×10^{-5}	
		10 Hz ~ 1 kHz	5.2×10^{-5}	
		(1 ~ 10) kHz	5.0×10^{-5}	
		(5 ~ 10) A		
		10 Hz	8.6×10^{-5}	
		10 Hz ~ 1 kHz	5.9×10^{-5}	
		(1 ~ 10) kHz	7.8×10^{-5}	
		(10 ~ 20) A		
		10 Hz	9.3×10^{-5}	
		10 Hz ~ 1 kHz	6.8×10^{-5}	
		(1 ~ 10) kHz	7.8×10^{-5}	
		(20 ~ 50) A		
		10 Hz	1.0×10^{-4}	
		10 Hz ~ 1 kHz	8.3×10^{-5}	
		(1 ~ 10) kHz	1.1×10^{-4}	
		(50 ~ 100) A		
		10 Hz	1.2×10^{-4}	
		10 Hz ~ 1 kHz	9.7×10^{-5}	
		(1 ~ 10) kHz	1.3×10^{-4}	
		(100 ~ 200) A		
		60 Hz	4.5×10^{-4}	
		0 Ω	0.14 μΩ	
		(0 ~ 1) Ω	6.6×10^{-6}	
		(1 ~ 1.9) Ω	8.4×10^{-6}	
		(1.9 ~ 10) Ω	3.6×10^{-6}	
		(10 ~ 19) Ω	2.6×10^{-6}	
		(19 ~ 100) Ω	2.8×10^{-6}	
		(0.1 ~ 1) kΩ	2.5×10^{-6}	
		(1 ~ 1.9) kΩ	3.8×10^{-6}	
		(1.9 ~ 10) kΩ	2.0×10^{-6}	
		(10 ~ 19) kΩ	1.3×10^{-6}	
		(19 ~ 100) kΩ	1.9×10^{-6}	
		(100 ~ 190) kΩ	2.0×10^{-6}	
		(0.19 ~ 1) MΩ	2.9×10^{-6}	
		(1 ~ 1.9) MΩ	3.1×10^{-6}	
		(1.9 ~ 10) MΩ	3.6×10^{-6}	
		(10 ~ 19) MΩ	2.9×10^{-6}	
		(19 ~ 100) MΩ	1.5×10^{-5}	

404. Other DC & LF measurements

Measured Quantity Instrument or Gauge	Field Code	Range	Measurement uncertainty (The Confidence Level is about 95 %)	Standard/Method of Measurement etc.
Multimeter calibrators Multimeter calibrators(property) (Digital sampling) AC Voltage	40403	(1 mV) 0.1 Hz ~ 3 kHz	8.4×10^{-4}	Reference Multimeter/ SICT-CP-40403
		(1 ~ 2) mV 0.1 Hz ~ 3 kHz	4.2×10^{-4}	
		(2 ~ 3) mV 0.1 Hz ~ 3 kHz	2.8×10^{-4}	
		(3 ~ 5) mV 0.1 Hz ~ 3 kHz	1.7×10^{-4}	
		(5 ~ 10) mV 0.1 Hz ~ 3 kHz	8.8×10^{-5}	
		(10 ~ 20) mV 0.1 Hz ~ 3 kHz	4.8×10^{-5}	
		(20 ~ 30) mV 0.1 Hz ~ 3 kHz	3.6×10^{-5}	
		(30 ~ 50) mV 0.1 Hz ~ 3 kHz	3.0×10^{-5}	
		(50 ~ 100) mV 0.1 Hz ~ 3 kHz	2.6×10^{-5}	
		(100 ~ 200) mV 0.1 Hz ~ 3 kHz	4.8×10^{-5}	
		(200 ~ 300) mV 0.1 Hz ~ 3 kHz	3.6×10^{-5}	
		(300 ~ 500) mV 0.1 Hz ~ 3 kHz	2.8×10^{-5}	
		(500 mV ~ 1 V) 0.1 Hz ~ 3 kHz	2.4×10^{-5}	
		(1 ~ 2) V 0.1 Hz ~ 3 kHz	4.8×10^{-5}	
		(2 ~ 3) V 0.1 Hz ~ 3 kHz	3.6×10^{-5}	
(3 ~ 5) V 0.1 Hz ~ 3 kHz	3.0×10^{-5}			
(5 ~ 10) V 0.1 Hz ~ 3 kHz	2.6×10^{-5}			

404. Other DC & LF measurements

Measured Quantity Instrument or Gauge	Field Code	Range	Measurement uncertainty (The Confidence Level is about 95 %)	Standard/Method of Measurement etc.
Oscilloscope calibrators Sine Wave Generator Time Marker Generator Impedance Mesurement	40404	(600 mV ~ 1 V) 50 kHz (50 ~ 500) kHz 0.5 MHz ~ 1 GHz (1 ~ 6) GHz (0.1 ~ 1) ns (1 ~ 10) ns (10 ~ 100) ns 0.1 μs ~ 10 ms (10 ~ 100) ms (0.1 ~ 1) s (1 ~ 5) s (50 ~ 75) Ω 75 Ω ~ 1 MΩ	0.58 mV 1.0×10^{-3} 1.7×10^{-2} 1.9×10^{-2} 5.8×10^{-8} 6.5×10^{-9} 3.1×10^{-9} 5.8×10^{-8} 6.1×10^{-9} 5.8×10^{-8} 1.2×10^{-8} 1.7×10^{-4} 2.1×10^{-4}	Calibrator/ SICT-CP-40404
CD/DVD meters/analyzers Jitter	40405	(1.0 ~ 60.0) ns 1 % 2 % 4 % 8 % 10 % 15 %	1.7×10^{-3} 0.05 % 0.09 % 0.19 % 0.36 % 0.44 % 0.67 %	Modulation Domain Analyzer/ SICT-CP-40405
Video signal generators NTSC, PAL Multiburst NTSC, PAL, SECAM Pulse and Bar NTSC, PAL, SECAM Frequency Video frequency Video level TTL Sync level D-TV Level	40406	(0.1 ~ 1) MHz (1 ~ 2) MHz (2 ~ 6) MHz (0 ~ 300) ns (0 ~ 1 000) mV 1 Hz ~ 10 MHz (10 ~ 100) Hz 100 Hz ~ 500 MHz (30 ~ 600) mV (600 ~ 1 200) mV (1 ~ 5) V (30 ~ 600) mV (600 ~ 1 200) mV	6.0×10^{-2} 6.2×10^{-3} 3.1×10^{-3} 4.2×10^{-4} 3.5×10^{-3} 1.6×10^{-9} 6.2×10^{-8} 6.2×10^{-9} 2.6×10^{-3} 2.3×10^{-3} 2.7×10^{-3} 2.6×10^{-3} 2.3×10^{-3}	Video Measurement/ SICT-CP-40406

404. Other DC & LF measurements

Measured Quantity Instrument or Gauge	Field Code	Range	Measurement uncertainty (The Confidence Level is about 95 %)	Standard/Method of Measurement etc.
Video signal generators NTSC, PAL, H-Timing(Level)	40406	(0 ~ 100) mV	2.6×10^{-3}	Video Measurement/ SICT-CP-40406
		(100 ~ 1 000) mV	3.4×10^{-3}	
(Time)		(0 ~ 254) ns	1.2×10^{-2}	
		(254 ~ 300) ns	3.8×10^{-3}	
		300 ns ~ 3 μ s	3.2×10^{-3}	
		(3 ~ 7) μ s	7.4×10^{-3}	
		(7 ~ 10) μ s	4.2×10^{-3}	
NTSC, PAL Color Bar(Luminance Level)		(0 ~ 100) mV	0.06 mV	
		(100 ~ 1 000) mV	3.4×10^{-3}	
NTSC, PAL Color Bar(Chrominance Level)		(0 ~ 100) mV	0.06 mV	
		(100 ~ 1 000) mV	3.4×10^{-3}	
NTSC, PAL Color Bar(Phase)		(0 ~ 360)°	0.13°	
SECAM Color Bar Frequency		(D'R & D'B) (3 ~ 5) MHz	1.2×10^{-3}	
RF Output frequency		10 kHz ~ 10 MHz (10 ~ 100) MHz (100 ~ 1 000) MHz	6.0×10^{-4} 6.0×10^{-5} 6.0×10^{-6}	
RF Output level	(0.1 ~ 10) mV (10 ~ 500) mV	1.4×10^{-2} 1.3×10^{-2}		
Sound Frequency	10 Hz ~ 100 kHz 100 kHz ~ 1 MHz	6.1×10^{-8} 6.1×10^{-7}		
Audio distortion analyzers/meters Input Frequency	40407	1 Hz ~ 200 kHz	6.1×10^{-7}	Calibrator/ SICT-CP-40407
Output Level Flatness Test		(10 ~ 100) kHz	0.008 3 dB	
Input DC Voltage		0 mV (0 ~ 1) mV (1 ~ 10) mV 10 mV ~ 300 V	0.27 μ V 5.8×10^{-3} 5.8×10^{-4} 5.8×10^{-4}	
Input Distortion		(100 Hz ~ 10 kHz) (-10 ~ -40) dB (-40 ~ -50) dB (-50 ~ -60) dB (-60 ~ -70) dB (-70 ~ -80) dB	0.005 8 dB 0.006 0 dB 0.006 8 dB 0.012 dB 0.028 dB	

404. Other DC & LF measurements

Measured Quantity Instrument or Gauge	Field Code	Range	Measurement uncertainty (The Confidence Level is about 95 %)	Standard/Method of Measurement etc.
Audio distortion analyzers/meters	40407	(10 kHz ~ 50 kHz)		Calibrator/ SICT-CP-40407
Input Distortion		(-10 ~ -40) dB	0.005 9 dB	
		(-40 ~ -50) dB	0.006 3 dB	
		(-50 ~ -60) dB	0.008 2 dB	
		(-60 ~ -70) dB	0.019 dB	
		(-70 ~ -80) dB	0.052 dB	
Input AC Voltage		(10 ~ 100) Hz		
		(1 ~ 10) mV	9.0×10^{-4}	
		(10 ~ 100) mV	4.0×10^{-4}	
		100 mV ~ 100 V	4.2×10^{-4}	
		(100 ~ 300) V	5.3×10^{-4}	
		(100 Hz ~ 1 kHz)		
		(1 ~ 10) mV	8.4×10^{-4}	
		(10 ~ 100) mV	1.8×10^{-4}	
		100 mV ~ 10 V	1.1×10^{-4}	
		(10 ~ 100) V	1.0×10^{-4}	
		(100 ~ 300) V	2.3×10^{-4}	
		(1 ~ 10) kHz		
		(1 ~ 10) mV	8.4×10^{-4}	
		(10 ~ 100) mV	1.8×10^{-4}	
		100 mV ~ 10 V	1.5×10^{-4}	
		(10 ~ 100) V	2.7×10^{-4}	
		(10 ~ 100) kHz		
		(1 ~ 10) mV	1.4×10^{-3}	
		(10 ~ 100) mV	7.6×10^{-4}	
		100 mV ~ 1 V	4.8×10^{-4}	
		(1 ~ 10) V	4.1×10^{-4}	
	(10 ~ 100) V	3.4×10^{-4}		
Input Attenuation	(10 Hz)			
	(30 ~ -50) dB	0.006 8 dB		
	(-50 ~ -60) dB	0.016 dB		
	(-60 ~ -80) dB	0.052 dB		
	(10 Hz ~ 10 kHz)			
	(30 ~ -60) dB	0.008 3 dB		
	(-60 ~ -70) dB	0.014 dB		
	(-70 ~ -80) dB	0.042 dB		
	(10 ~ 100) kHz			
	(30 ~ -50) dB	0.009 1 dB		
	(-50 ~ -70) dB	0.023 dB		
	(-70 ~ -80) dB	0.057 dB		
Input Impedance	300 Ω ~ 200 kΩ	3.1×10^{-4}		
Input Filter	(10 Hz ~ 100 kHz)			
	1 V	8.3×10^{-4}		
(Distortion meter calibrator) Distortion	(400 Hz , 1 kHz)			
	(-10 ~ -20) dB	0.15 dB		
	(-20 ~ -40) dB	0.14 dB		
	(-40 ~ -60) dB	0.17 dB		
	(-60 ~ -80) dB	0.26 dB		

404. Other DC & LF measurements

Measured Quantity Instrument or Gauge	Field Code	Range	Measurement uncertainty (The Confidence Level is about 95 %)	Standard/Method of Measurement etc.
LF filters Filter	40408	10 Hz ~ 50 kHz (50 ~ 100) kHz (100 ~ 150) kHz	5.8×10^{-4} 1.2×10^{-3} 5.8×10^{-3}	Audio Analyzer/ SICT-CP-40408
LF/audio signal analyzers Output Frequency AC Output Level AC Output Level Flatness Output Attenuation Output DC Offset Output Impedance Input Frequency AC Input Level Flatness DC Input Level Input Distortion	40409	1 Hz ~ 200 kHz (10 ~ 100) Hz (1 ~ 10) mV 10 mV ~ 30 V (-20 ~ 10) dBm (100 Hz ~ 10 kHz) (1 ~ 10) mV 10 mV ~ 30 V (-20 ~ 10) dBm (10 ~ 100) kHz (1 ~ 10) mV 10 mV ~ 30 V (-20 ~ 10) dBm 10 Hz ~ 100 kHz (0 ~ -60) dB (±) 0 mV (0 ~ 1) mV (1 ~ 10) mV 10 mV ~ 50 V 5 Ω (10 ~ 600) Ω 1 Hz ~ 200 kHz 10 Hz ~ 100 kHz (±) 0 mV (0 ~ 1) mV (1 ~ 10) mV 10 mV ~ 300 V (100 Hz ~ 10 kHz) (-10 ~ -40) dB (-40 ~ -50) dB (-50 ~ -60) dB (-60 ~ -70) dB (-70 ~ -80) dB	5.8×10^{-6} 8.7×10^{-4} 9.4×10^{-5} 0.005 8 dB 8.7×10^{-4} 6.5×10^{-5} 8.7×10^{-4} 9.4×10^{-5} 0.005 8 dB 0.007 1 dB 0.005 8 dB 0.7 μV 1.0×10^{-3} 1.0×10^{-4} 7.0×10^{-5} 1.2×10^{-3} 6.0×10^{-4} 6.1×10^{-7} 0.008 3 dB 0.27 μV 5.8×10^{-3} 5.8×10^{-4} 5.8×10^{-4} 0.005 8 dB 0.006 0 dB 0.006 8 dB 0.012 dB 0.028 dB	Calibrator, Reference Multimeter/ SICT-CP-40409

404. Other DC & LF measurements

Measured Quantity Instrument or Gauge	Field Code	Range	Measurement uncertainty (The Confidence Level is about 95 %)	Standard/Method of Measurement etc.	
LF/audio signal analyzers	40409	(10 kHz ~ 50 kHz) (-10 ~ -40) dB (-40 ~ -50) dB (-50 ~ -60) dB (-60 ~ -70) dB (-70 ~ -80) dB	0.005 9 dB	Calibrator, Reference Multimeter/ SICT-CP-40409	
Input Distortion			0.006 3 dB		
			0.008 2 dB		
			0.019 dB		
			0.052 dB		
AC Input Level		(10 ~ 100) Hz			
		(1 ~ 10) mV	9.0×10^{-4}		
		(10 ~ 100) mV	4.0×10^{-4}		
		100 mV ~ 100 V	4.2×10^{-4}		
		(100 ~ 300) V	5.3×10^{-4}		
		(100 Hz ~ 1 kHz)			
		(1 ~ 10) mV	8.4×10^{-4}		
		(10 ~ 100) mV	1.8×10^{-4}		
		100 mV ~ 10 V	1.1×10^{-4}		
		(10 ~ 100) V	1.0×10^{-4}		
		(100 ~ 300) V	2.3×10^{-4}		
		(1 ~ 10) kHz			
		(1 ~ 10) mV	8.4×10^{-4}		
		(10 ~ 100) mV	1.8×10^{-4}		
	100 mV ~ 10 V	1.5×10^{-4}			
	(10 ~ 100) V	2.7×10^{-4}			
	Input Attenuation	(10 ~ 100) kHz			
		(1 ~ 10) mV	1.4×10^{-3}		
(10 ~ 100) mV		7.6×10^{-4}			
100 mV ~ 1 V		4.1×10^{-4}			
(1 ~ 10) V		3.4×10^{-4}			
(10 ~ 100) V		2.6×10^{-4}			
(10 Hz)					
(30 ~ -50) dB		0.006 8 dB			
(-50 ~ -60) dB		0.016 dB			
(-60 ~ -80) dB		0.052 dB			
(10 Hz ~ 10 kHz)					
(30 ~ -60) dB		0.008 3 dB			
(-60 ~ -70) dB	0.014 dB				
(-70 ~ -80) dB	0.042 dB				
Input Impedance	(10 ~ 100) kHz				
	(30 ~ -50) dB	0.009 1 dB			
	(-50 ~ -70) dB	0.023 dB			
	(-70 ~ -80) dB	0.057 dB			
Input Filter	300 Ω ~ 200 kΩ	3.1×10^{-4}			
	(10 Hz ~ 100 kHz)				
	1 V	8.3×10^{-4}			
Line frequency meters	40410	16 Hz ~ 1 kHz	1.3×10^{-4}	Calibrator/ SICT-CP-40410	
Frequency					

404. Other DC & LF measurements

Measured Quantity Instrument or Gauge	Field Code	Range	Measurement uncertainty (The Confidence Level is about 95 %)	Standard/Method of Measurement etc.
Function generators	40411			Audio Analyzer, Digital Multimeter/ SICT-CP-40411
Frequency		(0.01 ~ 0.1) Hz	5.8×10^{-6}	
		(0.1 ~ 1) Hz	5.8×10^{-7}	
		1 Hz ~ 1 GHz	5.8×10^{-9}	
		(1 ~ 4) GHz	1.5×10^{-8}	
Output Level		(10 ~ 100) Hz		
		1 mV	1.0×10^{-3}	
		(1 ~ 10) mV	1.0×10^{-4}	
		10 mV ~ 100 V	7.0×10^{-5}	
		(100 Hz ~ 10 kHz)		
		1 mV	1.0×10^{-3}	
		(1 ~ 10) mV	1.0×10^{-4}	
		10 mV ~ 100 V	3.0×10^{-5}	
		(10 ~ 100) kHz		
		1 mV	1.0×10^{-3}	
		(1 ~ 10) mV	1.0×10^{-4}	
		10 mV ~ 100 V	8.0×10^{-5}	
DC Offset		(±)		
		0 mV	0.7 μV	
		(0 ~ 1) mV	0.7 μV	
		(1 ~ 10) mV	1.0×10^{-4}	
		10 mV ~ 20 V	6.0×10^{-5}	
Level Flatness		(100 mV)		
		(10 ~ 100) Hz	0.099 dB	
		100 Hz ~ 10 kHz	0.083 dB	
		(10 ~ 100) kHz	0.095 dB	
		(100 mV ~ 1 V)		
		(10 ~ 100) Hz	0.005 4 dB	
		100 Hz ~ 10 kHz	0.001 1 dB	
		(10 ~ 100) kHz	0.007 2 dB	
		(1 ~ 30) V		
		(10 ~ 100) Hz	0.021 dB	
		100 Hz ~ 10 kHz	0.015 dB	
		(10 ~ 100) kHz	0.027 dB	
Attenuation		(10 Hz ~ 100 kHz)		
		(0 ~ 80) dB	0.006 1 dB	
Distortion		(20 Hz ~ 1 kHz)		
		(3.16 ~ 0.010) %	1.5×10^{-1}	
		(1 ~ 100) kHz		
		(3.16 ~ 0.010) %	3.2×10^{-1}	

404. Other DC & LF measurements

Measured Quantity Instrument or Gauge	Field Code	Range	Measurement uncertainty (The Confidence Level is about 95 %)	Standard/Method of Measurement etc.
Function generators Rise Fall Time Duty cycle High Frequency Flatness Test FM Modulation AM Modulation	40411	100 μ s ~ 100 ns (100 ~ 10) ns (10 ~ 1) ns 1 ns ~ 100 ps (1 ~ 99) % (100 kHz ~ 80 MHz) (0 ~ 20) dBm (0.1 ~ 400) kHz (0.1 ~ 100) %	7.0×10^{-4} 7.8×10^{-4} 4.7×10^{-3} 4.6×10^{-2} 0.006 1 % 0.11 dB 1.2×10^{-2} 1.2×10^{-2}	Audio Analyzer, Digital Multimeter/ SICT-CP-40411
Genescopes Marker Frequency RF Level	40412	9 kHz ~ 10 MHz (10 ~ 200) MHz 9 kHz ~ 200 MHz (100 ~ 50) dB μ V	2.8×10^{-6} 6.4×10^{-7} 0.31 dB	Signal Generator/ SICT-CP-40412
AC/DC high voltages voltmeters DC Voltage AC Voltage	40413	(\pm) 0 kV (0 ~ 0.5) kV (0.5 ~ 1) kV (1 ~ 2) kV (2 ~ 100) kV (50 Hz) 0.01 kV (0.01 ~ 0.5) kV (0.5 ~ 1) kV (1 ~ 2) kV (2 ~ 3) kV (3 ~ 15 kV (15 ~ 100) kV (60 Hz) 0.01 kV (0.01 ~ 0.5) kV (0.5 ~ 1) kV (1 ~ 2) kV (2 ~ 3) kV (3 ~ 15 kV (15 ~ 100) kV	0.58 V 1.2×10^{-3} 6.1×10^{-4} 4.4×10^{-4} 3.4×10^{-4} 0.58 V 1.2×10^{-3} 6.2×10^{-4} 5.5×10^{-4} 5.3×10^{-4} 5.0×10^{-4} 5.7×10^{-4} 0.58 V 1.2×10^{-3} 6.2×10^{-4} 5.5×10^{-4} 4.7×10^{-4} 4.5×10^{-4} 5.4×10^{-4}	Calibrator/ SICT-CP-40413

404. Other DC & LF measurements

Measured Quantity Instrument or Gauge	Field Code	Range	Measurement uncertainty (The Confidence Level is about 95 %)	Standard/Method of Measurement etc.
Jitter meters CD/DVD Jitter VTR Jitter	40415	(1 ~ 20) ns (20 ~ 60) ns 0.05 μs (0.05 ~ 0.1) μs (0.1 ~ 0.2) μs (0.2 ~ 0.5) μs (0.5 ~ 0.7) μs 1 % 2 % 4 % 8 % 10 % 15 %	1.7×10^{-3} 1.6×10^{-3} 0.66 ns 0.77 ns 1.2 ns 2.8 ns 4.3 ns 0.05 % 0.09 % 0.19 % 0.36 % 0.44 % 0.67 %	Modulation Domain Analyzer/ SICT-CP-40415
Leakage current testers DC Current AC Current	40416	0 μA (0 ~ 1) μA (1 ~ 2) μA (2 ~ 5) μA (5 ~ 10) μA (10 ~ 20) μA (20 ~ 50) μA (50 ~ 100) μA (100 ~ 200) μA (0.2 ~ 100) mA (20 μA) 10 Hz (10 ~ 20) Hz (0.02 ~ 1) kHz (1 ~ 5) kHz (5 ~ 10) kHz (20 ~ 50) μA 10 Hz (10 ~ 20) Hz (0.02 ~ 1) kHz (1 ~ 5) kHz (5 ~ 10) kHz (50 ~ 100) μA 10 Hz (10 ~ 20) Hz (0.02 ~ 1) kHz (1 ~ 5) kHz (5 ~ 10) kHz	7.0 nA 2.4×10^{-3} 3.6×10^{-3} 1.4×10^{-3} 7.4×10^{-4} 4.0×10^{-4} 1.8×10^{-4} 1.3×10^{-4} 8.5×10^{-5} 6.1×10^{-4} 26 nA 8.5×10^{-4} 7.0×10^{-4} 1.3×10^{-3} 5.5×10^{-3} 6.8×10^{-4} 4.4×10^{-4} 3.4×10^{-4} 6.8×10^{-4} 2.8×10^{-3} 4.9×10^{-4} 3.2×10^{-4} 2.3×10^{-4} 4.9×10^{-4} 4.0×10^{-4}	Calibrator/ SICT-CP-40416

404. Other DC & LF measurements

Measured Quantity Instrument or Gauge	Field Code	Range	Measurement uncertainty (The Confidence Level is about 95 %)	Standard/Method of Measurement etc.
Leakage current testers	40416	AC Current		Calibrator/ SICT-CP-40416
		(100 ~ 200) μ A		
		10 Hz	3.9×10^{-4}	
		(10 ~ 20) Hz	2.5×10^{-4}	
		(0.02 ~ 1) kHz	1.7×10^{-4}	
		(1 ~ 5) kHz	4.0×10^{-4}	
		(5 ~ 10) kHz	1.7×10^{-3}	
		(200 ~ 500) μ A		
		10 Hz	4.4×10^{-4}	
		(10 ~ 20) Hz	3.2×10^{-4}	
		(0.02 ~ 1) kHz	2.4×10^{-4}	
		(1 ~ 5) kHz	5.4×10^{-4}	
		(5 ~ 10) kHz	2.8×10^{-3}	
		(0.5 ~ 1) mA		
		10 Hz	7.0×10^{-4}	
		(10 ~ 20) Hz	6.6×10^{-4}	
		(0.02 ~ 1) kHz	6.3×10^{-4}	
		(1 ~ 5) kHz	7.2×10^{-4}	
		(5 ~ 10) kHz	2.1×10^{-3}	
		(1 ~ 100) mA		
		10 Hz	7.0×10^{-4}	
		(10 ~ 20) Hz	6.6×10^{-4}	
		(0.02 ~ 1) kHz	6.3×10^{-4}	
		(1 ~ 5) kHz	7.0×10^{-4}	
		(5 ~ 10) kHz	2.7×10^{-3}	
		DC Voltage		
		0 V	0.06 mV	
		(0 ~ 0.1) V	6.0×10^{-4}	
		(0.1 ~ 0.2) V	3.0×10^{-4}	
		(0.2 ~ 0.5) V	1.2×10^{-4}	
		(0.5 ~ 1) V	6.0×10^{-5}	
		(1 ~ 2) V	3.1×10^{-4}	
		(2 ~ 5) V	1.2×10^{-4}	
		(5 ~ 10) V	6.1×10^{-5}	
		(10 ~ 20) V	3.1×10^{-5}	
		(20 ~ 50) V	1.4×10^{-5}	
		(50 ~ 100) V	8.8×10^{-6}	
		(100 ~ 200) V	3.1×10^{-5}	
		(200 ~ 300) V	2.3×10^{-5}	
		(300 ~ 500) V	1.2×10^{-4}	
		(500 ~ 1 000) V	5.8×10^{-5}	
		AC Voltage		
		0.1 V		
		10 Hz	0.074 mV	
		(0.01 ~ 50) kHz	6.5×10^{-4}	
		(50 ~ 100) kHz	8.3×10^{-4}	
		(100 ~ 300) kHz	1.2×10^{-3}	
		(300 ~ 500) kHz	2.0×10^{-3}	
		(0.5 ~ 1) MHz	3.6×10^{-3}	

404. Other DC & LF measurements

Measured Quantity Instrument or Gauge	Field Code	Range	Measurement uncertainty (The Confidence Level is about 95 %)	Standard/Method of Measurement etc.			
Leakage current testers AC Voltage	40416	(5 ~ 10) V 10 Hz	3.3×10^{-4}	Calibrator/ SICT-CP-40416			
		(10 ~ 20) Hz (0.02 ~ 20) kHz (20 ~ 100) kHz (100 ~ 300) kHz (300 ~ 500) kHz (0.5 ~ 1) MHz	1.4×10^{-4} 8.9×10^{-5} 1.4×10^{-4} 3.9×10^{-4} 1.4×10^{-3} 2.2×10^{-3}				
Resistance	40416	(10 ~ 20) V 10 Hz	3.1×10^{-4}				
		(10 ~ 20) Hz (0.02 ~ 20) kHz (20 ~ 50) kHz (50 ~ 100) kHz	1.2×10^{-4} 6.0×10^{-5} 9.0×10^{-5} 1.1×10^{-4}				
		(20 ~ 50) V 10 Hz	4.2×10^{-4}				
		(10 ~ 20) Hz (0.02 ~ 50) kHz (50 ~ 100) kHz	2.2×10^{-4} 1.8×10^{-4} 2.8×10^{-4}				
		(50 ~ 100) V 10 Hz	3.4×10^{-4}				
		(0.01 ~ 50) kHz (50 ~ 100) kHz	1.4×10^{-4} 2.2×10^{-4}				
		(100 ~ 1 000) V (0.05 ~ 1) kHz	1.1×10^{-4}				
		100 mΩ 1 Ω ~ 10 kΩ	$7.7 \mu\Omega$ 6.2×10^{-5}				
		Input Voltage to Output Current Display(U1)	40416		20 Hz (4.75 ~ 5.25) mA	0.006 3 mA	
					50 Hz (4.77 ~ 5.28) mA	0.006 1 mA	
60 Hz (4.77 ~ 5.28) mA	0.006 1 mA						
100 Hz (4.85 ~ 5.36) mA	0.006 1 mA						
200 Hz (5.11 ~ 5.65) mA	0.006 1 mA						

404. Other DC & LF measurements

Measured Quantity Instrument or Gauge	Field Code	Range	Measurement uncertainty (The Confidence Level is about 95 %)	Standard/Method of Measurement etc.
Leakage current testers Input Voltage to Output Current Display(U1)	40416	500 Hz (6.64 ~ 7.34) mA	0.006 1 mA	Calibrator/ SICT-CP-40416
		1 kHz (9.70 ~ 10.73) mA	0.006 1 mA	
		2 kHz (14.07 ~ 15.56) mA	0.006 2 mA	
		5 kHz (17.82 ~ 19.70) mA	0.006 2 mA	
		10 kHz (18.66 ~ 20.63) mA	0.006 2 mA	
		20 kHz (18.92 ~ 20.92) mA	0.006 2 mA	
		50 kHz (19.00 ~ 21.00) mA	0.006 4 mA	
		100 kHz (19.00 ~ 21.00) mA	0.006 7 mA	
		200 kHz (19.00 ~ 21.00) mA	0.010 mA	
		500 kHz (19.00 ~ 21.00) mA	0.030 mA	
		1 MHz (19.00 ~ 21.00) mA	0.046 mA	
Input Voltage to Output Current Display(U2)		20 Hz (4.75 ~ 5.25) mA	0.006 3 mA	
		50 Hz (4.77 ~ 5.28) mA	0.006 1 mA	
		60 Hz (4.77 ~ 5.28) mA	0.006 1 mA	
		100 Hz (4.80 ~ 5.30) mA	0.006 1 mA	
		200 Hz (4.92 ~ 5.44) mA	0.006 1 mA	
		500 Hz (5.37 ~ 5.93) mA	0.006 1 mA	

404. Other DC & LF measurements

Measured Quantity Instrument or Gauge	Field Code	Range	Measurement uncertainty (The Confidence Level is about 95 %)	Standard/Method of Measurement etc.	
Leakage current testers	40416	1 kHz (5.56 ~ 6.14) mA	0.006 1 mA	Calibrator/ SICT-CP-40416	
Input Voltage to Output Current Display(U2)		2 kHz (4.68 ~ 5.17) mA	0.006 1 mA		
		5 kHz (2.53 ~ 2.80) mA	0.000 63 mA		
		10 kHz (1.35 ~ 1.49) mA	0.000 62 mA		
		20 kHz (0.683 ~ 0.755) mA	0.000 61 mA		
		50 kHz (274.57 ~ 303.47) mA	0.029 μ A		
		100 kHz (137.48 ~ 151.95) μ A	0.020 μ A		
		200 kHz (68.82 ~ 76.06) μ A	0.030 μ A		
		500 kHz (27.43 ~ 30.32) μ A	0.042 μ A		
		1 MHz (13.71 ~ 15.16) μ A	0.033 μ A		
		Input Voltage to Output Current Display(U3)	20 Hz (4.75 ~ 5.25) mA		0.006 3 mA
			50 Hz (4.77 ~ 5.28) mA		0.006 1 mA
			60 Hz (4.77 ~ 5.28) mA		0.006 1 mA
			100 Hz (4.80 ~ 5.30) mA		0.006 1 mA
200 Hz (4.95 ~ 5.47) mA	0.006 1 mA				
500 Hz (5.65 ~ 6.25) mA	0.006 1 mA				
1 kHz (6.60 ~ 7.29) mA	0.006 1 mA				

404. Other DC & LF measurements

Measured Quantity Instrument or Gauge	Field Code	Range	Measurement uncertainty (The Confidence Level is about 95 %)	Standard/Method of Measurement etc.
Leakage current testers Input Voltage to Output Current Display(U3)	40416	2 kHz (7.14 ~ 7.89) mA	0.006 1 mA	Calibrator/ SICT-CP-40416
		5 kHz (5.31 ~ 5.87) mA	0.006 1 mA	
		10 kHz (3.12 ~ 3.45) mA	0.000 64 mA	
		20 kHz (1.63 ~ 1.81) mA	0.000 62 mA	
		50 kHz (0.664 ~ 0.734) mA	0.000 62 mA	
		100 kHz (322.16 ~ 367.12) μA	0.046 μA	
		200 kHz (166.03 ~ 183.81) μA	0.070 μA	
		500 kHz (66.37 ~ 73.35) μA	0.10 μA	
		1 MHz (33.14 ~ 36.63) μA	0.08 μA	
		Input Voltage to Output Voltage Ratio(U1)	40416	
3.98 (50 Hz)	6.5×10^{-5}			
3.97 (60 Hz)	6.5×10^{-5}			
3.92 (100 Hz)	6.5×10^{-5}			
3.72 (200 Hz)	6.5×10^{-5}			
2.87 (500 Hz)	6.4×10^{-5}			
1.96 (1 kHz)	6.4×10^{-5}			
1.96 (2 kHz)	6.4×10^{-5}			
1.96 (5 kHz)	6.4×10^{-5}			
1.96 (10 kHz)	6.4×10^{-5}			
1.00 (20 kHz)	6.7×10^{-5}			
1.00 (50 kHz)	9.6×10^{-5}			
1.00 (100 kHz)	1.2×10^{-4}			
1.00 (200 kHz)	4.2×10^{-4}			
1.00 (500 kHz)	1.5×10^{-3}			
1.00 (1 MHz)	2.6×10^{-3}			

404. Other DC & LF measurements

Measured Quantity Instrument or Gauge	Field Code	Range	Measurement uncertainty (The Confidence Level is about 95 %)	Standard/Method of Measurement etc.		
Leakage current testers Input Voltage to Output Voltage Ratio(U2)	40416	4.00 (20 Hz)	1.3×10^{-4}	Calibrator/ SICT-CP-40416		
		3.99 (50 Hz)	6.5×10^{-5}			
		3.99 (60 Hz)	6.5×10^{-5}			
		3.96 (100 Hz)	6.5×10^{-5}			
		3.87 (200 Hz)	6.5×10^{-5}			
		3.54 (500 Hz)	6.5×10^{-5}			
		3.43 (1 kHz)	6.5×10^{-5}			
		4.06 (2 kHz)	6.5×10^{-5}			
		7.50 (5 kHz)	6.6×10^{-5}			
		14.1 (10 kHz)	7.0×10^{-5}			
		27.8 (20 kHz)	3.6×10^{-5}			
		69.2 (50 kHz)	4.8×10^{-5}			
		138 (100 kHz)	1.0×10^{-4}			
		272 (200 kHz)	2.7×10^{-4}			
		691 (500 kHz)	1.1×10^{-3}			
		1 382 (1 MHz)	3.0×10^{-3}			
Input Voltage to Output Voltage Ratio(U3)			4.00 (20 Hz)		1.3×10^{-4}	
			3.99 (50 Hz)		6.5×10^{-5}	
			3.98 (60 Hz)		6.5×10^{-5}	
			3.95 (100 Hz)		6.6×10^{-5}	
			3.83 (200 Hz)		6.5×10^{-5}	
			2.36 (500 Hz)		6.5×10^{-5}	
			2.87 (1 kHz)		6.4×10^{-5}	
			2.65 (2 kHz)		6.4×10^{-5}	
			3.57 (5 kHz)		6.5×10^{-5}	
			6.09 (10 kHz)		6.5×10^{-5}	
			11.6 (20 kHz)		6.9×10^{-5}	
			28.7 (50 kHz)		3.8×10^{-5}	
			57.2 (100 kHz)		7.9×10^{-5}	
			114 (200 kHz)		1.9×10^{-4}	
			286 (500 kHz)		6.1×10^{-4}	
			572 (1 MHz)		2.3×10^{-3}	
mAs Meter			1 mAs		1.2×10^{-3}	
		(1 ~ 2 000) mAs	1.0×10^{-3}			
		(2 000 ~ 9 999) mAs	1.1×10^{-3}			
Electronic AC/DC loads DC Voltage	40417	0 mV	0.058 mV	Calibrator/ SICT-CP-40417		
		(0 ~ 5) mV	5.8×10^{-2}			
		(5 ~ 20) mV	5.8×10^{-3}			
		(20 ~ 100) mV	1.2×10^{-3}			
		(0.1 ~ 1) V	6.2×10^{-5}			
		(1 ~ 2) V	3.2×10^{-5}			
		(2 ~ 4) V	2.1×10^{-5}			
		(4 ~ 7) V	1.3×10^{-5}			
		(7 ~ 9) V	9.1×10^{-6}			
		(9 ~ 10) V	7.9×10^{-6}			
		(10 ~ 50) V	3.1×10^{-5}			
		(50 ~ 100) V	1.0×10^{-5}			
		(100 ~ 200) V	3.4×10^{-5}			
		(200 ~ 400) V	2.5×10^{-5}			
		(400 ~ 1 000) V	1.6×10^{-5}			

404. Other DC & LF measurements

Measured Quantity Instrument or Gauge	Field Code	Range	Measurement uncertainty (The Confidence Level is about 95 %)	Standard/Method of Measurement etc.
Electronic AC/DC loads	40417	1 mA	5.8 μ A	Calibrator/ SICT-CP-40417
DC Current		(1 ~ 2) mA	2.9×10^{-3}	
		(2 ~ 5) mA	1.2×10^{-3}	
		(5 ~ 20) mA	5.8×10^{-4}	
		(20 ~ 50) mA	1.2×10^{-4}	
		(50 ~ 100) mA	5.9×10^{-5}	
		(0.1 ~ 0.2) A	2.9×10^{-4}	
		(0.2 ~ 0.4) A	1.9×10^{-4}	
		(0.4 ~ 0.6) A	1.2×10^{-4}	
		(0.6 ~ 0.8) A	8.4×10^{-5}	
		(0.8 ~ 1) A	6.6×10^{-5}	
		(1 ~ 3) A	5.1×10^{-5}	
		(3 ~ 6) A	2.6×10^{-5}	
		(6 ~ 10) A	1.6×10^{-5}	
		(10 ~ 40) A	4.0×10^{-5}	
		(40 ~ 100) A	2.9×10^{-5}	
(100 ~ 1 000) A		1.4×10^{-4}		
(1 000 ~ 2 000) A		4.9×10^{-4}		
Charge voltage		0 mV	0.058 mV	
		(0 ~ 5) mV	5.8×10^{-2}	
		(5 ~ 20) mV	5.8×10^{-3}	
		(20 ~ 100) mV	1.2×10^{-3}	
		(0.1 ~ 1) V	6.2×10^{-5}	
		(1 ~ 2) V	3.2×10^{-5}	
		(2 ~ 4) V	2.1×10^{-5}	
		(4 ~ 7) V	1.3×10^{-5}	
		(7 ~ 9) V	9.1×10^{-6}	
		(9 ~ 10) V	7.9×10^{-6}	
		(10 ~ 50) V	3.1×10^{-5}	
		(50 ~ 100) V	1.0×10^{-5}	
		(100 ~ 200) V	3.4×10^{-5}	
		(200 ~ 400) V	2.5×10^{-5}	
		(400 ~ 1 000) V	1.6×10^{-5}	
(1 000 ~ 1 200) V		1.0×10^{-3}		
(1 200 ~ 1 400) V		9.2×10^{-4}		
(1 400 ~ 1 500) V		8.7×10^{-4}		
Charge and Discharge Current	(\pm)			
	1 mA	5.8 μ A		
	(1 ~ 2) mA	2.9×10^{-3}		
	(2 ~ 5) mA	1.2×10^{-3}		
	(5 ~ 20) mA	5.8×10^{-4}		
	(20 ~ 50) mA	1.2×10^{-4}		
	(50 ~ 100) mA	5.9×10^{-5}		
	(0.1 ~ 0.2) A	2.9×10^{-4}		
	(0.2 ~ 0.4) A	1.9×10^{-4}		
	(0.4 ~ 0.6) A	1.2×10^{-4}		
	(0.6 ~ 0.8) A	8.4×10^{-5}		
	(0.8 ~ 1) A	6.6×10^{-5}		
	(1 ~ 3) A	5.1×10^{-5}		
	(3 ~ 6) A	2.6×10^{-5}		
	(6 ~ 10) A	1.6×10^{-5}		
(10 ~ 40) A	4.0×10^{-5}			
(40 ~ 100) A	2.9×10^{-5}			
(100 ~ 1 000) A	1.4×10^{-4}			
(1 000 ~ 3 000) A	4.9×10^{-4}			

404. Other DC & LF measurements

Measured Quantity Instrument or Gauge	Field Code	Range	Measurement uncertainty (The Confidence Level is about 95 %)	Standard/Method of Measurement etc.	
Electronic AC/DC loads	40417	Resistance	0.1 Ω (0.1 ~ 1) Ω (1 ~ 2) Ω (2 ~ 4) Ω (4 ~ 500) Ω (0.5 ~ 2) kΩ (2 ~ 10) kΩ	0.58 mΩ 2.1×10^{-3} 4.0×10^{-3} 2.3×10^{-3} 1.6×10^{-3} 9.0×10^{-4} 2.0×10^{-4}	Calibrator/ SICT-CP-40417
		AC Voltage	(0.001 V) (40 ~ 400) Hz (0.001 ~ 0.1) V (40 ~ 400) Hz (0.1 ~ 0.2) V (40 ~ 400) Hz (0.2 ~ 0.5) V (40 ~ 400) Hz (0.5 ~ 2) V (40 ~ 400) Hz (2 ~ 3) V (40 ~ 400) Hz (3 ~ 7) V (40 ~ 400) Hz (7 ~ 20) V (40 ~ 50) Hz (50 ~ 400) Hz (20 ~ 80) V (40 ~ 50) Hz (50 ~ 400) Hz (80 ~ 200) V (40 ~ 400) Hz (200 ~ 500) V (50 ~ 400) Hz	0.61 mV 6.1×10^{-3} 3.1×10^{-3} 1.2×10^{-3} 6.2×10^{-4} 2.8×10^{-4} 2.3×10^{-4} 1.5×10^{-4} 9.8×10^{-5} 2.1×10^{-4} 1.2×10^{-4} 1.3×10^{-4} 1.8×10^{-4}	
		AC Current	(1 mA) (40 ~ 400) Hz (1 ~ 100) mA (40 ~ 400) Hz (100 mA ~ 0.2 A) (40 ~ 400) Hz	0.58 mA 5.8×10^{-2} 5.8×10^{-3}	

404. Other DC & LF measurements

Measured Quantity Instrument or Gauge	Field Code	Range	Measurement uncertainty (The Confidence Level is about 95 %)	Standard/Method of Measurement etc.	
Electronic AC/DC loads AC Current	40417	(0.2 ~ 0.6) A (40 ~ 400) Hz (0.6 ~ 2) A (40 ~ 400) Hz (2 ~ 5) A (40 ~ 400) Hz (5 ~ 20) A (40 ~ 400) Hz	2.0×10^{-3} 9.4×10^{-4} 1.2×10^{-3} 1.0×10^{-3}	Calibrator/ SICT-CP-40417	
AC Resistance		(1 Ω) (40 ~ 400) Hz (1 ~ 50) Ω (40 ~ 400) Hz (50 ~ 100) Ω (40 ~ 400) Hz (100 Ω ~ 10 k Ω) (40 ~ 400) Hz	$1.0 \text{ m}\Omega$ 1.5×10^{-3} 1.1×10^{-3} 1.7×10^{-3}		
Modulation meters Frequency Modulation	40418	0 kHz (0 ~ 400) kHz	1 Hz 1.2×10^{-2}		Measuring Receiver/ SICT-CP-40418
Amplitude Modulation		0 % (0 ~ 100) %	0.01 % 1.2×10^{-2}		
Phase Modulation		0 rad (0 ~ 400) rad	1.2 mrad 1.2×10^{-2}		
Analogue/digital multimeters DC Voltage	40419	(\pm) 0 mV (0 ~ 1) mV (1 ~ 2) mV (2 ~ 5) mV (5 ~ 10) mV (10 ~ 15) mV (15 ~ 20) mV (20 ~ 50) mV (0.05 ~ 0.2) V (0.2 ~ 0.5) V (0.5 ~ 1) V (1 ~ 2) V (2 ~ 5) V (5 ~ 10) V (10 ~ 20) V (20 ~ 50) V (50 ~ 100) V (100 ~ 200) V (200 ~ 500) V (500 ~ 1 000) V	0.43 μ V 5.0×10^{-4} 2.5×10^{-4} 1.0×10^{-4} 5.0×10^{-5} 3.3×10^{-5} 2.5×10^{-6} 1.2×10^{-5} 8.0×10^{-6} 4.8×10^{-6} 3.8×10^{-6} 4.0×10^{-6} 2.6×10^{-6} 2.3×10^{-6} 6.0×10^{-6} 4.0×10^{-6} 3.5×10^{-6} 8.0×10^{-6} 5.2×10^{-6} 4.5×10^{-6}		Calibrator/ SICT-CP-40419

404. Other DC & LF measurements

Measured Quantity Instrument or Gauge	Field Code	Range	Measurement uncertainty (The Confidence Level is about 95 %)	Standard/Method of Measurement etc.
Analogue/digital multimeters AC Voltage	40419	(0.6 mV) 1 kHz	4.1 μ V	Calibrator/ SICT-CP-40419
		(1 mV) 10 Hz	4.2 μ V	
		(10 ~ 40) Hz	4.2 μ V	
		(0.04 ~ 20) kHz	4.1 μ V	
		(20 ~ 50) kHz	4.2 μ V	
		(50 ~ 100) kHz	5.5 μ V	
		(100 ~ 300) kHz	11 μ V	
		(300 ~ 500) kHz	21 μ V	
		(0.5 ~ 1) MHz	23 μ V	
		(1 ~ 2) mV 10 Hz	2.2×10^{-3}	
		(10 ~ 40) Hz	2.2×10^{-3}	
		(0.04 ~ 20) kHz	2.1×10^{-3}	
		(20 ~ 50) kHz	2.2×10^{-3}	
		(50 ~ 100) kHz	3.0×10^{-3}	
		(100 ~ 300) kHz	6.0×10^{-3}	
		(300 ~ 500) kHz	1.1×10^{-2}	
		(0.5 ~ 1) MHz	1.3×10^{-2}	
		(2 ~ 5) mV 10 Hz	1.1×10^{-3}	
		(10 ~ 40) Hz	9.2×10^{-4}	
		(0.04 ~ 20) kHz	9.0×10^{-4}	
		(20 ~ 50) kHz	1.0×10^{-3}	
		(50 ~ 100) kHz	1.5×10^{-3}	
		(100 ~ 300) kHz	3.0×10^{-3}	
		(300 ~ 500) kHz	5.2×10^{-3}	
		(0.5 ~ 1) MHz	6.8×10^{-3}	
		(5 ~ 10) mV 10 Hz	6.3×10^{-4}	
		(10 ~ 40) Hz	5.0×10^{-4}	
		(0.04 ~ 20) kHz	4.9×10^{-4}	
		(20 ~ 50) kHz	5.9×10^{-4}	
		(50 ~ 100) kHz	9.5×10^{-4}	
		(100 ~ 300) kHz	1.9×10^{-3}	
		(300 ~ 500) kHz	3.2×10^{-3}	
		(0.5 ~ 1) MHz	4.3×10^{-3}	
		(10 ~ 15) mV 10 Hz	4.8×10^{-4}	
		(10 ~ 40) Hz	3.6×10^{-4}	
		(0.04 ~ 20) kHz	3.5×10^{-4}	
		(20 ~ 50) kHz	4.5×10^{-4}	
		(50 ~ 100) kHz	7.6×10^{-4}	
		(100 ~ 300) kHz	1.5×10^{-3}	
		(300 ~ 500) kHz	2.5×10^{-3}	
		(0.5 ~ 1) MHz	3.7×10^{-3}	

404. Other DC & LF measurements

Measured Quantity Instrument or Gauge	Field Code	Range	Measurement uncertainty (The Confidence Level is about 95 %)	Standard/Method of Measurement etc.
Analogue/digital multimeters AC Voltage	40419	(15 ~ 20) mV		Calibrator/ SICT-CP-40419
		10 Hz	4.1×10^{-4}	
		(10 ~ 40) Hz	2.9×10^{-4}	
		(0.04 ~ 20) kHz	2.8×10^{-4}	
		(20 ~ 50) kHz	3.8×10^{-4}	
		(50 ~ 100) kHz	6.7×10^{-4}	
		(100 ~ 300) kHz	1.4×10^{-3}	
		(300 ~ 500) kHz	2.2×10^{-3}	
		(0.5 ~ 1) MHz	3.4×10^{-3}	
		(20 ~ 50) mV		
		10 Hz	4.6×10^{-4}	
		(10 ~ 40) Hz	2.6×10^{-4}	
		(0.04 ~ 20) kHz	2.1×10^{-4}	
		(20 ~ 50) kHz	2.7×10^{-4}	
		(50 ~ 100) kHz	6.6×10^{-4}	
		(100 ~ 300) kHz	1.0×10^{-3}	
		(300 ~ 500) kHz	1.6×10^{-3}	
		(0.5 ~ 1) MHz	3.3×10^{-3}	
		(50 ~ 100) mV		
		10 Hz	3.3×10^{-4}	
		(10 ~ 40) Hz	1.6×10^{-4}	
		(0.04 ~ 20) kHz	1.3×10^{-4}	
		(20 ~ 50) kHz	1.9×10^{-4}	
		(50 ~ 100) kHz	4.8×10^{-4}	
		(100 ~ 300) kHz	7.6×10^{-4}	
		(300 ~ 500) kHz	1.3×10^{-3}	
		(0.5 ~ 1) MHz	2.8×10^{-3}	
		(100 ~ 150) mV		
		10 Hz	2.9×10^{-4}	
		(10 ~ 40) Hz	1.3×10^{-4}	
		(0.04 ~ 20) kHz	1.0×10^{-4}	
		(20 ~ 50) kHz	1.6×10^{-4}	
		(50 ~ 100) kHz	4.1×10^{-4}	
		(100 ~ 300) kHz	6.8×10^{-4}	
		(300 ~ 500) kHz	1.3×10^{-3}	
		(0.5 ~ 1) MHz	2.6×10^{-3}	
		(150 ~ 200) mV		
		10 Hz	2.7×10^{-4}	
		(10 ~ 40) Hz	1.2×10^{-4}	
		(0.04 ~ 20) kHz	9.2×10^{-5}	
		(20 ~ 50) kHz	1.4×10^{-4}	
		(50 ~ 100) kHz	3.9×10^{-4}	
		(100 ~ 300) kHz	6.4×10^{-4}	
		(300 ~ 500) kHz	1.2×10^{-3}	
		(0.5 ~ 1) MHz	2.6×10^{-3}	

404. Other DC & LF measurements

Measured Quantity Instrument or Gauge	Field Code	Range	Measurement uncertainty (The Confidence Level is about 95 %)	Standard/Method of Measurement etc.
Analogue/digital multimeters AC Voltage	40419	(0.2 ~ 0.5) V		Calibrator/ SICT-CP-40419
		10 Hz	3.0×10^{-4}	
		(10 ~ 20) Hz	1.3×10^{-4}	
		(20 ~ 40) Hz	9.0×10^{-5}	
		(0.04 ~ 20) kHz	6.6×10^{-5}	
		(20 ~ 50) kHz	1.0×10^{-4}	
		(50 ~ 100) kHz	1.6×10^{-4}	
		(100 ~ 300) kHz	4.6×10^{-4}	
		(300 ~ 500) kHz	1.2×10^{-3}	
		(0.5 ~ 1) MHz	2.7×10^{-3}	
		(0.5 ~ 1) V		
		10 Hz	2.5×10^{-4}	
		(10 ~ 20) Hz	1.0×10^{-4}	
		(20 ~ 40) Hz	5.8×10^{-5}	
		(0.04 ~ 20) kHz	4.9×10^{-5}	
		(20 ~ 50) kHz	7.7×10^{-5}	
		(50 ~ 100) kHz	1.2×10^{-4}	
		(100 ~ 300) kHz	3.6×10^{-4}	
		(300 ~ 500) kHz	1.0×10^{-3}	
		(0.5 ~ 1) MHz	2.5×10^{-3}	
		(1 ~ 2) V		
		10 Hz	2.2×10^{-4}	
		(10 ~ 20) Hz	8.5×10^{-5}	
		(20 ~ 40) Hz	4.5×10^{-5}	
		(0.04 ~ 20) kHz	4.2×10^{-5}	
		(20 ~ 50) kHz	6.8×10^{-5}	
		(50 ~ 100) kHz	9.6×10^{-5}	
		(100 ~ 300) kHz	3.2×10^{-4}	
		(300 ~ 500) kHz	9.0×10^{-4}	
		(0.5 ~ 1) MHz	2.4×10^{-3}	
		(2 ~ 5) V		
		10 Hz	3.0×10^{-4}	
		(10 ~ 20) Hz	1.3×10^{-4}	
		(20 ~ 40) Hz	8.2×10^{-5}	
		(0.04 ~ 20) kHz	6.2×10^{-5}	
		(20 ~ 50) kHz	1.0×10^{-4}	
		(50 ~ 100) kHz	1.4×10^{-4}	
		(100 ~ 300) kHz	4.4×10^{-4}	
		(300 ~ 500) kHz	1.3×10^{-3}	
		(0.5 ~ 1) MHz	2.2×10^{-3}	
		(5 ~ 10) V		
		10 Hz	2.5×10^{-4}	
		(10 ~ 20) Hz	9.8×10^{-5}	
		(20 ~ 40) Hz	5.4×10^{-5}	
		(0.04 ~ 20) kHz	4.7×10^{-5}	
		(20 ~ 50) kHz	7.7×10^{-5}	
		(50 ~ 100) kHz	1.1×10^{-4}	
		(100 ~ 300) kHz	3.2×10^{-4}	
(300 ~ 500) kHz	1.0×10^{-3}			
(0.5 ~ 1) MHz	1.7×10^{-3}			

404. Other DC & LF measurements

Measured Quantity Instrument or Gauge	Field Code	Range	Measurement uncertainty (The Confidence Level is about 95 %)	Standard/Method of Measurement etc.
Analogue/digital multimeters AC Voltage	40419	(10 ~ 15) V		Calibrator/ SICT-CP-40419
		10 Hz	2.3×10^{-4}	
		(10 ~ 20) Hz	8.7×10^{-5}	
		(20 ~ 40) Hz	4.6×10^{-5}	
		(0.04 ~ 20) kHz	4.3×10^{-5}	
		(20 ~ 50) kHz	7.1×10^{-5}	
		(50 ~ 100) kHz	9.5×10^{-5}	
		(100 ~ 300) kHz	2.9×10^{-4}	
		(300 ~ 500) kHz	9.4×10^{-4}	
		(0.5 ~ 1) MHz	1.5×10^{-3}	
		(15 ~ 20) V		
		10 Hz	2.2×10^{-4}	
		(10 ~ 20) Hz	8.5×10^{-5}	
		(20 ~ 40) Hz	4.3×10^{-5}	
		(0.04 ~ 20) kHz	4.1×10^{-5}	
		(20 ~ 50) kHz	6.8×10^{-5}	
		(50 ~ 100) kHz	9.0×10^{-5}	
		(100 ~ 300) kHz	2.8×10^{-4}	
		(300 ~ 500) kHz	9.1×10^{-4}	
		(0.5 ~ 1) MHz	1.4×10^{-3}	
		(20 ~ 50) V		
		10 Hz	3.2×10^{-4}	
		(10 ~ 20) Hz	1.4×10^{-4}	
		(20 ~ 40) Hz	9.8×10^{-5}	
		(0.04 ~ 20) kHz	7.4×10^{-5}	
		(20 ~ 50) kHz	1.1×10^{-5}	
		(50 ~ 100) kHz	2.1×10^{-4}	
		(50 ~ 100) V		
		10 Hz	2.5×10^{-4}	
		(10 ~ 20) Hz	1.0×10^{-4}	
		(20 ~ 40) Hz	6.5×10^{-5}	
		(0.04 ~ 20) kHz	5.6×10^{-5}	
		(20 ~ 50) kHz	8.5×10^{-5}	
		(50 ~ 100) kHz	1.6×10^{-4}	
		(100 ~ 200) V		
		10 Hz	2.3×10^{-4}	
		(10 ~ 20) Hz	9.3×10^{-5}	
		(20 ~ 40) Hz	5.6×10^{-5}	
		(0.04 ~ 20) kHz	5.1×10^{-5}	
		(20 ~ 50) kHz	7.9×10^{-5}	
		(50 ~ 100) kHz	1.4×10^{-4}	
		(200 ~ 500) V		
		50 Hz ~ 1 kHz	6.7×10^{-5}	
		(500 ~ 1 000) V		
		50 Hz ~ 1 kHz	6.3×10^{-5}	

404. Other DC & LF measurements

Measured Quantity Instrument or Gauge	Field Code	Range	Measurement uncertainty (The Confidence Level is about 95 %)	Standard/Method of Measurement etc.	
Analogue/digital multimeters	40419	Resistance	0 Ω	0.001 0 mΩ	Calibrator/ SICT-CP-40419
			0 Ω ~ 10 kΩ	1.2×10^{-6}	
		(10 ~ 100) kΩ	1.4×10^{-6}		
		(0.1 ~ 1) MΩ	7.2×10^{-6}		
		(1 ~ 10) MΩ	7.7×10^{-6}		
		(10 ~ 100) MΩ	1.2×10^{-5}		
		(0.1 ~ 1) GΩ	3.2×10^{-4}		
		DC Current	(±)		
		0 nA	6.0 nA		
		(0 ~ 1) nA	6.9×10^{-3}		
		(1 ~ 100) nA	4.6×10^{-3}		
		(0.1 ~ 1) μA	6.0×10^{-3}		
		(1 ~ 2) μA	3.1×10^{-3}		
		(2 ~ 5) μA	1.2×10^{-3}		
		(5 ~ 10) μA	6.3×10^{-4}		
		(10 ~ 20) μA	3.5×10^{-4}		
		(20 ~ 50) μA	1.6×10^{-4}		
		(50 ~ 100) μA	9.4×10^{-5}		
		(100 ~ 200) μA	6.3×10^{-5}		
		(0.2 ~ 0.5) mA	4.8×10^{-5}		
		(0.5 ~ 1) mA	3.5×10^{-5}		
		(1 ~ 1.5) mA	3.1×10^{-5}		
		(1.5 ~ 2) mA	3.0×10^{-5}		
		(2 ~ 5) mA	4.4×10^{-5}		
		(5 ~ 10) mA	3.2×10^{-5}		
		(10 ~ 15) mA	2.9×10^{-5}		
		(15 ~ 20) mA	2.8×10^{-5}		
		(20 ~ 50) mA	5.6×10^{-5}		
		(50 ~ 100) mA	4.4×10^{-5}		
		(100 ~ 150) mA	4.1×10^{-5}		
		(150 ~ 200) mA	3.9×10^{-5}		
		(0.2 ~ 0.5) A	9.4×10^{-5}		
		(0.5 ~ 1) A	6.9×10^{-5}		
		(1 ~ 1.5) A	6.1×10^{-5}		
		(1.5 ~ 2) A	5.8×10^{-5}		
		(2 ~ 3) A	3.3×10^{-4}		
		(3 ~ 5) A	2.4×10^{-4}		
		(5 ~ 10) A	1.6×10^{-4}		
		(10 ~ 20) A	1.2×10^{-4}		
		(20 ~ 30) A	2.4×10^{-4}		

404. Other DC & LF measurements

Measured Quantity Instrument or Gauge	Field Code	Range	Measurement uncertainty (The Confidence Level is about 95 %)	Standard/Method of Measurement etc.
Analogue/digital multimeters AC Current	40419	(20 μ A)		Calibrator/ SICT-CP-40419
		1 kHz	11 nA	
		10 kHz	81 nA	
		(20 ~ 50) μ A		
		10 Hz	1.4×10^{-4}	
		(10 ~ 20) Hz	9.0×10^{-5}	
		20 Hz ~ 1 kHz	7.3×10^{-5}	
		(1 ~ 5) kHz	1.5×10^{-4}	
		(5 ~ 10) kHz	5.5×10^{-4}	
		(50 ~ 100) μ A		
		10 Hz	1.9×10^{-4}	
		(10 ~ 20) Hz	1.2×10^{-4}	
		20 Hz ~ 1 kHz	9.5×10^{-5}	
		(1 ~ 5) kHz	2.0×10^{-4}	
		(5 ~ 10) kHz	7.5×10^{-4}	
		(0.1 ~ 0.2) mA		
		10 Hz	3.0×10^{-4}	
		(10 ~ 20) Hz	1.9×10^{-4}	
		20 Hz ~ 1 kHz	1.4×10^{-5}	
		(1 ~ 5) kHz	3.1×10^{-4}	
		(5 ~ 10) kHz	1.2×10^{-3}	
		(0.2 ~ 0.5) mA		
		10 Hz	9.0×10^{-5}	
		(10 ~ 20) Hz	7.0×10^{-5}	
		20 Hz ~ 1 kHz	6.0×10^{-5}	
		(1 ~ 5) kHz	1.2×10^{-4}	
		(5 ~ 10) kHz	5.7×10^{-4}	
		(0.5 ~ 1) mA		
		10 Hz	1.4×10^{-4}	
		(10 ~ 20) Hz	1.0×10^{-4}	
		20 Hz ~ 1 kHz	8.0×10^{-5}	
		(1 ~ 5) kHz	1.6×10^{-4}	
		(5 ~ 10) kHz	7.6×10^{-4}	
		(1 ~ 2) mA		
		10 Hz	2.4×10^{-4}	
		(10 ~ 20) Hz	1.6×10^{-4}	
		20 Hz ~ 1 kHz	1.2×10^{-4}	
		(1 ~ 5) kHz	2.4×10^{-4}	
		(5 ~ 10) kHz	1.2×10^{-3}	
		(2 ~ 5) mA		
		10 Hz	9.0×10^{-5}	
		(10 ~ 20) Hz	7.0×10^{-5}	
		20 Hz ~ 1 kHz	5.2×10^{-5}	
		(1 ~ 5) kHz	1.1×10^{-4}	
		(5 ~ 10) kHz	5.4×10^{-4}	

404. Other DC & LF measurements

Measured Quantity Instrument or Gauge	Field Code	Range	Measurement uncertainty (The Confidence Level is about 95 %)	Standard/Method of Measurement etc.
Analogue/digital multimeters AC Current	40419	(5 ~ 10) mA		Calibrator/ SICT-CP-40419
		10 Hz	1.4×10^{-4}	
		(10 ~ 20) Hz	1.0×10^{-4}	
		20 Hz ~ 1 kHz	7.3×10^{-5}	
		(1 ~ 5) kHz	1.4×10^{-4}	
		(5 ~ 10) kHz	7.2×10^{-4}	
		(10 ~ 20) mA		
		10 Hz	2.4×10^{-4}	
		(10 ~ 20) Hz	1.6×10^{-4}	
		20 Hz ~ 1 kHz	1.2×10^{-4}	
		(1 ~ 5) kHz	2.2×10^{-4}	
		(5 ~ 10) kHz	1.1×10^{-3}	
		(20 ~ 50) mA		
		10 Hz	1.0×10^{-4}	
		(10 ~ 20) Hz	8.0×10^{-5}	
		20 Hz ~ 1 kHz	4.8×10^{-5}	
		(1 ~ 5) kHz	1.1×10^{-4}	
		(5 ~ 10) kHz	4.0×10^{-4}	
		(50 ~ 100) mA		
		10 Hz	1.4×10^{-4}	
		(10 ~ 20) Hz	1.0×10^{-4}	
		20 Hz ~ 1 kHz	6.8×10^{-5}	
		(1 ~ 5) kHz	1.4×10^{-4}	
		(5 ~ 10) kHz	6.0×10^{-4}	
		(0.1 ~ 0.2) A		
		10 Hz	2.4×10^{-4}	
		(10 ~ 20) Hz	1.6×10^{-4}	
		20 Hz ~ 1 kHz	1.1×10^{-4}	
		(1 ~ 5) kHz	2.1×10^{-4}	
		(5 ~ 10) kHz	1.0×10^{-3}	
		(0.2 ~ 1) A		
		40 Hz	1.4×10^{-4}	
		40 Hz ~ 1 kHz	1.4×10^{-4}	
		(1 ~ 5) kHz	2.6×10^{-4}	
		(5 ~ 10) kHz	2.7×10^{-3}	
		(1 ~ 2) A		
40 Hz ~ 1 kHz	2.4×10^{-4}			
(1 ~ 5) kHz	4.2×10^{-4}			
(5 ~ 10) kHz	5.2×10^{-3}			
(2 ~ 3) A				
(40 ~ 100) Hz	1.8×10^{-4}			
100 Hz ~ 1 kHz	1.9×10^{-4}			
(1 ~ 10) kHz	9.9×10^{-4}			

404. Other DC & LF measurements

Measured Quantity Instrument or Gauge	Field Code	Range	Measurement uncertainty (The Confidence Level is about 95 %)	Standard/Method of Measurement etc.
Analogue/digital multimeters	40419	AC Current		Calibrator/ SICT-CP-40419
			(3 ~ 5) A (40 ~ 100) Hz 100 Hz ~ 1 kHz (1 ~ 10) kHz (5 ~ 10) A (40 ~ 100) Hz 100 Hz ~ 1 kHz (1 ~ 10) kHz (10 ~ 20) A (40 ~ 60) Hz (60 ~ 100) Hz 100 Hz ~ 1 kHz (1 ~ 10) kHz (20 ~ 30) A (40 ~ 60) Hz (60 ~ 100) Hz 100 Hz ~ 1 kHz (1 ~ 10) kHz 10 Hz ~ 10 MHz	
(Digital Sampling)		Frequency		
AC Voltage		(1 mV) 0.1 Hz ~ 3 kHz (1 mV ~ 2 mV) 0.1 Hz ~ 3 kHz (2 mV ~ 3 mV) 0.1 Hz ~ 3 kHz (3 mV ~ 5 mV) 0.1 Hz ~ 3 kHz (5 mV ~ 10 mV) 0.1 Hz ~ 3 kHz (10 mV ~ 20 mV) 0.1 Hz ~ 3 kHz (20 mV ~ 30 mV) 0.1 Hz ~ 3 kHz (30 mV ~ 50 mV) 0.1 Hz ~ 3 kHz (50 mV ~ 100 mV) 0.1 Hz ~ 3 kHz	8.4×10^{-4} 4.2×10^{-4} 2.8×10^{-4} 1.7×10^{-4} 8.8×10^{-5} 4.8×10^{-5} 3.6×10^{-5} 3.0×10^{-5} 2.6×10^{-5}	

404. Other DC & LF measurements

Measured Quantity Instrument or Gauge	Field Code	Range	Measurement uncertainty (The Confidence Level is about 95 %)	Standard/Method of Measurement etc.
Analogue/digital multimeters (Digital Sampling) AC Voltage	40419	(100 mV ~ 200 mV) 0.1 Hz ~ 3 kHz	4.8×10^{-5}	Calibrator/ SICT-CP-40419
		(200 mV ~ 300 mV) 0.1 Hz ~ 3 kHz	3.6×10^{-5}	
		(300 mV ~ 500 mV) 0.1 Hz ~ 3 kHz	2.8×10^{-5}	
		(500 mV ~ 1 V) 0.1 Hz ~ 3 kHz	2.4×10^{-5}	
		(1 V ~ 2 V) 0.1 Hz ~ 3 kHz	4.8×10^{-5}	
		(2 V ~ 3 V) 0.1 Hz ~ 3 kHz	3.6×10^{-5}	
		(3 V ~ 5 V) 0.1 Hz ~ 3 kHz	3.0×10^{-5}	
		(5 V ~ 10 V) 0.1 Hz ~ 3 kHz	2.6×10^{-5}	
		(10 V ~ 30 V) 10 Hz ~ 3 kHz	3.6×10^{-5}	
		(30 V ~ 50 V) 10 Hz ~ 3 kHz	2.8×10^{-5}	
		(50 V ~ 100 V) 10 Hz ~ 3 kHz	2.4×10^{-5}	
		(100 V ~ 200 V) 10 Hz ~ 3 kHz	4.8×10^{-5}	
		(200 V ~ 1 000 V) 50 Hz ~ 1 kHz	2.4×10^{-5}	

404. Other DC & LF measurements

Measured Quantity Instrument or Gauge	Field Code	Range	Measurement uncertainty (The Confidence Level is about 95 %)	Standard/Method of Measurement etc.
Noise meters AC Voltage Test	40420	(600 μ V) 1 kHz	7.8×10^{-3}	Calibrator/ SICT-CP-40420
		(600 μ V ~ 20 mV) (10 ~ 40) Hz 40 Hz ~ 20 kHz (20 ~ 100) kHz (100 ~ 300) kHz 300 kHz ~ 1 MHz	2.6×10^{-3} 2.5×10^{-3} 3.5×10^{-3} 7.0×10^{-3} 1.5×10^{-2}	
		(20 ~ 200) mV (10 ~ 40) Hz 40 Hz ~ 20 kHz (20 ~ 100) kHz 100 kHz ~ 1 MHz	5.2×10^{-4} 3.4×10^{-4} 8.8×10^{-4} 4.3×10^{-3}	
		(200 mV ~ 2 V) (10 ~ 40) Hz 40 Hz ~ 20 kHz (20 ~ 100) kHz (100 ~ 300) kHz 300 kHz ~ 1 MHz	3.5×10^{-4} 1.5×10^{-4} 4.6×10^{-4} 8.8×10^{-4} 3.4×10^{-3}	
		(2 ~ 20) V (10 ~ 40) Hz 40 Hz ~ 100 kHz (100 ~ 300) kHz 300 kHz ~ 1 MHz	3.0×10^{-4} 1.2×10^{-4} 4.4×10^{-4} 2.2×10^{-3}	
		(20 ~ 200) V (10 ~ 40) Hz 40 Hz ~ 20 kHz (20 ~ 100) kHz	3.0×10^{-4} 1.2×10^{-4} 1.8×10^{-4}	
		(200 ~ 500) V 50 Hz ~ 1 kHz	3.8×10^{-4}	
		(500 ~ 1 000) V 50 Hz ~ 1 kHz	3.7×10^{-4}	
Weighting Test		(25 ~ 500) mV (1 ~ 30) MHz	2.1×10^{-2}	
		(500 mV ~ 2 V) (0.1 ~ 30) MHz	2.1×10^{-2}	
		(DIN/NOISE) 31.5 Hz ~ 10 kHz (JIS A) 31.5 Hz ~ 16 kHz (CCIR) 31.5 Hz ~ 31.5 kHz (CCIR/ARM) 31.5 Hz ~ 31.5 kHz	0.12 dB 0.12 dB 0.12 dB 0.12 dB	

404. Other DC & LF measurements

Measured Quantity Instrument or Gauge	Field Code	Range	Measurement uncertainty (The Confidence Level is about 95 %)	Standard/Method of Measurement etc.
Noise meters	40420	(10 mV) 1 kHz	2.8×10^{-3}	Calibrator/ SICT-CP-40420
		(10 mV ~ 1 V) 20 Hz ~ 1 kHz (1 ~ 10) kHz (10 ~ 100) kHz	8.5×10^{-5} 1.3×10^{-4} 6.9×10^{-4}	
DC Voltage Output		0 mV 100 mV ~ 1 V	0.99 μ V 1.1×10^{-5}	
Oscilloscopes	40421			Calibration Generator/ SICT-CP-40421
Impedance Measure		50 Ω 75 Ω 1 M Ω	3.5×10^{-5} 2.7×10^{-5} 2.5×10^{-5}	
DC Voltage		(\pm) 0 mV (0 ~ 1) mV (1 ~ 5) mV (5 ~ 10) mV (10 ~ 100) mV (100 ~ 900) mV (0.9 ~ 9) V (9 ~ 200) V	0.79 μ V 8.0×10^{-4} 4.1×10^{-4} 1.7×10^{-4} 8.5×10^{-5} 1.5×10^{-5} 9.1×10^{-6} 9.5×10^{-6}	
AC Voltage(Square wave)		(1 kHz) 1 mV (1 ~ 25) mV (0.025 ~ 0.5) V (0.5 ~ 2.2) V (2.2 ~ 130) V	6.5×10^{-3} 8.8×10^{-4} 9.1×10^{-4} 6.8×10^{-4} 8.4×10^{-4}	
Time Marker		100 ps (100 ~ 200) ps 200 ps ~ 20 ms 20 ms ~ 5 s	6.2×10^{-7} 3.1×10^{-7} 1.7×10^{-6} 1.6×10^{-5}	
CAL Output Amplitude		(40 Hz ~ 20 kHz) 100 mV 100 mV ~ 12 V	3.2×10^{-5} 1.9×10^{-5}	
CAL Output Frequency		100 Hz ~ 10 MHz	6.2×10^{-7}	
Sinewave Signal Generator Level		50 kHz 50 kHz ~ 1 MHz 1 MHz ~ 1 GHz (1 ~ 4) GHz (4 ~ 18) GHz (18 ~ 25) GHz (25 ~ 33) GHz (33 ~ 40) GHz	2.3×10^{-2} 4.7×10^{-2} 1.5×10^{-2} 1.8×10^{-2} 3.2×10^{-2} 5.5×10^{-2} 5.8×10^{-2} 6.0×10^{-2}	

404. Other DC & LF measurements

Measured Quantity Instrument or Gauge	Field Code	Range	Measurement uncertainty (The Confidence Level is about 95 %)	Standard/Method of Measurement etc.
Oscilloscopes AC Voltage(Sine wave)	40421	(10 ~ 40) Hz 2 mV (2 ~ 20) mV (20 ~ 200) mV (0.2 ~ 20) V (20 ~ 100) V (40 Hz ~ 1 kHz) 2 mV (2 ~ 20) mV (20 ~ 800) mV (0.8 ~ 20) V (20 ~ 200) V (1 ~ 50) kHz 2 mV (2 ~ 20) mV (20 ~ 200) mV (0.2 ~ 20) V (20 ~ 100) V (50 ~ 100) kHz 2 mV (2 ~ 20) mV (20 ~ 200) mV (0.2 ~ 20) V (20 ~ 100) V	5.3 μV 1.9×10^{-3} 6.8×10^{-4} 4.3×10^{-4} 4.5×10^{-4} 5.0 μV 1.7×10^{-3} 3.3×10^{-4} 1.7×10^{-4} 1.8×10^{-4} 5.2 μV 1.9×10^{-3} 4.8×10^{-4} 1.3×10^{-4} 1.7×10^{-4} 7.1 μV 2.7×10^{-3} 9.0×10^{-4} 1.9×10^{-4} 3.0×10^{-4}	Calibration Generator/ SICT-CP-40421
LF phase meters Phase Test	40422	(1 Hz ~ 200 kHz) (-180 ~ 180) °	0.074 °	Multi Function Generator/ SICT-CP-40422
Volt/Current recorders DC Voltage DC Current	40424	(±) (0 ~ 100) μV (0.1 ~ 1) mV (1 ~ 10) mV (0.01 ~ 1) V (1 ~ 10) V (10 ~ 100) V (100 ~ 1 000) V (±) (0 ~ 1) nA (1 ~ 100) nA (0.1 ~ 1) μA (1 ~ 10) μA (10 ~ 100) μA (0.1 ~ 10) mA (10 ~ 100) mA (0.1 ~ 1) A (1 ~ 100) A	0.51 μV 5.2×10^{-4} 5.9×10^{-5} 6.7×10^{-6} 4.3×10^{-6} 6.3×10^{-6} 8.7×10^{-6} 6.9 pA 4.6×10^{-3} 2.3×10^{-3} 7.2×10^{-4} 1.4×10^{-4} 7.6×10^{-5} 8.4×10^{-5} 1.2×10^{-4} 2.1×10^{-4}	Calibrator/ SICT-CP-40424

404. Other DC & LF measurements

Measured Quantity Instrument or Gauge	Field Code	Range	Measurement uncertainty (The Confidence Level is about 95 %)	Standard/Method of Measurement etc.
Relay test sets	40425			Digital Multimeter/ SICT-CP-40425
DC Voltage		1 mV 1 mV ~ 1 V (1 ~ 100) V (100 ~ 1 000) V	6 μV 7.0×10^{-4} 7.0×10^{-5} 2.2×10^{-5}	
DC Current		1 mA 1 mA ~ 1 A (1 ~ 20) A (20 ~ 100) A	58 μA 6.0×10^{-4} 2.5×10^{-4} 4.0×10^{-4}	
AC Voltage		(1 mV) 20 Hz ~ 100 kHz (1 ~ 100) mV 20 Hz ~ 10 kHz (10 ~ 100) kHz (100 mV ~ 1 V) 20 Hz ~ 10 kHz (10 ~ 100) kHz (1 ~ 10) V 20 Hz ~ 10 kHz (10 ~ 100) kHz 100 kHz ~ 1 MHz (10 ~ 100) V 20 Hz ~ 10 kHz (10 ~ 100) kHz (100 ~ 1 000) V 50 Hz ~ 10 kHz (10 ~ 30) kHz	58 μV 6.1×10^{-4} 1.2×10^{-3} 7.6×10^{-4} 1.3×10^{-3} 2.0×10^{-2} 2.2×10^{-4} 1.1×10^{-3} 2.1×10^{-2} 1.8×10^{-4} 1.1×10^{-3} 1.9×10^{-4} 4.5×10^{-4}	
AC Current		(1 mA) 40 Hz ~ 10 kHz (1 ~ 100) mA 40 Hz ~ 10 kHz (100 mA ~ 1 A) 40 Hz ~ 10 kHz (1 ~ 10) A 40 Hz ~ 10 kHz (10 ~ 100) A 40 Hz ~ 10 kHz	58 μA 8.6×10^{-4} 9.1×10^{-4} 9.9×10^{-4} 2.3×10^{-4}	
Timer		(1 ~ 100) s	5.8×10^{-6}	

404. Other DC & LF measurements

Measured Quantity Instrument or Gauge	Field Code	Range	Measurement uncertainty (The Confidence Level is about 95 %)	Standard/Method of Measurement etc.
LF signal generators	40426			Audio Analyzer, Digital Multimeter/ SICT-CP-40426
Frequency Test		(0.1 ~ 1) Hz 1 Hz ~ 100 MHz	5.8×10^{-7} 5.8×10^{-9}	
Output Level Test		(10 ~ 100) Hz 1 mV (1 ~ 10) mV 10 mV ~ 100 V	1.0×10^{-3} 1.0×10^{-4} 7.0×10^{-5}	
		(100 Hz ~ 10 kHz) 1 mV (1 ~ 10) mV 10 mV ~ 100 V	1.0×10^{-3} 1.0×10^{-4} 3.0×10^{-5}	
		(10 ~ 100) kHz 1 mV (1 ~ 10) mV 10 mV ~ 100 V	1.0×10^{-3} 1.0×10^{-4} 8.0×10^{-5}	
DC Offset		(±) 0 mV (0 ~ 1) mV (1 ~ 10) mV 10 mV ~ 20 V	0.7 μV 0.7 μV 1.0×10^{-4} 6.0×10^{-5}	
Output Level Flatness Test		(100 mV) (10 ~ 100) Hz 100 Hz ~ 10 kHz (10 ~ 100) kHz	0.099 dB 0.083 dB 0.095 dB	
		(100 mV ~ 1 V) (10 ~ 100) Hz 100 Hz ~ 10 kHz (10 ~ 100) kHz	0.005 4 dB 0.001 1 dB 0.007 2 dB	
		(1 ~ 30) V (10 ~ 100) Hz 100 Hz ~ 10 kHz (10 ~ 100) kHz	0.021 dB 0.015 dB 0.027 dB	
Attenuator Test		(10 Hz ~ 100 kHz) (0 ~ 80) dB	0.006 1 dB	
Distortion		(20 Hz ~ 1 kHz) (3.16 ~ 0.010) %	1.5×10^{-1}	
		(1 ~ 100) kHz (3.16 ~ 0.010) %	3.2×10^{-1}	
Rise/Fall Time		100 μs ~ 100 ns (100 ~ 10) ns (10 ~ 1) ns 1 ns ~ 100 ps	7.0×10^{-4} 7.8×10^{-4} 4.7×10^{-3} 4.6×10^{-2}	
Duty cycle		(1 ~ 99) %	0.006 1 %	

404. Other DC & LF measurements

Measured Quantity Instrument or Gauge	Field Code	Range	Measurement uncertainty (The Confidence Level is about 95 %)	Standard/Method of Measurement etc.
LF spectrum analyzers	40427			Synthesizer Function Generator/ SICT-CP-40427
Reference Frequency		10 MHz	7.7×10^{-12}	
Center Frequency		10 Hz	6.1×10^{-5}	
		(10 ~ 100) Hz	6.1×10^{-6}	
		100 Hz ~ 1 kHz	6.1×10^{-7}	
		1 kHz ~ 1 MHz	6.1×10^{-8}	
		(1 ~ 100) MHz	6.1×10^{-9}	
		100 MHz ~ 1 GHz	6.1×10^{-8}	
Frequency Range		10 Hz	1.1×10^{-3}	
		(10 ~ 100) Hz	1.1×10^{-4}	
		100 Hz ~ 1 kHz	1.1×10^{-5}	
		(1 ~ 100) kHz	1.1×10^{-4}	
		100 kHz ~ 1 MHz	1.1×10^{-6}	
		(1 ~ 100) MHz	1.1×10^{-7}	
		100 MHz ~ 1 GHz	1.1×10^{-9}	
Resolution Bandwidth		100 Hz	3.3×10^{-2}	
		100 Hz ~ 3 kHz	3.1×10^{-2}	
		(3 ~ 300) kHz	3.3×10^{-2}	
		300 kHz ~ 1 MHz	3.4×10^{-2}	
Absolute Amplitude		(-60 dBV)		
		10 Hz	0.043 dB	
		10 Hz ~ 10 kHz	0.042 dB	
		(10 ~ 100) kHz	0.056 dB	
		(-60 ~ -50) dBV		
		10 Hz	0.017 dB	
		10 Hz ~ 10 kHz	0.015 dB	
		(10 ~ 100) kHz	0.022 dB	
		(-50 ~ -40) dBV		
		10 Hz	0.009 dB	
		10 Hz ~ 10 kHz	0.009 8 dB	
		(10 ~ 100) kHz	0.012 dB	
		(-40 ~ -30) dBV		
		10 Hz	0.009 dB	
		10 Hz ~ 10 kHz	0.006 8 dB	
		(10 ~ 100) kHz	0.011 dB	
	(-30 ~ 30) dBV			
	10 Hz	0.016 dB		
	10 Hz ~ 10 kHz	0.006 3 dB		
	(10 ~ 100) kHz	0.007 3 dB		
Referency Level		(-60 dBV)		
		10 Hz ~ 100 kHz	0.17 dB	
		(-60 ~ 30) dBV		
	10 Hz ~ 100 kHz	0.16 dB		

404. Other DC & LF measurements

Measured Quantity Instrument or Gauge	Field Code	Range	Measurement uncertainty (The Confidence Level is about 95 %)	Standard/Method of Measurement etc.
LF spectrum analyzers	40427			Synthesizer Function Generator/ SICT-CP-40427
Frequency Response		10 Hz 10 Hz ~ 100 kHz	0.009 1 dB 0.008 7 dB	
Logscale Fidelity		(0 ~ -60) dB (-60 ~ -70) dB (-70 ~ -80) dB (-80 ~ -90) dB	0.009 2 dB 0.012 dB 0.016 dB 0.042 dB	
Output frequency		10 Hz ~ 300 MHz	6.1×10^{-11}	
Input Impedance		1 M Ω (50 ~ 75) Ω	0.000 12 M Ω 0.000 7 Ω	
Output Voltage		10 mV 10 mV ~ 5 V	0.000 38 mV 8.8×10^{-5}	
Output Offset Voltage		(-30 ~ 30) V	6.7×10^{-6}	
Output Voltage Flatness		10 Hz ~ 100 kHz	0.000 67 dB	
Spot generators	40428			Audio Analyzer, Digital Multimeter/ SICT-CP-40428
Frequency		(0.1 ~ 1) Hz 1 Hz ~ 100 kHz	5.8×10^{-7} 5.8×10^{-9}	
Output Level		(10 ~ 100) Hz 1 mV (1 ~ 10) mV 10 mV ~ 10 V	1.0×10^{-3} 1.0×10^{-4} 7.0×10^{-5}	
		(100 Hz ~ 10 kHz) 1 mV (1 ~ 10) mV 10 mV ~ 10 V	1.0×10^{-3} 1.0×10^{-4} 3.0×10^{-5}	
		(10 ~ 100) kHz 1 mV (1 ~ 10) mV 10 mV ~ 10 V	1.0×10^{-3} 1.0×10^{-4} 7.0×10^{-5}	
Output Level Flatness		(100 mV) (10 ~ 100) Hz 100 Hz ~ 10 kHz (10 ~ 100) kHz	 0.099 dB 0.083 dB 0.095 dB	
		(100 mV ~ 1 V) (10 ~ 100) Hz 100 Hz ~ 10 kHz (10 ~ 100) kHz	 0.005 4 dB 0.001 1 dB 0.007 2 dB	
		(1 ~ 10) V (10 ~ 100) Hz 100 Hz ~ 100 kHz	 0.010 dB 0.011 dB	

404. Other DC & LF measurements

Measured Quantity Instrument or Gauge	Field Code	Range	Measurement uncertainty (The Confidence Level is about 95 %)	Standard/Method of Measurement etc.
Spot generators	40428	Attenuation (10 Hz ~ 100 kHz) (0 ~ 80) dB	0.006 1 dB	Audio Analyzer, Digital Multimeter/ SICT-CP-40428
		Distortion (20 Hz ~ 1 kHz) (3.16 ~ 0.010) %	1.5×10^{-1}	
		(1 ~ 100) kHz (3.16 ~ 0.010) %	3.2×10^{-1}	
Sweep generators	40429	Frequency (0.1 ~ 1) Hz 1 Hz ~ 100 kHz	5.8×10^{-7} 5.8×10^{-9}	Audio Analyzer, Digital Multimeter/ SICT-CP-40429
		Output Level Test (10 ~ 100) Hz 1 mV (1 ~ 10) mV 100 mV ~ 10 V	1.0×10^{-3} 1.0×10^{-4} 7.0×10^{-5}	
		(100 Hz ~ 10 kHz) 1 mV (1 ~ 100) mV 100 mV ~ 10 V	1.0×10^{-3} 1.0×10^{-4} 3.0×10^{-5}	
		(10 ~ 100) kHz 1 mV (1 ~ 100) mV 100 mV ~ 10 V	1.0×10^{-3} 1.0×10^{-4} 7.0×10^{-5}	
		Output Level Flatness (100 mV) (10 ~ 100) Hz 100 Hz ~ 10 kHz (10 ~ 100) kHz	0.099 dB 0.083 dB 0.095 dB	
		(100 mV ~ 1 V) (10 ~ 100) Hz 100 Hz ~ 10 kHz (10 ~ 100) kHz	0.005 4 dB 0.001 1 dB 0.007 2 dB	
		(1 ~ 10) V (10 ~ 100) Hz 100 Hz ~ 100 kHz	0.010 dB 0.011 dB	
		Attenuation (10 Hz ~ 10 kHz) (0 ~ 80) dB	0.006 1 dB	
		Distortion (20 Hz ~ 1 kHz) (3.16 ~ 0.010) %	1.5×10^{-1}	
		(1 ~ 100) kHz (3.16 ~ 0.010) %	3.2×10^{-1}	

404. Other DC & LF measurements

Measured Quantity Instrument or Gauge	Field Code	Range	Measurement uncertainty (The Confidence Level is about 95 %)	Standard/Method of Measurement etc.
Signal transducers	40430			Digital Multimeter/ SICT-CP-40430
Voltage		1 mV (1 ~ 10) mV 10 mV ~ 100 V (100 ~ 300) V	5.2×10^{-4} 8.8×10^{-5} 3.1×10^{-5} 4.3×10^{-3}	
Current		10 μ A (10 ~ 100) μ A 100 μ A ~ 100 mA 100 mA ~ 20 A	9.5×10^{-4} 9.7×10^{-5} 7.0×10^{-5} 2.0×10^{-4}	
Frequency		(1 ~ 10) Hz 10 Hz ~ 100 kHz	3.1×10^{-4} 7.2×10^{-5}	
Transistor curve tracers	40432			Digital Multimeter/ SICT-CP-40432
DC Voltage(Source)		0 mV (0 ~ 100) mV 100 mV ~ 1 V (1 ~ 10) V (10 ~ 100) V (100 ~ 1 000) V	1.0 μ V 1.1×10^{-5} 1.0×10^{-5} 9.8×10^{-6} 1.1×10^{-5} 8.0×10^{-6}	
DC Current(Source)		0 nA (0 ~ 1) nA (1 ~ 100) nA (0.1 ~ 1) μ A (1 ~ 10) μ A 10 μ A ~ 10 mA (10 ~ 100) mA 100 mA ~ 10 A	0.12 nA 1.0×10^{-2} 8.0×10^{-3} 8.0×10^{-4} 9.0×10^{-5} 1.6×10^{-5} 5.0×10^{-5} 2.5×10^{-4}	
DC Voltage(Measure)		0 mV (0 ~ 100) mV 100 mV ~ 1 V (1 ~ 100) V (100 ~ 1 000) V	0.78 μ V 1.5×10^{-5} 6.0×10^{-4} 6.4×10^{-4} 6.2×10^{-5}	
AC/DC high voltage generators	40434			High Voltage Digital Meter/ SICT-CP-40434
DC Voltage		(\pm) 0 kV (0 ~ 0.5) kV (0.5 ~ 1) kV (1 ~ 2) kV (2 ~ 100) kV (100 ~ 200) kV	0.58 V 1.2×10^{-3} 6.1×10^{-4} 3.0×10^{-4} 2.3×10^{-4} 1.2×10^{-2}	
AC Voltage		(50 Hz) 0.01 kV (0.01 ~ 0.5) kV (0.5 ~ 1) kV (1 ~ 100) kV (100 ~ 200) kV (60 Hz) 0.01 kV (0.01 ~ 0.5) kV (0.5 ~ 1) kV (1 ~ 100) kV (100 ~ 200) kV	0.58 V 1.2×10^{-3} 6.1×10^{-4} 5.7×10^{-4} 1.2×10^{-2} 0.58 V 1.2×10^{-3} 6.2×10^{-4} 5.2×10^{-4} 1.2×10^{-2}	

404. Other DC & LF measurements

Measured Quantity Instrument or Gauge	Field Code	Range	Measurement uncertainty (The Confidence Level is about 95 %)	Standard/Method of Measurement etc.
AC/DC high voltage probes DC Voltage AC Voltage	40435	(±) 0 kV (0 ~ 0.5) kV (0.5 ~ 1) kV (1 ~ 100) kV (50 Hz) 0.01 kV (0.01 ~ 0.5) kV (0.5 ~ 1) kV (1 ~ 3) kV (3 ~ 5) kV (5 ~ 10) kV (10 ~ 20) kV (20 ~ 100) kV (60 Hz) 0.01 kV (0.01 ~ 0.5) kV (0.5 ~ 1) kV (1 ~ 3) kV (3 ~ 5) kV (5 ~ 10) kV (10 ~ 20) kV (20 ~ 100) kV	0.06 V 4.2×10^{-4} 2.1×10^{-4} 3.5×10^{-4} 2.2 V 4.4×10^{-3} 2.3×10^{-3} 1.2×10^{-3} 7.5×10^{-4} 6.0×10^{-4} 4.0×10^{-4} 3.7×10^{-4} 2.2 V 4.4×10^{-3} 2.3×10^{-3} 1.2×10^{-3} 7.5×10^{-4} 6.0×10^{-4} 4.0×10^{-4} 3.7×10^{-4}	DC Power Supply/ SICT-CP-40435
Logic analyzers DC Voltage Clock frequency	40436	(0 ~ 100) mV (0.1 ~ 1) V (1 ~ 10) V 10 MHz	1.5 μV 8.8×10^{-6} 7.2×10^{-6} 7.7×10^{-12}	Calibrator/ SICT-CP-40436
Telephone testers L1, L2 Output Voltage Loop Current Ring Output Voltage Ring Frequency D.T.M.F & Pulse D.T.M.F & Frequency	40437	(1 ~ 100) mV (0.1 ~ 1) V (1 ~ 10) V (10 ~ 1 000) V (0.1 ~ 10) mA (10 ~ 100) mA (0.1 ~ 1) A (1 ~ 10) A (10 Hz ~ 20 kHz) 100 mV ~ 1 V (1 ~ 100) V (100 ~ 1 000) V (1 ~ 1 000) Hz (+10 ~ -39.9) dBm (697 ~ 1 477) Hz	9.9×10^{-4} 1.1×10^{-5} 7.1×10^{-6} 8.5×10^{-6} 2.5×10^{-5} 5.2×10^{-5} 2.2×10^{-4} 4.7×10^{-4} 4.7×10^{-4} 2.9×10^{-4} 3.1×10^{-4} 7.0×10^{-5} 0.09 dB 0.59 Hz	Tone Pulse Simulator/ SICT-CP-40437

404. Other DC & LF measurements

Measured Quantity Instrument or Gauge	Field Code	Range	Measurement uncertainty (The Confidence Level is about 95 %)	Standard/Method of Measurement etc.
Video signal analyzers	40438			Video Amplitude Calibration
Color Bar Decoding Accuracy(Gain)		(0 ~ 5) mV	2.5×10^{-1}	Fixture/ SICT-CP-40438
		(5 ~ 10) mV	5.0×10^{-2}	
		(10 ~ 100) mV	8.2×10^{-2}	
		(100 ~ 200) mV	4.1×10^{-2}	
		(200 ~ 500) mV	2.1×10^{-2}	
		(500 ~ 1 000) mV	8.5×10^{-3}	
Frequency		20 Hz ~ 5 MHz	5.8×10^{-6}	
Color Bar Decoding Accuracy(Phase)		(0 ~ 360)°	0.70°	
Measure Square Wave		(0 ~ 5) mV	9.4×10^{-2}	
		(5 ~ 10) mV	2.0×10^{-2}	
		(10 ~ 100) mV	9.9×10^{-3}	
		(100 ~ 300) mV	2.1×10^{-3}	
		(300 ~ 400) mV	1.5×10^{-3}	
		(400 ~ 600) mV	1.2×10^{-3}	
		(600 ~ 999.9) mV	9.4×10^{-4}	
Measure Sine Wave		No Filter, PAL NTS BW Lim, NTSC,PAL Chroma BP, NTSC,PAL (10 kHz ~ 10 MHz) 500 mV	7.0×10^{-3}	
Burst Frequency		(3 ~ 5) MHz	4.0×10^{-7}	
vertical Gain		(0 ~ 5) mV	9.4×10^{-2}	
		(5 ~ 10) mV	2.0×10^{-2}	
		(10 ~ 100) mV	9.9×10^{-3}	
		(100 ~ 300) mV	2.1×10^{-3}	
		(300 ~ 600) mV	1.5×10^{-3}	
		(600 ~ 999.9) mV	9.4×10^{-4}	
Horizontal Frequency		(20 ~ 100) Hz	3.1×10^{-3}	
		100 Hz ~ 10 kHz	6.1×10^{-4}	
		10 kHz ~ 10 MHz	6.1×10^{-5}	
Gain Frequency Response		Flat, Luminance, Chroma at (20 Hz ~ 20 MHz) 700 mV	7.0×10^{-3}	
Transient Response		(0 ~ 1 000) mV	1.3×10^{-2}	
(Video Noise)				
Luminance Volt Level		(0 ~ -30) dB	4.8×10^{-1}	
Chrominance AM/PM Level		(0 ~ -30) dB	6.7×10^{-1}	
Luminance Volt Level		(0 ~ 1 000) mV	1.7×10^{-5}	
Luminance Input Level		(0 ~ 1 000) mV	1.8×10^{-5}	
Chrominance Input Level		(0 ~ 1 000) mV	1.7×10^{-5}	

405. Low frequency electric & magnetic fields

Measured Quantity Instrument or Gauge	Field Code	Range	Measurement uncertainty (The Confidence Level is about 95 %)	Standard/Method of Measurement etc.
Flux meters Flux	40503	0.1 mWb ~ 10 Wb	5.8×10^{-3}	Flux sources/ SICT-CP-40503
Flux sources Flux	40504	(0.1 ~ 50) mWb (0.05 ~ 0.1) Wb (0.1 ~ 10) Wb	6.6×10^{-4} 2.3×10^{-5} 1.4×10^{-5}	GPS receiver, Frequency counter/ SICT-CP-40504
Magnetometers Gauss	40508	(0 ~ 0.1) mT (0.1 ~ 0.5) mT (0.5 ~ 3) mT (3 ~ 5) mT (5 ~ 20) mT (20 ~ 30) mT (30 ~ 1 700) mT	7.1×10^{-2} 1.4×10^{-2} 7.0×10^{-3} 4.0×10^{-3} 3.0×10^{-3} 6.7×10^{-3} 6.4×10^{-3}	Helmholtz coil, Standard magnets/ SICT-CP-40508
Reference/standard magnets Gauss	40510	(1.5 ~ 30) mT (30 ~ 1 000) mT	7.3×10^{-3} 2.6×10^{-3}	Gaussmeters/ SICT-CP-40510

406. Radio frequency measurement

Measured Quantity Instrument or Gauge	Field Code	Range	Measurement uncertainty (The Confidence Level is about 95 %)	Standard/Method of Measurement etc.
RF amplifiers	Gain	10 Hz ~ 10 kHz (0 ~ 80) dB	0.07 dB	Power Sensor, Attenuator/ SICT-CP-40601
		10 kHz ~ 10 GHz (0 ~ 40) dB (40 ~ 80) dB	0.08 dB 0.11 dB	
(10 ~ 18) GHz (0 ~ 40) dB (40 ~ 80) dB		0.10 dB 0.13 dB		
(18 ~ 30) GHz (0 ~ 60) dB (60 ~ 70) dB (70 ~ 80) dB		0.20 dB 0.31 dB 0.75 dB		
(30 ~ 40) GHz (0 ~ 60) dB (60 ~ 70) dB (70 ~ 80) dB		0.26 dB 0.35 dB 0.76 dB		
(40 ~ 50) GHz (0 ~ 60) dB (60 ~ 70) dB (70 ~ 80) dB		0.41 dB 0.47 dB 0.82 dB		
(50 ~ 67) GHz (0 ~ 20) dB (20 ~ 45) dB		0.36 dB 0.45 dB		
Harmonics		(9 kHz ~ 40 GHz) (0 ~ 100) dBc	0.90 dB	
Reflection coefficient		(0 ~ 1)		
		10 Hz ~ 2 GHz	4.7×10^{-3}	
		(2 ~ 20) GHz	9.2×10^{-3}	
		(20 ~ 40) GHz	1.5×10^{-2}	
		(40 ~ 50) GHz	1.9×10^{-2}	
SWR	(50 ~ 67) GHz	3.3×10^{-2}		
	(1 ~ ∞)			
	10 Hz ~ 2 GHz	9.5×10^{-3}		
	(2 ~ 20) GHz	1.9×10^{-2}		
	(20 ~ 40) GHz	3.1×10^{-2}		
(40 ~ 50) GHz	3.9×10^{-2}			
(50 ~ 67) GHz	6.7×10^{-2}			

406. Radio frequency measurement

Measured Quantity Instrument or Gauge	Field Code	Range	Measurement uncertainty (The Confidence Level is about 95 %)	Standard/Method of Measurement etc.
Coaxial attenuators Attenuation	40602	(10 Hz ~ 1 kHz) (0 ~ 40) dB (40 ~ 50) dB (50 ~ 70) dB (1 kHz ~ 9 kHz) (0 ~ 40) dB (40 ~ 50) dB (50 ~ 70) dB (9 kHz ~ 26.5 GHz) (0 ~ 10) dB (10 ~ 30) dB (30 ~ 40) dB (40 ~ 50) dB (50 ~ 60) dB (60 ~ 70) dB (70 ~ 80) dB (80 ~ 90) dB (90 ~ 110) dB (110 ~ 120) dB (26.5 ~ 45) GHz (0 ~ 20) dB (20 ~ 70) dB (45 ~ 67) GHz (0 ~ 10) dB (10 ~ 50) dB (50 ~ 60) dB (60 ~ 70) dB	0.063 dB 0.070 dB 0.12 dB 0.063 dB 0.068 dB 0.11 dB 0.064 dB 0.069 dB 0.073 dB 0.077 dB 0.081 dB 0.086 dB 0.090 dB 0.095 dB 0.11 dB 0.12 dB 0.21 dB 0.24 dB 0.23 dB 0.25 dB 0.27 dB 0.32 dB	Power Sensor, Directional Coupler/ SICT-CP-40602
Reflection coefficient		(0 ~ 1) 10 Hz ~ 2 GHz (2 ~ 20) GHz (20 ~ 40) GHz (40 ~ 50) GHz (50 ~ 67) GHz	0.004 7 0.009 2 0.015 0.019 0.033	
SWR		(1 ~ ∞) 10 Hz ~ 2 GHz (2 ~ 20) GHz (20 ~ 40) GHz (40 ~ 50) GHz (50 ~ 67) GHz	0.009 5 0.019 0.031 0.039 0.067	

406. Radio frequency measurement

Measured Quantity Instrument or Gauge	Field Code	Range	Measurement uncertainty (The Confidence Level is about 95 %)	Standard/Method of Measurement etc.
Burst pulse generators Burst Volatage	40605	50 Ω (±) 5 V (5 ~ 100) V (0.1 ~ 8) kV	2.0×10^{-2} 1.6×10^{-2} 2.0×10^{-2}	Digital Oscilloscope/ SICT-CP-40605
Rise/Fall Time		1 kΩ (±) 5 V ~ 8 kV	4.0×10^{-2}	
Pulse Width		1 ns (1 ~ 2) ns (2 ~ 4) ns 4 ns ~ 1 μs (1 ~ 2) μs (2 ~ 4) μs (4 ~ 10) μs	2.0×10^{-2} 6.8×10^{-3} 2.6×10^{-3} 1.5×10^{-3} 6.2×10^{-3} 2.6×10^{-3} 1.3×10^{-3}	
Time measurement by section		1 ns (1 ~ 2) ns 2 ns ~ 200 ms	6.0×10^{-3} 3.1×10^{-3} 1.5×10^{-3}	
Repeat Frequency		1 ns (1 ~ 2) ns 2 ns ~ 400 ms 400 ms ~ 10 s	6.0×10^{-3} 3.1×10^{-3} 1.5×10^{-3} 1.2×10^{-3}	
		1 Hz ~ 25 MHz	1.6×10^{-3}	
Attenuator calibrators Attenuation	40606	(0 ~ 10) dB (10 ~ 20) dB (20 ~ 30) dB (30 ~ 40) dB (40 ~ 50) dB (50 ~ 60) dB (60 ~ 70) dB (70 ~ 80) dB (80 ~ 90) dB (90 ~ 100) dB (100 ~ 110) dB (110 ~ 120) dB	0.024 dB 0.025 dB 0.027 dB 0.029 dB 0.031 dB 0.034 dB 0.036 dB 0.039 dB 0.042 dB 0.045 dB 0.048 dB 0.052 dB	Verification Kit/ SICT-CP-40606
RF power meter calibrators Output Power	40607	3 μW 10 μW 30 μW 100 μW 300 μW 1 mW 3 mW 10 mW 30 mW 100 mW	0.1 nW 0.2 nW 0.5 nW 1 nW 4 nW 0.18 μW 0.19 μW 0.2 μW 0.3 μW 1 μW	Digital Multimeter/ SICT-CP-40607

406. Radio frequency measurement

Measured Quantity Instrument or Gauge	Field Code	Range	Measurement uncertainty (The Confidence Level is about 95 %)	Standard/Method of Measurement etc.
EMC transducers ; current probes, absorbing clamps, etc. Transfer Impedance Insertion Loss Electric Magnetic Near-Field Reflection coefficient SWR	40608	10 Hz ~ 50 MHz (50 ~ 200) MHz 200 MHz ~ 3 GHz 30 MHz ~ 1 GHz 100 kHz ~ 1 GHz (0 ~ 1) 10 Hz ~ 1 GHz (1 ~ 3) GHz (1 ~ ∞) 10 Hz ~ 1 GHz (1 ~ 3) GHz	0.60 dB 1.1 dB 1.9 dB 1.9 dB 1.9 dB 4.2×10^{-3} 6.0×10^{-3} 9.0×10^{-3} 1.3×10^{-2}	Power Senso, Network analyzer/ SICT-CP-40608
Coaxial directional couplers/ splitters Coupling Factor	40610	(10 Hz ~ 10 kHz) (0 ~ 40) dB (40 ~ 50) dB (50 ~ 70) dB (10 kHz ~ 100 kHz) (0 ~ 30) dB (30 ~ 50) dB (50 ~ 70) dB (100 kHz ~ 15 GHz) (0 ~ 40) dB (40 ~ 50) dB (50 ~ 70) dB (15 GHz ~ 18 GHz) (0 ~ 70) dB (18 GHz ~ 26.5 GHz) (0 ~ 70) dB (26.5 GHz ~ 45 GHz) (0 ~ 20) dB (20 ~ 70) dB (45 GHz ~ 67 GHz) (0 ~ 10) dB (10 ~ 50) dB (50 ~ 60) dB (60 ~ 70) dB	0.063 dB 0.070 dB 0.12 dB 0.064 dB 0.087 dB 0.098 dB 0.090 dB 0.093 dB 0.11 dB 0.12 dB 0.17 dB 0.21 dB 0.24 dB 0.23 dB 0.25 dB 0.27 dB 0.32 dB	Power Sensor, Synthesized Sweeper/ SICT-CP-40610

406. Radio frequency measurement

Measured Quantity Instrument or Gauge	Field Code	Range	Measurement uncertainty (The Confidence Level is about 95 %)	Standard/Method of Measurement etc.
Coaxial directional couplers/ splitters Reflection coefficient	40610	(0 ~ 1) 10 Hz ~ 2 GHz (2 ~ 20) GHz (20 ~ 40) GHz (40 ~ 50) GHz (50 ~ 67) GHz	0.004 7 0.009 2 0.015 0.019 0.033	Power Sensor, Synthesized Sweeper/
SWR		(1 ~ ∞) 10 Hz ~ 2 GHz (2 ~ 20) GHz (20 ~ 40) GHz (40 ~ 50) GHz (50 ~ 67) GHz	0.009 5 0.019 0.031 0.039 0.067	
Electrostatic discharge generators Peak Current(Ip)	40613	(±) (3.75 ~ 7.5) A (7.5 ~ 15) A (15 ~ 22.5) A (22.5 ~ 56.3) A (56.3 ~ 93.8) A (93.8 ~ 112.5) A (112.5 ~ 150) A	5.1×10^{-2} 5.3×10^{-2} 4.6×10^{-2} 5.2×10^{-2} 4.9×10^{-2} 5.7×10^{-2} 5.2×10^{-2}	Digital Oscilloscope/ SICT-CP-40613
Current I1 (30 ~ 60) ns		(±) 2 A (2 ~ 4) A (4 ~ 8) A (8 ~ 16) A (16 ~ 36) A (36 ~ 50) A (50 ~ 60) A (60 ~ 80) A	4.5×10^{-2} 5.0×10^{-2} 5.3×10^{-2} 4.9×10^{-2} 5.0×10^{-2} 4.4×10^{-2} 5.7×10^{-2} 5.2×10^{-2}	
Current I2 (60 ~ 130) ns		(±) 1 A (1 ~ 2) A (2 ~ 4) A (4 ~ 6) A (6 ~ 8) A (8 ~ 15) A (15 ~ 25) A (25 ~ 30) A (30 ~ 40) A	5.0×10^{-2} 5.4×10^{-2} 5.7×10^{-2} 4.9×10^{-2} 5.4×10^{-2} 6.5×10^{-2} 5.2×10^{-2} 6.7×10^{-2} 6.1×10^{-2}	

406. Radio frequency measurement

Measured Quantity Instrument or Gauge	Field Code	Range	Measurement uncertainty (The Confidence Level is about 95 %)	Standard/Method of Measurement etc.		
Electrostatic discharge generators Current I3 (360 ~ 800) ns	40613	(±) 0.275 A (0.275 ~ 0.55) A (0.55 ~ 1.1) A (1.1 ~ 1.65) A (1.65 ~ 4.13) A (4.13 ~ 6.88) A (6.88 ~ 8.25) A (8.25 ~ 11) A	1.5×10^{-1} 2.2×10^{-1} 1.9×10^{-1} 1.6×10^{-1} 2.3×10^{-1} 1.5×10^{-1} 2.4×10^{-1} 1.9×10^{-1}	Digital Oscilloscope/ SICT-CP-40613		
Current I4 (30 ~ 65) ns		(±) 0.15 A (0.15 ~ 0.3) A (0.3 ~ 0.6) A (0.6 ~ 1.2) A (1.2 ~ 2.25) A (2.25 ~ 2.7) A (2.7 ~ 3.75) A (3.75 ~ 4.5) A (4.5 ~ 6) A	1.3×10^{-1} 1.9×10^{-1} 3.0×10^{-1} 2.1×10^{-1} 2.5×10^{-1} 2.0×10^{-1} 1.5×10^{-1} 2.9×10^{-1} 2.0×10^{-1}			
Semiconductor Peak Current HBM		(±) (20 ~ 83.3) mA (0.083 3 ~ 1.33) A (1.33 ~ 6.66) A	3.1×10^{-2} 3.6×10^{-2} 2.7×10^{-2}			
Semiconductor Peak Current MM		(±) (0.219 ~ 14) A (14 ~ 35) A	3.5×10^{-2} 3.1×10^{-2}			
Time		0.1 ns 0.1 ns ~ 1 ms	2.7×10^{-2} 2.4×10^{-2}			
Peak Voltage		(±) 1 kV (1 ~ 35) kV	3.0×10^{-2} 2.5×10^{-2}			
EMC receivers		40614	100 kHz ~ 1 GHz		6.1×10^{-10}	Network Analyzer, Pulse Generator/ SICT-CP-40614
Frequency accuracy			9 kHz ~ 50 MHz		0.011	
SWR			50 MHz ~ 8 GHz		0.028	
			(8 ~ 19) GHz		0.035	
			(19 ~ 26) GHz		0.045	
			(26 ~ 40) GHz		0.064	
IF Band Accuracy			1 Hz ~ 10 MHz		65 mHz	
IF Band Selectivity			1 Hz ~ 10 MHz		6.7×10^{-4}	
IF Band Linearity		1 Hz ~ 1 GHz	0.12 dB			

406. Radio frequency measurement

Measured Quantity Instrument or Gauge	Field Code	Range	Measurement uncertainty (The Confidence Level is about 95 %)	Standard/Method of Measurement etc.		
EMC receivers	40614	Frequency Response	10 Hz ~ 5 kHz 0.01 dB 5 kHz ~ 1 GHz 0.07 dB (1 ~ 10) GHz 0.08 dB (10 ~ 18) GHz 0.09 dB (18 ~ 26.5) GHz 0.11 dB (26.5 ~ 40) GHz 0.16 dB (40 ~ 50) GHz 0.20 dB	Network Analyzer, Pulse Generator/ SICT-CP-40614		
Frequency Response (CISPR)		9 kHz ~ 1 GHz 0.80 dB				
Display linearity accuracy		(80 ~ 50) dB μ V 0.10 dB (50 ~ 0) dB μ V 0.14 dB				
Input Attenuation		(0 ~ 30) dB 0.15 dB (30 ~ 70) dB 0.12 dB (70 ~ 110) dB 0.10 dB				
Noise Indicator		DC ~ 26.5 GHz 0.16 dB				
Interference Immunity		9 kHz ~ 40 GHz 0.67 dB				
RF filters		40615	Reject Frequency		(9 ~ 90) kHz 0.024 kHz (90 ~ 900) kHz 0.24 kHz 900 kHz ~ 900 MHz 0.025 MHz 900 MHz ~ 18 GHz 0.068 MHz (18 ~ 50) GHz 0.12 MHz	Network Analyzer/ SICT-CP-40615
Insertion Loss			(9 kHz ~ 8 GHz)			
			(0 ~ 10) dB 0.13 dB			
			(10 ~ 20) dB 0.14 dB			
	(20 ~ 40) dB 0.15 dB					
	(40 ~ 50) dB 0.16 dB					
	(50 ~ 60) dB 0.18 dB					
	(60 ~ 70) dB 0.23 dB					
	(70 ~ 80) dB 0.66 dB					
	(80 ~ 90) dB 1.7 dB					
	(90 ~ 100) dB 4.3 dB					
	(8 ~ 18) GHz					
	(0 ~ 10) dB 0.23 dB					
	(10 ~ 30) dB 0.24 dB					
	(30 ~ 50) dB 0.25 dB					
	(50 ~ 60) dB 0.26 dB					
	(60 ~ 70) dB 0.31 dB					
	(70 ~ 80) dB 0.73 dB					
	(80 ~ 90) dB 1.7 dB					
	(90 ~ 100) dB 4.3 dB					

406. Radio frequency measurement

Measured Quantity Instrument or Gauge	Field Code	Range	Measurement uncertainty (The Confidence Level is about 95 %)	Standard/Method of Measurement etc.
RF filters Insertion Loss	40615	(18 ~ 50) GHz (0 ~ 10) dB (10 ~ 20) dB (20 ~ 30) dB (20 ~ 40) dB (40 ~ 50) dB (50 ~ 60) dB (60 ~ 70) dB (70 ~ 80) dB (80 ~ 90) dB (90 ~ 100) dB	0.48 dB 0.51 dB 0.52 dB 0.53 dB 0.54 dB 0.59 dB 0.78 dB 1.6 dB 2.8 dB 6.0 dB	Network Analyzer/ SICT-CP-40615
RF impedance meters RF Level Frequency Load Measurement	40616	(100 kHz ~ 18 GHz) (35 ~ 20) dBm (20 Hz ~ 18 GHz) (20 ~ -70) dBm 9 kHz ~ 0.1 MHz 0.1 MHz ~ 18 GHz DC 10 Hz ~ 100 MHz (100 ~ 500) MHz 500 MHz ~ 1.8 GHz (1.8 ~ 3.0) GHz (3.0 ~ 18) GHz	0.11 dB 0.12 dB 6.8×10^{-10} 6.2×10^{-11} 0.02 Ω 0.06 Ω 0.15 Ω 0.21 Ω 0.41 Ω 1.1 Ω	Performance Kit/ SICT-CP-40616
RF impulse generators Pulse Level	40617	9 kHz ~ 1 GHz	0.33 dB	Digital Oscilloscope/ SICT-CP-40617
Line impedance stabilization networks; LISN, CDN, ISN, etc. Impedance Phase Insertion Loss Decoupling attenuation(Isolation) Coupling/Decoupling network(Impedance) Coupling/Decoupling network (Insertion loss)	40618	9 kHz ~ 1 000 MHz 9 kHz ~ 1 000 MHz (0 ~ 100) dB 9 kHz ~ 100 MHz (100 ~ 1 000) MHz (0 ~ 100) dB (9 ~ 30) kHz (0.03 ~ 20) MHz (20 ~ 1 000) MHz 9 kHz ~ 1 000 MHz (0 ~ 100) dB 9 kHz ~ 1 000 MHz	2.0×10^{-2} 1.2 ° 0.07 dB 0.08 dB 0.21 dB 0.20 dB 0.21 dB 2.0×10^{-2} 0.10 dB	Impedance/Gain-Phase Analyzer, Calibration Kit/ SICT-CP-40618

406. Radio frequency measurement

Measured Quantity Instrument or Gauge	Field Code	Range	Measurement uncertainty (The Confidence Level is about 95 %)	Standard/Method of Measurement etc.						
Coaxial standard mismatches	40619	(0 ~ 1) 10 Hz ~ 2 GHz (2 ~ 20) GHz (20 ~ 40) GHz (40 ~ 50) GHz (50 ~ 67) GHz	0.004 7 0.009 2 0.015 0.019 0.033	Network Analyzer, Calibration Kit/ SICT-CP-40619-1						
(Coaxial standard mismatches) Reflection coefficient										
SWR					(1 ~ ∞) 10 Hz ~ 2 GHz (2 ~ 20) GHz (20 ~ 40) GHz (40 ~ 50) GHz (50 ~ 67) GHz	0.009 5 0.019 0.031 0.039 0.067				
							(Calibration kit) Magnitude of reflection coefficient	SICT-CP-40619-2		
									(Termination) 9 kHz ~ 2 GHz (2 ~ 20) GHz (20 ~ 40) GHz (40 ~ 50) GHz (50 ~ 67) GHz	0.004 7 0.009 2 0.015 0.019 0.033
		SWR	(1 ~ 1.01) 9 kHz ~ 2 GHz (2 ~ 20) GHz (20 ~ 40) GHz (40 ~ 50) GHz (50 ~ 67) GHz	0.009 5 0.019 0.031 0.039 0.067						
(1.01 ~ 1.05) 9 kHz ~ 2 GHz (2 ~ 20) GHz (20 ~ 40) GHz (40 ~ 50) GHz (50 ~ 67) GHz					0.011 0.020 0.032 0.040 0.070					

406. Radio frequency measurement

Measured Quantity Instrument or Gauge	Field Code	Range	Measurement uncertainty (The Confidence Level is about 95 %)	Standard/Method of Measurement etc.
Coaxial standard mismatches	40619	(1.05 ~ 1.2)		Network Analyzer, Calibration Kit/ SICT-CP-40619-2
SWR		9 kHz ~ 45 MHz	0.015	
		45 MHz ~ 2 GHz	0.014	
		(2 ~ 20) GHz	0.024	
		(20 ~ 40) GHz	0.039	
		(40 ~ 50) GHz	0.049	
		(50 ~ 67) GHz	0.083	
		(1.2 ~ 1.5)		
		9 kHz ~ 45 MHz	0.023	
		45 MHz ~ 2 GHz	0.021	
		(2 ~ 20) GHz	0.035	
		(20 ~ 40) GHz	0.054	
		(40 ~ 50) GHz	0.066	
		(50 ~ 67) GHz	0.12	
		(1.5 ~ 2)		
		9 kHz ~ 45 MHz	0.040	
		45 MHz ~ 2 GHz	0.036	
		(2 ~ 20) GHz	0.055	
		(20 ~ 40) GHz	0.086	
		(40 ~ 50) GHz	0.11	
		(50 ~ 67) GHz	0.18	
		(2 ~ 3)		
		9 kHz ~ 45 MHz	0.096	
		45 MHz ~ 2 GHz	0.076	
		(2 ~ 20) GHz	0.12	
		(20 ~ 40) GHz	0.20	
		(40 ~ 50) GHz	0.24	
		(50 ~ 67) GHz	0.35	
		(3 ~ 9)		
		9 kHz ~ 45 MHz	0.80	
		45 MHz ~ 2 GHz	0.70	
		(2 ~ 20) GHz	1.1	
		(20 ~ 40) GHz	1.8	
		(40 ~ 50) GHz	2.2	
		(50 ~ 67) GHz	2.8	
Phase of reflection coefficient		(Termination)		
		9 kHz ~ 67 GHz	180°	
		(Short, Open circuit)		
		9 kHz ~ 45 MHz	1.2°	
		45 MHz ~ 2 GHz	0.87°	
		(2 ~ 20) GHz	1.5°	
		(20 ~ 40) GHz	2.6°	
		(40 ~ 50) GHz	3.2°	
		(50 ~ 67) GHz	3.8°	

406. Radio frequency measurement

Measured Quantity Instrument or Gauge	Field Code	Range	Measurement uncertainty (The Confidence Level is about 95 %)	Standard/Method of Measurement etc.		
Mobile communication test sets RF Output Level	40621	(35 ~ 20) dBm 100 kHz ~ 18 GHz)	0.08 dB	Measuring Receiver, RF Signal Generator/ SICT-CP-40621		
		(20 ~ -20) dBm 9 kHz ~ 1 GHz (1 ~ 18) GHz (18 ~ 40) GHz (40 ~ 50) GHz	0.06 dB 0.11 dB 0.14 dB 0.18 dB			
		(-20 ~ -60) dBm 9 kHz ~ 1 GHz (1 ~ 18) GHz (18 ~ 40) GHz (40 ~ 50) GHz	0.06 dB 0.11 dB 0.16 dB 0.21 dB			
		(-60 ~ -70) dBm 9 kHz ~ 1 GHz (1 ~ 18) GHz (18 ~ 40) GHz (40 ~ 50) GHz	0.08 dB 0.10 dB 0.18 dB 0.21 dB			
		(-70 ~ -120) dBm 9 kHz ~ 26.5 GHz	0.15 dB			
		Amplitude Modulation	(0.1 ~ 100) %		1.2×10^{-2}	
		Frequency Modulation	(0.1 ~ 400) kHz		1.2×10^{-2}	
		Phase Modulation	(0.1 ~ 400) rad		1.2×10^{-2}	
		Distortion Harmonics of Modulation Rate Signal	≤ 20 %		2.3×10^{-2}	
		Hamonics	(0 ~ -90) dB		0.36 dB	
		Frequency Output Accuracy	9 kHz ~ 40 GHz		7.9×10^{-11}	
		AC Output Level	(10 Hz ~ 100 kHz) (1 ~ 100) mV 100 mV ~ 100 V		5.2×10^{-4} 5.8×10^{-4}	
			DC Output Level		1 mV ~ 1 V (1 ~ 10) V (10 ~ 100) V	1.5×10^{-6} 1.3×10^{-6} 1.8×10^{-6}

406. Radio frequency measurement

Measured Quantity Instrument or Gauge	Field Code	Range	Measurement uncertainty (The Confidence Level is about 95 %)	Standard/Method of Measurement etc.
Mobile communication test sets AC Input Level	40621	(10 Hz ~ 100 kHz)		Measuring Receiver, RF Signal Generator/ SICT-CP-40621
		(1 ~ 10) mV	7.6×10^{-3}	
		(10 ~ 100) mV	1.3×10^{-3}	
		(0.1 ~ 1) V	6.7×10^{-4}	
		(1 ~ 10) V	1.7×10^{-4}	
		(10 ~ 100) V	2.0×10^{-4}	
DC Input Level		(1 ~ 10) mV	1.3×10^{-3}	
		(10 ~ 100) mV	3.1×10^{-4}	
		(0.1 ~ 1) V	6.2×10^{-5}	
		(1 ~ 100) V	6.1×10^{-5}	
RF Input Level		(9 kHz ~ 18 GHz)		
		(10 ~ -70) dBm	0.10 dB	
	(18 ~ 40) GHz			
	(10 ~ -70) dBm	0.16 dB		
Modulation meters Amplitude Modulation	40622	0 kHz	0.01 %	Measuring Receiver/ SICT-CP-40622
		(0 ~ 400) kHz	1.2×10^{-2}	
Frequency Modulation		0 %	1 Hz	
		(0 ~ 100) %	1.2×10^{-2}	
Phase Modulation		0 rad	1.2 mrad	
		(0 ~ 400) rad	1.2×10^{-2}	
Network analyzers Frequency	40623	10 Hz ~ 40 GHz	6.8×10^{-10}	Power Sensor, Verification Kit/ SICT-CP-40623
Source Power Level		(20 ~ -30) dBm		
		10 Hz ~ 100 Hz	0.01 dB	
		100 Hz ~ 500 MHz	0.08 dB	
		500 MHz ~ 10 GHz	0.09 dB	
		(10 ~ 18) GHz	0.11 dB	
		(18 ~ 27) GHz	0.13 dB	
		(27 ~ 40) GHz	0.16 dB	
		(40 ~ 50) GHz	0.21 dB	
		(50 ~ 80) GHz	0.45 dB	
		(80 ~ 110) GHz	0.53 dB	
		(-30 ~ -60) dBm		
		9 kHz ~ 500 MHz	0.08 dB	
		500 MHz ~ 10 GHz	0.09 dB	
		(10 ~ 18) GHz	0.11 dB	
		(18 ~ 27) GHz	0.13 dB	
		(27 ~ 40) GHz	0.16 dB	

406. Radio frequency measurement

Measured Quantity Instrument or Gauge	Field Code	Range	Measurement uncertainty (The Confidence Level is about 95 %)	Standard/Method of Measurement etc.
Network analyzers	40623	(100 kHz ~ 18 GHz)		Power Sensor, Verification Kit/ SICT-CP-40623
Dynamic Range		(0 ~ 10) dB	0.086 dB	
		(10 ~ 20) dB	0.087 dB	
		(20 ~ 30) dB	0.088 dB	
		(30 ~ 40) dB	0.091 dB	
		(40 ~ 50) dB	0.099 dB	
		(50 ~ 60) dB	0.11 dB	
		(60 ~ 70) dB	0.12 dB	
		(70 ~ 80) dB	0.14 dB	
		(80 ~ 90) dB	0.15 dB	
		(90 ~ 100) dB	0.18 dB	
Attenuation		(20 dB)		
		300 kHz ~ 1.5 GHz	0.050 dB	
		(1.5 ~ 8) GHz	0.051 dB	
		(8 ~ 18) GHz	0.055 dB	
		(18 ~ 26.5) GHz	0.067 dB	
		(40 dB)		
		300 kHz ~ 1.5 GHz	0.054 dB	
		(1.5 ~ 8) GHz	0.055 dB	
		(8 ~ 18) GHz	0.059 dB	
		(18 ~ 26.5) GHz	0.082 dB	
Phase		($\pm 180^\circ$)		
		300 kHz ~ 45 MHz	0.04°	
		45 MHz ~ 2.0 GHz	0.09°	
		(2.0 ~ 3.0) GHz	0.10°	
		(3.0 ~ 4.5) GHz	0.11°	
		(4.5 ~ 6.0) GHz	0.15°	
		(6.0 ~ 7.5) GHz	0.19°	
		(7.5 ~ 8.0) GHz	0.21°	
		(8.0 ~ 9.0) GHz	0.22°	
		(9.0 ~ 10.5) GHz	0.29°	
		(10.5 ~ 12.0) GHz	0.28°	
		(12.0 ~ 13.5) GHz	0.26°	
		(13.5 ~ 15.0) GHz	0.27°	
		(15.0 ~ 16.5) GHz	0.26°	
		(16.5 ~ 18.0) GHz	0.29°	
		(18.0 ~ 21.0) GHz	0.31°	
		(21.0 ~ 22.5) GHz	0.28°	
		(22.5 ~ 24.0) GHz	0.39°	
		(24.0 ~ 25.5) GHz	0.33°	
		(25.5 ~ 26.5) GHz	0.44°	

406. Radio frequency measurement

Measured Quantity Instrument or Gauge	Field Code	Range	Measurement uncertainty (The Confidence Level is about 95 %)	Standard/Method of Measurement etc.
Network analyzers SWR	40623	(30 kHz ~ 2 GHz) 1.05 1.20 1.50 2.00 (2 ~ 18) GHz 1.05 1.20 1.50 2.00	0.021 0.021 0.021 0.021 0.018 0.018 0.018 0.024	Power Sensor, Verification Kit/ SICT-CP-40623
Noise figure meters Tuning Accuracy Referency frequency Input VSWR DC voltage Range Noise Figure	40624	10 MHz ~ 26.5 GHz 10 MHz 9 kHz ~ 1 GHz (1 ~ 20) GHz (20 ~ 26.5) GHz (0 ~ 28) V (0 ~ 30) dB 10 MHz ~ 8 GHz (8 ~ 18) GHz (18 ~ 26.5) GHz	4.3×10^{-5} 6.1×10^{-10} 0.008 0.019 0.03 0.000 18 V 0.052 dB 0.12 dB 0.16 dB 0.37 dB	Noise Source/ SICT-CP-40624
Noise generators Noise Power Scale Fidelity	40625	(-80 ~ -130) dBm/Hz (0 ~ 50) dB	0.10 dB 0.27 dB	Spectrum Analyzer/ SICT-CP-40625
Noise impulse simulators Peak Voltage Rise/Fall Time Pulse Width	40626	(±) 0.1 kV (0.1 ~ 5) kV 1 ns (1 ~ 2) ns (2 ~ 4) ns 10 ns (10 ~ 1 000) ns	4.0×10^{-2} 3.5×10^{-2} 6.0×10^{-3} 3.1×10^{-3} 1.5×10^{-3} 2.0×10^{-3} 1.5×10^{-3}	Digital Oscilloscope/ SICT-CP-40626
RF phase noise meters RF phase noise	40627	(Carrier Frequency) 100 MHz ~ 18 GHz (Offset Frequency) 10 Hz ~ 100 MHz	1.0 dB 1.0 dB	RF Signal analyzer/ SICT-CP-40627

406. Radio frequency measurement

Measured Quantity Instrument or Gauge	Field Code	Range	Measurement uncertainty (The Confidence Level is about 95 %)	Standard/Method of Measurement etc.
Coaxial noise sources	40628	(4.5 ~ 16) dB (0.01 ~ 1) GHz (1 ~ 7) GHz (7 ~ 8) GHz (8 ~ 14) GHz (14 ~ 18) GHz (12 ~ 17) dB (0.01 ~ 1) GHz (1 ~ 2) GHz (2 ~ 6) GHz (6 ~ 7) GHz (7 ~ 12) GHz (12 ~ 18) GHz (18 ~ 26.5) GHz	0.28 dB 0.27 dB 0.30 dB 0.31 dB 0.32 dB 0.31 dB 0.28 dB 0.30 dB 0.29 dB 0.40 dB 0.41 dB 0.47 dB	Coaxial noise sources, Noise figure analyzer/ SICT-CP-40628
	ENR			
	SWR	(0 ~1) (0.01 ~ 3) GHz (3 ~ 20) GHz (20 ~ 26.5) GHz	0.006 8 0.010 0.015	
RF power meters	40635	(0.1 ~ 500) W 10 kHz ~ 250 MHz (0.1 ~ 150) W (80 ~ 1 000) MHz (0.1 ~ 10) W (1 000 ~ 4 200) MHz	2.6×10^{-2} 2.6×10^{-2} 2.7×10^{-2}	Range Calibrator/ SICT-CP-40635
	High power			
	Zero Carryover	10 μ W ~ 1 mW (1 ~ 100) mW	3 nW 0.01 mW	
	Power	3 μ W ~ 100 mW	1.6×10^{-3}	
	Calibration Factor	(88 ~ 100) %	0.5×10^{-3}	
	Power Ref. Output	50 MHz, 1 mW	8 μ W	

406. Radio frequency measurement

Measured Quantity Instrument or Gauge	Field Code	Range	Measurement uncertainty (The Confidence Level is about 95 %)	Standard/Method of Measurement etc.
Diode power sensors Cal factor	40636	(1 ~ 10) μ W		Therimistor Mount, Synthesized Sweeper/ SICT-CP-40636
		9 kHz ~ 100 kHz	0.4×10^{-2}	
		100 kHz ~ 1 GHz	0.9×10^{-2}	
		(1 ~ 10) GHz	1.1×10^{-2}	
		(10 ~ 18) GHz	1.9×10^{-2}	
		(18 ~ 26.5) GHz	2.8×10^{-2}	
		(26.5 ~ 40) GHz	4.0×10^{-2}	
		(10 μ W ~ 10 mW)		
		9 kHz ~ 100 kHz	0.4×10^{-2}	
		100 kHz ~ 1 GHz	0.9×10^{-2}	
		(1 ~ 10) GHz	1.1×10^{-2}	
		(10 ~ 18) GHz	1.9×10^{-2}	
		(18 ~ 26.5) GHz	2.6×10^{-2}	
		(26.5 ~ 40) GHz	3.5×10^{-2}	
Reflection coefficient		(0 ~ 1)		
		20 Hz ~ 1 GHz	4.2×10^{-3}	
		(1 ~ 20) GHz	9.4×10^{-3}	
	(20 ~ 40) GHz	1.5×10^{-2}		
SWR	(1 ~ ∞)			
	20 Hz ~ 1 GHz	9.7×10^{-3}		
	(1 ~ 20) GHz	2.4×10^{-2}		
	(20 ~ 40) GHz	3.8×10^{-2}		
Thermocouple power sensors Cal Factor	40637	(1 ~ 10) μ W		Therimistor Mount, Synthesized Sweeper/ SICT-CP-40637
		9 kHz ~ 100 kHz	0.4×10^{-2}	
		100 kHz ~ 1 GHz	0.9×10^{-2}	
		(1 ~ 10) GHz	1.1×10^{-2}	
		(10 ~ 18) GHz	1.9×10^{-2}	
		(18 ~ 26.5) GHz	2.8×10^{-2}	
		(26.5 ~ 40) GHz	4.0×10^{-2}	
		(10 μ W ~ 10 mW)		
		9 kHz ~ 100 kHz	0.4×10^{-2}	
		100 kHz ~ 1 GHz	0.9×10^{-2}	
		(1 ~ 10) GHz	1.1×10^{-2}	
		(10 ~ 18) GHz	1.9×10^{-2}	
		(18 ~ 26.5) GHz	2.6×10^{-2}	
		(26.5 ~ 40) GHz	3.5×10^{-2}	
Reflection coefficient		(0 ~ 1)		
		20 Hz ~ 1 GHz	4.2×10^{-3}	
		(1 ~ 20) GHz	9.4×10^{-3}	
	(20 ~ 40) GHz	1.5×10^{-2}		
SWR	(1 ~ ∞)			
	20 Hz ~ 1 GHz	9.7×10^{-3}		
	(1 ~ 20) GHz	2.4×10^{-2}		
	(20 ~ 40) GHz	3.8×10^{-2}		

406. Radio frequency measurement

Measured Quantity Instrument or Gauge	Field Code	Range	Measurement uncertainty (The Confidence Level is about 95 %)	Standard/Method of Measurement etc.
Pulse generators	40638			Digital Oscilloscope/ SICT-CP-40638
Period		100 ps ~ 1 s	5.8×10^{-9}	
Frequency		1 Hz ~ 1 GHz (1 ~ 3.35) GHz	5.8×10^{-9} 1.7×10^{-8}	
Width		100 ps ~ 1 s	1.2×10^{-3}	
Delay Time		100 ps ~ 1 s	1.2×10^{-3}	
Double Pulse		100 ps ~ 1 s	1.2×10^{-3}	
Duty Cycle		(1 ~ 99) %	0.006 2 %	
DC Level		$\pm(10 \text{ mV} \sim 100 \text{ V})$	5.8×10^{-4}	
Output Level		(100 Hz ~ 10 kHz) (10 ~ -20) dBm	0.018 dB	
Radar test sets	40639			Signal Analyzer, SART Generator, EPIRB Generator/ SICT-CP-40639
(Ship) RF Level		(20 ~ -20) dBm 20 Hz ~ 1 GHz (1 ~ 18) GHz	0.09 dB 0.13 dB	
		(-20 ~ -60) dBm 9 kHz ~ 1 GHz (1 ~ 18) GHz	0.06 dB 0.11 dB	
		(-60 ~ -120) dBm 10 MHz ~ 18 GHz	0.25 dB	
Amplitude Modulation		(0.1 ~ 100) %	1.2×10^{-2}	
Frequency Modulation		(0.1 ~ 400) kHz	1.2×10^{-2}	
Phase Modulation		(0.1 ~ 400) rad	1.2×10^{-2}	
Distortion of Modulation		(0 ~ 2) %	1.2×10^{-3}	
Hamonics		(9 kHz ~ 18 GHz) (0 ~ -110) dB	0.25 dB	
Frequency		9 kHz ~ 18 GHz	6.2×10^{-11}	
Pulse Period		1 ns ~ 10 ms	1.2×10^{-2}	
High power		(0.1 ~ 500) W 10 kHz ~ 250 MHz	2.6×10^{-2}	
		(0.1 ~ 150) W (80 ~ 1 000) MHz	2.6×10^{-2}	
		(0.1 ~ 10) W (1 000 ~ 4 200) MHz	2.7×10^{-2}	

406. Radio frequency measurement

Measured Quantity Instrument or Gauge	Field Code	Range	Measurement uncertainty (The Confidence Level is about 95 %)	Standard/Method of Measurement etc.
Radar test sets (flight) Frequency(VOR/ILS/DME) Amplitude Modulation(VOR/ILS) 고주파 레벨(VOR/ILS) DDM(VOR/ILS)	40639	(74.6 ~ 1 150) MHz Localizer (108.1 ~ 111.95) MHz (0.1 ~ 20) % Glideslope (330.95 ~ 334.70) MHz (20 ~ 40) % Marker Beacon (74.6 ~ 75.4) MHz (40 ~ 95) % VOR (108 ~ 117.95) MHz (0.1 ~ 30) % Localizer (108.1 ~ 111.95) MHz (10 ~ -30) dBm (-30 ~ -50) dBm (-50 ~ -70) dBm (-70 ~ -110) dBm (-110 ~ -120) dBm Glideslope (330.95 ~ 334.70) MHz (10 ~ -30) dBm (-30 ~ -50) dBm (-50 ~ -70) dBm (-70 ~ -110) dBm (-110 ~ -120) dBm Localizer (108.1 ~ 111.95) MHz LEFT(-0.200 ~ -0.155) LEFT(-0.155 ~ -0.093) CENTER(0.000) RIGHT(0.093 ~ 0.155) RIGHT(0.155 ~ 0.200) Glideslope (330.95 ~ 334.70) MHz DOWN(0.400 ~ 0.175) DOWN(0.175 ~ 0.091) CENTER(0.000) UP(-0.091 ~ -0.175) UP(-0.175 ~ -0.400)	8.2 × 10 ⁻⁸ 0.62 % 0.84 % 1.4 % 0.62 % 0.19 dB 0.23 dB 0.24 dB 0.34 dB 0.35 dB 0.19 dB 0.23 dB 0.24 dB 0.34 dB 0.35 dB 0.000 5 0.000 5 0.000 5 0.000 5 0.000 5 0.000 5 0.000 5 0.000 5 0.000 5 0.000 5 0.000 5	Signal Analyzer, SART Generator, EPIRB Generator/ SICT-CP-40639

406. Radio frequency measurement

Measured Quantity Instrument or Gauge	Field Code	Range	Measurement uncertainty (The Confidence Level is about 95 %)	Standard/Method of Measurement etc.
Radar test sets SDM(VOR/ILS) BEARING ANGLE(VOR)	40639	Localizer (108.1 ~ 111.95) MHz (0 ~ 40) % Glideslope (330.95 ~ 334.70) MHz (40 ~ 80) % VOR (108 ~ 117.95) MHz (0 ~ 360) °	0.87 % 1.2 % 0.04 °	Signal Analyzer, SART Generator, EPIRB Generator/ SICT-CP-40639
RF signal generators Frequency Modulation Amplitude Modulation Phase Modulation Pulse Modulation Distortion RF Level	40640	(0.1 ~ 400) kHz (0.1 ~ 100) % (0.1 ~ 400) rad (100 kHz ~ 12 000 MHz) Period (1 μs ~ 1 s) ton (100 ns ~ 100 μs) PRR ≤ 20 % (54 ~ 57) dBm 100 kHz ~ 500 MHz (51 ~ 54) dBm 100 kHz ~ 2 GHz (35 ~ 51) dBm 100 kHz ~ 18 GHz (20 ~ 35) dBm 100 kHz ~ 10 GHz (10 ~ 18) GHz (-30 ~ 20) dBm 20 Hz ~ 10 GHz (10 ~ 18) GHz (18 ~ 28) GHz (28 ~ 40) GHz (40 ~ 50) GHz (50 ~ 70) GHz (70 ~ 110) GHz (-30 ~ -60) dBm 20 Hz ~ 10 GHz (10 ~ 18) GHz (18 ~ 28) GHz (28 ~ 40) GHz (40 ~ 50) GHz	1.2 × 10 ⁻² 1.2 × 10 ⁻² 1.2 × 10 ⁻² 1.2 × 10 ⁻³ 1.2 × 10 ⁻³ 3.1 × 10 ⁻³ 2.3 × 10 ⁻² 0.35 dB 0.32 dB 0.32 dB 0.26 dB 0.27 dB 0.09 dB 0.11 dB 0.12 dB 0.16 dB 0.20 dB 0.29 dB 0.38 dB 0.10 dB 0.11 dB 0.12 dB 0.16 dB 0.21 dB	Measuring Receiver/ SICT-CP-40640

406. Radio frequency measurement

Measured Quantity Instrument or Gauge	Field Code	Range	Measurement uncertainty (The Confidence Level is about 95 %)	Standard/Method of Measurement etc.	
RF signal generators RF Level	40640	(-120 ~ -60) dBm 20 Hz ~ 4.2 GHz (4.2 ~ 8) GHz (8 ~ 12.4) GHz (12.4 ~ 18) GHz (18 ~ 26.5) GHz	0.21 dB 0.23 dB 0.24 dB 0.27 dB 0.31 dB	Measuring Receiver/ SICT-CP-40640	
Harmonic		(-10 ~ -110) dBc	0.37 dB		
Frequency		9 kHz ~ 40 GHz	2.1×10^{-11}		
RF spectrum analyzers Center Frequency	40641	(3 ~ 100) Hz (100 ~ 500) Hz (500 ~ 900) Hz 900 Hz ~ 100 kHz 0.1 MHz ~ 40 GHz	2.0×10^{-4} 6.1×10^{-6} 1.2×10^{-6} 6.8×10^{-7} 6.2×10^{-9}	Power Sensor, Synthesized Sweeper/ SICT-CP-40641	
Frequency Counter		(3 ~ 100) Hz (100 ~ 500) Hz (500 ~ 900) Hz 900 Hz ~ 100 kHz 0.1 MHz ~ 40 GHz	2.0×10^{-4} 6.1×10^{-6} 1.2×10^{-6} 6.8×10^{-7} 6.2×10^{-9}		
Span		10 Hz ~ 100 kHz 0.1 MHz ~ 40 GHz	7.6×10^{-3} 7.7×10^{-6}		
RBW		1 Hz ~ 100 MHz	6.2×10^{-6}		
RBW Selectivity		1 Hz ~ 100 MHz	3.2×10^{-2}		
RBW Switching		1 Hz ~ 100 MHz	0.022 dB		
Scale Switching		1 dB ~ 10 dB scale/div	0.022 dB		
Scale Fidelity		(0 ~ -30) dB (-30 ~ -40) dB (-40 ~ -50) dB (-50 ~ -60) dB (-60 ~ -80) dB (-80 ~ -100) dB	0.073 dB 0.077 dB 0.082 dB 0.095 dB 0.13 dB 0.17 dB		
Frequency Response		(10 ~ 100) Hz 100 Hz ~ 1 GHz (1 ~ 6) GHz (6 ~ 10) GHz (10 ~ 18) GHz (18 ~ 26.5) GHz (26.5 ~ 30) GHz (30 ~ 35) GHz (35 ~ 40) GHz	0.01 dB 0.15 dB 0.16 dB 0.17 dB 0.19 dB 0.21 dB 0.23 dB 0.28 dB 0.32 dB		
Average Noise Level		DC ~ 40 GHz	0.17 dB		
Sideband Noise Level		(-30 ~ 30) kHz	0.33 dB		
CAL Output Freq. & Int. Frequency		DC ~ 1 GHz	6.2×10^{-9}		
CAL Output Level		(-20 ~ 20) dBm	0.09 dB		
RF speed guns	40642	(5 ~ 3 000) m/s	0.01 m/s		Signal Generator/ SICT-CP-40642

406. Radio frequency measurement

Measured Quantity Instrument or Gauge	Field Code	Range	Measurement uncertainty (The Confidence Level is about 95 %)	Standard/Method of Measurement etc.
Surge generators	40643	(±)		Digital Oscilloscope/ SICT-CP-40643
Surge Voltage		5 mV	3.2×10^{-2}	
		5 mV ~ 2 V	3.0×10^{-2}	
		(2 ~ 5) V	4.0×10^{-2}	
		5 V ~ 200 kV	3.5×10^{-2}	
Surge Current		(±)		
		5 A	3.3×10^{-2}	
		5 A ~ 200 kA	3.6×10^{-2}	
Rise/Fall Time		1 ns	6.0×10^{-3}	
		(1 ~ 2) ns	3.0×10^{-3}	
		2 ns ~ 10 s	2.0×10^{-3}	
Pulse Width		1 ns	6.0×10^{-3}	
		(1 ~ 2) ns	3.0×10^{-3}	
	2 ns ~ 10 s	2.0×10^{-3}		
Time measurement by section	1 ns	6.0×10^{-3}		
	(1 ~ 2) ns	3.0×10^{-3}		
	2 ns ~ 10 s	2.0×10^{-3}		
Frequency measurement by section	1 Hz ~ 25 MHz	1.6×10^{-3}		
Phase Shifiting	at 50 Hz (0 ~ 360)°	1.2°		
	at 60 Hz (0 ~ 360)°	1.4°		
SWR meters	40644	9 kHz ~ 18 GHz	6.4×10^{-5}	Coaxial Mismatch/ SICT-CP-40644
Frequency				
Output Level		30 kHz ~ 100 MHz	0.06 dB	
		100 MHz ~ 10 GHz	0.08 dB	
		(10 ~ 18) GHz	0.09 dB	
SWR		(30 kHz ~ 30 MHz)		
		1.05	0.019	
		1.20	0.019	
		1.50	0.019	
		2.00	0.020	
		(30 MHz ~ 2 GHz)		
		1.05	0.021	
		1.20	0.021	
		1.50	0.021	
		2.00	0.021	
		(2 ~ 18) GHz		
		1.05	0.018	
		1.20	0.018	
	1.50	0.018		
	2.00	0.024		

406. Radio frequency measurement

Measured Quantity Instrument or Gauge	Field Code	Range	Measurement uncertainty (The Confidence Level is about 95 %)	Standard/Method of Measurement etc.
RF terminations (Open, Short, Phase)	40645	($\pm 180^\circ$)		Network Analyzer, Coaxial Mismatch/ SICT-CP-40645
		10 Hz ~ 2 GHz	0.49°	
		(2 ~ 20) GHz	0.61°	
		(20 ~ 40) GHz	0.95°	
		(40 ~ 50) GHz	1.2°	
(Reflection coefficient)		(0 ~ 1)		
		10 Hz ~ 100 kHz	0.004 3	
		100 kHz ~ 500 MHz	0.006 0	
		500 MHz ~ 20 GHz	0.009 5	
		(20 ~ 40) GHz	0.016	
		(40 ~ 50) GHz	0.019	
(SWR)		(1 ~ ∞)		
		10 Hz ~ 100 kHz	0.008 6	
		100 kHz ~ 500 MHz	0.012	
		500 MHz ~ 20 GHz	0.019	
		(20 ~ 40) GHz	0.032	
	(40 ~ 50) GHz	0.038		
(Impedance)	(0.000 0 ~ 0.047 6)			
	10 Hz ~ 500 MHz	0.64 Ω		
	500 MHz ~ 20 GHz	1.0 Ω		
	(20 ~ 40) GHz	1.6 Ω		
	(40 ~ 50) GHz	2.0 Ω		
	(0.047 6 ~ 0.090 9)			
	10 Hz ~ 500 MHz	0.71 Ω		
	500 MHz ~ 20 GHz	1.1 Ω		
	(20 ~ 40) GHz	1.8 Ω		
	(40 ~ 50) GHz	2.2 Ω		
	(0.090 9 ~ 0.166 7)			
	10 Hz ~ 500 MHz	0.84 Ω		
	500 MHz ~ 20 GHz	1.3 Ω		
	(20 ~ 40) GHz	2.1 Ω		
	(40 ~ 50) GHz	2.7 Ω		
	(0.166 7 ~ 0.230 8)			
	10 Hz ~ 500 MHz	0.99 Ω		
	500 MHz ~ 20 GHz	1.6 Ω		
	(20 ~ 40) GHz	2.5 Ω		
	(40 ~ 50) GHz	3.1 Ω		
	(0.230 8 ~ 0.285 7)			
	10 Hz ~ 500 MHz	1.1 Ω		
	500 MHz ~ 20 GHz	1.8 Ω		
	(20 ~ 40) GHz	2.9 Ω		
	(40 ~ 50) GHz	3.6 Ω		
	(0.285 7 ~ 0.333 4)			
	10 Hz ~ 500 MHz	1.3 Ω		
	500 MHz ~ 20 GHz	2.1 Ω		
	(20 ~ 40) GHz	3.3 Ω		
	(40 ~ 50) GHz	4.2 Ω		

406. Radio frequency measurement

Measured Quantity Instrument or Gauge	Field Code	Range	Measurement uncertainty (The Confidence Level is about 95 %)	Standard/Method of Measurement etc.
RF terminations (Impedance Phase)	40645	(0.000 0 ~ 0.047 6, ±180 °) 10 Hz ~ 500 MHz 500 MHz ~ 20 GHz (20 ~ 40) GHz (40 ~ 50) GHz (0.047 6 ~ 0.090 9, ±180 °) 10 Hz ~ 500 MHz 500 MHz ~ 20 GHz (20 ~ 40) GHz (40 ~ 50) GHz (0.090 9 ~ 0.166 7, ±180 °) 10 Hz ~ 500 MHz 500 MHz ~ 20 GHz (20 ~ 40) GHz (40 ~ 50) GHz (0.166 7 ~ 0.230 8, ±180 °) 10 Hz ~ 500 MHz 500 MHz ~ 20 GHz (20 ~ 40) GHz (40 ~ 50) GHz (0.230 8 ~ 0.285 7, ±180 °) 10 Hz ~ 500 MHz 500 MHz ~ 20 GHz (20 ~ 40) GHz (40 ~ 50) GHz (0.285 7 ~ 0.333 4, ±180 °) 10 Hz ~ 500 MHz 500 MHz ~ 20 GHz (20 ~ 40) GHz (40 ~ 50) GHz	0.68° 1.1° 1.7° 2.2° 0.67° 1.1° 1.7° 2.1° 0.66° 1.1° 1.7° 2.1° 0.65° 1.0° 1.6° 2.1° 0.64° 1.0° 1.6° 2.0° 0.62° 1.0° 1.6° 2.0°	Network Analyzer, Coaxial Mismatch/ SICT-CP-40645
Coaxial thermistor mounts Cal Factor	40646	(1 ~ 10) μW (9 ~ 100) kHz 100 kHz ~ 1 GHz (1 ~ 10) GHz (10 ~ 18) GHz (18 ~ 26.5) GHz (26.5 ~ 40) GHz (10 μW ~ 10 mW) (9 ~ 100) kHz 100 kHz ~ 1 GHz (1 ~ 10) GHz (10 ~ 18) GHz (18 ~ 26.5) GHz (26.5 ~ 40) GHz	0.4 × 10 ⁻² 0.9 × 10 ⁻² 1.1 × 10 ⁻² 1.9 × 10 ⁻² 2.8 × 10 ⁻² 4.0 × 10 ⁻² 0.4 × 10 ⁻² 0.9 × 10 ⁻² 1.1 × 10 ⁻² 1.9 × 10 ⁻² 2.6 × 10 ⁻² 3.5 × 10 ⁻²	Thermistor Mount, Synthesized Sweeper/ SICT-CP-40646

406. Radio frequency measurement

Measured Quantity Instrument or Gauge	Field Code	Range	Measurement uncertainty (The Confidence Level is about 95 %)	Standard/Method of Measurement etc.
Coaxial thermistor mounts Reflection coefficient SWR	40646	(0 ~ 1) 20 Hz ~ 1 GHz (1 ~ 20) GHz (20 ~ 40) GHz (1 ~ ∞) 20 Hz ~ 1 GHz (1 ~ 20) GHz (20 ~ 40) GHz	4.2×10^{-3} 9.4×10^{-3} 1.5×10^{-2} 9.7×10^{-3} 2.4×10^{-2} 3.8×10^{-2}	Synthesized Sweeper/ SICT-CP-40646
RF voltmeters RF Voltage	40650	3 V 1 V 300 mV 270 mV 240 mV 210 mV 180 mV 150 mV 120 mV 100 mV 90 mV 60 mV 30 mV 10 mV 3 mV 1 mV	4.2 mV 1.4 mV 0.36 mV 0.32 mV 0.28 mV 0.26 mV 0.24 mV 0.22 mV 0.17 mV 0.16 mV 0.13 mV 0.11 mV 0.048 mV 0.020 mV 0.018 mV 0.013 mV	RF Millivolt Meter Calibrator/ SICT-CP-40650
Vector voltmeters RF Voltage RF Phase	40651	3 V 1 V 300 mV 100 mV 30 mV 10 mV 3 mV 1 mV (0 ~ 270)°	4.2 mV 1.4 mV 0.36 mV 0.16 mV 0.048 mV 0.046 mV 0.022 mV 0.024 mV 0.006°	Signal Generator/ SICT-CP-40651
Field strength meters Center frequency Scale Fidelity Frequency response	40652	(9 ~ 100) kHz 0.1 MHz ~ 18 GHz (0 ~ -50) dB (-50 ~ -60) dB (-60 ~ -70) dB (-70 ~ -100) dB 9 kHz ~ 500 MHz 500 MHz ~ 18 GHz	6.8×10^{-8} 6.2×10^{-9} 0.11 dB 0.12 dB 0.13 dB 0.18 dB 0.05 dB 0.08 dB	Signal Generator/ SICT-CP-40652
AM/FM test sources Output frequency	40653	(10 ~ 560) MHz	6.2×10^{-10}	Measuring Receiver/ SICT-CP-40653

406. Radio frequency measurement

Measured Quantity Instrument or Gauge	Field Code	Range	Measurement uncertainty (The Confidence Level is about 95 %)	Standard/Method of Measurement etc.
Dip simulators	40654			Digital Oscilloscope/ SICT-CP-40654
DC Voltage		1 V (1 ~ 5) V (5 ~ 10) V (10 ~ 50) V (50 ~ 100) V (100 ~ 500) V	1.1×10^{-5} 6.4×10^{-6} 5.4×10^{-6} 9.3×10^{-6} 8.0×10^{-6} 1.1×10^{-5}	
AC Voltage		(50 ~ 60) Hz 50 V (50 ~ 100) V (100 ~ 500) V	5.0×10^{-5} 2.5×10^{-5} 1.6×10^{-4}	
Frequency		50 Hz 60 Hz	8.4×10^{-6} 8.3×10^{-6}	
Dip DC Voltage		(0 ~ 50) V 0 % (0 ~ 120) %	0.2 V 3.4×10^{-2}	
Dip AC Voltage		(50 Hz ~ 60 Hz, 0 V ~ 400 V) 0 % (0 ~ 120) %	0.9 V 3.4×10^{-2}	
Time measurement by section		100 ns ~ 2 μ s (2 ~ 4) μ s (4 ~ 400) μ s (0.4 ~ 2) ms 2 ms ~ 5 s	1.8×10^{-3} 2.0×10^{-3} 1.6×10^{-3} 2.0×10^{-3} 1.6×10^{-3}	
Inrush Current		(5 ~ 1 000) A	3.6×10^{-2}	
Phase Shifting		at 50 Hz (0 ~ 360) $^{\circ}$ at 60 Hz (0 ~ 360) $^{\circ}$	1.2 $^{\circ}$ 1.4 $^{\circ}$	

407. Field strength & antenna

Measured Quantity Instrument or Gauge	Field Code	Range	Measurement uncertainty (The Confidence Level is about 95 %)	Standard/Method of Measurement etc.	
Probes Electric Field Probe	40702	9 kHz ~ 300 MHz (1 ~ 750) V/m	0.12	RF Power Meter, Multi Meter/ SICT-CP-40702	
		300 MHz ~ 400 MHz (1 ~ 300) V/m	0.12		
		400 MHz ~ 1 GHz (1 ~ 150) V/m	0.12		
		1 GHz ~ 6 GHz (1 ~ 150) V/m	0.12		
		6 GHz ~ 10 GHz (1 ~ 100) V/m	0.13		
		10 GHz ~ 18 GHz (2 ~ 100) V/m	0.13		
		18 GHz ~ 40 GHz (2 ~ 100) V/m	0.15		
Magnetic Field Probe			10 Hz ~ 1 kHz (0.39 ~ 1 000) A/m		0.07
			1 kHz ~ 10 kHz (0.39 ~ 600) A/m		0.07
			10 kHz ~ 30 kHz (2.65 ~ 390) mA/m (0.39 ~ 100) A/m		0.12 0.07
			30 kHz ~ 150 kHz (2.65 ~ 390) mA/m (0.39 ~ 20) A/m		0.12 0.07
			150 kHz ~ 200 kHz (2.65 ~ 390) mA/m (0.39 ~ 10) A/m		0.12 0.07
			200 kHz ~ 300 MHz 2.65 mA/m ~ 1.98 A/m		0.12
			300 MHz ~ 400 MHz 2.65 mA/m ~ 0.79 A/m		0.12
		400 MHz ~ 1 GHz 2.65 mA/m ~ 0.39 A/m	0.12		

407. Field strength & antenna

Measured Quantity Instrument or Gauge	Field Code	Range	Measurement uncertainty (The Confidence Level is about 95 %)	Standard/Method of Measurement etc.
Dipole antennas (Dipole Antenna) Antenna Factor Voltage Standing Wave Ratio Antenna Pattern (Biconical Antenna) Antenna Factor Voltage Standing Wave Ratio Antenna Pattern (Log Periodic Antenna) Antenna Factor Voltage Standing Wave Ratio Antenna Pattern	40703	20 MHz ~ 18 GHz (1 ~ ∞) 20 MHz ~ 1 GHz 1 GHz ~ 18 GHz 700 MHz ~ 18 GHz 20 MHz ~ 18 GHz (1 ~ ∞) 20 MHz ~ 1 GHz 1 GHz ~ 18 GHz 700 MHz ~ 18 GHz 20 MHz ~ 18 GHz (1 ~ ∞) 20 MHz ~ 1 GHz 1 GHz ~ 18 GHz 700 MHz ~ 18 GHz	1.1 dB 0.022 0.039 1.4 dB 1.2 dB 0.022 0.039 1.4 dB 1.2 dB 0.022 0.039 1.4 dB	Network analyzer/ SICT-CP-40703 ancillary facilities(Chungju)
Loop antennas Antenna Factor	40704	10 Hz ~ 30 MHz	1.2 dB	Signal generator1, Signal analyzer/ SICT-CP-40704
Monopole antennas Antenna Factor	40705	10 Hz ~ 30 MHz	1.4 dB	Signal generator1, Signal analyzer/ SICT-CP-40705
Horn antennas Antenna Factor Voltage Standing Wave Ratio Antenna Pattern	40707	200 MHz ~ 18 MHz 18 GHz ~ 40 GHz (1 ~ ∞) 200 MHz ~ 1 GHz 1 GHz ~ 18 GHz 18 GHz ~ 40 GHz 700 MHz ~ 18 GHz	1.1 dB 1.4 dB 0.022 0.039 0.041 1.4 dB	Network analyzer/ SICT-CP-40707 ancillary facilities(Chungju)

501. Contact thermometry

Measured Quantity Instrument or Gauge	Field Code	Range	Measurement uncertainty (The Confidence Level is about 95 %)	Standard/Method of Measurement etc.
Temperature generators: ovens, furnaces, isothermal liquid baths, ice-point baths, dry-block calibrators	50101	0 ℃ (-196 ~ -95) ℃ (-95 ~ -90) ℃ (-90 ~ 250) ℃ (250 ~ 550) ℃ (550 ~ 660) ℃ (660 ~ 1 100) ℃ (1 100 ~ 1 600) ℃	0.010 ℃ 0.060 ℃ 0.030 ℃ 0.017 ℃ 0.020 ℃ 0.060 ℃ 0.7 ℃ 1.7 ℃	SPRT, STANDARD TC/ SICT-CP-50101
Temperature indicators/recorders /controllers, temperature calibrators (Temperature indicators/recorders/controllers) With Sensor Without Sensor (temperature calibrators) Output Input	50102	(-196 ~ 500) ℃ (500 ~ 660) ℃ (660 ~ 700) ℃ (700 ~ 900) ℃ (900 ~ 1 100) ℃ (1 100 ~ 1 400) ℃ (1 400 ~ 1 600) ℃ (-196 ~ 0) ℃ (0 ~ 100) ℃ (100 ~ 200) ℃ (200 ~ 300) ℃ (300 ~ 400) ℃ (400 ~ 500) ℃ (500 ~ 600) ℃ (600 ~ 700) ℃ (700 ~ 800) ℃ (800 ~ 1 300) ℃ (1 300 ~ 1 600) ℃ (-196 ~ 500) ℃ (500 ~ 600) ℃ (600 ~ 800) ℃ (800 ~ 1 300) ℃ (1 300 ~ 1 600) ℃ (-196 ~ 500) ℃ (500 ~ 600) ℃ (600 ~ 800) ℃ (800 ~ 1 300) ℃ (1 300 ~ 1 600) ℃	0.020 ℃ 0.045 ℃ 0.59 ℃ 0.60 ℃ 0.61 ℃ 2.0 ℃ 2.1 ℃ 0.010 ℃ 0.013 ℃ 0.018 ℃ 0.022 ℃ 0.025 ℃ 0.029 ℃ 0.033 ℃ 0.040 ℃ 0.044 ℃ 0.07 ℃ 0.09 ℃ 0.005 ℃ 0.006 ℃ 0.007 ℃ 0.08 ℃ 0.10 ℃ 0.03 ℃ 0.04 ℃ 0.05 ℃ 0.07 ℃ 0.09 ℃	SPRT, STANDARD TC/ SICT-CP-50102
Glass thermometers: liquid-in-glass, Beckmann liquid-in-glass	50103	(-90 ~ -58) ℃ (-58 ~ 400) ℃ (400 ~ 500) ℃	0.15 ℃ 0.04 ℃ 0.15 ℃	SPRT/ SICT-CP-50103

501. Contact thermometry

Measured Quantity Instrument or Gauge	Field Code	Range	Measurement uncertainty (The Confidence Level is about 95 %)	Standard/Method of Measurement etc.
Temperature transducers	50107	(-196 ~ 400) °C (400 ~ 500) °C (500 ~ 660) °C (660 ~ 800) °C (800 ~ 1 100) °C (1 100 ~ 1 300) °C (1 300 ~ 1 600) °C	0.031 °C 0.043 °C 0.072 °C 0.6 °C 0.7 °C 2.1 °C 2.2 °C	SPRT, THERMOCOUPLE, MULTIMETER SICT-CP-50107
Primary fixed-point cells and apparatus H ₂ O TP	50108	0.01 °C	0.24 mK	Triple-Point Cell SICT-CP-50108

502. non contact thermometry

Measured Quantity Instrument or Gauge	Field Code	Range	Measurement uncertainty (The Confidence Level is about 95 %)	Standard/Method of Measurement etc.
Optical pyrometers	50203	(900 ~ 1 800) °C	5 °C	Standard Lamp/ SICT-CP-50203
Standard radiation thermometers	50204	(-40 ~ -20) °C (-20 ~ 0) °C (0 ~ 10) °C (10 ~ 50) °C (50 ~ 100) °C (100 ~ 200) °C (200 ~ 300) °C (300 ~ 400) °C (400 ~ 500) °C (500 ~ 600) °C (600 ~ 700) °C (700 ~ 800) °C (800 ~ 900) °C (900 ~ 1 200) °C (1 200 ~ 1 400) °C (1 400 ~ 1 500) °C (1 500 ~ 1 600) °C (1 600 ~ 1 800) °C (1 800 ~ 2 000) °C (2 000 ~ 2 100) °C (2 100 ~ 2 200) °C (2 200 ~ 2 300) °C (2 300 ~ 2 400) °C	0.9 °C 0.7 °C 0.4 °C 0.3 °C 0.4 °C 0.5 °C 0.7 °C 0.8 °C 1.0 °C 1.1 °C 1.3 °C 1.6 °C 1.7 °C 1.8 °C 1.9 °C 2.0 °C 2.1 °C 2.5 °C 2.6 °C 4.2 °C 4.4 °C 4.6 °C 4.7 °C	Transfer Standard Pyrometer/ SICT-CP-50204
Thermal image apparatus	50205	(-40 ~ -20) °C (-20 ~ 0) °C (0 ~ 10) °C (10 ~ 50) °C (50 ~ 100) °C (100 ~ 200) °C (200 ~ 300) °C (300 ~ 400) °C (400 ~ 500) °C (500 ~ 600) °C (600 ~ 700) °C (700 ~ 800) °C (800 ~ 900) °C (900 ~ 1 200) °C (1 200 ~ 1 400) °C (1 400 ~ 1 500) °C (1 500 ~ 1 600) °C (1 600 ~ 1 800) °C (1 800 ~ 2 000) °C (2 000 ~ 2 100) °C (2 100 ~ 2 200) °C (2 200 ~ 2 300) °C (2 300 ~ 2 400) °C	0.9 °C 0.7 °C 0.4 °C 0.3 °C 0.4 °C 0.5 °C 0.7 °C 0.8 °C 1.0 °C 1.1 °C 1.3 °C 1.6 °C 1.7 °C 1.8 °C 1.9 °C 2.0 °C 2.1 °C 2.5 °C 2.6 °C 4.2 °C 4.4 °C 4.6 °C 4.7 °C	Transfer Standard Pyrometer/ SICT-CP-50205 SICT-CP-50205

502. non contact thermometry

Measured Quantity Instrument or Gauge	Field Code	Range	Measurement uncertainty (The Confidence Level is about 95 %)	Standard/Method of Measurement etc.
Blackbody furnaces	50206	(-40 ~ 0) °C	0.6 °C	Transfer Standard Pyrometer/ SICT-CP-50206
		(0 ~ 10) °C	0.4 °C	
		(10 ~ 50) °C	0.3 °C	
		(50 ~ 100) °C	0.4 °C	
		(100 ~ 200) °C	0.5 °C	
		(200 ~ 300) °C	0.7 °C	
		(300 ~ 400) °C	0.8 °C	
		(400 ~ 500) °C	0.9 °C	
		(500 ~ 600) °C	1.0 °C	
		(600 ~ 700) °C	1.1 °C	
		(700 ~ 1 100) °C	1.4 °C	
		(1 100 ~ 1 300) °C	1.5 °C	
		(1 300 ~ 1 500) °C	1.6 °C	
		(1 500 ~ 1 700) °C	1.8 °C	
		(1 700 ~ 1 800) °C	1.9 °C	
		(1 800 ~ 1 900) °C	2.0 °C	
		(1 900 ~ 2 000) °C	2.1 °C	
(2 000 ~ 2 100) °C	3.7 °C			
(2 100 ~ 2 200) °C	3.9 °C			
(2 200 ~ 2 300) °C	4.1 °C			
(2 300 ~ 2 400) °C	4.3 °C			
Others; ear thermometers, etc.	50207	(30 ~ 45) °C	0.07 °C	Standard prt/ SICT-CP-50207

503. Humidity

Measured Quantity Instrument or Gauge	Field Code	Range	Measurement uncertainty (The Confidence Level is about 95 %)	Standard/Method of Measurement etc.
Dew-point hygrometers; chilled mirror, alumina thin film, etc.	50301	(-90 ~ -80) °C D.P. (-80 ~ -70) °C D.P. (-70 ~ -50) °C D.P. (-50 ~ -20) °C D.P. (-20 ~ 90) °C D.P. (90 ~ 95) °C D.P.	0.60 °C D.P. 0.32 °C D.P. 0.20 °C D.P. 0.19 °C D.P. 0.13 °C D.P. 0.15 °C D.P.	Dewpoint Meter/ SICT-CP-50301
Relative humidity hygrometers; polimer thin film, hair, etc. humidity Temperature	50302	(3 ~ 60) % R.H. (60 ~ 90) % R.H. (90 ~ 98) % R.H. (-80 ~ 0) °C (0 ~ 80) °C (80 ~ 100) °C (100 ~ 180) °C	1.3 % R.H. 1.4 % R.H. 1.5 % R.H. 0.6 °C 0.3 °C 0.5 °C 1.5 °C	Dewpoint Meter/ SICT-CP-50302
Psychrometers; Assmann ventilated, PRT type, etc. assmann ventilated (humidity) (Temperature) PRT type (humidity) (Temperature)	50303	(10 ~ 50) % R.H. (50 ~ 70) % R.H. (70 ~ 90) % R.H. (90 ~ 95) % R.H. (0 ~ 50) °C (10 ~ 50) % R.H. (50 ~ 80) % R.H. (80 ~ 98) % R.H. (0 ~ 80) °C (80 ~ 100) °C	1.3 % R.H. 1.4 % R.H. 1.5 % R.H. 1.6 % R.H. 0.3 °C 1.3 % R.H. 1.4 % R.H. 1.5 % R.H. 0.3 °C 0.5 °C	Dewpoint Meter/ SICT-CP-50303
Temperature humidity recorders; hygrothermograph, etc. Humidity Temperature	50304	(5 ~ 70) % R.H. (70 ~ 95) % R.H. (-20 ~ 80) °C	2.1 % R.H. 2.2 % R.H. 0.7 °C	Dewpoint Meter/ SICT-CP-50304

503. Humidity

Measured Quantity Instrument or Gauge	Field Code	Range	Measurement uncertainty (The Confidence Level is about 95 %)	Standard/Method of Measurement etc.
Transducers; dew-point /relative humidity (Dew-point Transducers) Dew point (Relative humidity Transducers) Humidity Temperature	50305	(-90 ~ -80) °C D.P. (-80 ~ -70) °C D.P. (-70 ~ -60) °C D.P. (-60 ~ -40) °C D.P. (-40 ~ -20) °C D.P. (-20 ~ 0) °C D.P. (0 ~ 50) °C D.P. (50 ~ 90) °C D.P. (90 ~ 95) °C D.P. (3 ~ 50) % R.H. (50 ~ 80) % R.H. (80 ~ 98) % R.H. (-80 ~ 0) °C (0 ~ 80) °C (80 ~ 100) °C (100 ~ 180) °C	0.60 °C D.P. 0.33 °C D.P. 0.22 °C D.P. 0.21 °C D.P. 0.20 °C D.P. 0.15 °C D.P. 0.14 °C D.P. 0.15 °C D.P. 0.17 °C D.P. 1.3 % R.H. 1.4 % R.H. 1.5 % R.H. 0.7 °C 0.3 °C 0.5 °C 1.5 °C	Dewpoint Meter/ SICT-CP-50305
Humidity generators; two-pressure, two-temperature, flow mixing humidity generator, constant temperature and humidity chamber, etc. Dew point Humidity Temperature	50306	(-90 ~ -80) °C D.P. (-80 ~ -70) °C D.P. (-70 ~ -50) °C D.P. (-50 ~ -30) °C D.P. (-30 ~ -10) °C D.P. (-10 ~ 60) °C D.P. (60 ~ 80) °C D.P. (80 ~ 95) °C D.P. (3 ~ 20) % R.H. (20 ~ 30) % R.H. (30 ~ 40) % R.H. (40 ~ 50) % R.H. (50 ~ 70) % R.H. (70 ~ 90) % R.H. (90 ~ 98) % R.H. (-90 ~ 50) °C (50 ~ 100) °C (100 ~ 200) °C	0.60 °C D.P. 0.32 °C D.P. 0.19 °C D.P. 0.17 °C D.P. 0.16 °C D.P. 0.13 °C D.P. 0.14 °C D.P. 0.15 °C D.P. 1.8 % R.H. 1.7 % R.H. 1.4 % R.H. 1.5 % R.H. 1.6 % R.H. 1.8 % R.H. 1.9 % R.H. 0.4 °C 0.5 °C 0.6 °C	Dewpoint Meter/ SICT-CP-50306

504. Moisture

Measured Quantity Instrument or Gauge	Field Code	Range	Measurement uncertainty (The Confidence Level is about 95 %)	Standard/Method of Measurement etc.
Cereal moisture meters Moisture	50401	(9 ~ 20) % M.C.	0.7 % M.C.	Balance/ SICT-CP-50401
Wood moisture meters Moisture	50402	(8 ~ 25) % M.C.	2.5 % M.C.	Balance/ SICT-CP-50402
Paper moisture meters Moisture	50403	(8 ~ 20) % M.C.	3.4 % M.C.	Balance/ SICT-CP-50403

601. Sound in air

Measured Quantity Instrument or Gauge	Field Code	Range	Measurement uncertainty (The Confidence Level is about 95 %)	Standard/Method of Measurement etc.
Sound calibrators Pistonphones Sound Pressure Level Calibrators Multifunction Acoustic Calibrators	60102	(200 ~ 300) Hz (200 ~ 300) Hz (900 ~ 1 100) Hz (28 ~ 35) Hz (35 ~ 90) Hz (90 ~ 4 500) Hz (4 500 ~ 9 000) Hz (9 000~ 14 000) Hz (14 000~ 17 000) Hz	0.08 dB 0.08 dB 0.08 dB 0.12 dB 0.09 dB 0.08 dB 0.09 dB 0.13 dB 0.21 dB	Reference microphone/ SICT-CP-60102
Microphones	60104	20 Hz (20 ~ 25) Hz (25 ~ 31.5) Hz (31.5 ~ 50) Hz (50 ~ 63) Hz (63 ~ 8 000) Hz (8 000 ~ 10 000) Hz (10 000 ~ 12 500) Hz (12 500 ~ 16 000) Hz (16 000 ~ 20 000) Hz	0.15 dB 0.13 dB 0.12 dB 0.10 dB 0.09 dB 0.08 dB 0.09 dB 0.10 dB 0.12 dB 0.16 dB	Reference microphone/ SICT-CP-60104
Sound level meters	60106	20 Hz (20 ~ 50) Hz (50 ~ 160) Hz (160 ~ 2 000) Hz (2 000 ~ 8 000) Hz (8 000 ~ 16 000) Hz (16 000 ~ 20 000) Hz	0.5 dB 0.4 dB 0.3 dB 0.2 dB 0.3 dB 0.4 dB 0.5 dB	Reference microphone/ SICT-CP-60106

603. Vibration

Measured Quantity Instrument or Gauge	Field Code	Range	Measurement uncertainty (The Confidence Level is about 95 %)	Standard/Method of Measurement etc.
Vibration calibrators	60301	(10 ~ 5 000) Hz	1.6×10^{-2}	Reference Accelerometer/ SICT-CP-60301
Vibration transducers Vibration transducers	60302	(0.2 ~ 0.3) Hz	1.4×10^{-2}	Reference Accelerometer(Shock)/ SICT-CP-60302
		(0.3 ~ 20) Hz	1.3×10^{-2}	
		(20 ~ 1 250) Hz	1.1×10^{-2}	
		(1 250 ~ 2 500) Hz	1.2×10^{-2}	
		(2 500 ~ 5 000) Hz	2.4×10^{-2}	
		(5 000 ~ 10 000) Hz	2.7×10^{-2}	
		(10 000 ~ 15 000) Hz	3.0×10^{-2}	
		(15 000 ~ 20 000) Hz	3.8×10^{-2}	
Shock transducers		at Pulse duration : (0.1 ~ 5) ms		
		(200 ~ 2 000) m/s ²	1.0×10^{-2}	
		(2 000 ~ 20 000) m/s ²	1.9×10^{-2}	
		(20 000 ~ 100 000) m/s ²	3.3×10^{-2}	
Vibration measuring instruments Acceleration	60303	(10 ~ 20) Hz	1.6×10^{-2}	Reference Accelerometer/ SICT-CP-60303
		(20 ~ 1 250) Hz	1.5×10^{-2}	
		(1 250 ~ 2 500) Hz	1.6×10^{-2}	
		(2 500 ~ 5 000) Hz	1.7×10^{-2}	
Velocity		(10 ~ 20) Hz	1.6×10^{-2}	
		(20 ~ 1 250) Hz	1.5×10^{-2}	
		(1 250 ~ 2 500) Hz	1.6×10^{-2}	
Displacement		(10 ~ 160) Hz	1.4×10^{-2}	
		(160 ~ 315) Hz	2.1×10^{-2}	
		(315 ~ 630) Hz	5.9×10^{-2}	

701. Photometry

Measured Quantity Instrument or Gauge	Field Code	Range	Measurement uncertainty (The Confidence Level is about 95 %)	Standard/Method of Measurement etc.
Illuminance meters Illuminance	70101	(0.5 ~ 20 000) lx	1.7×10^{-2}	Illuminance Meters/ SICT-CP-70101
Luminance meters Luminance	70102	1 cd/m ² (1 ~ 10) cd/m ² (10 ~ 3 000) cd/m ² (3 000 ~ 15 000) cd/m ²	2.1×10^{-2} 1.7×10^{-2} 1.4×10^{-2} 1.6×10^{-2}	Luminance Standard Sources/ SICT-CP-70102
Total luminous flux meters Total luminous flux	70103	70 lm (70 ~ 4 650) lm	3.2×10^{-2} 1.5×10^{-2}	Total Luminous Flux Standard Lamps/ SICT-CP-70103
Luminous intensity meters Luminance	70104	(72 ~ 3 200) cd	3.7×10^{-2}	Luminous Intensity Standard Lamps, Illuminance Meters / SICT-CP-70104

702. Property of detectors & sources

Measured Quantity Instrument or Gauge	Field Code	Range	Measurement uncertainty (The Confidence Level is about 95 %)	Standard/Method of Measurement etc.
Color temperature meters Color temperature Chromaticity	70202	(2 677 ~ 3 333) K x y	25 K 0.004 0.004	Color Temperature Standard Lamps/ SICT-CP-70202
Color temperature standard lamps Color temperature Chromaticity	70203	(2 677 ~ 3 333) K x y	27 K 0.005 0.005	Spectroradiometers/ SICT-CP-70203
Colorimeters; source color Luminance Chromaticity	70204	1 cd/m ² (1 ~ 10) cd/m ² (10 ~ 3 000) cd/m ² (3 000 ~ 15 000) cd/m ² (WHITE) x y (RED) x y (GREEN) x y (BLUE) x y (CIE Standard Illuminant A) x y	2.1 × 10 ⁻² 1.7 × 10 ⁻² 1.4 × 10 ⁻² 1.6 × 10 ⁻² 0.004 0.004 0.004 0.004 0.004 0.004 0.004 0.004 0.003 0.003	Luminance Standard Sources/ SICT-CP-70204
Laser power meters	70207	(405 nm) (0.75 ~ 9) mW (660 nm) (0.7 ~ 47) mW (785 nm) (0.7 ~ 46) mW (1 080 nm) (1 ~ 40) W	1.2 × 10 ⁻² 1.2 × 10 ⁻² 1.2 × 10 ⁻² 3.3 × 10 ⁻²	Optical Power Meters/ SICT-CP-70207
Standard LED light sources Total luminous flux	70208	(68.4 ~ 72.6) lm	3.8 × 10 ⁻²	Total Spectral Radiant Flux Meters/ SICT-CP-70208
Total luminous flux standard lamps Total luminous flux	70209	(320 ~ 10 000) lm	4.7 × 10 ⁻²	Total Luminous Flux Standard l _{lmme} / SICT-CP-70209

702. Property of detectors & sources

Measured Quantity Instrument or Gauge	Field Code	Range	Measurement uncertainty (The Confidence Level is about 95 %)	Standard/Method of Measurement etc.
Optical detectors Relative spectral responsivity	70210	(0 ~ 1) 300 nm (300 ~ 305) nm (305 ~ 310) nm (310 ~ 320) nm (320 ~ 370) nm (370 ~ 440) nm (440 ~ 525) nm (525 ~ 630) nm (630 ~ 955) nm (955 ~ 990) nm (990 ~ 1 100) nm	8.1×10^{-2} 7.0×10^{-2} 6.1×10^{-2} 5.2×10^{-2} 3.9×10^{-2} 3.0×10^{-2} 1.4×10^{-2} 1.0×10^{-2} 1.2×10^{-2} 2.9×10^{-2} 4.0×10^{-2}	Photodiodes/ SICT-CP-70210
Pyranometers and pyrhemometers Irradiance responsivity	70211	(250 ~ 2 500) nm (1 000 ± 150)W/m ²	2.9×10^{-2}	Standard pyranometers/ SICT-CP-70211
Display color analyzers: luminance, chromaticity, white balance, etc. Luminance Chromaticity	70213	1 cd/m ² (1 ~ 5) cd/m ² (5 ~ 200) cd/m ² (WHITE) x y (RED) x y (GREEN) x y (BLUE) x y	3.8×10^{-2} 1.8×10^{-2} 1.7×10^{-2} 0.004 4 0.006 1 0.003 6 0.003 3 0.003 5 0.004 2 0.003 5 0.003 2	Luminance Meters/ SICT-CP-70213
Luminous intensity standard lamps Luminous intensity	70214	(10 ~ 20 000) cd	4.0×10^{-2}	Spectroradiometers/ SICT-CP-70214
Spectral irradiance standard lamps Illuminance Spectral irradiance	70215	(792 ~ 7 105) lx (Deuterium arc lamp) 200 nm (200 ~ 205) nm (205 ~ 400) nm (Tungsten halogen lamp) 250 nm (250 ~ 270) nm (270 ~ 295) nm (295 ~ 375) nm (375 ~ 2 295) nm (2 295 ~ 2 345) nm (2 345 ~ 2 400) nm	2.8×10^{-2} 5.4×10^{-2} 5.3×10^{-2} 4.9×10^{-2} 5.5×10^{-2} 5.2×10^{-2} 5.0×10^{-2} 4.4×10^{-2} 3.8×10^{-2} 4.0×10^{-2} 4.6×10^{-2}	Spectral Irradiance Standard Lamps/ SICT-CP-70215

702. Property of detectors & sources

Measured Quantity Instrument or Gauge	Field Code	Range	Measurement uncertainty (The Confidence Level is about 95 %)	Standard/Method of Measurement etc.
Total spectral radiant flux standard lamps Total spectral radiant flux	70216	350 nm (350 ~ 365) nm (365 ~ 380) nm (380 ~ 400) nm (400 ~ 455) nm (455 ~ 850) nm	6.7×10^{-2} 6.3×10^{-2} 5.8×10^{-2} 4.2×10^{-2} 3.9×10^{-2} 3.6×10^{-2}	Total Spectral Radiant Flux Standard Lamps/ SICT-CP-70216
Luminance standard sources Luminance Chromaticity	70217	1 cd/m ² (1 ~ 10) cd/m ² (10 ~ 3 000) cd/m ² (3 000 ~ 15 000) cd/m ² (WHITE) x y (RED) x y (GREEN) x y (BLUE) x y (CIE Standard Illuminant A) x y	2.2×10^{-2} 1.8×10^{-2} 1.5×10^{-2} 1.8×10^{-2} 0.005 0.005 0.005 0.005 0.005 0.005 0.005 0.005 0.004 0.004	Luminance Standard Sources/ SICT-CP-70217
Spectral radiance standard sources Spectral radiance	70218	300 nm (300 ~ 305) nm (305 ~ 310) nm (310 ~ 315) nm (315 ~ 320) nm (320 ~ 330) nm (330 ~ 340) nm (340 ~ 425) nm (425 ~ 470) nm (470 ~ 1 050) nm (1 050 ~ 1 600) nm	2.0×10^{-1} 1.7×10^{-1} 1.2×10^{-1} 8.9×10^{-2} 7.4×10^{-2} 4.8×10^{-2} 4.1×10^{-2} 3.5×10^{-2} 3.0×10^{-2} 2.8×10^{-2} 3.0×10^{-2}	Spectral Radiance Standard Sources/ SICT-CP-70218
UV irradiance meters Irradiance (UV Meter)	70219	(254 nm) 50 μW/cm ² ~ 3 mW/cm ² (365 nm) 10 μW/cm ² ~ 230 mW/cm ² (405 nm) 10 μW/cm ² ~ 230 mW/cm ²	3.7×10^{-2} 3.8×10^{-2} 3.8×10^{-2}	UV Meter Standard Detectors/ SICT-CP-70219

702. Property of detectors & sources

Measured Quantity Instrument or Gauge	Field Code	Range	Measurement uncertainty (The Confidence Level is about 95 %)	Standard/Method of Measurement etc.
Spectral irradiance meters Wavelength Illuminance Spectral Irradiance	70220	(250 ~ 2 030) nm (813 ~ 6 879) lx 200 nm (200 ~ 245) nm (245 ~ 345) nm (345 ~ 375) nm (375 ~ 895) nm (895 ~ 1 050) nm (1 050 ~ 2 295) nm (2 295 ~ 2 345) nm (2 345 ~ 2 400) nm	0.3 nm 2.1×10^{-2} 4.9×10^{-2} 4.8×10^{-2} 4.4×10^{-2} 3.8×10^{-2} 3.4×10^{-2} 3.0×10^{-2} 3.4×10^{-2} 3.7×10^{-2} 4.3×10^{-2}	Spectral Irradiance Standard Lamps/ SICT-CP-70220
Total spectral radiant flux meters Wavelength Total spectral radiant flux	70221	(350 ~ 850) nm 350 nm (350 ~ 365) nm (365 ~ 375) nm (375 ~ 390) nm (390 ~ 445) nm (445 ~ 850) nm	0.25 nm 2.0×10^{-2} 1.8×10^{-2} 1.7×10^{-2} 1.6×10^{-2} 1.5×10^{-2} 1.4×10^{-2}	Total Spectral Radiant Flux Standard Lamps/ SICT-CP-70221
Spectral radiance meters Wavelength Spectral radiance	70222	(350 ~ 1 694) nm 300 nm (300 ~ 305) nm (305 ~ 310) nm (310 ~ 315) nm (315 ~ 320) nm (320 ~ 325) nm (325 ~ 335) nm (335 ~ 345) nm (345 ~ 405) nm (405 ~ 455) nm (455 ~ 755) nm (755 ~ 1 400) nm (1 400 ~ 1 525) nm (1 525 ~ 1 600) nm	0.25 nm 2.0×10^{-1} 1.7×10^{-1} 1.2×10^{-1} 8.8×10^{-2} 7.2×10^{-2} 5.5×10^{-2} 4.6×10^{-2} 3.7×10^{-2} 3.5×10^{-2} 3.0×10^{-2} 2.6×10^{-2} 2.7×10^{-2} 3.0×10^{-2} 2.8×10^{-2}	Spectral Radiance Standard Sources/ SICT-CP-70222

703. Property of materials

Measured Quantity Instrument or Gauge	Field Code	Range	Measurement uncertainty (The Confidence Level is about 95 %)	Standard/Method of Measurement etc.
Colorimeters; material color	70301			Color Standard Tiles/ SICT-CP-70301
Included Reflectance Std. Light Source A(2°, 10°), C(2°, 10°), D65(2°, 10°) <small>T_{illma}</small>				
1. White	X		1.0 × 10 ⁻²	
	Y		1.0 × 10 ⁻²	
	Z		1.0 × 10 ⁻²	
2. I, Gray	X		1.0 × 10 ⁻²	
	Y		1.0 × 10 ⁻²	
	Z		1.0 × 10 ⁻²	
3. m, Gray	X		1.0 × 10 ⁻²	
	Y		1.0 × 10 ⁻²	
	Z		1.0 × 10 ⁻²	
4. d, Gray	X		1.1 × 10 ⁻²	
	Y		1.0 × 10 ⁻²	
	Z		1.0 × 10 ⁻²	
5. Red	X		1.1 × 10 ⁻²	
	Y		1.2 × 10 ⁻²	
	Z		1.8 × 10 ⁻²	
6. Yellow	X		1.0 × 10 ⁻²	
	Y		1.0 × 10 ⁻²	
	Z		1.6 × 10 ⁻²	
7. Green	X		1.0 × 10 ⁻²	
	Y		1.0 × 10 ⁻²	
	Z		1.1 × 10 ⁻²	
8. Cyan	X		1.0 × 10 ⁻²	
	Y		1.0 × 10 ⁻²	
	Z		1.0 × 10 ⁻²	
Included Reflectance Std. Light Source A(2°, 10°), C(2°, 10°), D65(2°, 10°) <small>T_{illma}</small>				
1. White	L*		0.36	
	a*		0.09	
	b*		0.07	
2. I, Gray	L*		0.32	
	a*		0.08	
	b*		0.07	
3. m, Gray	L*		0.24	
	a*		0.06	
	b*		0.06	
4. d, Gray	L*		0.17	
	a*		0.04	
	b*		0.04	
5. Red	L*		0.25	
	a*		0.27	
	b*		0.26	
6. Yellow	L*		0.34	
	a*		0.17	
	b*		0.43	
7. Green	L*		0.24	
	a*		0.13	
	b*		0.12	
8. Cyan	L*		0.24	
	a*		0.14	
	b*		0.15	

703. Property of materials

Measured Quantity Instrument or Gauge	Field Code	Range	Measurement uncertainty (The Confidence Level is about 95 %)	Standard/Method of Measurement etc.
Colorimeters; material color	70301			Color Standard Tiles/ SICT-CP-70301
Included Reflectance Std. Light Source Type A(2°, 10°), C(2°, 10°), D65(2°, 10°)				
1. White	x		1.3×10^{-3}	
	y		1.3×10^{-3}	
2. I, Gray	x		1.3×10^{-3}	
	y		1.3×10^{-3}	
3. m, Gray	x		1.4×10^{-3}	
	y		1.3×10^{-3}	
4. d, Gray	x		1.4×10^{-3}	
	y		1.3×10^{-3}	
5. Red	x		2.7×10^{-3}	
	y		1.3×10^{-3}	
6. Yellow	x		1.2×10^{-3}	
	y		1.3×10^{-3}	
7. Green	x		1.4×10^{-3}	
	y		1.0×10^{-3}	
8. Cyan	x		2.0×10^{-3}	
	y		1.7×10^{-3}	
Exclude Reflectance Std. Light Source Type A(2°, 10°), C(2°, 10°), D65(2°, 10°)				
1. White	X		1.0×10^{-2}	
	Y		1.0×10^{-2}	
	Z		1.0×10^{-2}	
2. I, Gray	X		1.0×10^{-2}	
	Y		1.0×10^{-2}	
	Z		1.0×10^{-2}	
3. m, Gray	X		1.0×10^{-2}	
	Y		1.0×10^{-2}	
	Z		1.0×10^{-2}	
4. d, Gray	X		1.1×10^{-2}	
	Y		1.0×10^{-2}	
	Z		1.4×10^{-2}	
5. Red	X		1.2×10^{-2}	
	Y		1.3×10^{-2}	
	Z		3.1×10^{-2}	
6. Yellow	X		1.0×10^{-2}	
	Y		1.0×10^{-2}	
	Z		2.3×10^{-2}	
7. Green	X		1.0×10^{-2}	
	Y		1.0×10^{-2}	
	Z		1.2×10^{-2}	
8. Cyan	X		1.0×10^{-2}	
	Y		1.0×10^{-2}	
	Z		1.0×10^{-2}	

703. Property of materials

Measured Quantity Instrument or Gauge	Field Code	Range	Measurement uncertainty (The Confidence Level is about 95 %)	Standard/Method of Measurement etc.
Colorimeters; material color	70301			Color Standard Tiles/ SICT-CP-70301
Exclude Reflectance Std. Light Source Type A(2°, 10°), C(2°, 10°), D65(2°, 10°)				
1. White	L*		0.36	
	a*		0.09	
	b*		0.07	
2. I, Gray	L*		0.31	
	a*		0.08	
	b*		0.07	
3. m, Gray	L*		0.23	
	a*		0.06	
	b*		0.05	
4. d, Gray	L*		0.15	
	a*		0.04	
	b*		0.04	
5. Red	L*		0.25	
	a*		0.32	
	b*		0.66	
6. Yellow	L*		0.33	
	a*		0.18	
	b*		0.58	
7. Green	L*		0.23	
	a*		0.14	
	b*		0.14	
8. Cyan	L*		0.23	
	a*		0.16	
	b*		0.16	
Exclude Reflectance Std. Light Source Type A(2°, 10°), C(2°, 10°), D65(2°, 10°)				
1. White	x		1.3×10^{-3}	
	y		1.3×10^{-3}	
2. I, Gray	x		1.3×10^{-3}	
	y		1.3×10^{-3}	
3. m, Gray	x		1.4×10^{-3}	
	y		1.3×10^{-3}	
4. d, Gray	x		1.3×10^{-3}	
	y		1.3×10^{-3}	
5. Red	x		5.3×10^{-3}	
	y		1.3×10^{-3}	
6. Yellow	x		1.3×10^{-3}	
	y		1.5×10^{-3}	
7. Green	x		1.5×10^{-3}	
	y		1.0×10^{-3}	
8. Cyan	x		2.1×10^{-3}	
	y		1.8×10^{-3}	

703. Property of materials

Measured Quantity Instrument or Gauge	Field Code	Range	Measurement uncertainty (The Confidence Level is about 95 %)	Standard/Method of Measurement etc.
Colorimeters; material color	70301			Color Standard Tiles/ SICT-CP-70301
Transmittance Std. Light Source Type A(2°, 10°), C(2°, 10°), D65(2°, 10°)				
1. E-LA200	X		4.0×10^{-3}	
	Y		4.0×10^{-3}	
	Z		9.0×10^{-3}	
2. G533	X		7.0×10^{-3}	
	Y		5.0×10^{-3}	
	Z		1.3×10^{-2}	
3. B460	X		5.0×10^{-3}	
	Y		4.0×10^{-3}	
	Z		3.0×10^{-3}	
4. ND 25	X		3.0×10^{-3}	
	Y		3.0×10^{-3}	
	Z		5.0×10^{-3}	
5. ND 40	X		3.0×10^{-3}	
	Y		3.0×10^{-3}	
	Z		3.0×10^{-3}	
6. ND 50	X		3.0×10^{-3}	
	Y		3.0×10^{-3}	
	Z		3.0×10^{-3}	
7. ND 70	X		3.0×10^{-3}	
	Y		2.0×10^{-3}	
	Z		3.0×10^{-3}	
Transmittance Std. Light Source Type A(2°, 10°), C(2°, 10°), D65(2°, 10°)				
1. E-LA200	L*		0.11	
	a*		0.09	
	b*		0.22	
2. G533	L*		0.14	
	a*		0.12	
	b*		0.19	
3. B460	L*		0.12	
	a*		0.08	
	b*		0.16	
4. ND 25	L*		0.07	
	a*		0.04	
	b*		0.06	
5. ND 40	L*		0.07	
	a*		0.04	
	b*		0.05	
6. ND 50	L*		0.08	
	a*		0.05	
	b*		0.05	
7. ND 70	L*		0.09	
	a*		0.05	
	b*		0.05	

703. Property of materials

Measured Quantity Instrument or Gauge	Field Code	Range	Measurement uncertainty (The Confidence Level is about 95 %)	Standard/Method of Measurement etc.
Colorimeters; material color Transmittance Std. Light Source Type A(2°, 10°), C(2°, 10°), D65(2°, 10°)	70301			Color Standard Tiles/ SICT-CP-70301
1. E-LA200	x		1.0×10^{-3}	
	y		1.0×10^{-3}	
2. G533	x		1.4×10^{-3}	
	y		1.6×10^{-3}	
3. B460	x		2.0×10^{-3}	
	y		1.6×10^{-3}	
4. ND 25	x		1.3×10^{-3}	
	y		1.2×10^{-3}	
5. ND 40	x		1.3×10^{-3}	
	y		1.3×10^{-3}	
6. ND 50	x		1.3×10^{-3}	
	y		1.3×10^{-3}	
7. ND 70	x		1.3×10^{-3}	
	y		1.3×10^{-3}	
Color standard tiles Included Reflectance Std. Light Source <small>Transmittance</small> A(2°, 10°), C(2°, 10°), D65(2°, 10°)	70304			Color Standard Tiles/ SICT-CP-70304
1. White	X		0.95	
	Y		0.86	
	Z		0.99	
2. I, Gray	X		0.66	
	Y		0.60	
	Z		0.70	
3. m, Gray	X		0.29	
	Y		0.26	
	Z		0.31	
4. d, Gray	X		0.11	
	Y		0.10	
	Z		0.11	
5. Red	X		0.36	
	Y		0.22	
	Z		0.14	
6. Yellow	X		0.78	
	Y		0.68	
	Z		0.21	
7. Green	X		0.19	
	Y		0.23	
	Z		0.20	
8. Cyan	X		0.20	
	Y		0.24	
	Z		0.49	

703. Property of materials

Measured Quantity Instrument or Gauge	Field Code	Range	Measurement uncertainty (The Confidence Level is about 95 %)	Standard/Method of Measurement etc.
Color standard tiles	70304			Color Standard Tiles/ SICT-CP-70304
Included Reflectance Std. Light Source <small>Turne</small> A(2°, 10°), C(2°, 10°), D65(2°, 10°)				
1. White		L*	0.37	
		a*	0.09	
		b*	0.07	
2. l,Gray		L*	0.32	
		a*	0.08	
		b*	0.07	
3. m,Gray		L*	0.24	
		a*	0.06	
		b*	0.06	
4. d,Gray		L*	0.17	
		a*	0.04	
		b*	0.04	
5. Red		L*	0.25	
		a*	0.27	
		b*	0.26	
6. Yellow		L*	0.34	
		a*	0.17	
		b*	0.43	
7. Green		L*	0.24	
		a*	0.13	
		b*	0.12	
8. Cyan		L*	0.24	
		a*	0.14	
		b*	0.15	
Included Reflectance Std. Light Source <small>Turne</small> A(2°, 10°), C(2°, 10°), D65(2°, 10°)				
1. White		x	0.000 7	
		y	0.000 6	
2. l,Gray		x	0.000 7	
		y	0.000 6	
3. m,Gray		x	0.000 7	
		y	0.000 6	
4. d,Gray		x	0.000 7	
		y	0.000 6	
5. Red		x	0.001 4	
		y	0.000 6	
6. Yellow		x	0.000 7	
		y	0.000 8	
7. Green		x	0.000 6	
		y	0.000 7	
8. Cyan		x	0.000 6	
		y	0.000 6	

703. Property of materials

Measured Quantity Instrument or Gauge	Field Code	Range	Measurement uncertainty (The Confidence Level is about 95 %)	Standard/Method of Measurement etc.
Color standard tiles	70304			Color Standard Tiles/ SICT-CP-70304
Exclude Reflectance Std. Light Source Type A(2°, 10°), C(2°, 10°), D65(2°, 10°)				
1. White	X		0.91	
	Y		0.82	
	Z		0.95	
2. I, Gray	X		0.62	
	Y		0.56	
	Z		0.66	
3. m, Gray	X		0.25	
	Y		0.23	
	Z		0.26	
4. d, Gray	X		0.07	
	Y		0.06	
	Z		0.07	
5. Red	X		0.32	
	Y		0.18	
	Z		0.12	
6. Yellow	X		0.74	
	Y		0.64	
	Z		0.19	
7. Green	X		0.15	
	Y		0.20	
	Z		0.16	
8. Cyan	X		0.17	
	Y		0.21	
	Z		0.45	
Exclude Reflectance Std. Light Source Type A(2°, 10°), C(2°, 10°), D65(2°, 10°)				
1. White	L*		0.36	
	a*		0.09	
	b*		0.07	
2. I, Gray	L*		0.31	
	a*		0.08	
	b*		0.07	
3. m, Gray	L*		0.23	
	a*		0.06	
	b*		0.05	
4. d, Gray	L*		0.15	
	a*		0.04	
	b*		0.04	
5. Red	L*		0.25	
	a*		0.32	
	b*		0.66	
6. Yellow	L*		0.33	
	a*		0.18	
	b*		0.58	
7. Green	L*		0.23	
	a*		0.14	
	b*		0.14	
8. Cyan	L*		0.23	
	a*		0.16	
	b*		0.16	

703. Property of materials

Measured Quantity Instrument or Gauge	Field Code	Range	Measurement uncertainty (The Confidence Level is about 95 %)	Standard/Method of Measurement etc.
Color standard tiles Exclude Reflectance Std. Light Source Type A(2°, 10°), C(2°, 10°), D65(2°, 10°) 1. White 2. l,Gray 3. m,Gray 4. d,Gray 5. Red 6. Yellow 7. Green 8. Cyan Absolute Spectral Reflectance White Plate (Include, Exclude Reflectance)	70304	x y x y x y x y x y x y x y 360 nm (360 ~ 830) nm	0.000 6 0.000 6 0.000 6 0.000 6 0.000 6 0.000 6 0.002 9 0.000 6 0.000 8 0.000 9 0.000 6 0.000 7 0.000 5 0.000 5 0.009 4 0.012	Color Standard Tiles/ SICT-CP-70304
Gloss meters Gloss	70306	20 ° 60 ° 85 °	8.9×10^{-3} 9.5×10^{-3} 8.0×10^{-3}	Gloss Standard/ SICT-CP-70306
Gloss standard plates Gloss	70307	20° 60° 85°	9.5×10^{-3} 9.8×10^{-3} 8.3×10^{-3}	Gloss Meter/ SICT-CP-70307
Haze meters Haze Transmittance	70308	H-1 H-5 H-10 H-20 H-30 T-30 T-50 T-70 T-90	0.30 0.26 0.4 0.6 0.8 0.50 0.50 0.50 0.50	Haze Standard Plate, Transmittance Standard Plates/ SICT-CP-70308
Lens meters Vertex diopter	70312	-25 D ~ 25 D	0.03 D	Reference Lens/ SICT-CP-70312
Optical densitometers Density	70315	1 Step ~ 10 Step 11 Step 11 Step ~ 15 Step	0.03 0.06 0.11	Density CRM/ SICT-CP-70315

703. Property of materials

Measured Quantity Instrument or Gauge	Field Code	Range	Measurement uncertainty (The Confidence Level is about 95 %)	Standard/Method of Measurement etc.
Reflectance meters Reflectance	70319	380 nm ~ 780 nm	1.1×10^{-2}	Absolute Spectral Reflectance White Standard Plates/ SICT-CP-70319
Refractometers Refracto	70321	(1.332 99 ~ 1.505 80) nD 1.51 nD 1.62 nD	0.000 04 nD 0.000 2 nD 0.000 2 nD	Reference Refracto CRM/ SICT-CP-70321
Transmittance meters	70323	(0.1) (250 ~ 750) nm (0.5) (250 ~ 750) nm (0.9) (250 ~ 750) nm	6.1×10^{-3} 3.8×10^{-3} 2.2×10^{-3}	Transmittance Filter/ SICT-CP-70323
Spectrophotometers including FT-IR spectrophotometers Wavelength Transmittance	70325	(240.7 ~ 976.1) nm (990.2 ~ 2 536.5) nm (Filter NO 10) 250 nm 300 nm 350 nm 400 nm 450 nm 500 nm 550 nm 600 nm 650 nm 700 nm 750 nm 900 nm 1 000 nm 1 200 nm 1 400 nm 1 600 nm 1 800 nm 2 000 nm 2 200 nm 2 400 nm 2 500 nm	0.4 nm 0.5 nm 8.7×10^{-3} 9.2×10^{-3} 8.2×10^{-3} 6.6×10^{-3} 6.8×10^{-3} 6.5×10^{-3} 6.6×10^{-3} 6.8×10^{-3} 6.4×10^{-3} 6.7×10^{-3} 6.6×10^{-3} 8.0×10^{-3} 8.1×10^{-3} 8.4×10^{-3} 7.7×10^{-3} 8.0×10^{-3} 8.2×10^{-3} 8.1×10^{-3} 8.6×10^{-3} 9.2×10^{-3} 1.7×10^{-2}	Wavelength Filters, Transmittance Filters, Absolute Spectral Reflectance White Standard Plates, Wavelength Filters/ SICT-CP-70325

703. Property of materials

Measured Quantity Instrument or Gauge	Field Code	Range	Measurement uncertainty (The Confidence Level is about 95 %)	Standard/Method of Measurement etc.
Spectrophotometers including FT-IR spectrophotometers Transmittance	70325	(Filter NO 30, 40, 50)		Wavelength Filters, Transmittance Filters, Absolute Spectral Reflectance White Standard Plates, Wavenumber Filters/ SICT-CP-70325
		250 nm	8.3×10^{-3}	
		300 nm	8.2×10^{-3}	
		350 nm	8.0×10^{-3}	
		400 nm	5.5×10^{-3}	
		450 nm	5.6×10^{-3}	
		500 nm	5.7×10^{-3}	
		550 nm	5.6×10^{-3}	
		600 nm	5.6×10^{-3}	
		650 nm	5.5×10^{-3}	
		700 nm	5.4×10^{-3}	
		750 nm	5.5×10^{-3}	
		(Filter NO 30)		
		900 nm	7.7×10^{-3}	
		1 000 nm	7.4×10^{-3}	
		1 200 nm	7.3×10^{-3}	
		1 400 nm	7.3×10^{-3}	
		1 600 nm	7.4×10^{-3}	
		1 800 nm	7.3×10^{-3}	
		2 000 nm	7.3×10^{-3}	
		2 200 nm	8.0×10^{-3}	
		2 400 nm	7.3×10^{-3}	
		2 500 nm	8.9×10^{-3}	
		(Filter NO 90)		
		250 nm	8.0×10^{-3}	
		300 nm	8.0×10^{-3}	
		350 nm	7.8×10^{-3}	
		400 nm	5.4×10^{-3}	
		450 nm	5.3×10^{-3}	
		500 nm	5.4×10^{-3}	
		550 nm	5.4×10^{-3}	
		600 nm	5.4×10^{-3}	
		650 nm	5.4×10^{-3}	
		700 nm	5.4×10^{-3}	
		750 nm	5.4×10^{-3}	
		900 nm	7.3×10^{-3}	
		1 000 nm	7.3×10^{-3}	
		1 200 nm	7.3×10^{-3}	
		1 400 nm	7.3×10^{-3}	
		1 600 nm	7.3×10^{-3}	
		1 800 nm	7.3×10^{-3}	
		2 000 nm	7.3×10^{-3}	
		2 200 nm	7.3×10^{-3}	
		2 400 nm	7.3×10^{-3}	
		2 500 nm	7.8×10^{-3}	

703. Property of materials

Measured Quantity Instrument or Gauge	Field Code	Range	Measurement uncertainty (The Confidence Level is about 95 %)	Standard/Method of Measurement etc.
Spectrophotometers including FT-IR spectrophotometers	70325	Transmittance		Wavelength Filters, Transmittance Filters, Absolute Spectral Reflectance White Standard Plates, Wavenumber Filters/ SICT-CP-70325
		(Filter NO 1)		
		440 nm	1.4 × 10 ⁻²	
		465 nm	9.1 × 10 ⁻³	
		546 nm	9.4 × 10 ⁻³	
		590 nm	1.1 × 10 ⁻²	
		635 nm	1.0 × 10 ⁻²	
		(Filter NO 3)		
		440 nm	7.9 × 10 ⁻³	
		465 nm	5.8 × 10 ⁻³	
		546 nm	6.1 × 10 ⁻³	
		590 nm	6.3 × 10 ⁻³	
		635 nm	6.2 × 10 ⁻³	
		(Filter NO 10)		
		250 nm	0.003 7	
		300 nm	0.003 8	
		350 nm	0.003 5	
		400 nm	0.002 7	
		450 nm	0.002 6	
		500 nm	0.002 5	
		550 nm	0.002 5	
		600 nm	0.002 5	
		650 nm	0.002 8	
		700 nm	0.002 6	
		750 nm	0.002 4	
		900 nm	0.003 3	
		1 000 nm	0.003 3	
		1 200 nm	0.003 3	
		1 400 nm	0.003 3	
		1 600 nm	0.003 2	
		1 800 nm	0.003 3	
		2 000 nm	0.003 3	
		2 200 nm	0.003 4	
		2 400 nm	0.003 7	
		2 500 nm	0.007 2	
		(Filter NO 30, 40, 50)		
		250 nm	0.003 8	
		300 nm	0.003 7	
		350 nm	0.003 6	
		400 nm	0.002 5	
		450 nm	0.002 5	
		500 nm	0.002 6	
550 nm	0.002 6			
600 nm	0.002 6			
650 nm	0.002 5			
700 nm	0.002 5			
750 nm	0.002 5			
Absorbance				

703. Property of materials

Measured Quantity Instrument or Gauge	Field Code	Range	Measurement uncertainty (The Confidence Level is about 95 %)	Standard/Method of Measurement etc.
Spectrophotometers including FT-IR spectrophotometers Absorbance	70325	(Filter NO 30)		Wavelength Filters, Transmittance Filters, Absolute Spectral Reflectance White Standard Plates, Wavenumber Filters/ SICT-CP-70325
		900 nm	0.003 5	
		1 000 nm	0.003 4	
		1 200 nm	0.003 2	
		1 400 nm	0.003 3	
		1 600 nm	0.003 4	
		1 800 nm	0.003 2	
		2 000 nm	0.003 3	
		2 200 nm	0.003 5	
		2 400 nm	0.003 3	
		2 500 nm	0.003 9	
		(Filter NO 90)		
		250 nm	0.003 6	
		300 nm	0.003 6	
		350 nm	0.003 5	
		400 nm	0.002 5	
		450 nm	0.002 5	
		500 nm	0.002 5	
		550 nm	0.002 6	
		600 nm	0.002 6	
		650 nm	0.002 6	
		700 nm	0.002 5	
		750 nm	0.002 6	
		900 nm	0.003 3	
		1 000 nm	0.003 3	
		1 200 nm	0.003 3	
		1 400 nm	0.003 3	
		1 600 nm	0.003 2	
		1 800 nm	0.003 4	
		2 000 nm	0.003 3	
		2 200 nm	0.003 3	
		2 400 nm	0.003 3	
		2 500 nm	0.003 6	
		(Filter NO 1)		
		440 nm	0.004 1	
		465 nm	0.002 8	
		546 nm	0.002 8	
		590 nm	0.003 0	
		635 nm	0.003 5	
		(Filter NO 3)		
		440 nm	0.003 2	
		465 nm	0.002 4	
		546 nm	0.002 6	
		590 nm	0.002 5	
		635 nm	0.002 7	

703. Property of materials

Measured Quantity Instrument or Gauge	Field Code	Range	Measurement uncertainty (The Confidence Level is about 95 %)	Standard/Method of Measurement etc.
Spectrophotometers including FT-IR spectrophotometers Spectral Reflectance Wavenumber	70325	250 nm	1.5×10^{-2}	Wavelength Filters, Transmittance Filters, Absolute Spectral Reflectance White Standard Plates, Wavenumber Filters/ SICT-CP-70325
		(250 ~ 2 500) nm	1.5×10^{-2}	
		544.9 cm^{-1}	2.5 cm^{-1}	
		842.1 cm^{-1}	1.3 cm^{-1}	
		906.82 cm^{-1}	0.12 cm^{-1}	
		1 028.42 cm^{-1}	0.28 cm^{-1}	
		1 069.27 cm^{-1}	0.78 cm^{-1}	
		1 154.62 cm^{-1}	0.12 cm^{-1}	
		1 583.04 cm^{-1}	0.12 cm^{-1}	
		1 601.38 cm^{-1}	0.13 cm^{-1}	
		2 850.20 cm^{-1}	0.14 cm^{-1}	
		3 001.40 cm^{-1}	0.12 cm^{-1}	
		3 026.44 cm^{-1}	0.12 cm^{-1}	
		3 060.14 cm^{-1}	0.12 cm^{-1}	
3 082.22 cm^{-1}	0.12 cm^{-1}			
Wavelength reference materials; absorption cell, bandpass filter, etc. Wavelength Transmittance	70326	(240 ~750) nm	0.5 nm	Spectrophotometers, Absolute Spectral Reflectance White Standard Plates/ SICT-CP-70326
		(0.1 ~ 0.3)		
		250 nm	8.5×10^{-3}	
		300 nm	8.1×10^{-3}	
		350 nm	8.1×10^{-3}	
		400 nm	5.9×10^{-3}	
		450 nm	5.7×10^{-3}	
		500 nm	5.7×10^{-3}	
		550 nm	5.7×10^{-3}	
		600 nm	5.7×10^{-3}	
		650 nm	5.7×10^{-3}	
		700 nm	5.7×10^{-3}	
		750 nm	5.7×10^{-3}	
		(0.3 ~ 0.5)		
		250 nm	8.3×10^{-3}	
		300 nm	8.1×10^{-3}	
		350 nm	8.0×10^{-3}	
		400 nm	5.7×10^{-3}	
		450 nm	5.7×10^{-3}	
		500 nm	5.7×10^{-3}	
		550 nm	5.7×10^{-3}	
		600 nm	5.7×10^{-3}	
		650 nm	5.7×10^{-3}	
		700 nm	5.7×10^{-3}	
750 nm	5.7×10^{-3}			

703. Property of materials

Measured Quantity Instrument or Gauge	Field Code	Range	Measurement uncertainty (The Confidence Level is about 95 %)	Standard/Method of Measurement etc.
Wavelength reference materials; absorption cell, bandpass filter, etc.	70326			Spectrophotometers, Absolute Spectral Reflectance White Standard Plates/ SICT-CP-70326
Transmittance		(0.5 ~ 0.9)		
		250 nm	8.2×10^{-3}	
		300 nm	8.1×10^{-3}	
		350 nm	8.0×10^{-3}	
		400 nm	5.7×10^{-3}	
		450 nm	5.7×10^{-3}	
		500 nm	5.7×10^{-3}	
		550 nm	5.7×10^{-3}	
		600 nm	5.6×10^{-3}	
		650 nm	5.6×10^{-3}	
		700 nm	5.7×10^{-3}	
		750 nm	5.9×10^{-3}	
Absorbance		(0.1 ~ 0.3)		
		250 nm	0.003 7	
		300 nm	0.003 7	
		350 nm	0.003 8	
		400 nm	0.002 7	
		450 nm	0.002 7	
		500 nm	0.002 8	
		550 nm	0.002 8	
		600 nm	0.002 7	
		650 nm	0.002 7	
		700 nm	0.002 7	
		750 nm	0.002 8	
		(0.3 ~ 0.5)		
		250 nm	0.003 6	
		300 nm	0.003 6	
		350 nm	0.003 6	
		400 nm	0.002 4	
		450 nm	0.002 4	
		500 nm	0.002 4	
		550 nm	0.002 4	
		600 nm	0.002 4	
		650 nm	0.002 4	
		700 nm	0.002 4	
		750 nm	0.002 5	
		(0.5 ~ 0.9)		
		250 nm	0.003 6	
		300 nm	0.003 5	
		350 nm	0.003 5	
		400 nm	0.002 4	
		450 nm	0.002 4	
		500 nm	0.002 4	
		550 nm	0.002 4	
		600 nm	0.002 4	
		650 nm	0.002 4	
		700 nm	0.002 4	
		750 nm	0.002 4	
Reflectance		(360 ~ 830) nm	1.0×10^{-2}	

704. Fiber optics

Measured Quantity Instrument or Gauge	Field Code	Range	Measurement uncertainty (The Confidence Level is about 95 %)	Standard/Method of Measurement etc.
Broadband light sources Wavelength output Optical power output	70402	1 310 nm, 1 550 nm 1 310 nm, 1 550 nm (0 ~ -60) dBm	0.058 nm 0.070 dB	Optical spectrum analyzer, Optical powermeter/ SICT-CP-70402
Optical attenuators Optical Attenuation	70410	1 310 nm, 1 550 nm (-60 ~ 0) dB	0.08 dB	Optical powermeter, Optical power stabilized lasers and LDs/ SICT-CP-70410
Fiber-optic power meters Absolute optical power Optical Linearity	70412	1 310 nm, 1 550 nm (0 ~ -60) dBm 1 310 nm, 1 550 nm (0 ~ -60) dB	0.072 dB 0.03 dB	Optical powermeter, Optical power stabilized lasers and LDs, Optical attenuator/ SICT-CP-70412
Optical loss testers Optical Attenuation	70413	1 310 nm, 1 550 nm (0 ~ -60) dB	0.03 dB	Optical attenuator/ SICT-CP-70413
Optical multimeters Absolute optical power measure Linearity measure	70415	1 310 nm, 1 550 nm (0 ~ -60) dBm 1 310 nm, 1 550 nm (0 ~ -60) dB	0.072 dB 0.03 dB	Optical powermeter, Optical power stabilized lasers and LDs, Optical attenuator/ SICT-CP-70415
Optical network analyzer (Optical multimeter) Absolute optical power (광)Optical spectrum analyzer) Wavelength measure Resolution measure Absolute optical power measure (Optical attenuator) Optical Attenuation Return loss (Optical time domain reflectometer) Wavelength output Optical Length measure	70416	1 310 nm, 1 550 nm (-60 ~ 0) dBm 1 310 nm 1 550 nm Resolution: (0.1 ~ 1) nm 1 310 nm 1 550 nm 1 310 nm, 1 550 nm (-60 ~ 0) dBm 1 310 nm, 1 550 nm (-60 ~ 0) dB 1 310 nm, 1 550 nm (20 ~ 40) dB 1 310 nm, 1 550 nm 1 310 nm 3.3 km Fiber 13.4 km Fiber 1 550 nm 3.3 km Fiber 13.4 km Fiber	0.072 dB 0.058 nm 0.058 nm 0.058 nm 0.058 nm 0.072 dB 0.07 dB 0.8 dB 0.082 nm 0.081 m 0.34 m 0.080 m 0.34 m	Optical powermeter, OTDR, Fiber reference, Wavelength meter Optical spectrum analyzer Optical attenuator Optical Returnloss generator/ SICT-CP-70416

704. Fiber optics

Measured Quantity Instrument or Gauge	Field Code	Range	Measurement uncertainty (The Confidence Level is about 95 %)	Standard/Method of Measurement etc.
Optical network analyzer Optical loss measure	70416	1 310 nm 7.20 dB Fiber 2.90 dB Fiber 1 550 nm 4.20 dB Fiber 1.60 dB Fiber	0.13 dB 0.05 dB 0.05 dB 0.05 dB	Optical powermeter, OTDR, Fiber reference, Wavelength meter Optical spectrum analyzer Optical attenuator Optical Returnloss generator/ SICT-CP-70416
Optical spectrum analyzers Wavelength measure Resolution measure Absolute optical power measure Linearity measure	70417	1 310 nm 1 550 nm Resolution : (0.1 ~ 1) nm 1 310 nm 1 550 nm 1 310 nm, 1 550 nm (-60 ~ 0) dBm 1 310 nm, 1 550 nm (-60 ~ 0) dB	0.058 nm 0.058 nm 0.058 nm 0.058 nm 0.072 dB 0.03 dB	Optical powermeter, Optical power stabilized lasers and LDs, Optical attenuator, Optical spectrum analyzer/ SICT-CP-70417
Optical time domain reflectometers; OTDR Wavelength output Optical Length measure Optical loss measure	70418	1 310 nm, 1 550 nm 1 310 nm 3.3 km Fiber 13.4 km Fiber 1 550 nm 3.3 km Fiber 13.4 km Fiber 1 310 nm 7.20 dB Fiber 2.90 dB Fiber 1 550 nm 4.20 dB Fiber 1.60 dB Fiber	0.08 nm 0.081 m 0.34 m 0.080 m 0.34 m 0.13 dB 0.05 dB 0.05 dB 0.05 dB	Optical length fiber reference, Optical fiberloss reference, Optical spectrum analyzer/ SICT-CP-70418
Return loss meters Return loss measure	70423	1 310 nm, 1 550 nm 20 dB ~ 40 dB	0.8 dB	Optical Returnloss generator SICT-CP-70423
Frequency stabilized lasers and LDs Wavelength optical power	70429	1 310 nm 1 550 nm 1 310 nm, 1 550 nm (-60 ~ 0) dBm	4 pm 4 pm 0.07 dB	Wavelength meter, Optical powermeter/ SICT-CP-70429

704. Fiber optics

Measured Quantity Instrument or Gauge	Field Code	Range	Measurement uncertainty (The Confidence Level is about 95 %)	Standard/Method of Measurement etc.
ASE light sources Wavelength output Optical power output	70430	1 310 nm, 1 550 nm 1 310 nm, 1 550 nm (-60 ~ 0) dBm	0.058 nm 0.07 dB	Optical spectrum analyzer, Optical powermeter/ SICT-CP-70430
Optical power stabilized lasers and LDs Wavelength output Optical power output	70433	1 310 nm 1 550 nm 1 310 nm, 1 550 nm (-60 ~ 0) dBm	4 pm 4 pm 0.07 dB	Wavelength meter, Optical powermeter/ SICT-CP-70433

901. Chemical analysis

Measured Quantity Instrument or Gauge	Field Code	Range	Measurement uncertainty (The Confidence Level is about 95 %)	Standard/Method of Measurement etc.
Breath alcohol analyzers Dry process Wet process	90101	(0.000 ~ 0.080) %BAC (0.080 ~ 0.190) %BAC (0.000 ~ 0.080) %BAC (0.080 ~ 0.150) %BAC (0.150 ~ 0.400) %BAC	3.3×10^{-2} 2.1×10^{-2} 2.9×10^{-2} 1.6×10^{-2} 1.3×10^{-2}	Standard gas/ SICT-CP-90101
Environmental air quality monitoring instruments Carbon monoxide Carbon dioxide Nitrogen monoxide Isobutane Methane Hydrogen sulfide Propane Isobutylene Ammonia Sulfur dioxide Nitrogen dioxide Hydrogen Hydrogen chloride Sulfur hexafluoride Ozone	90102	(0 ~ 700) $\mu\text{mol/mol}$ (0.07 ~ 1.5) cmol/mol (1.5 ~ 20) cmol/mol (0 ~ 850) $\mu\text{mol/mol}$ (0 ~ 0.50) cmol/mol (0.50 ~ 5.00) cmol/mol (5.00 ~ 19.00) cmol/mol (0 ~ 850) $\mu\text{mol/mol}$ (0 ~ 0.8) cmol/mol (0 ~ 2.0) cmol/mol (0 ~ 45) $\mu\text{mol/mol}$ (0 ~ 2 000) $\mu\text{mol/mol}$ (0 ~ 25) $\mu\text{mol/mol}$ (0 ~ 50) $\mu\text{mol/mol}$ (0 ~ 850) $\mu\text{mol/mol}$ (0 ~ 1 000) $\mu\text{mol/mol}$ (0 ~ 500) $\mu\text{mol/mol}$ (0.05 ~ 2.0) cmol/mol (0 ~ 50) $\mu\text{mol/mol}$ (0 ~ 100) cmol/mol 0.0 nmol/mol (0.0 ~ 1 000.0) nmol/mol	1.0×10^{-2} 2.0×10^{-2} 1.2×10^{-2} 2.2×10^{-2} 2.0×10^{-2} 1.5×10^{-2} 2.1×10^{-2} 2.1×10^{-2} 2.2×10^{-2} 1.4×10^{-2} 3.6×10^{-2} 3.0×10^{-2} 1.0×10^{-2} 4.9×10^{-2} 2.2×10^{-2} 1.0×10^{-2} 2.3×10^{-2} 2.1×10^{-2} 4.8×10^{-2} 0.1×10^{-2} 2.2 nmol/mol 2.5×10^{-2}	Standard gas/ SICT-CP-90102
Gas analyzers Oxygen Carbon monoxide Carbon dioxide Nitrogen monoxide Isobutane Methane Hydrogen sulfide Propane Isobutylene Ammonia Sulfur dioxide Nitrogen dioxide Hydrogen Hydrogen chloride Sulfur hexafluoride Ozone	90103	(0 ~ 700) $\mu\text{mol/mol}$ (0.07 ~ 1.5) cmol/mol (1.5 ~ 20) cmol/mol (0 ~ 850) $\mu\text{mol/mol}$ (0 ~ 0.50) cmol/mol (0.50 ~ 5.00) cmol/mol (5.00 ~ 19.00) cmol/mol (0 ~ 850) $\mu\text{mol/mol}$ (0 ~ 0.8) cmol/mol (0 ~ 2.0) cmol/mol (0 ~ 45) $\mu\text{mol/mol}$ (0 ~ 2 000) $\mu\text{mol/mol}$ (0 ~ 25) $\mu\text{mol/mol}$ (0 ~ 50) $\mu\text{mol/mol}$ (0 ~ 850) $\mu\text{mol/mol}$ (0 ~ 1 000) $\mu\text{mol/mol}$ (0 ~ 500) $\mu\text{mol/mol}$ (0.05 ~ 2.0) cmol/mol (0 ~ 50) $\mu\text{mol/mol}$ (0 ~ 100) cmol/mol 0.0 nmol/mol (0.0 ~ 1 000.0) nmol/mol	1.0×10^{-2} 2.0×10^{-2} 1.2×10^{-2} 2.2×10^{-2} 2.0×10^{-2} 1.5×10^{-2} 2.1×10^{-2} 2.1×10^{-2} 2.2×10^{-2} 1.4×10^{-2} 3.6×10^{-2} 3.0×10^{-2} 1.0×10^{-2} 4.9×10^{-2} 2.2×10^{-2} 1.0×10^{-2} 2.3×10^{-2} 2.1×10^{-2} 4.8×10^{-2} 0.1×10^{-2} 2.2 nmol/mol 2.5×10^{-2}	Standard gas/ SICT-CP-90103

901. Chemical analysis

Measured Quantity Instrument or Gauge	Field Code	Range	Measurement uncertainty (The Confidence Level is about 95 %)	Standard/Method of Measurement etc.
Exhaust gas test instruments	90104			Standard gas/ SICT-CP-90103
Oxygen		(0 ~ 1.5) $\mu\text{mol/mol}$	2.0×10^{-2}	
		(1.5 ~ 20) cmol/mol	1.1×10^{-2}	
Carbon monoxide		(0 ~ 5.0) cmol/mol	2.1×10^{-2}	
Carbon dioxide		(0 ~ 19) cmol/mol	2.0×10^{-2}	
Nitrogen monoxide		(0 ~ 2 000) $\mu\text{mol/mol}$	2.0×10^{-2}	
Isobutane		(0 ~ 0.8) cmol/mol	2.2×10^{-2}	
Methane		(0 ~ 2.0) cmol/mol	1.4×10^{-2}	
Propane		(0 ~ 2 000) $\mu\text{mol/mol}$	3.0×10^{-2}	
Ammonia		(0 ~ 50) $\mu\text{mol/mol}$	4.9×10^{-2}	
Sulfur dioxide		(0 ~ 850) $\mu\text{mol/mol}$	2.2×10^{-2}	
Nitrogen dioxide		(0 ~ 1 000) $\mu\text{mol/mol}$	1.0×10^{-2}	
Hydrogen		(0 ~ 500) $\mu\text{mol/mol}$	2.3×10^{-2}	
		(0.05 ~ 2.0) cmol/mol	2.1×10^{-2}	
Others: pH meter, Electrical conductivity meter	90104			CRM/ SICT-CP-90199
pH meter		(4 ~ 10) pH	0.013 pH	
Electrical conductivity meter		100 $\mu\text{S/cm}$	3.1 $\mu\text{S/cm}$	
		1 413 $\mu\text{S/cm}$	9.7 $\mu\text{S/cm}$	
		12.85 mS/cm	0.073 mS/cm	
	111.3 mS/cm	0.78 mS/cm		